MIL-T-29009A(TD)
8 February 1982
SUPERSEDING
MIL-T-29009(TD)
28 January 1972

MILITARY SPECIFICATION
TRAINING AID; RADIO MAGNETIC INDICATOR

This specification has been approved by the Naval Training Equipment Center, Department of the Navy.

1. SCOPE

1.1 This specification covers the requirements for the production of a radio magnetic indicator training aid.

1.1.1 This item has been designated by the Naval Training Equipment Center, as Device 2B25 for Navy Procurement.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on the date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

STANDARDS

Military

MIL-STD-129	Marking for Shipment and Storage
MIL-STD-794	Parts and Equipment; Procedures for Packaging and Packing of

DRAWINGS

Naval Training Equipment Center (NAVTRAEQUIPCEN)

2B25-1	Assembly and Details T/A Radio Magnetic Indicator

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

3. REQUIREMENTS

3.1 Materials. Materials shall be as specified on Engineering Drawing 2B25-1. Materials not specified on the drawing shall satisfy the performance requirements of this specification.

3.2 Design.- Design shall be in accordance with the engineering drawing of 2.1.

3.3 Construction.- Construction shall be as shown on the engineering drawing of 2.1.

Source: https://assist.dla.mil -- Downloaded: 202610-20T21:20Z
Check the source to verify that this is the current version before use.

3.4 Performance.- All movable parts of the training aid shall rotate smoothly without binding when turned with finger pressure. No part shall move without the application of external force.

3.5 Details of components.- The training aid shall consist of a baseplate five inches in diameter with a compass disk four inches in diameter and two needle pointers, all concentrically fastened together with a metal grommet.

3.6 Dimensions and tolerances. - Dimensions and tolerances shall be as shown on the engineering drawing of 2.1. Tolerances not shown on the drawings shall be such as to ensure meeting the performance requirements specified in 3.4.

3.7 Finish and color.- The finish and color of the training aid shall be as shown on the engineering drawing of 2.1.

3.8 Nameplates or product markings.- Nameplates or product markings shall be as shown on the engineering drawing of 2.1.

3.8.1 Envelope marking.- The envelope enclosing each training aid shall be printed with the same information that appears on the back of the training aid.

3.9 Government-furnished property.- The Government-furnished property will be as specified by the procuring activity (see 6.2).

3.10 Workmanship.- The training aid shall be constructed and finished with particular attention given to neatness and thoroughness of printing, cutting and assembly.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may utilize his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections.- Inspections to be performed are classified as follows:

(a) In-process inspection

(b) Quality conformance inspection.

Source: https://assist.dla.mil -- Downloaded: 202640-20T21:20Z
Check the source to verify that this is the currenversion before use.

4.2.1 In-process inspection.- In-process inspection shall include such visual, electrical, and mechanical examinations and testing of materials, subassemblies, parts and accessories (including purchased standard items) during the manufacturing process as may be necessary to assure conformance to all the requirements of this specification.

4.2.2 Quality conformance inspection. Quality conformance inspection shall consist of the following:

(a) Preproduction inspection

(b) Production inspection.

4.2.2.1 Preproduction inspection.- Preproduction inspection shall be conducted on the preproduction model and shall consist of all the examinations and tests specified in 4.3 and 4.4.

4.2.2.2 Production inspection.- Production models shall be inspected to the extent necessary to maintain quality control and conformance to the Government-accepted preproduction model.

4.3 Examinations.- The training aid shall be examined to verify conformance to the following requirements of this specification:

(a) Materials

(b) Design

(c) Construction

(d) Dimensions and tolerances

(e) Finish and color

(f) Nameplates or product markings

(g) Workmanship

(h) Preparation for delivery.

4.4 Tests.- The training aid shall be subjected to an operating test.

4.5 Test methods.-

4.5.1 Radio magnetic indicator operating test.- The movable parts of the training aid shall be rotated to determine conformance to the requirements of 3.4.

5. PREPARATION FOR DELIVERY

5.1 Packaging and packing shall be in accordance with MIL-STD-794. The level of protection required shall be specified in the contract or purchase order.

Source: https://assist.dla.mil -- Downloaded: 202640-20T21:20Z
Check the source to verify that this is the currentversion before use.

5.2 Marking.- Interior packages and exterior shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use.- The training aid will be used by individual students for familiarization with the configuration of the ID-250 Radio Magnetic Indicator.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number and date of specification

(b) Procuring activity designation (device number or other) (see 1.1.1)

(c) Government-furnished property (see 3.9)

(d) Selection of applicable levels of preservation, packaging and packing (see 5.1 and 5.2).

6.3 Definitions.- Except as specified in 6.3.1 and 6.3.2, definitions will be furnished upon written request to the procuring activity.

6.3.1 Preproduction model.- A model suitable for complete evaluation of mechanical and electrical form, design and performance. It shall be final mechanical and electrical form, employ standard or nonstandard parts (approved by the agency concerned) and be completely representative of final equipment.

6.3.2 Production model.- A model in its final mechanical and electrical form of final production design made by production tools, jigs, fixtures and methods. It shall use standard or nonstandard parts (approved by the agency concerned).

CUSTODIAN:
Navy-TD

PREPARING ACTIVITY:
Navy-TD
Project No. 6910-N423

Source: https://assist.dla.mil -- Downloaded: 20260-20T21:20Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS. This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE. This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER (Number) AND TITLE

MIL-T-29009A(TD) Training aid; Radio Magnetic Indicator

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1 ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDED WORDING CHANGE

C REASON FOR RECOMMENDED CHANGE(S)

2 REMARKS

SUBMITTED BY (Printed or typed name and address - Optional)

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426

Replaces edition of 1 Jan 72 which may be used.

S/N 0102-LF-001-4260

Source: https://assist.dla.mil -- Downloaded: 20260-20T21:20Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL

FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

COMMANDING OFFICER
NAVAL TRAINING EQUIPMENT CENTER
ATTN: CODE N-423
ORLANDO, FL 32813

FOLD

☆ U.S. GOVERNMENT PRINTING OFFICE: 1982—509-022/13' 3-

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:20Z
Check the source to verify that this is the current version before use.