MILITARY SPECIFICATION

TRAINING AID, DEMONSTRATOR; AUTOMOTIVE FUEL PUMP

This specification has been approved by the Naval Training Device Center, Department of the Navy

The technical requirements for procuring the training aid described herein shall consist of this document and the issue in effect of MIL-T-29019.

1. SCOPE

1.1 This specification covers the requirements for a panel-mounted, enlarged scale sectionalized mockup of a single diaphragm type automotive fuel pump demonstrator.

1.1.1 This item has been designated by the Naval Training Device Center as Device 29EX1B for Navy procurement.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bid or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Military

MIL-T-29019	Training Aid, Demonstrator, Automotive Equipment, General Specification for

DRAWINGS

Naval Training Device Center (NAVTRADEVCEN)

DL 640470	Training Aid, Automotive Fuel Pump Demonstrator

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

FSC 6910

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:22Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials.- Materials shall be as specified in the engineering drawings of NAVTRADEVCEN DL640470 selected to meet the materials requirements of MIL-T-29019.

3.2 Design.- The training aid shall be a scale mockup of a single diaphragm type automotive fuel pump as shown on the drawings of 3.1.

3.3 Construction.- Except as specified in 3.1.1 through 3.3.3, construction shall be in accordance with the drawings of 3.1.

3.3.1 Controls.- In addition to the control handle mounted on the simulated cam shaft, there shall be an additional control (crank) mounted on the rear of the panel. The crank shall have the same throw as the front control handle and shall be located 24 inches above the cam shaft. The additional control shall be connected to and be of the same construction as the controls for the front operation. The sprocket ratio shall be 1:1.

3.3.2 Markings.- The construction of nomenclature plates and discs shall be as specified in MIL-T-29019.

3.3.3 Dust cover.- A dust cover shall be fabricated of 16 ounce, light gray vinyl-covered nylon to cover the training aid, excluding the base, when not in use. Covering material used shall be compatible with all finishes of the training aid so that no migrating solvents, contained within the material, will adversely affect any part of the training aid.

3.4 Performance.- The training aid shall be capable of demonstrating the sequence of events, in order, as occurring in operational fuel pumps.

3.5 Details of components.- The training aid shall consist of the following major components. Except as specified in 3.3.1 through 3.3.3, the details of components shall be in accordance with the drawings of 3.1.

(a) Sectionalized mockup

(b) Panel and stand

(c) Nomenclature plates

(d) Dust cover.

3.6 Dimensions and tolerances.- Dimensions and tolerances shall be as specified on the drawings of 3.1.

3.7 Finish and color.- Finish and color shall be as specified on the drawings of 3.1 selected to meet the finish and color requirements of MIL-T-29019.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:22Z
Check the source to verify that this is the current version before use.

3.8 Nameplates or product markings.- Nameplates and product markings shall be as specified on the drawings of 3.1.

3.9 Nomenclature plates.- The following components and areas shall be identified, in the terminology listed, with discs and a legend plate in accordance with MIL-T-29019.

(a) Cam shaft

(b) Rocker arm assembly

(c) Rocker arm housing

(d) Rocker arm follower spring

(e) Diaphragm

(f) Diaphragm pull rod assembly

(g) Diaphragm spring

(h) Bowl

(i) Bowl gasket

(j) Filter screen

(k) Inlet valve assembly

(l) Discharge valve assembly

(m) Bowl retainer assembly.

3.10 Workmanship.- The training aid shall be constructed and finished in accordance with the workmanship requirements of MIL-T-29019.

4. QUALITY ASSURANCE PROVISIONS

4.1 Quality assurance provisions shall be in accordance with the quality assurance provisions of MIL-T-29019.

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery shall be in accordance with the preparation for delivery requirements of MIL-T-29019.

6. NOTES

6.1 Intended use.- The training aid will be used in classrooms to assist military personnel in understanding the configuration, relative size and locations of major components of a single diaphragm type fuel pump.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:22Z
Check the source to verify that this is the current version before use.

6.2 Ordering data.- The ordering data considerations of MIL-T-29019 are applicable.

CUSTODIAN:
Navy-TD

PREPARING ACTIVITY
Navy-TD
Project No. 6910-N256

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:22Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)* | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT
$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)* | DATE

DD, FORM 1426 APR 63 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:22Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

Commanding Officer
Naval Training Device Center
Specifications Control Office, Code 301
Orlando, Florida 32813

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:22Z
Check the source to verify that this is the current version before use.