INCH-POUND

MIL-T-27/224B
20 April 1993
SUPERSEDING
MIL-T-27/224A
7 October 1987


MILITARY SPECIFICATION SHEET


TRANSFORMER, POWER, STEP-DOWN, TF5T03ZZ

(B) Inactive for new design after the date of this specification

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation MIL-T-27





WORKING VOLTAGE 120 Vrms
ALTITUDE 70L FT, MAX
CIRCUIT DIAGRAM AND MARKING

Inches	mm
002	0 05
01	0 3
02	0 5
032	0 81
0625	1 588
164	4.17
.218	5 54
25	6 4
305	7 75
500	12.70
1 437	36.50
1 875	47 62
1 968	49 99
2 187	55 55
2 625	66 68

NOTES
1. Dimensions are in inches
2. Metric equivalents are given for information only
3. Marking shall be on side of the case

FIGURE 1. Dimensions and configurations

(B) denotes changes

AMSC N/A

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:54Z
Check the source to verify that this is the current version before use.

REQUIREMENTS (When numbers in parentheses, i e , (1 2) are used, they indicate the winding and the extreme terminals of the windings)

Electrical ratings

Primary voltage (1-2) 107 volts, 400 Hz ±20

Primary current (1-2) 2 amperes

Voltamperes 214 voltamperes

Secondary voltage

(3-5) 49 volts ct
(6-7) 5.76 volts
(7-8) 8 24 volts

Secondary current

(3-5) 0 010 ampere
(6-7) 30 amperes
(7-8) 2 14 amperes

Working voltage 120 volts rms

Design and construction

Dimensions and configuration See figure 1

Duty cycle Continuous

Case Encapsulated

Terminals, solder 1, 2, 3, 4, and 5 shall be Malco no 2309 or equivalent and terminals 6 and 7 shall be .375 x .0625 x 1 500 flat copper lug and terminal 8 shall be Zierick no 179 or equivalent

Terminal height Not to exceed case height

Weight 18 5 ounces maximum

Altitude 70,000 feet maximum

Operating temperature range -55°C to +170°C

Terminal strength MIL-STD-202, method 211, test condition A, 5 pounds

Dielectric withstanding voltage

At sea level 1,000 volts rms
At barometric pressure 300 volts rms

Electrical characteristics

No load With 107 volts rms, 400 Hz across (1-2), the current in (1-2) shall not exceed 2 amperes and the power in (1-2) shall not exceed 215 watts

Voltage across

(3-5) 49 volts ±10 percent
(6-7) 5 76 volts ±10 percent
(7-8) 8 24 volts ±10 percent

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:54Z
Check the source to verify that this is the current version before use.

Rated load With 107 volts rms, 400 Hz across (1-2), the voltage across

(3-5) 49 volts ct ±10 percent
(6-7) 5 76 volts ±10 percent
(7-8) 8 24 volts ±10 percent

DC resistance

(1-2) 0.8 ohm, maximum
(3-5) 20 ohms, maximum
(6-7) 0 025 ohm, maximum
(7-8) 0 25 ohm, maximum

Polarity Additive, with terminals 2 and 3, and 5 and 6 connected

Temperature rise 99°C with 107 volts rms, 400 Hz across (1-2) at an ambient temperature of 71°C

(B) Quality assurance provisions

Qualification inspection Not applicable for this specification sheet

Quality conformance inspection Groups A and B tests of MIL-T-27 shall be applicable

Marking location See figure 1

Part or Identifying Number (PIN) M27/224-01

CONCLUDING MATERIAL

Custodians
Army - ER
Navy - EC
Air Force - 85

Review activities
Army - MI
Navy - OS, SH
Air Force - 17, 99
DLA - ES

User activities
Army - AR, ME
Navy - AS, MC
Air Force - 19

Preparing activity:
Army - ER

Agent
DLA - ES

(Project 5950-0815-26)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:54Z
Check the source to verify that this is the current version before use.