MILITARY SPECIFICATION

ACTUATOR, PISTON, PA532
LOADING, ASSEMBLING, AND PACKING

This Specification is approved for use within the US Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification contains requirements not normally covered by the drawings, and provides quality assurance provisions for the fabrication of parts, assembling, and packing for one type of piston actuator designated as Actuator, Piston, PA532.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

TT-I-1795 - Ink, Marking, Stencil, Opaque. (Porous and Non-Porous Surfaces)

MILITARY

MIL-P-116 - Preservation-Packing, Methods of.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament Munitions and Chemical Command, Attn. AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1345
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

MIL-B-117 - Bag, Sleeve and Tubing - Interior, Packing.
MIL-P-22264 - Powder, Ignition, Gasless, A-1A
MIL-G-45204 - Gold Plating, Electrodeposited
MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspections By Attributes.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

PRODUCT AND PACKAGING DRAWINGS

8796522 - Marking Diagram and Sealing for Wood Packing Boxes.
12631047 - Piston, Actuator, PA532.

INSPECTION EQUIPMENT DRAWING

12631059 - Piston, Actuator, PA532 Test Fixture Assembly.

"(Copies of specifications, standards, handbooks, drawings, publications , and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)"

2.1.3 Other publications. The following documents forms a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

CODE OF FEDERAL REGULATIONS

Title 49 - Transportation, Parts 100-177

(The Code of Federal Regulations is available from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402. Orders should specify, "49 CFR 100-177 (latest revision)".)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings, specifications and standards.

3.2 Assembly. The assembly shall comply with all requirements specified on Drawing (Dwg.) 12631047 and all associated drawings and with all requirements specified in applicable specifications and standards.

3.3 Moisture content ignition powder. The moisture content at the time and place of loading the actuator shall not exceed 0.20 percent when tested as specified in 4.4.3.1.

3.4 Functioning tests- sensitivity and output.

3.4.1 No-fire test. The piston actuator, after being conditioned at 70° ± 10°F for two hours minimum, shall not exhibit any signs of the output requirements of 3.4.2 after being exposed to the no-fire stimulus specified in 4.5.2.1.

3.4.2 All-fire output test. The piston actuator, after being conditioned at 70° ± 10°F for two hours minimum, shall function on the first attempt, shall shear a .050 inch diameter aluminum pin, travel a minimum (min.) of .200 inch, and not shear the .080 inch diameter stop pin when tested as specified in 4.5.2.2.

3.5 Environmental conditioning.

3.5.1 Resistance between electrode and cup, thermal shock,vibration and function. The piston actuator shall comply with the resistance requirement of Dwg. 12631047, with the output requirements of 3.4.2 and shall function on the first attempt after being exposed to thermal shock and vibration when tested as specified in 4.5.3.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

3.5.2 Waterproofness. The actuator shall comply with the output requirements of 3.4.2 after being submerged in water to a minimum depth of 2 inches for not less than 48 hours, at a temperature of 70° ± 10°F when tested as specified in 4.5.3.2.

3.5.3 Cold temperature. The piston actuator assembly shall comply with the output requirements of 3.4.2 after being conditioned at minus 65° - 5°F for two hours minimum and tested as specified in 4.5.3.3.

3.5.4 Hot temperature. The piston actuator assembly shall comply with the output requirements of 3.4.2 after being conditioned at 160° + 5°F for two hours minimum and tested as specified in 4.5.3.4.

3.6 First article inspection. This specification contains technical provisions for first article inspection. Requirements for submission of first article samples shall be specified in the contract.

3.7 Workmanship. All parts and assemblies shall be fabricated and assembled in a thorough, workmanlike manner, and all manufacturing, processing, and assembling operations shall be correctly performed. All parts and assemblies shall be clean, free of burrs, sharp edges, cracks, dirt, grease, rust and other foreign matter that may impair proper functioning. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents. All required markings and stampings shall be neat and sharply defined. Required packing shall be dry.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item.

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in the quantities as indicated.

PART DESCRIPTION	DRAWINGS	QUANTITY
Cup	12631048	25
Bridge Plug and Ignition Assy.	12631053	25
Plug Assembly	12631055	25
Header	12631057	25
Piston	12631050	25
Actuator, Piston, PA532	12631047	200

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I as specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS MIL-A-48690(AR)

PARAGRAPH	TITLE: PA352 Piston Actuator and Components		SHEET 1 OF 2		DRAWING NUMBER: See Below NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cup (Dwg. 12631048)				
	Examination for defects	25		3.2	4.4.2.1
	Bridge Plug and Ignition Assembly (Dwg.12631053)				
	Examination for defects	25		3.2	4.4.2.2
	Plug Assembly (Dwg. 12631055)				
	Examination for defects	25		3.2	4.4.2.3
	Insulation resistance between electrode and header of plug assembly	25		3.2	4.5.5
	Pull test of electrode	25	0-1	3.2	4.5.8
	Header (Dwg. 12631057)				
	Examination for defects	25		3.2	4.4.2.4
	Piston (Dwg. 12631050)				
	Examination for defects	25		3.2	4.4.2.5

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-48690(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
	PA532 Piston Actuator and Components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Actuator, Piston, PA532 (Dwg.12631047)	200			
	Examination for defects	1/		3.2	4.4.2.7
	Functioning tests-sensitivity and output				
	(a) No-fire test	1/	0-1	3.4.1	4.5.2.1
	(b) All-fire output test	75,2/	0-1	3.4.2	4.5.2.2
	Environmental tests				
	(a) Resistance between electrode and cap, thermal shock, vibration, and function	50,2/	0-1	3.5.1	4.5.3.1
	(b) Waterproofness test	25,2/	0-1	3.5.2	4.5.2.2
	(c) Cold test	25,2/	0-1	3.5.3	4.5.3.3
	(d) Hot test	25,2/	0-1	3.5.4	4.5.3.4

NOTES: 1/ The entire quantity of piston actuators shall be subjected to the specific examination/test prior to testing.
2/ Samples for this test shall be taken from no-fire test samples.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formations. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. (See MIL-A-48078). Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-48690(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12631048
4.4.2.1	Cup				NEXT HIGHER ASSEMBLY 12631047
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness of bottom		0.40%	3.2	Gage
102	Outside diameter (O.D.)		0.40%	3.2	Gage
103	True piston of electrode hole incorrect		0.40%	3.2	Gage
104	Overall Length		0.40%	3.2	Gage
105	Cup dented, distorted, or otherwise damaged		0.40%	3.2	Visual
Minor					
201	Inside diameter, min.		0.65%	3.2	Gage
202	Poor workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-48690(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Bridged Plug and Ignition Assembly				12631053
					NEXT HIGHER ASSEMBLY 12631047
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Spot charge missing		0.40%	3.2	Visual
102	Cracks or voids in spot charge		0.40%	3.2	Visual
103	LMNR composition missing or does not cover spot charge completely		0.40%	3.2	Visual
104	Ignition material on outside of plug		100%	3.2	Visual
Minor					
201	Poor workmanship		1.0%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-48690(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Plug Assembly				12631055
					NEXT HIGHER ASSEMBLY 12631054
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pull test of electrode	50	0-1	3.2	4.5.8
102	Insulation resistance test		100%	3.2	4.5.5
103	Outside diameter		0.40%	3.2	Gage
104	Plating improper	1/	1/	3.2	4.5.7
105	Glass pellet cracked		0.40%	3.2	Visual
106	Length of exposed pellet, max		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.7	Visual

NOTES:

1/ Sampling and rejection shall be in accordance with MIL-G-45204.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-48690(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Header				12631057
					NEXT HIGHER ASSEMBLY 12631055
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Small inside diameter (I.D.)		0.40%	3.2	Gage
102	True position of large I.D.		0.40%	3.2	Gage
103	True position of small outside diamter (O.D.)		0.40%	3.2	Gage
104	Overall length		0.40%	3.2	Gage
105	Length of small O.D.		0.40%	3.2	Gage
Minor					
201	Large O.D.		0.65%	3.2	Gage
202	Small O.D.		0.65%	3.2	Gage
203	Poor workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-48690(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Piston				12631050
					NEXT HIGHER ASSEMBLY 12631049
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Overall length		0.40%	3.2	Gage
102	Length of cavity		0.40%	3.2	Gage
103	Outside diameter		0.40%	3.2	Gage
104	Inside diameter		0.40%	3.2	Gage
105	Surface finish of outside diameter improper		0.40%	3.2	Gage
Minor					
201	True position of inside diameter		0.65%	3.2	Gage
202	Poor workmanship		1.0 %	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-48690(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Actuator, Piston, PA532				12631047
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Cup cracked or split		100%	3.2	Visual
2	Explosive on exterior of cup		100%	3.2	Visual
Minor					
101	Length of electrode		0.40%	3.2	Gage
102	Length, sealed end to base		0.40%	3.2	Gage
103	Diameter of cup		0.40%	3.2	Gage
104	Resistance between electrode and cup		0.40%	3.2	Gage,4.5.6
105	Sealant not present 360°F		100%	3.2	Visual
106	Presence of sealant on electrode beyond sealed area		0.40%	3.2	Visual
107	Sensitivity - no-fire	200	0-1	3.4.1	4.5.2.1
108	Functioning - all-fire	2/	0-1,1/	3.4.2	4.5.2.2
109	Environmental test				
	(a) Resistance between electrode and cup, thermal shock,vibration and function	50	0-1	3.5.1	4.5.3.1
	(b) Waterproofness	25	0-1	3.5.2	4.5.3.2
	(c) Cold temperature conditioning	25	0-1	3.5.3	4.5.3.3
	(d) Hot temperature conditioning	25	0-1	3.5.4	4.5.3.4
Minor					
201	Poor workmanship		1.0%	3.7	Visual

NOTES:
1/ Any actuator that fails to function on first attempt or fails to produce the required output shall be classed defective.
2/ Samples from this test shall be taken from no-fire samples.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.3.1 Moisture content of ignition powder. The contractor shall provide adequate controls to ensure compliance with the requirement of 3.3 and shall test for verification one (1) sample of material from each eight (8) hours of production in accordance with 4.5.1. Composite samples shall not be used. If the moisture content of a sample exceeds the requirements and loading has not begun, that quantity of material represented by the sample shall be rejected. If the piston actuators have been loaded with material containing excessive moisture, the remaining material that is represented by the sample, together with all piston actuators loaded with the non-conforming material, shall be rejected.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6. herein.

4.5 Methods of inspection.

4.5.1 Moisture content ignition powder. The moisture content shall be determined in accordance with MIL-P-22264. Observation shall be made for compliance with the applicable requirement.

4.5.2 Functioning tests- sensitivity and output.

4.5.2.1 No-fire test. The piston actuator, maintained at the conditioning temperature, shall be subjected to the specified no-fire voltage by discharging a capacitor across the bridge circuit in accordance with the requirements of Dwg. 12631047. Any sample which fails to comply with the requirement of 3.4.1 shall be classed defective and shall cause the lot to be rejected. (Non-destructive test).

4.5.2.2 All-fire output. The piston actuator,maintained at the conditioning temperature, shall be assembled in the specified test fixture (Dwg. 12631059) and subjected to the specified all-fire voltage by discharging a capacitor across the bridge circuit in accordance with the requirements of Dwg. 12631047. Observation shall be made for compliance with the requirements of 3.4.2. Any sample which fails to fire on the first attempt shall be classed defective. (Destructive test).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

4.5.3 Environmental tests.

4.5.3.1 Resistance between electrode and cup, thermal shock, vibration, and function. The piston actuators shall be tested as follows, in the sequence specified, using approved equipment:

a. Measure resistance between the electrode and cup in accordance with 4.5.6.

b. Condition for two (2) hours minimum at minus 65° -5°F.

c. Remove from cold chamber and within 20 seconds transfer to a hot chamber at 160° + 5 °F.

d. Condition for two (2) hours minimum at 160° + 5°F and 20 % maximum relative humidity.

e. Remove from hot chamber and immediately transfer to the vibrator.

f. Vibrate for 15 minutes, minimum, in a sweep covering a frequency range of 25-500-25 cycles per second, parallel to the transverse orthogonal axis, with output end down and a 2 ± 0.2 G's peak amplitude.

g. Measure resistance between electrode and cup in accordance with 4.5.6.

h. The piston actuators shall be tested as specified in 4.5.2.2. Any piston actuator which fails to comply with the applicable requirement shall be classed defective. (Destructive test)

4.5.3.2 Waterproofness . The piston actuator assemblies shall be immersed in water at a two (2) to three (3) inch depth for 48 hours, minimum at the conditioning temperature. At the end of the immersion time, the piston actuator assemblies shall be removed from the water, tested according to 4.5.2.2, and observed for compliance with the requirements of 3.4.2. Any sample which fails to comply with the applicable requirements shall be classed defective. (Destructive test)

4.5.3.3 Cold temperature. The piston actuator assemblies, maintained at the conditioning temperature, shall be functioned as specified in 4.5.2.2. (Destructive test).

4.5.3.4 Hot temperature. The piston actuator assemblies, maintained at the conditioning temperature, shall be functioned as specified in 4.5.2.2. (Destructive test).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

4.5.4 Resistance between electrode and header. The bridge assembly shall be connected to the equipment and the bridge resistance shall be measured when a current limited to one (1) milliampere is applied. Any bridge assembly that fails to comply with the drawing requirement shall be classed defective and removed from the lot. (Non-destructive test)

4.5.5 Insulation resistance between electrode and header of plug assembly. The required D.C. voltage shall be applied to the plug assembly between the electrode and the header for not less than one or more than two seconds. If the resistance measures less than the specified resistance, the plug assembly shall be classed defective and removed from the lot. (Non-destructive test)

4.5.6 Resistance between electrode and cup. The piston actuator assembly shall be connected to the equipment and the resistance shall be measured between the electrode and the cup when a current limited to one (1) milliampere is applied. Any actuator assembly that fails to comply with the drawing requirement shall be classed defective and removed from the lot. (Non-destructive test)

4.5.7 Plating of electrodes. The plating shall be verified within the applicable drawing requirement. (Test samples shall not be returned to the lot).

4.5.8 Pull test of electrode of plug assembly. The plug assembly shall be tested in accordance with the applicable drawing requirements. (Destructive test).

5. PACKAGING

5.1 Preservation and packaging.

5.1.1 Level B. Piston actuators shall be packaged in accordance with Code of Federal Regulations Title 49, Para 100-177. In addition, each actuator shall be electrically shorted during shipment and storage by means of a metallic connection between the electrode and cup. When destined for shipment and uncovered storage in excess of 180 days from the loading date shown on the packing box to the date of the assembly into the end item, the following shall be included:

Each intermediate carton, set-up box or comparable container, after blunting corners, shall be placed in a water and vapor proof bag manufactured in accordance with Type I, Class E of MIL-B-117. The bag shall be closed. All excess air shall be exhausted from within the bag and the bag then sealed in accordance with the manufacturer's instructions. The seal shall be located at the edge of the bag to provide for a minimum of two (2) subsequent seals, if required. The seal shall comply with the heat seal requirements of MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

5.1.3 Level C. Unless otherwise specified, the piston actuator shall be packaged in accordance with 5.1.1, except that the barrier bag is not required.

5.2 Packing.

5.2.1 Level B. A suitable number of piston actuators packaged as specified in 5.1.1, shall be packed in an outer box in accordance with Code of Federal Regulations Title 49: Transportation of Explosives and Other Dangerous Articles, Paragraph 173.66.

5.2.2 Level C. Unless otherwise specified, piston actuators shall be packed as specified in 5.2.1.

5.3 Marking. Each inner container and intermediate carton set-up box or comparable container shall be printed, stamped or labeled and each barrier bag printed or stamped in accordance with the following information and instructions:

a. (Number) Actuator, Piston, PA532:
Lot NO. Date Packed (Mo/Yr)

b. All letters shall be upper case. Size of letters and numerals shall be a minimum of 1/4 inch high applied with black waterproof ink. Stencil ink shall conform to TT-I-1795.

c. Printing and labeling shall be commerical type. Labels shall be on white gummed paper.

d. Exterior boxes shall be marked in accordance with Dwg. 8796522. The DOT designation shall be: Electric Blasting Caps - Handle Carefully (see NOTE).

e. NOTE: " The number of caps packed in one (1) outer pack shall be shown in the marking."

6. NOTES

6.1 Intended use. The Actuator, Piston, PA532 is intended for use in munition assemblies.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment design for approvals. (See MIL-A-48078.) Submit equipment designs as required to Commander, US Army Armament Research, Development and Engineering Center, ATTN: AMSMC-QAT-I(D), Dover, New Jersey 07801-5001.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

6.4 Distribution of ammunition data cards, inspection and test results. Distribution of data cards, inspection, and test results shall include the following: Commander, US Army Armament Research, Development and Engineering Center, ATTN: AMSMC-QAT-M(D), Dover, New Jersey 07801-5001.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, ARRADCOM, or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.6 Subject term (key word) listing.
Actuator
Piston
Sensitivity
Output
No-fire
All fire
Resistance
Quality
Electrode

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A367)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.