INCH-POUND

MIL-C-48156 (AR)
AMENDMENT 5
4 February 1993
SUPERSEDING
AMENDMENT 4
27 May 1992

MILITARY SPECIFICATION

CARTRIDGE, IGNITION, XM299
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of MIL-C-48156 (PA), dated 01 September 1974, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 2.1, Add new military specification as follows:

"MIL-P-60312 - Parts, Molded, Plastic Foam, Polystyrene (For use with ammunition)"

Delete under Federal Specifications: "L-T-90 - Tape, Pressure Sensitive"

PAGE 3

* 3.7, Delete paragraph in its entirety.

PAGE 5

* 4.4.1.e, Change to read as follows:

"Heat shrinkable tubing from not more than one lot from one manufacturer."

PAGE 6

* 4.3.2.1, Critical 1, change "tape" to "heat shrinkable tubing."

AMSC N/A FSC 1315

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

PAGE 7

* 4.3.2.2, Delete majors 132, 133 in their entirety.

Major 134, change to read as follows:

"Length of tubing overlap, min."

Major 135, change to read as follows:

"Tubing missing, loose, wrinkled, separating or inadequately covering external surface ...0.40% ...3.2 ...Visual/manual."

PAGE 8

4.3.2.3, Add Critical 3 which reads:

"3. Firing plug above flush with head surface ...100% ...3.2 ... Gage

Add new Major and note a. at bottom of page as follows:

"Major 104 Environmental conditions inadequate .../a ...3.2 ...Gage.

a. Temperature and humidity shall be checked at the beginning and end of each shift. If conditions are not proper at either time, the quantity of product represented by the conditioning shall be rejected."

Major 132: Delete in its entirety and substitute:

"132 Percussion primer above flush (max) of body ...100%... 3.2 ...Gage"

Major B, Add new major:

"137 Stakes missing ...0.40% ...3.2 ...Visual"

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:15Z
Check the source to verify that this is the current version before use.

PAGE 10

4.3.2.4, Major category:

Major 101: Add new defect which reads as follows:

"101 Environmental conditions inadequate .../a ...3.2 ...Gage."

Major B, 133: Delete in its entirety.

Major 135: Delete in its entirety.

Major 136: Delete in its entirety and substitute:

"136 Position of outside diameter to major diameter of threads ...0.40% ...3.2 ...Gage."

Note a: Add note a. which reads as follows: "a. Temperature and humidity shall be checked at the beginning and end of each shift. If conditions are not proper at either time, the quantity of product represented by the conditioning shall be rejected."

PAGE 11

* 4.3.2.5, Add new major 101 and notes (a) (b) as follows:

"101 Moisture content excessive (a) (b) 5.1 (a) (b)"

(a) Requirement and inspection procedure shall be per MIL-P-60312. Two (2) samples shall be randomly selected from a quantity of trays for scheduled production for five (5) consecutive shifts. If one or more samples are defective, the quantity of trays represented by the samples shall be rejected. Inspection shall be accomplished within 24 hours of scheduled use of the trays.

(b) Moisture content determination not required when this packing material is stored in an environmentally controlled area maintained at 40% Max Relative Humidity (R.H.) @ 72 degrees F for at least 24 hours prior to using."

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:15Z
Check the source to verify that this is the current version before use.

PAGE 12

4.3.2.6, Add new Majors and notes as follows:

"101	Moisture content excessive for any packaging component (4 items)	(a)	5.1	Gage
102	Environmental conditions inadequate	(b)	5.1	Gage"

"(a) Components shall be inspected prior to use every hour during the production shift. If any sample exceeds the requirement, the inspection lot shall be rejected from further processing.

(b) Temperature and humidity shall be checked at the beginning and end of each shift. If conditions are not proper at either time, the quantity of product represented by the conditioning shall be rejected for further processing."

PAGE 18

* 4.4.3.5, Delete paragraph in its entirety and substitute:

"4.4.3.5 Leak test (see 3.5). Sixty (60) ignition cartridges from each day's production shall be leak tested as specified in 4.5.3. If more than 3 failures occur, that day's production shall be 100% screened.

PAGE 19

* 4.4.3.8, Delete paragraph in its entirety.

4.5.3, Add at the beginning of the paragraph as follows:

"After the ignition cartridges have been assembled and the RTV is applied, the ignition cartridges will be kept in the controlled environmental storage for two (2) hours minimum prior to performing the leak test."

PAGE 21

* 4.5.7, Delete paragraph in its entirety.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:15Z
Check the source to verify that this is the current version before use.

NOTE: The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1315-AE57)

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:15Z
Check the source to verify that this is the current version before use.