INCH-POUND

MIL-C-60255(AR)
AMENDMENT 2
1 February 1991
SUPERSEDING
AMENDMENT 1
30 March 1970

MILITARY SPECIFICATION

CASE, TELESCOPE; M164

This Amendment forms a part of Military Specification MIL-C-60255 (MU), dated 5 November 1965, and is approved for use within the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 2.1, Standards: Add "MIL-STD-810".

* 2.1, Packaging data sheet: Delete "MIL-P-14232".

PAGE 2

* 3.3: Delete and substitute:

"3.3 General specification. The contractor shall be responsible for the compliance with the requirements of specification MIL-F-13926."

* 3.4.1: Delete and substitute:

"3.4.1 Storage temperatures. The case shall show no evidence of physical failure after having been exposed to, and thermally stabilized at, ambient temperature of -80 degrees F (-62 degrees C) +/- 5 degrees F (+/- 2 degrees C) and +160 degrees F (+71 degrees C) +/- 5 degrees F (+/- 2 degrees C). Subsequent to the above temperature changes the case shall meet the requirements of 3.5 at standard ambient temperature."

* 3.4.2: Delete and substitute:

"3.4.2 Standard ambient temperature. The case shall meet all performance requirements, 3.5, of this specification at a standard ambient temperature between +60 degrees F (+16 degrees C) and +90 degrees F (+32 degrees C), except as otherwise noted."

AMSC N/A FSC 1290

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:23Z
Check the source to verify that this is the current version before use.

* 3.4.3, line 3: Delete: "-65 degrees F and +150 degrees F." and substitute "-65 degrees F (-54 degrees C) +/- 5 degrees F (+/- 2 degrees C) and +150 degrees F (+66 degrees C) +/- 5 degrees F (+/- 2 degrees C)."

* 3.4.4: Delete and substitute:

"3.4.4 Rain exposure. The interior of the case shall show no evidence of leakage or moisture after the latched case has been exposed to the rain test, section I, procedure I, 506.2, MIL-STD-810, under the following test conditions:

a. The temperature of the item under test shall be 10 degrees C (18 degrees F) +/- 1 degree C (+/- 2 degrees F) higher than the rain temperature at the start of each exposure.

b. Rainfall shall be 4 +/- .4 inches/hour.

c. Wind velocity shall be 40 +/- 4 miles/hour.

d. Exposure shall be horizontal, hinge up, for 30 +/- 3 minutes and vertical for 30 +/- 3 minutes."

3.4.5: Delete: "4 pound" and substitute "2 pound".

PAGE 4

* 4.3.2: Add:

"105 Fabrication	3.2	Applicable drawing Visual
106 Packaging	5.1	4.7"

* 4.4.1: Delete in its entirety.

* 4.4.2, 305: Delete "Water immersion" and substitute "Rain exposure".

PAGE 5

* 4.6.1.1: Delete and substitute:

"4.6.1.1 Storage temperatures. The case shall be exposed to temperatures specified in 3.4.1 in accordance with procedure II of MIL-F-13926, except that soak time shall be 2 hours, and temperature shall be reduced and increased at a rate that will not cause thermal shock, or fractures to the item under test. After exposure, the case shall show no evidence of damage and shall meet the requirements of 3.4.1. This test can be performed concurrently with 4.6.1.2 in accordance with procedure I of MIL-F-13926."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:23Z
Check the source to verify that this is the current version before use.

* 4.6.1.2: Delete and substitute:

"4.6.1.2 Extreme operating temperatures. The case shall be exposed to the temperatures specified in 3.4.3 in accordance with procedure I of MIL-F-13926, except that soak time shall be 2 hours and temperature shall be reduced and increased at a rate that will not cause thermal shock or fractures to the item under test. While exposed to these temperatures the case shall meet the requirements of 3.5. This test can be performed concurrently with 4.6.1.1."

* 4.6.1.3: Delete and substitute:

"4.6.1.3 Rain exposure. This test shall be performed in accordance with rain test, section II, procedure I, 506.2, MIL-STD-810, and shall show no evidence of leakage or moisture to meet the requirements of 3.4.4."

* Add new 4.7:

"4.7 Packaging inspection. The preservation, packaging and marking shall be inspected to verify conformance to the requirements of 5.1."

* 5.1, line 3: Delete "MIL-P-14232/".

*The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evalutate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

Project (1290-A460)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:23Z
Check the source to verify that this is the current version before use.