MIL-I-60867(MU)
7 October 1968
SUPERSEDING
FA-PD-MI-2429, Rev. 1
16 May 1961

MILITARY SPECIFICATION
INITIATOR, CARTRIDGE ACTUATED: DELAY, M51 ASSEMBLY

1. SCOPE

1.1 This specification covers Initiator, Cartridge Actuated, Delay, M51 Assembly, loaded with Cartridge, Initiator, Delay, M89, for use with other propellant actuated devices in aircrew emergency escape systems.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-A-2550	- Ammunition and Special Weapons, General Specification For

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-414	- Sampling Procedures and Tables for Inspection by Variables for Percent Defective
MIL-STD-1167	- Ammunition Data Card
MS28741	- Hose Assembly, Detachable End Fitting, Medium Pressure, Size No. 4

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:02Z
Check the source to verify that this is the current version before use.

2.1 (Cont'd)

DRAWINGS

Munitions Command

F8597920	- Initiator, Cartridge Actuated, Delay, M51 Assembly
C8846788	- Box, Packing, Ammunition, For Initiator, Cartridge Actuated, Delay, M51 in Fiber Container M458
C8846787	- Container, Ammunition, Fiber, M458 for Initiator, Cartridge Actuated, Delay, M51
IEL-8597920	- Inspection Equipment List for Initiator, Cartridge Actuated, Delay, M51 Assembly

(Copies of specifications, standards and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General.- Materials, parts and assemblies shall comply with the requirements specified on the applicable drawings and referenced specifications.

3.2 Breakaway torque.- The chamber and cap of the assembled initiator shall withstand a breakaway torque application of 400 inch-pounds without loosening or deformation.

3.3 Residual magnetism.- The initiator shall not deflect the indicator of an approved compass more than 3 degrees in either direction when passed in front of the compass at a distance of 6 inches.

3.4 Functional.

3.4.1 Ballistics.- Initiators loaded with accepted cartridges and temperature conditioned shall produce pressure values specified in Table I. Pressure values shall be recorded at the end of 15 feet of aircraft hose, Size No. 4, in accordance with MS28741.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:02Z
Check the source to verify that this is the current version before use.

3.4.1 (Cont'd)

TABLE I

Temperature	Pressure (PSI)	Ignition Delay (See 6.3)
-65° to -70°F	500 - 1500	2.50 seconds, max.
65° to 75°F	575 - 1500	2.0 ± 0.2 seconds
160° to 165°F	625 - 1500	1.60 Seconds, min.

3.4.1.1 Initiation.- The initiator shall be fired by a source delivering an output equal to that of an M3A2 Initiator at the end of 15 feet of Aircraft Hose, size No. 4, MS28741, at 70° ± 5°F.

3.4.2 The initiator shall not fail to fire.

3.4.3 The initiator shall function without mechanical failure (See 6.2).

3.5 Workmanship.- The requirements for workmanship are as specified on the applicable drawings, referenced specifications and the following:

3.5.1 Metal defects.- The part shall be free from cracks, splits, cold shuts, inclusions, porosity or other metal defects.

3.5.2 Burr.- The part shall not have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.5.3 Foreign matter.- The part or assembly shall not contain chips, dirt, grease, rust, corrosion or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.- Reference shall be made to MIL-STD-109 to define quality assurance terms used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:02Z
Check the source to verify that this is the current version before use.

4.1.2 Inspection.- Inspection shall be in accordance with MIL-A-2550.

4.2 Inspection provisions.

4.2.1 Lot.

4.2.1.1 Submission of product.- The product shall be submitted in accordance with MIL-STD-105.

4.2.1.2 Size of lot.- A lot shall consist of an identifiable group of assembled units containing metal parts assemblies produced by a homogeneous process and loaded with accepted cartridges.

4.2.2 Examination.- One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects, using the sampling plan and associated criteria in Table II. All nonconforming material shall be rejected. The total number of allowable defects per class for either the major or minor classification shall not exceed the acceptance number of Table II. Four power (4X) magnification may be used for inspection of such defects as burr and foreign matter.

TABLE II

Lot Size	Sample Size	Major		Minor	
		Accept	Reject	Accept	Reject
1 - 300	100% Examination	-	-	-	-
301 - 800	50	0	1	1	2
801 - 1800	90	1	2	2	3

4.2.2.1 Cartridge, Initiator, Delay, XM89, Drawing D10519995, covering a detail of Drawing F8597920.

Defect	Method of Inspection
CRITICAL	
1. Mixed cartridges	Visual
2. Metal defective	Visual
3. Marking missing, incorrect or illegible	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:02Z
Check the source to verify that this is the current version before use.

4.2.2.1 (Cont'd)

Defect	Method of Inspection
MAJOR	
101. Foreign matter	Visual
MINOR	
201. Case scratched, wrinkled, bulged or dented	Visual
202. Varnish missing or inadequate	Visual

4.2.2.2 Assembly, Drawing F8597920, less all drawings except D10520557, C10520474, B10520475, B10520496 and MS29513-9.

CRITICAL	
1. Firing pin protrusion	Gage
2. Shear pin not engaged in firing pin	Gage
3. Striker hole in initiator cap obstructed	Visual
MAJOR	
101. "O" ring not lubricated	Visual
102. Burr	Visual
103. Foreign matter	Visual
MINOR	
None defined	

4.2.2.3 Assembly, Drawing F8597920, less all drawings except D10520407, C10520414 and D10519995.

CRITICAL	
1. Cartridge not properly seated	Visual
2. Filter missing or insecure	Visual
3. Nylon patch missing or improperly applied	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:02Z
Check the source to verify that this is the current version before use.

4.2.2.3 (Cont'd)

Defect	Method of Inspection
MAJOR	
101. Burr	Visual
102. Foreign matter	Visual
MINOR	
None defined	

4.2.2.4 Assembly, Drawing F8597920

CRITICAL	
1. Cartridge face not seated against base of firing pin housing	X-Ray
2. Any part missing	X-Ray
3. Improper assembly	X-Ray
4. Marking missing, incorrect or illegible	Visual
MAJOR	
101. Set screw missing or insecure	Visual
102. Burr	Visual
103. Foreign matter	Visual
MINOR	
201. Thread sealing compound missing from set screws	Visual
202. Shipping cap or plug missing	Visual
203. Protective finish inadequate or defective	Visual

4.2.2.5 Fiber Container, Drawing C8846787.

CRITICAL

None defined

MAJOR

None defined

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:02Z
Check the source to verify that this is the current version before use.

4.2.2.5 (Cont'd)

Defect	Method of Inspection
MINOR	
201. Gap between body and cover, max.	Manual
202. Contents loose	Manual
203. Metal ends loose or distorted	Manual
204. Cut or damaged through all impregnated layers	Visual
205. Marking missing, incorrect or illegible	Visual
206. Tape incomplete or badly wrinkled	Visual
207. Length of tear tab, min.	Visual
208. Color of tape incorrect	Visual

4.2.2.6 Box, Packing, Drawing C8846788.

CRITICAL	
None defined	
MAJOR	
None defined	
MINOR	
201. Contents loose	Manual and Visual
202. Hardware missing, loose, broken or improperly engaged	Manual and Visual
203. Strapping missing, loose, broken or improperly assembled	Manual and Visual
204. Contents of box exposed	Visual
205. Box damaged	Visual
206. Marking missing, incorrect or illegible	Visual
207. Number of units incorrect	Visual
208. Car seal missing, unsealed or improperly positioned	Visual

4.2.3 Inspection testing.- The following tests shall be performed in accordance with 4.3.

4.2.3.1 Breakaway torque.- Each initiator shall be subjected to the breakaway torque application. Failure of any initiator to comply with the requirements of 3.2 shall be cause for rejection of the initiator.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:02Z
Check the source to verify that this is the current version before use.

4.2.3.2 Residual magnetism.- Each initiator shall be subjected to the test for excessive residual magnetism. Failure of any initiator to comply with the requirements of 3.3 shall be cause for rejection of the initiator.

4.2.3.3 Functional.- The following test shall be performed by the Government.

4.2.3.3.1 Ballistics.- Twenty-one units shall be tested to determine compliance with the requirements of 3.4.1, 3.4.2 and 3.4.3. The units shall be temperature conditioned as provided in Table III and 4.3.3.1.1. The variables sampling plan of MIL-STD-414, Example C-2 or C-3, as applicable for the AQL listed in Table III shall be used for each sample of 7 units. Failure of any unit to comply with the requirements of 3.4.1, 3.4.2 and 3.4.3 or failure of a sample to meet the criteria of the variable sampling plan shall be cause for rejection of the lot.

TABLE III

Temperature	Sample Size
-65° to -70°F	7
65° to 75°F	7
160° to 165°F	7

4.2.4 Inspection equipment.- The examination and tests shall be made using equipment approved by the Government.

4.3 Test methods and procedures.

4.3.1 Breakaway torque.- A torque wrench set at the torque requirement specified in 3.2 shall be used in conjunction with the fixture to determine the adequacy of the joint. The torque shall be applied to the cap.

4.3.2 Residual magnetism.- The initiator shall be tested for excessive residual magnetism in an area free of local magnetic effects by placing the initiator 6 inches from and at the same height as the compass, in a north-south horizontal position (cap end at south) with the compass set in an east-west heading. The initiator shall be moved slowly past the compass in a longitudinal direction for its entire length, rotated 90 degrees in the horizontal position about its longitudinal axis and moved slowly back past the compass. This procedure shall be repeated for each 90 degree rotation of the initiator.

4.3.3 Functional.

4.3.3.1 Ballistics.- The test sample shall be rigidly supported in the fixture. The sample shall be tested within 5 minutes after removal from the conditioning chamber. When this time limit is exceeded, the sample units shall be reconditioned in accordance with 4.3.3.1.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:02Z
Check the source to verify that this is the current version before use.

4.3.3.1.1 Temperature conditioning.- A standard M51 Initiator, loaded with a dummy M89 cartridge, containing a temperature sensitive element, shall be placed in the conditioning chamber at the same time as the samples. The conditioning time shall be a minimum of one hour longer than the time necessary to bring the element contained in the dummy cartridge to the required temperature.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking.- Packing and marking shall be in accordance with Drawings C8846787 and C8846788.

5.2 Data card.- Data card information shall be as specified in MIL-STD-1167.

6. NOTES

6.1 Ordering data.- Procurement documents should specify the title, number and date of this specification.

6.2 A mechanical failure is defined as any deformation or breakage of a part, the occurrence of which is other than a design function.

6.3 Ignition delay is defined as the time that elapses between the firing of the pressure element and the beginning of the continuous pressure rise on the pressure time record.

6.4 Supersession data.- This specification includes the requirements of Purchase Description FA-PD-MI-2429, Rev. 1 dated 16 May 1961.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1377-A232

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:02Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity).*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:02Z
Check the source to verify that this is the current version before use.

FOLD

Department of the Army

Frankford Arsenal
Philadelphia, Pa. 19137

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
Department of the Army

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-N1100
Philadelphia, Pa. 19137

FOLD

☆ U. S. GOVERNMENT PRINTING OFFICE: 1968-341-512/A-2025

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:02Z
Check the source to verify that this is the current version before use.