MIL-R-50068A

30 SEPTEMBER 1964

SUPERSEDING
MIL-R-50068(CmlC)
30 JUNE 1959

MILITARY SPECIFICATION

RING, CRIMPING (FOR ABC-M17 MASK)

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of crimping ring (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 **Government documents.** The following documents of the issue in effect on date of invitation for bids, or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

PPP-B-636 – Box, Fiberboard.

STANDARDS

MILITARY

MIL-STD-105 – Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-129 – Marking for Shipment and Storage.

DRAWINGS

EDGEWOOD ARSENAL

C5-2-975 – Ring, Crimping (Assembly and Bill of Material).

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials and components. All materials and components shall conform to specifications and drawings forming a part of this specification.

3.2 Manufacture. The crimping ring shall be manufactured as specified on Drawing C5-2-975.

FSC 4240

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:15Z
Check the source to verify that this is the current version before use.

3.3 Preproduction sample. Prior to the start of regular production a preproduction sample of five crimping rings shall be produced using the same methods, materials and equipment as will be used during regular production. Any change in materials, operating conditions or tools shall require a new preproduction sample.

3.4 Workmanship. The crimping ring shall be free from foreign matter and damage such as distortion, surface irregularities and dents which might impair use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to insure that supplies and services conform to specified requirements.

4.2 Special provisions.

4.2.1 *Alternative inspection.* The supplier may utilize any alternative inspection procedure which will provide equal or better assurance of quality by submitting a written proposal with justification and obtaining written approval from the Government prior to its institution. In case of dispute, the procedures of the specification will govern.

4.2.2 *Objective evidence.* The supplier shall provide objective evidence, acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2.3 *Inspection substation.* If the supplier elects to establish inspection substations for the purpose of conducting inspection for certain listed defects, the Acceptable Quality Levels (AQL's) for each inspection substation shall be equal to the AQL which is the next numerically lower value than the AQL specified for the total listed defects. The requirements of MIL-STD-105 are applicable to each substation and to the end item.

4.3 Preproduction sample inspection.

4.3.1 *Examination.* The sample crimping rings shall be inspected for all requirements of the drawings and this specification.

4.3.2 *Acceptance/rejection criteria.* The crimping rings shall meet the examinations specified by paragraph 4.3.1 to be acceptable. The supplier shall obtain written approval from the contracting officer before proceeding with regular production.

4.4 Lotting. A lot shall consist of the crimping rings produced by one manufacturer at one plant, from the same materials, under essentially the same manufacturing conditions.

4.5 Sampling for examination. Sampling shall be conducted in accordance with MIL-STD-105.

4.6 Inspection provisions.

4.6.1 *For examination.* Sample crimping rings and preparation for delivery thereof shall be examined in accordance with the classification of defects and with MIL-STD-105.

4.6.2 *Classification of defects.*

4.6.2.1 *Ring, crimping (Dwg C5-2-975).*

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:15Z
Check the source to verify that this is the current version before use.

Categories	Defects
Critical:	None defined.
Major:	AQL 2.5 percent defective.
101	Plan view profile incorrect.
*102	Height of inner flange (0.094) incorrect.
*103	Notches missing, incorrect or incorrectly located.
104	Flange length incorrect (11/32 inch).
105	Rivet incorrect, missing, loose, or incorrectly located.
106	Workmanship (3.4).
Minor:	AQL 6.0 percent defective.
201	Protective finish missing or incorrect.

*These characteristics are tool controlled and should be periodically checked.

4.6.2.2 *Preparation for delivery (see section 5).*

Categories	Defects
Critical:	None defined.
Major:	AQL 4.0 percent defective.
101	Contents loose within container.
102	Marking incorrect, missing, or illegible.

5. PREPARATION FOR DELIVERY

(For repair parts packaging, see 6.3).

5.1 Packing, level C. Crimping rings shall be packed in two or more layers in a type I, class 1, fiberboard box conforming to PPP-B-636. The interior of the box shall be divided into equal-sized cells through use of interlocking slotted partitions, with a separator placed between each slotted partitioned layer. The cells formed by the interlocking slotted partitions shall be sufficient size to contain a uniform quantity of crimping rings (not less than 10), accordion wrapped in minimum 40-pound basis-weight kraft wrapping paper. The interlocking slotted partitions and separators shall be fabricated from the same material as the box. The fiberboard box shall be closed in accordance with the applicable appendix requirements of PPP-B-636.

5.2 Marking. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. This specification covers the crimping ring that seals the C29R1 voice-mitter-outlet-valve assembly to the C17 face-blank.

6.2 Ordering data. Procurement documents should specify the title, number and date of this specification.

6.3 Repair parts packaging. When repair parts packaging is required for items authorized for stocking as repair parts, the repair parts packaging data sheets covering the crimping ring should be used.

(Copies of repair parts packaging data sheets may be obtained from the Director of Engineering and Industrial Services, ATTN: Chief, Design Branch, U.S. Army Edgewood Arsenal, Md. 21010.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:15Z
Check the source to verify that this is the current version before use.

shown on figure 2 when used by a typical U.S. Navy and exhalation pressure

6.4 **International interest.** Certain provisions of this specification are the subject of ABC international standardization agreement. When amendment, revision, or cancellation of this specification is proposed, the departmental custodians will inform their respective Departmental Standardization Offices so that appropriate action may be taken respecting the international agreement concerned.

Custodians:

Army—MU

Navy—SH

Air Force—84

International interest (see 6.4)

Review activities:

Army—MD

Navy—SH

User activities:

Navy—MC

Air Force—84

Preparing activity:

Army—MU (EA)

Project No. 4240-0071

★ U. S. GOVERNMENT PRINTING OFFICE: 751—078—1005 (T-814)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:15Z
Check the source to verify that this is the current version before use.