MILITARY SPECIFICATION
SWITCH INTEGRATOR
MARK 62 MOD 2

This amendment forms a part of Military Specification MIL-S-82492 (OS) of 26 July 1967 and is approved for use by The Naval Sea Systems Command (OS), Department of the Navy, and is available for use by all departments and agencies of the Department of Defense.

Wherever it appears in specification delete "Bureau of Naval Weapons" and substitute "Naval Sea Systems Command (Code Ident 10001)"; also delete "BuWeps" and substitute "NAVSEA".

Page 1, bottom center of page, add:

> Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: (Commanding Officer, Naval Ordnance Station (611), Indian Head, MD.) by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Page 2, paragraph 2.1, under "DRAWINGS": Delete "LD 540557" and associated title and substitute "DL 1984430 Magnetic Tester Assembly, Integrator Switch".

Page 2, paragraph 2.1, under "PUBLICATIONS": Delete "OD 13770" and associated title and substitute "OD 45397 Operation and Maintenance of Magnetic Tester for Integrator Switch Mark 62 Mod 2".

Page 6, paragraph 4.1, delete and substitute:

"4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

FSC 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:12Z
Check the source to verify that this is the current version before use.

Page 8, paragraph 4.4.1.d, delete in its entirety and substitute:

"d.	Magnetic tester assembly, integrator switch	NAVSEA DL 1984430. Operate in accordance with OD 45397".

Page 14, paragraph 4.6.1.4.2, delete and substitute:

"4.6.1.4.2 Functional acceleration. Mount the switch in the magnetic fixture of the integrator switch tester, specified in 4.4.1d; subject the switch to the acceleration listed in Table III in the direction shown in Figure 3, using the centrifuge specified in 4.4.1b. The switch closure g-second product shall be computed as follows:

Switch closure g-second product equals the switch closure time in seconds times the acceleration in g's for that run.

The switch closure g-second product shall be as listed in Table III. If the switch circuits do not return to the normal positions during testing, the timing weight gear rack and pinion may not have reengaged. Recycle test fixture as required to obtain normal conditions of circuits. If the switch does not reset, stop centrifuge and remove switch. Hold switch in hand with leads up; shake vigorously to reorient pinion gear. The sound of reengagement will be noted when the normally-closed circuit closes. Replace switch in fixture and continue testing".

Custodian
Navy-OS

Preparing Activity
Navy-OS
Project No. 1375-N122

*U.S. GOVERNMENT PRINTING OFFICE: 1976-703-020/1613

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:12Z
Check the source to verify that this is the current version before use.