FEDERAL STANDARD STOCK CATALOG

Section IV

(Part 5)

FEDERAL SPECIFICATION

FOR

CASES; BRIEF, LEATHER

This specification was approved on the above date by the Director of Procurement, for the use of all departments and establishments of the Government, and shall become effective not later than October 15, 1942. It may be put into effect, however, at any earlier date after promulgation.

A. APPLICABLE SPECIFICATIONS.

A–1. The following Federal specifications, of the issue in effect on date of invitation for bids, shall form a part of this specification:

V–T–291. Thread; Linen.
KK–L–166. Leather; Case.
DDD–S–751. Stitches; Seams; and Stitching.

B. TYPES.

B–1. Cases shall be of the following types, as specified in the invitation for bids:

Type I. Lawyer.
Type II. Special lawyer.
Type III. Secretary.
Type IV. Special secretary.
Type V. Investigator.
Type VI. Inspector.
Type VII. Brief bag.
Type VIII. Catalog.

C. MATERIAL AND WORKMANSHIP.

C–1. *Leather.*—The leather used in the manufacture of the cases, except for the partitions, shall conform to the requirements of Federal specification KK–L–166, and be of the type hereinafter specified: *Provided, however,* That no leather, which has open grub holes, brands, open scratches, or cuts on either grain or flesh, or soft and pipey stock from flanks and bellies, shall be used.

C–2. *Thread.*—All stitching shall be done with not less than 4-cord linen thread, or its equivalent in strength, in accordance with Federal specification V–T–291.

461160—42

Source: https://assist.dla.mil -- Do
Check the source to verify that this

D. GENERAL REQUIREMENTS.

D-1. *Tolerance in thickness.*—The thickness of each piece shall be subject to a plus tolerance of ½ sixty-fourth inch; and to a minus tolerance of ½ sixty-fourth inch over not to exceed 50 percent of the area.

E. DETAIL REQUIREMENTS.

E-1. *Type I. Lawyer.*—

E-1a. *Leather.*—

E-1a (1). *Fronts, backs, flaps, straps, and loops.*—Shall be made from type I, smooth case leather covered by Federal specification KK-L-166. The thickness of the leather shall be 5/64 inch.

E-1a (2). *Gussets.*—Shall be made from type II, hand boarded case leather covered by Federal specification KK-L-166. The thickness shall be 3/64 inch.

E-1a (3). *Partitions.*—Shall be made from firm split cowhide 5/64 inch, finished smooth on both sides and colored to match the case leather. There shall be two full-length partitions forming pockets approximately 8 inches deep, attached to the ends. One partition shall have attached two envelopes and one pencil pocket formed from one full-length piece of approximately 3½ sixty-fourths inch thick split bag leather sewed at the ends and middle.

E-1b. *Color.*—Shall be black or brown as specified.

E-1c. *Sizes.*—Shall be 16 by 10 inches or 17 by 11 inches as specified. The size shall be measured on the outside of the front piece of the case and a plus or minus tolerance of ⅛ inch will be permitted.

E-1d. *Pockets.*—Cases shall have two, three, or four pockets as specified. Each pocket shall have an expansion of 1½ inches. The expansion shall be measured on the outside of the pocket between the edges of the gusset. A plus or minus tolerance of ⅛ inch will be permitted.

E-1e. *Locks.*—Cases shall be equipped with a brass, three-position, extension lock suitably secured to the front of the case. Two keys shall be furnished with each lock. The inside of the lock shall be covered with a piece of buffing leather 4 inches in diameter. The brass member attached to the flap shall be secured by riveting.

E-1f. *Buckles.*—The buckles shall be a good grade single prong type. They shall be brass or steel, suitably coated to resist corrosion. They shall be ⅞ inch wide with the base securely attached to the strap by stitching.

E-1g. *Handles.*—Shall be of the round-bag type, covered with type I, smooth case leather, Federal Specification KK-L-166. The thickness of the leather shall be 4½ sixty-fourths inch. The handles shall be reinforced with a steel wire or strip which shall loop around two brass dees attached to the ends of the handles. The spread of the handle between the dees shall be 5½ inches, ±¼ inch.

E-1h. *Construction.*—

E-1h (1). *Fronts.*—Shall be indented 1 inch below partitions at the top by cutting on a radius of approximately 12 inches.

E-1h (2). *Flaps.*—The corners of the flaps shall be cut on a radius of approximately 2 inches.

Source: https://assist.dla.mil -- Check the source to verify that thi

E–1h (3). *Stitching.*—Stitch type 301, Federal specification DDD–S–751, shall be used. All stitching shall be by a single row with from 6 to 8 stitches per inch. At the end of a row of stitching there shall be at least 3 back stitches.

E–1h (4). *Gussets.*—Each pocket shall have a continuous gusset made from one piece of leather. Gussets shall be turned in at the top from 1 to 1½ inches and secured to the case and partitions at the top edges with tubular or bifurcated rivets of a color to match the color of the leather. Gussets shall be attached by cementing and stitching.

E–1h (5). *Straps.*—Each case shall be equipped with two ⅞-inch straps running entirely around the case. Straps shall be creased ⅛ inch from each edge. One end shall have a turn-back loop 1⅝ inches long for holding the buckle. A ½-inch leather keeper shall be sewed in the turn-back loop near the end of the buckle. The end of the strap extending over the flap shall be punched with 5 holes 1 inch apart, beginning 2½ inches from the end.

E–1h (6) *Loops.*—Each strap shall be held in place by four leather loops. Two shall be on the back of the case, one on the front, and the other on the top. The top loop shall be a part of the loop used for attaching the handle.

E–1h (7). *Handles and flap reinforcement.*—A spring steel reinforcing strip, ½-inch wide and 1/32-inch thick with smoothed ends, shall be placed on the inside of the flap immediately under the handle and shall extend across the flap to within ⅜ inch of either end. This strip shall be perforated in two places to permit attachment with solid rivets which pass through the handle loops. The strip shall be covered with a strip of leather (see par. E–1a (1)) approximately 1½ inches in width. The leather handle loops shall contain a steel strip through thich the dee rings are passed. This construction is designed to allow all carrying parts to be metal against metal. The top pieces of the handle loops shall extend along the top of the case to also form a strap loop. Handle loops shall be secured to the case by stitching.

E–1h (8). *Finish.*—All cut edges of the leather shall be stained to match the case and the finish shall be in accordance with the best commercial practice, and shall be such that the color will not rub off.

E–2. *Type II. Special lawyer.*—Type II cases shall be the same as type I cases in all respects as noted hereafter.

E–2a. *Color.*—Shall be brown.

E–2b. *Size.*—Shall be 16 inches long by 11 inches deep.

E–2c. *Pockets.*—Shall have three pockets. Each of the first two shall have an expansion of 1¾ inches, and the third or rear pocket shall have an expansion of 3¾ inches. The tolerance on the former shall be plus or minus ⅛ inch, and on the latter, plus or minus ¼ inch.

E–2d. *Handles.*—Shall be of the flat type made from the case leather. It shall be ½ inch thick and be covered with a leather 3/64 inch thick. Shall be reinforced with a metal strip through which brass dees shall be passed on either end. The spread of the handle between the dees shall be 5½ inches, ±¼ inch.

E–3. *Type III. Secretary.*—

E–3a. *Leather.*—

Source: https://assist.dla.mil --
Check the source to verify that t

E-3a (1). All parts of the case except the inner lining, shall be made from type II, hand boarded leather covered by Federal Specification KK-L-166. The thickness of the leather shall be 4½ sixty-fourths inch except the gussets which shall be ¾ inch.

E-3a (2). *Lining.*—Shall be cowhide buffing leather 1½ to 2 sixty-fourths inch thick.

E-3b. *Color.*—Shall be brown.

E-3c. *Size.*—Shall be 16 by 11 inches measured on the front of the case. A plus or minus tolerance of ½ inch will be permitted.

E-3d. *Pockets.*—Cases shall have two large pockets, two small inner pockets, and a pencil pocket. The large pockets shall have an expansion of 1½ inches with a tolerance of plus or minus ⅛ inch. The small pockets shall have an expansion of not less than ¾ inch. The small pockets shall be formed from a single piece of leather without separate gussets.

E-3e. *Locks.*—Same as for type I. (See par. E–1e.)

E-3f. *Buckles.*—Same as for type I. (See par. E–1f.)

E-3g. *Handles.*—Same as for type I, paragraph E–1g, except that type II, hand-boarded leather shall be used.

E-3h. *Construction.*—

E-3h (1). *Body.*—The front, back, flap, and lower pocket of the case shall be made from a single piece of leather.

E-3h (2). *Pockets.*—The upper pocket shall have two small pockets approximately 7 inches deep by 6 inches wide sewed to it. Between them a pencil pocket shall be placed with space for four pencils. The pencil pocket shall be formed by making four loops and a flap at either end for protecting the pencils.

E-3h (3). *Flaps.*—The lower pocket shall have a flap with two snap fasteners. The corners of this flap and the outside flap shall be cut on a radius of approximately 2 inches.

E-3h (4). *Lining.*—The inside of the outside flap and the space between the upper and lower large pockets shall be lined with leather. (See par. E–3a (2).)

E-3h (5). *Straps.*—The straps shall be ¾ inch in width and be made by stitching together along the edges two pieces of the body leather. The front straps shall be 9 inches long and stitched to the flap 3 inches from the edge to the center of the strap. They shall overlap the flap by not less than 2½ inches. Five holes shall be punched in each strap ¾ inch apart beginning approximately 2½ inches from the end. The buckle straps shall cover the front of the case approximately 7 inches and shall be carried around under the bottom of the case and upward on the back at least 3 inches, where they shall be held in position by stitching. The buckles shall be held in position by a turnback loop not less than 1½ inches long in which a ½ inch leather keeper shall be sewed.

E-3h (6). *Loops.*—Each buckle strap shall be held in place on the front of the case by a leather loop, at least ¾ inch wide and 3 inches long, stitched in position.

E-3h (7). *Stitching.*—Same as for type I. (See par. E–1h (2).)

E-3h (8). *Gussets.*—Same as for type I. (See par. E–1h (4).)

Source: https://assist.dla.mil -- Check the source to verify that thi

E-3h (9). *Handles and flap reinforcement.*—Same as for type I. (See par. E-1h (7).)

E-3h (10). *Finish.*—Same as for type I. (See par. E-1h (8).)

E-4. *Type IV, Special Secretary.*—Shall be furnished with a slide fastener of the interlocking type on three sides with or without binder rings as specified in the invitation for bids.

E-4a. *Leather.*—Shall be one piece of top grain either smooth or embossed cowhide leather and unless otherwise specified not less than 3/64 inch thick.

E-4b. *Lining.*—Shall be of good grade imitation leather fabric, backed with a suitable stiffening board sewed and secured with waterproofed adhesive to the case leather.

E-4c. *Color.*—Shall be either brown or black as specified.

E-4d. *Size.*—Shall be 17 inches by 11 inches with an expansion of 2½ inches (inside dimensions). A plus or minus tolerance of ⅛ inch will be permitted.

E-4e. *Pockets.*—The case shall have either 2 or 4 inside pockets as specified. In both instances the case shall have an interlocking slide fastener on the outside, 1 inch from the top, giving access to a separate outer pocket that shall measure 15½ by 10 inches, ± ⅛ inch.

E-4e (1). *Two pockets.*—Shall have a full length gusseted inside pocket on one side, approximately 7 by 15½ inches, ± ⅛ inch, with an expansion of 1¼ inches, with a leather pencil loop sewed on top. On the other side there shall be a gusseted cross pocket (inside) 7 by 9 inches, ± ⅛ inch with an expansion of 1½ inches.

E-4e (2). *Four pockets.*—There shall be a full length gusseted inside pocket on one side with an expansion of 1¼ inches on which there shall be attached two flat pockets, each 6 by 7 inches, ± ⅛ inch and on the top a sewed-on leather pencil loop. On the other side there shall be a gusseted cross-pocket (inside) 7 by 9 inches, ± ⅛ inch, with an expansion of 1½ inches.

E-4e (3). *Partitions or inner pockets.*—Except where otherwise specified, shall be of same material as lining, backed with suitable stiffening board, and lined with rubberized cloth.

E-4f. *Handles.*—Shall be double and of the sliding or disappearing type.

E-4g. *Fasteners.*—Shall be a heavyweight interlocking slide fastener of the nonseparating open-top type. The fastener on the outer pocket may be of lighter weight than that on the gusset. All fasteners shall be attached to a suitable tape which is securely sewed to the case.

E-4h. *Construction.*—

E-4h (1). *Body.*—The front, back, and bottom of the case shall be made of one piece of top grain cowhide leather 3/64 inch thick.

E-4h (2). *Stitching.*—Shall be in accordance with Federal Specification DDD-S-751 stitch type 301.

E-4h (3). *Gusset.*—Shall consist of two 1-inch strips of top-grain embossed cowhide leather, 3/64 inch thick, reinforced with securely cemented fabric matching case leather on outside and partition lining on inside. Strips shall be securely sewed to the edges of the case on three sides underneath the body leather, and shall be of the slide fastener of the interlocking type which shall be securely sewed to the

Source: https://assist.daps... - D
Check the source to verify that this

All edges shall be turned and stitched to prevent open seams and ragged edges.

E-4h (4). *Handles.*—Shall be made of metal, without sharp edges or corners that will cut through the cover; shall be covered with leather which matches the case leather, and padded for the width and shall be inserted through the top, between the outside leather and the lining of the case, in such a manner that they are not visible on the inside. Where handles slide in between lining and cover, there shall be a reinforcing strip of cowhide, approximately 7½ inches long by 1 inch wide, sewn to the lining. Shall be reinforced at the bottom with substantial metal strips which shall hold the handles and prevent them from pulling loose.

E-4h (5). *Lining.*—Shall be of good grade fabric imitation leather, backed with suitable stiffening board, sewed and secured with water-proofed adhesive to the case leather.

E-4h (6). *Reinforcement.*—The bottom on the inside between the pockets shall be reinforced with a strip of leather approximately 2½ inches wide, which shall extend the full length of the case and shall be of the same grade and color as the case leather.

E-4h (7). *Ring binders.*—When specified, the binders shall have a 3-ring mechanism, capacity as specified, with metal ring protectors (approximately 11½ inches long), and securely fastened throughout the length of the case.

E-4h (7) a. *Spacing.*—The distance between rings shall be the standard commercial spacing for the type of opening and the size of the sheet (11 x 8½ inches).

E-4h (7) b. *Rings.*—Shall be made from nickel-plated steel wire of not less than $\frac{3}{32}$ inch in diameter and securely fastened to the prong plates. The rings shall have a Rockwell hardness of not less than 65 on the B scale, after forming. The rings, when closed, shall fit snugly after extensive use.

E-4h (7) c, *Prong plates.*—Each rib or plate shall measure not less than 0.045 inch by $\frac{1}{16}$ inch over-all in cross section. Shall be of the strip type made of cold-rolled steel, having a Rockwell hardness of not less than 80 on the B scale.

E-4h (7) d. *Booster triggers.*—Shall be made from nickel-plated steel, not less than 0.055 inch thick and sufficiently rugged.

E-4h (7) e. *Spring or tension plate.*—Shall be made from nickel-plated cold-rolled steel not less than 0.015 inch thick, having a Rockwell hardness of not less than 65 on the B scale.

E-5. *Type V, Investigator.*—

E-5a. *Leather.*—

E-5a (1). Same as for type I. See paragraph E-1a (1), fronts, backs, flaps, straps, and loops, except the thickness of the leather shall be $\frac{7}{64}$ inch.

E-5a (2). *Gussets.*—Same as for type I. See paragraph E-1a (2), except the thickness shall be 3½ sixty-fourths inch.

E-5a (3). *Partitions.*—Same as for type I. See paragraph E-1a (3), except that the thickness shall be $\frac{5}{64}$ inch.

E-5b. *Color.*—Shall be brown.

E-5c. *Size.*—Shall be 18 by 12 inches.

Source: https://assist.dla.mil -
Check the source to verify that t

E-5d. *Pockets.*—Same as for type I. See paragraph E–1d, except that a pencil pocket with flap, approximately 9 by 3½ inches, shall be attached to the last partition by stitching. The pencil pocket shall be made of gusset leather and the flap shall be provided with two snap fasteners.

E-5e. *Locks.*—Cases shall be equipped with a six-hole solid brass hasp and staple and a 1-inch pin tumbler padlock.

E-5f. *Buckles.*—The strap buckles shall be 1-inch brass of the roller type.

E-5g. *Handles.*—Shall be of the telescope strap type as described hereafter.

E-5h. *Construction.*—

E-5h (1). *Fronts.*—Same as for type I. (See par. E–1h (1).)

E-5h (2). *Flaps.*—Same as for type I. (See par. E–1h (2).)

E-5h (3). *Stitching.*—Same as for type I. (See par. E–1h (3).)

E-5h (4). *Gussets.*—Same as for type I. (See par. E–1h (4).)

E-5h (5). *Straps.*—Each case shall be equipped with two leather straps 1 inch wide running entirely around the case. Straps shall be creased ⅛ inch from each edge. One end shall have a trunback loop 1½ inches long for holding the buckle. A ¾-inch leather keeper shall be sewed in the turnback loop near the end of the buckle. The end of the strap passing over the flap shall be punched with five holes 1¼ inches apart beginning 3 inches from the end.

E-5h (6). *Loops.*—Each strap shall be held in place by five leather loops. Two shall be on the back of the case, one on the front, one on the flap, and one on the adjustable handle. The last loop shall be an extension of the loop with which the handle is attached.

E-5h (7). *Handles.*—Shall be built of the same leather as the body of the case 6 inches long, 1 inch wide, and ¾ inch thick. Shall be reinforced with a steel wire or strip looped at the ends through which 1-inch brass dees shall be passed. The handle shall be attached to a wood bar, 14 inches long, 2 inches wide, and ¼ inch thick and covered with gusset leather, by means of leather loops riveted to the bar. The loops shall be ⅞ inch wide and extend to the end of the bar and riveted to form a loop for the straps. The loops shall be reinforced with a metal strip where contact is made with the dees of the handle so that all carrying parts of the handle are metal against metal.

E-5h (8). *Safety straps.*—Safety strap loops shall be required approximately ½ inch wide. They shall be riveted to the flap, pass over the wood bar under the main strap and be riveted to the back of the case. Safety straps shall have enough slack so as not to be subject to the carrying strain when the case is closed. The purpose of the straps is to permit the case to be lifted by the handle, when open, without the main straps pulling out of the loops.

E-5h (9). *Finish.*—Same as for type I. (See par. E–1h (8).)

E-6. *Type VI, Inspector.*—Type VI cases shall be the same as type I cases in all respects except as noted immediately hereafter.

E-6a. *Color.*—Shall be brown.

E-6b. *Size.*—Shall be 17 inches long by 11 inches deep.

E-6c. *Pockets.*—Shall have two large pockets each [illegible] sion of 2 inches plus or minus ¼ inch. Also two small pockets, each

Source: http://assistdarmih-- D
Check the source to verify that this

6 inches wide and 7½ inches deep. Shall be attached to the front of the partition and located approximately 1¼ inches from the bottom and ends of the partition. The expansion of the small pockets shall not be less than 1½ inches.

E-6d. *Handles and flap reinforcement.*—Same as E–1h (7) except that reinforcing strip shall be ¾ inch in width and 1/16 inch in thickness.

E-6e. *Fronts.*—Same as E–1h (1) but also shall include indentation of the top of the partition.

E-7. *Type VII, Brief bag.*—

E-7a. *Leather.*—

E-7a (1). *Sides and bottom.*—Shall be made of not less than 5/64 inch thick top-grain embossed cowhide.

E–7a(2). *Gussets or end pieces.*—Shall be made of not less than 4/64 inch thick chrome-tanned, elk-finish cowhide.

E–7b. *Partitions.*—Shall be made from a reasonably stiff composition material approximately 4/64 inch thick, that will not fray on the edges. There shall be two full-length partitions approximately 8 inches deep, attached to the ends. One partition shall have attached two envelopes and one pencil pocket formed from one full length piece of approximately 3½ sixty-fourths inch thick split bag leather sewed at the ends and middle.

E–7. *Color.*—Shall be black or brown as specified.

E–70. *Size.*—Shall be 13 inches high, 17 inches long, and 7 inches wide (inside dimensions). A plus or minus tolerance of ⅛ inch will be permitted.

E–7e. *Handles.*—Shall be pressed and stitched solid leather double handles attached to case with D-rings through metal-reinforced leather ears riveted and sewed to the case.

E–7f. *Closures.*—

E–7f(1). *Top.*—Shall be a steel frame not less than 0.10 inch thick, covered with leather and hinged with rivets. It shall be approximately 7 inches wide when open.

E–7(2). *Bottom.*—Shall be of the following types as specified in the invitation for bids.

E–7(2)a. *Collapsible.*—The bottom shall be so constructed that it will fold or collapse lengthwise, but will not sag. The bottom shall be supported by six metal studs. Full length partitions shall form a center compartment approximately 4 inches wide, 8 inches deep, and each side compartment 1½ inches wide.

E–7(2)b. *Rigid.*—The corners shall be reinforced with leather extending under the bottom, shall be at least 2 inches wide, and extending at least 2 inches along the sides and 1 inch on the bottom. The inside bottom shall be reinforced with a stiff composition sheet approximately ⅛ inch thick securely fastened to the leather bottom by at least six rivets forming part of the studs. The bottom on the outside shall be supported by six metal studs equally spaced. There shall be two full-length partitions approximately 8 inches deep, equally spaced.

E–7g. *Locks.*—Cases shall be equipped with a brass case, three position, extension lock securely fastened to the front of the case. Two keys shall be furnished with each lock. The back of the lock

Source: https://assist.dla.mil
Check the source to verify that

showing through on the inside shall be covered with a piece of buffing leather 4 inches in diameter. The brass locking member attached to the lock strap shall be secured by riveting. The lock strap shall be made of the body leather 4 inches long and 2 inches wide securely fastened at one end by stitching in the seam of the top.

E–7h. *Stitches.*—Shall be made in accordance with Federal Specification No. DDD–S–751 type 301 using not less than 4-ply well-waxed linen thread in accordance with Federal Specification V–T–291, and shall have 6 to 8 stitches per inch. (See par. E–1H(3).)

E–7i. *Finish.*—All cut edges of the leather shall be stained to match the case and the finish shall be in accordance with the best commercial practice, and shall be such that the color will not rub on.

E–8. *Type VIII, Catalog.*—

E–8a. *Leather.*—The leather used in the manufacture of the cases, except for the partitions, shall conform to the requirements of Federal Specification No. KK–L–166, and be of the type specified hereinafter.

E–8(1) *Front, back, straps, loops, and corners.*—Shall be made from type I smooth case leather not less than 7/64 inch in thickness.

E–8a(2). *Gussets.*—Shall be made from type I smooth case leather not less than 7/64 inch in thickness, reinforced with not less than 5/64 inch thick split cowhide leather, colored to match case leather.

E–8a(3). *Bottoms.*—Shall be made from type I smooth case leather not less than 7/64 inch thick, reinforced with not less than 5/64 inch thick split cowhide leather colored to match case leather and with inner fiber board for strengthening. Shall have eight nickel-plated or brass bottom studs, three on each side edge and two in the center, evenly spaced.

E–8a(4). *Flaps.*—Shall have two flaps 6 inches square, made of type II leather not less than 3/64 inch thick. Shall be sewed to the top of the gussets.

E–8a(5). *Partitions.*—Shall be made of not less than 5/64 inch thick split cowhide leather finished smooth on both sides and colored to match the case leather.

E–8a(6). *Handles.*—Shall be double strap type made of type I smooth case leather not less than 7/64 inch thick.

E–8b. *Size.*—Shall be 11 inches high, 16 inches long, and 6 inches wide (inside dimensions). A tolerance of ±1/8 inch will be permitted.

E–8c. *Color.*—Shall be brown or black as specified in the invitation for bids.

E–8d. *Lock.*—The case shall be equipped with a three-position brass case extension lock suitably secured to the front of the case. Two keys shall be furnished with each lock. The back of the lock shall be covered with a piece of buffing leather approximately 4 inches in diameter. The brass locking member attached to the flap shall be secured by riveting.

E–8e. *Finish.*—All cut edges of the leather shall be stained to match the case and the finish shall be in accordance with the best commercial practice and shall be such that the color will not rub on.

E–8f. *Construction.*—

E–8f(1). *Fronts.*—Shall be of the full size of the case.

Source: https://assist.dla.mil -- I
Check the source to verify that thi

E–8f(2). *Flap.*—Shall extend for approximately 5 inches over the front of the case and shall have the corners cut on a radius of approximately 2 inches.

E–8f(3). *Gussets.*—The gussets shall be sewed and secured to the case and partitions at the top edge with smooth double headed rivets of color to match the case leather.

E–8f(4). *Pockets.*—The case shall have two or three pockets as specified. The two-pocket case shall have a 2 inch wide pocket to the front and a 4 inch wide pocket to the back of the case. The three-pocket case shall have three equally divided pockets 2 inches each in width. The front partition in either case shall have two flat pockets measuring 5½ to 7 inches square made of not less than 3/64 inch thickness type B hand boarded case leather.

E–8f(5). *Straps.*—Each case shall be equipped with two 1¼ inch straps extending entirely around the case forming the handles. The ends of the straps shall be riveted together at the bottom and held together at the top by a 4½ by 4½ leather tab with two brass snap fasteners. The tab shall be fastened to one strap by stitching. Each strap shall be held to the body of the case by three loops.

E–8f(6). *Loops.*—The loops shall be securely sewed on, two of the front of the case, two on back, and two on the bottom covering the riveted ends.

E–8f(7). *Corners.*—The lower corners shall be reinforced by a securely sewed strip of case leather not less than 5/64 inch thick, approximately 2½ inches wide, and extending across the bottom and up the front and back panels of the case approximately 2½ inches.

E–8f(8). *Stitches.*—Shall be in accordance with Federal Specification DDD–S–751 Type 301, using not less than 4-ply well waxed linen thread in accordance with Federal Specification V–T–291 and shall have 6 to 8 stitches, per inch.

E–8f(9). *Finish.*—Shall be in accordance with paragraph E–71.

F. METHODS OF SAMPLING, INSPECTION, AND TESTS.

F–1. *Sampling.*—One case shall be taken at random for test purposes from each lot of 100 or fraction thereof delivered. This case shall be examined as to details of construction, quality of leather, and stitching.

F–2. *Inspection.*—It is desirable to visually inspect each case for obvious items of construction and surface appearance of the leather. In cases where this inspection is done in the laboratory 1 out of 12 cases should be submitted. Such cases will not be destroyed.

F–3. *Thickness.*—The thickness of the leather shall be measured at various locations with a gage graduated in ½ sixty-fourths inch and having a contact foot 5/16 inch in diameter. The load on the foot shall be approximately 1 pound at the point on the scale corresponding to a thickness of 3/64 inch and approximately 2 pounds at the point corresponding to a thickness of 13/64 inch. A convenient type of gage is the U-shaped, thumb-operated one, made for use on leather.

F–4. *Leather.*—The leather shall be examined in accordance with the requirements of Federal Specification KK–L–166 [illegible] effect on date of invitation for bids.

Source: https://assist.dla.mil -
Check the source to verify that

F–5. *Stitching.*—For stitch type see Federal Specification DDD–S–751 of the issue in effect on date of invitation for bids.

G. PACKAGING, PACKING, AND MARKING FOR SHIPMENT.

G–1. *Packaging.*—Unless otherwise specified, commercial packages are acceptable under this specification.

G–2. *Packing.*—Unless otherwise specified, the subject commodity shall be delivered in standard commercial containers, so constructed as to insure acceptance by common or other carrier, for safe transportation, at the lowest rate, to the point of delivery.

G–3. *Marking.*—Unless otherwise specified, shipping containers shall be marked with the name of the material, the type, and the quantity contained therein, as defined by the contract or order under which the shipment is made, the name of the contractor, and the number of the contract or order.

H. REQUIREMENTS APPLICABLE TO INDIVIDUAL DEPARTMENTS.

H–1. The following departmental specifications, of the issue in effect on date of invitation for bids, shall form a part of this specification, and shall be applicable to purchases made under this specification by the respective departments.

H–2. *War Department.*—United States Army Specification No. 100–2, Standard Specification for Marking Shipments. Copies of this specification may be obtained by prospective bidders, without cost, upon application to the distributing agency indicated in the invitation for bids.

H–3. *Navy Department.*—General Specification for Inspection of Material (copies of which may be obtained, without cost, upon application to the Bureau of Supplies and Accounts, Navy Department, Washington, D. C.).

I. NOTES.

I–1. The thickness of leather expressed in "sixty-fourths of an inch" is numerically the same as if expressed in "ounces".

I–2. Purchasers should exercise any desired option offered herein and should specify the type, color, and number of pockets.

I–3. It is believed that this specification adequately describes the characteristics necessary to secure the desired material and that normally no samples will be necessary prior to award to determine compliance with this specification. If, for any particular purpose, samples with bids are necessary, they should be specifically asked for in the invitation for bids, and the particular purpose to be served by the bid sample should be definitely stated, the specification to apply in all other respects.

I–4. Federal specifications do not include all types, classes, grades, sizes, etc., of the commodities indicated by the titles of the specifications, or which are commercially available, but are intended to cover the types, etc., which are suitable for Federal Government requirements.

I–5. An Index of Federal Specifications may be purchased as noted in paragraph below, price to be obtained from the Superintendent of Documents.

Source: https://assist.dla.mil -
Check the source to verify that t

I-6. Copies of this specification and of V-T-291, KK-L-166, and DDD-S-751 may be obtained upon application, accompanied by money order, coupon, or cash, to Superintendent of Documents, United States Government Printing Office, Washington, D. C. Price, 5 cents each; except DDD-S-751, price 25 cents.

Notice.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Source: https://assist.dla.mil
Check the source to verify that