KK–W–266a
September 8, 1961

SUPERSEDING
Fed. Spec. KK–W–266
March 26, 1947

FEDERAL SPECIFICATION

WHEEL, BUFFING, CHAMOIS, DENTAL

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE

1.1 This specification covers chamois wheels suitable for use in buffing dental gold appliances.

2. APPLICABLE SPECIFICATIONS AND STANDARDS

2.1 The following specifications and standards, of the issues in effect on date of invitation for bids, form a part of this specification, to the extent specified herein:

Federal Specifications:

CCC–T–191—Textile Test Methods.
PPP–B–566—Boxes, Folding, Paperboard.
PPP–B–585—Boxes, Wood, Wirebound.
PPP–B–601—Boxes, Wood, Cleated-Plywood.
PPP–B–621—Boxes, Wood, Nailed and Lock-Corner.
PPP–B–636—Box, Fiberboard.
PPP–B–665—Boxes, Paperboard, Metal Stayed (Including Stay Material).
PPP–676—Boxes, Set-Up, Paperboard.

Federal Standards:

Fed. Std. No. 102—Preservation, Packaging, and Packing Levels.
Fed. Std. No. 123—Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications, Standards, and Handbooks and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington 25, D. C.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, Seattle, and Washington, D. C.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications, Standards, and Handbooks from established distribution points in their agencies.)

Military Specifications:

MIL–L–10547—Liners, Case, Waterproof.

Military Standards:

MIL–STD–105—Sampling Procedures and Tables for Inspection by Attributes.
MIL–STD–129—Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material.

3.1.1 *Chamois.* The chamois for buffing wheels shall be new, high-grade chamois leather, made from the flesh splits of sheepskins, split before tanning. The leather shall be double dressed (grain removed and suede-finished on both sides), and shall not be chemically bleached or dyed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:57Z
Check the source to verify that this is the current version before use.

3.1.2 *Thread.* The thread used for stitching shall be unbleached, soft finish, cotton thread with a minimum breaking strength of 6 pounds when tested as specified in 4.4.1.

3.2 Design and construction. Wheels shall be full disc type, made of 20 ±2 plies of chamois skins stitched together. The wheel center shall be drilled with an arbor hole, not less than ⅛ inch and not more than 5/16 inch in diameter, to receive the tapered chuck of a dental lathe. The wheels shall be so constructed that they will run true and evenly when mounted on a dental lathe chuck. The wheels shall be suitable for producing a high polish on dental gold appliances when used with rouge.

3.2.1 *Stitching.* The stitching shall be continuous and shall consist of three concentric circles: First circle ¼-⅜ inch from center; second circle ¼-⅜ inch from first circle; third circle ¼-⅜ inch from second circle. There shall be 4 to 6 stitches per inch of sewing.

3.2.2 *Center hardening.* The center of the wheels shall be hardened with a suitable hardening agent so that wheel will not tear loose or ride up on the lathe spindle. The use of leather reinforcement discs on either side of hardened center is optional.

3.3 Dimensions. The wheels shall be 3 inches ±⅛ inch in diameter and shall measure approximately ¾ inch in thickness before sewing.

3.4 Weight. The weight of each buffing wheel shall be 22 grams minimum, when tested as specified in 4.4.2.

3.5 Workmanship. Workmanship shall be first class throughout. The chamois wheels shall be free from defects which detract from their appearance or which may impair their serviceability.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Supplier responsibilities for inspection. The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examination and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 *Inspection.* Inspection, as used in this specification, is defined as both examination (such as visual, auditory, etc., investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

4.1.2 *Certificates of quality.* When available, certificates of quality, supplied by the manufacturer of the component or material, listing the specified test method and test results obtained, may be furnished in lieu of actual performance of such testing by the contractor.

4.2 Sampling.

4.2.1 *For examination.* Sampling for examination shall be conducted in accordance with Military Standard MIL–STD–105.

4.2.2 *For tests.* Sampling for tests shall be conducted in accordance with Military Standard MIL–STD–105, except that the acceptance number shall be zero for all sample sizes.

Component	Characteristic	Req. par.	Test procedure	Unit of product	Insp. level
Thread	Breaking strength	3.1.2	4.4.1	1—cone or 1—spool	L2* L2*
Finished wheel	Weight	3.4	4.4.2	1—wheel	

* A minimum of 3 units shall be tested regardless of lot size.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:57Z
Check the source to verify that this is the current version before use.

4.2.3 Where possible, the same unit of product shall be used for the determination of two or more test characteristics.

4.3 Examination. The wheels shall be examined to determine compliance with applicable requirements contained in this specification.

4.4 Tests. Tests shall be conducted, as necessary, to determine compliance with specification requirements.

4.4.1 *Breaking strength.* Test for breaking strength of thread shall be conducted in accordance with method 4100 of Federal Specification CCC–T–191.

4.4.2 *Weight.* The wheel shall be accurately weighed on a balance to the nearest 0.5 gram.

5. PREPARATION FOR DELIVERY

For civil agency procurement, Federal Standard No. 102 shall be referred to for definitions and applications of the various levels of packaging and packing protection for supplies and equipment.

5.1 Packaging.

5.1.1 *Level A or B.* Each wheel shall be packaged in a carton of appropriate size constructed in accordance with Federal Specification PPP–B–566, PPP–B–665, or PPP–B–676. Closure shall be in accordance with the appendix to the applicable box specification.

5.1.1.1 *Intermediate package.* Twelve unit packages (5.1.1) shall be intermediately packaged in a fiberboard box conforming to Federal Specification PPP–B–636, type I or II, class 1, style RSC, minimum bursting strength 175 p.s.i. Closure shall be in accordance with the appendix to the applicable box specification.

5.1.2 *Level C.* Wheels shall be packaged in accordance with the manufacturer's standard commercial practice.

5.2 Packing.

5.2.1 *Level A.* Thirty-six intermediate containers (5.1.1.1) shall be packed in shipping containers designed for type 2 load, and constructed in accordance with Federal Specification PPP–B–585, style 3, for class 3 use; PPP–B–601, table II, using type III, class 1 plywood; or PPP–B–621, table III. Each level A box shall be lined with a waterproof case liner conforming to Military Specification MIL–L–10547. Closure and sealing shall conform to applicable paragraphs of appendix thereto. Strapping, when required, shall be in accordance with applicable box specification.

NOTE: Strapping will not be required for shipments forwarded to a receiving activity within the continental limits of the United States for storage and redistribution.

5.2.2 *Level B.* Thirty-six intermediate containers (5.1.1.1) shall be packed in containers constructed in accordance with Federal Specification PPP–B–621, table I, or PPP–B–636, type I, class 1, fabricated from not less than 275 pound test fiberboard.

5.2.3 *Level C.* The subject commodity shall be packed in substantial commercial containers of the type, size, and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers, at the lowest rate, to point of delivery called for in the contract or purchase order.

5.3 Marking.

5.3.1 *Nonmilitary.* Unless otherwise specified in the contract or order, interior packages and exterior containers shall be marked in accordance with Federal Standard No. 123.

5.3.2 *Military.*

5.3.2.1 *Interior packages.* Each unit package and each intermediate package shall be marked in accordance with Military Standard MIL–STD–129.

5.3.2.2 *Exterior container.* Exterior container shall be marked in accordance with Military Standard MIL–STD–129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:57Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. Purchasers should exercise any desired options offered herein, and procurement documents should specify the following:

(*a*) Title, number, and date of this specification.

(*b*) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

(1) Level B preservation and packaging is intended to provide economical but limited protection, and should be specified only when it is determined the buffing wheels will be held in covered storage not more than 12 months from date of initial packaging.

6.2 This specification does not include all types, classes, grades, sizes, etc., of the commodity indicated by the title of this specification, or which are commercially available, but is intended to cover the types, etc., which are normally procured to meet Federal Government requirements.

6.3 Transportation description. Transportation description applicable to this item is:

Wheels, buffing or polishing NOIBN, in boxes.
Carload minimum weight 30,000 pounds in accordance with Uniform Freight Classification.
Truckload minimum weight 30,000 pounds in accordance with National Motor Freight Classification.

Notice. When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

MILITARY CUSTODIANS:

Army—M

Navy—Md

Air Force—AFCSG.

Copies of this specification may be purchased for 5 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:57Z
Check the source to verify that this is the current version before use.