MIL-F-70808A (AR)
17 October 1988
SUPERSEDING
MIL-F-70808 (AR)
11 March 1988

MILITARY SPECIFICATION

FUZE, PD: M745
(LOADING, ASSEMBLING, AND PACKING)

This specification is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements and quality assurance provisions for loading, assembling and packing of the M745 PD mortar fuze.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament, Munitions, and Chemical Command, Attn. AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1390

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Document https://assist.dla.mil - Downloaded: 2026-10-23T04:04:47
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

PRODUCT AND PACKAGING DRAWINGS (6.5)

11737000	- Fuze, PD: M745 Loaded Assembly
9347415	- Packing & Marking of Box, Fiberboard for Fuze, Multi-Option, M734 & Fuze, PD, M745
9347416	- Packing & Marking of Wood Box for Fuze, Multi-Option, M734 & Fuze, PD, M745
9381685	- Packing & Marking of Container, M548 for Fuze, Multi-Option, M734 & Fuze, PD, M745

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specification sheets or MS standards) the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications, and this specification.

3.2 Loaded fuze assemblies and parts. The loaded M745 fuze assemblies and parts shall comply with all requirements specified on drawing 11737000 and with all requirements specified in applicable specifications and standards.

3.3 Density, booster pellet. The density of the booster pellet shall be 1.64-1.70 g/cc.

3.4 Booster and lead output test. The booster pellet and lead charge shall be loaded into an M745 fuze base assembly (11737030). The loaded assembly shall be placed inside the cavity

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

of an aluminum block and shall be initiated remotely. The loaded assembly shall shear the aluminum block completely (360 degrees) upon initiation.

3.5 Fuze loading. Each fuze shall be checked, through the lead hole, to preclude the loading of a mechanically armed fuze.

3.6 Fuze intrusion length. The length from aft of the flange on the fuze base assembly to the aft of the fully loaded fuze shall be 1.120 inch maximum.

3.7 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be specified in the contract.

3.8 Workmanship. All parts and assemblies shall be in the condition and of a quality as specified on the applicable drawings and specifications. They shall be free from other defects such as, but not limited to, blemishes, burrs, cavities, pits, voids, corrosion, cracks, dents, distortion, warpage, gouges, scores, nicks, inclusions, laps, porosity, slivers or obstructions. Cleaning shall be thorough to remove all dirt, chips, grease, oil, flux, chemical deposits, residues, and other foreign matter. The cleaning method and agents used shall not be injurious to any part, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.1.1 Responsiblity for compliance. All items must meet all requirements of section 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The following types of inspections shall be conducted on this item:

a. First article inspection
b. Quality conformance inspection

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawing Number	Quantity
Pellet, Booster	11740826	10
Cap, Booster	11740828	10
Lead, Charge	11740829	10
Cup, Lead	11744120	10
Fuze PD: M745 Loaded assembly	11737000	25
Fuze Base Assembly (loaded)	11737030	200

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

Table I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70808A (AR)

PARAGRAPH	TITLE: Fuze, PD: M745 (Loading, Assembling, and Packing)		SHEET 1 OF 1		DRAWING NUMBER: See below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Pellet, Booster (dwg 11740826) Examination for defects	10	(a)	3.2	4.4.2.1
	Cap, Booster (dwg 11740828) Examination for defects	10	(a)	3.2	4.4.2.2
	Lead, Charge (dwg 11740829) Examination for defects	10	(a)	3.2	4.4.2.3
	Cup, Lead (dwg 11744120) Examination for defects	10	(a)	3.2	4.4.2.4
	Fuze, PD: M745 (dwg 11737000) Examination for defects	25	(a)	3.2	4.4.2.9
	Booster output test	200	(b)	3.4	4.5.3

NOTES: (a) One (1) or more defects shall be cause for rejection.
(b) Three (3) or more defects shall be cause for rejection.

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, each lot of M745 fuze shall contain:

a. Fuze assemblies of one lot from one manufacturer.

b. Booster pellets of one lot interfix from one manufacturer.

c. Lead charges of one lot interfix from one manufacturer.

4.4.2 Examination. See MIL-A-48078. Unless otherwise specified in the Classification of Defects and Test tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70808A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Pellet, Booster				11740826
					NEXT HIGHER ASSEMBLY
					11737000
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of pellet		0.40%	3.2	Gage
102	Length of pellet		0.40%	3.2	Gage
103	Chipped edge corners exceeding .25 inch		0.40%	3.2	Visual/Gage
104	Density of pellet		0.40%	3.3	4.5.2
Minor					
201	Poor workmanship		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.2	Cap, Booster	1	1	11740828
				NEXT HIGHER ASSEMBLY: 11737000

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Inner diameter		0.65%	3.2	Gage
202	Thickness of booster cap		0.65%	3.2	Gage
203	Length of booster cap		0.65%	3.2	Gage
204	Protective finish missing or incomplete		0.65%	3.2	Visual
205	Poor workmanship		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Lead, Charge				11740829
					NEXT HIGHER ASSEMBLY 11737000
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter of cup lead (after filling) max		0.40%	3.2	Gage
102	Length of lead cup (after filling) max		0.40%	3.2	Gage
103	Charge is not flush or below flush with cup		0.40%	3.2	Visual/Gage
Minor					
201	Poor workmanship		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70808A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Cup, Lead	1 OF 1	11744120
			NEXT HIGHER ASSEMBLY: 1740829

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Diameter of cup		0.65%	3.2	Gage
202	Diameter of cup flange		0.65%	3.2	Gage
203	Length of cup		0.65%	3.2	Gage
204	Protective finish missing or incomplete		0.65%	3.2	Visual
205	Poor workmanship		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

MIL-F-70808A (AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Fuze, PD: M745, Less Booster and Lead (Before Loading)	1 OF 1	11737001
			NEXT HIGHER ASSEMBLY: 11737000

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical I	Fuze S & A not in safe position		100%	3.5	Gage
Major	None defined				
Minor	None defined				

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the 1st source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Fuze, PD: M745 (After Loading of Lead)				11737000
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Lead charge missing in lead hole area		0.40%	3.2	Visual
Minor	None defined				

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.7	Fuze, PD: M745 (After Loading of Booster, Prior to Crimping)	1	1	11737000
				NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Booster pellet missing		0.40%	3.2	Visual
Minor	None defined				

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.8	Fuze Base Assembly (loaded)	1	1	11737030
				NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Booster and lead output test		(a)	3.4	4.5.3
Minor	None defined				

NOTES: (a) The test shall be conducted once for each combination of explosive lot of booster pellets and lead charges consisting of no more than 100,000 each. The sample size shall be two hundred (200) loaded fuze assemblies. Three or more defects shall be cause for the explosive lots to be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	Fuze, PD: M745 Loaded Assembly				11737000
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Booster cap improperly crimped to fuze base		0.40%	3.2	Visual
102	Fuze intrusion length		0.40%	3.6	Gage
Minor					
201	Marking missing or incomplete		0.65%	3.2	Visual
202	Poor workmanship		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET		DRAWING NUMBER
4.4.2.10	Packing and Marking of Box, Fiberboard for Fuze, PD: M745 (after boostering, before barrier bag and wood box)		1 OF 1		9347415
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Any material containing condensate or surface moisture		0.40%	5.1	Visual
102	Bottom support or loose partition missing or incomplete		0.40%	5.1	Visual
103	Separator missing or incomplete		0.40%	5.1	Visual
104	Fiberboard box not properly closed or sealed		0.40%	5.1	Visual
Minor					
201	Poor workmanship		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.11	Packing and Marking of Wood Box, for Fuze, PD, M745				9347416
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Fiberboard box improperly marked		0.40%	5.1	Visual
102	Barrier bag improperly sealed or marked		0.40%	5.1	Visual
103	Top, side or end fillers missing		0.40%	5.1	Visual
104	Wood box improperly sealed or marked		0.40%	5.1	Visual
Minor					
201	Poor workmanship		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.12	Packing and Marking of Container, M548 for Fuze, (unsealed)				9381685
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Any material containing condensate or surface moisture		0.40%	5.1	Visual
102	Bottom support or separators missing		0.40%	5.1	Visual
103	Partition missing or incomplete		0.40%	5.1	Visual
104	Top filler missing or insufficient (contents loose)		0.40%	5.1	Visual/Manual
105	Incorrect number of assemblies		0.40%	5.1	Visual
106	Fuze supports missing		0.40%	5.1	Visual
Minor	None defined				

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

MIL-F-70808A (AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.13	Packing and Marking of Container, M548 for Fuze, PD, M745 (sealed)				9381685
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Air leakage test		100%	5.1	4.5.4
Minor					
201	Marking missing or unidentifiable		0.65%	5.2.1	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. See 4.5.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph/Inspection Method" column in the tables starting with 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection.

4.5.1 Materials, components and processes. Compliance with all requirements of Section 3 of this specification shall be ascertained by current and continuing examination of inspection and test data to determine that all components (parts, sub-assemblies, and materials) have been inspected and tested and found to comply with their respective drawing and specification requirements, and that all specified manufacturing processes have been followed.

4.5.1.1 Visual and mechanical inspection. The visual, manual, tactile and mechanical inspection and tests shall verify compliance with the requirements of Section 3 and 5 of this specification in accordance with 4.4.2 herein and Table I.

4.5.2 Density of booster pellet. The density of each pellet shall be determined by using the following calculation.

$$\text{Density, g/cc} = \frac{\text{Mass in grams}}{(\text{Height, inches})\ (\text{Diameter, inches})^2} \quad (12.87)$$

4.5.3 Booster and lead output test. The booster and lead shall be assembled into an M745 fuze base assembly (11737030). A Government approved fixture shall be used to simulate an M745 fuze explosive train. The explosive train shall be initiated remotely. Any assembly that fails to shear the witness block (3.0 inch minimum diameter of 2011-T3 aluminum) 360 degrees upon initiation shall be classed defective.

WARNING: This test is dangerous and must be performed behind a suitable barricade.

4.5.4 Air leakage test (see drawing 9381685. The sealed metal ammunition container shall be tested in accordance with the procedures of 9246386.

5. PACKAGING

5.1 Unit Packaging.

5.1.1 Level A. Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

5.1.2 Level B. Packaging for fuzes with boosters shall be in accordance with the requirements of drawing 9347415.

5.1.3 Level C. Not applicable.

5.2 Packing

5.2.1 Level A. Fuzes with boosters shall be packed in accordance with the requirements of dwg. 9381685.

5.2.2 Level B. Fuzes with boosters shall be packed in accordance with the requirements of drawing 9387416.

5.2.3 Level C. Packing for fuzes without boosters shall be in accordance with the requirements of drawing 9347415.

5.3 Marking

5.3.1 Level A. Fuzes with boosters shall be marked in accordance with the requirements of drawing 9381685.

5.3.2 Level B. Fuzes with boosters shall be marked in accordance with the requirements of drawing 9347416.

5.3.3 Level C. Fuzes without boosters shall be marked in accordance with the requirements of drawing 9347415.

6. NOTES

6.1 Intended use. The Fuze, PD: M745 is designed to provide a means of detonating the M722 Smoke cartridge, 60mm, Lightweight Company Mortar System.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of designs for approval. See 6.2.3 of MIL-A-48078. Submit equipment designs, as required to: Commander, U.S. Army Armament Research, Development and Engineering Center, ATTN: AMSMC-QAT-I, Picatinny Arsenal, NJ 07806-5000. This address will be specified on the contract Data Requirements List, DD Form 1423 in the contract. Unless otherwise specified, data item DI-R-1714 will apply.

6.4 Subject term (key word) listing.

Air leakage test
Booster and lead output test
Fuze, PD, M745

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as ARRADCOM, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, Picatinny Arsenal drawings or Harry Diamond Laboratories. Technical data originally prepared by these activities is now under cognizance of ARDEC.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1390-A608)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-F-70808A (AR)	

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.