MIL-S-48303(PA)
30 May 1975
SUPERSEDING
See Section 6

MILITARY SPECIFICATION

SWITCH ASSEMBLY: M167

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of switch entitled Switch Assembly: M167 which is used in the Lance warhead section to select the mode of explosion.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-C-6021	- Casting, Classification and Inspection.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-130	- Identification, Marking of U.S. Military Property.
MIL-STD-202	- Test Methods for Electronic and Electrical Component Parts.
MIL-STD-456	- Electronic Parts, Date and Source Coding for.
MIL-STD-810	- Environmental Test Methods.
MIL-STD-1169	- Packaging, Packing and Marking for Shipment of Inert Ammunition Components.
MIL-STD-1460	- Soldering of Electrical Connections and Printed Wiring Assemblies, Procedures For.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

DRAWINGS

ORDNANCE CORPS

8880138	- Housing, Switch.
8880196	- Switch.
8880197	- Switch.
8879854	- Switch, Combined Option Selector: M167.
9236827	- Housing, Casting.
9236832	- Actuator Splicing Subassembly.
ET-8879854	- Equipment Tabulation.

PUBLICATIONS

PICATINNY ARSENAL

QAI-PA-1	- Quality Assurance Instructions for Reporting Data on Nuclear Weapons.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The switch shall comply with all requirements specified on the drawing (dwg) 8879854, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

3.4 Serialization. A six letter serial code shall be assigned to the item. Serial codes required on these items shall be obtained by means of a letter addressed to: Commanding Officer, Picatinny Arsenal, Dover, New Jersey 07801, ATTENTION: SARPA-QA-T-M. The letter of request shall include:

a. Exact nomenclature of the item as specified on the applicable drawing.
b. Name of the contractor.
c. Contract number or procurement request order number.
d. Number of serial codes required (unused code numbers shall be returned).

3.5 Circuit resistance. The circuit resistance between the terminal pins listed in Tables I and II shall not exceed 0.050 ohms when tested in accordance with 4.4.1. Record actual values in accordance with 3.13.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

Table I

No. 1 Switch positions (J1 connector)

HG P/P	Test Code No.	LG P/P	Test Code No.	G P/P	Test Code No.	H P/P	Test Code No.	L P/P	Test Code No.
16-23	004001	16-23	004015	16-23	004029	16-23	004035	16-23	004047
15-4	004002	15-4	004016	17-5	004030	15-4	004036	15-4	004048
30-29	004003	30-6	004017	21-9	004031	30-29	004037	30-6	004049
14-11	004004	14-11	004018	2-25	004032	14-11	004038	14-11	004050
17-5	004005	17-5	004019	22-10	004033	17-5	004039	17-5	004051
18-13	004006	18-7	004020	3-26	004034	18-13	004040	18-7	004052
21-9	004007	21-9	004021			21-9	004041	21-9	004053
2-25	004008	2-25	004022			19-28	004042	19-33	004054
19-28	004009	19-33	004023			31-12	004043	31-8	004055
22-10	004010	22-10	004024			1-36	004044	1-24	004056
31-12	004011	31-8	004025			3-26	004045	3-26	004057
1-36	004012	1-24	004026			20-27	004046	20-34	004058
3-26	004013	3-26	004027						
20-27	004014	20-34	004028						

Table II

No. 2 Switch positions (J2 connector)

A		B		C	
P/P	Test Code No.	P/P	Test Code No.	P/P	Test Code No.
M-R	004059	Y-T	004065	Y-G	004071
Z-S	004060	J-U	004066	J-H	004072
L-P	004061	M-A	004067	M-E	004073
K-N	004062	Z-B	004068	Z-V	004074
b-a*	004063	L-C	004069	L-F	004075
C-37(J1)	004064	K-D	004070	K-W	004076

*Resistance shall be 1.25 ± 0.20 ohms.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

3.6 Insulation resistance. The insulation resistance between each pin and all other pins, listed below at the designated switch positions, and the case shall not be less then 50 megohms when subjected to a potential of 500 volts direct current (vdc) with the current limited of five (5) milliamperes (ma) when tested as specified in 4.4.2. Record actual values in accordance to 3.13.

a. No. 1 Switch Positions (J1 Connector)

(1) position S:

Pin to Pin	Test Code No.
1 to 2 thru 31, 33, 34, 36, 37, case	005001
2 to 3 thru 31, 33, 34, 36, 37, case	005002
3 to 4 thru 31, 33, 34, 36, 37, case	005003
4 to 5 thru 31, 33, 34, 36, 37, case	005004
5 to 6 thru 31, 33, 34, 36, 37, case	005005
6 to 7 thru 31, 33, 34, 36, 37, case	005006
7 to 8 thru 31, 33, 34, 36, 37, case	005007
8 to 9 thru 31, 33, 34, 36, 37, case	005008
9 to 10 thru 31, 33, 34, 36, 37, case	005009
10 to 11 thru 31, 33, 34, 36, 37, case	005010
11 to 12 thru 31, 33, 34, 36, 37, case	005011
12 to 13 thru 31, 33, 34, 36, 37, case	005012
13 to 14 thru 31, 33, 34, 36, 37, case	005013
14 to 15 thru 31, 33, 34, 36, 37, case	005014
15 to 16 thru 31, 33, 34, 36, 37, case	005015
16 to 17 thru 31, 33, 34, 36, 37, case	005016
17 to 18 thru 31, 33, 34, 36, 37, case	005017
18 to 19 thru 31, 33, 34, 36, 37, case	005018
19 to 20 thru 31, 33, 34, 36, 37, case	005019
20 to 21 thru 31, 33, 34, 36, 37, case	005020
21 to 22 thru 31, 33, 34, 36, 37, case	005021
22 to 23 thru 31, 33, 34, 36, 37, case	005022
23 to 24 thru 31, 33, 34, 36, 37, case	005023
24 to 25 thru 31, 33, 34, 36, 37, case	005024
25 to 26 thru 31, 33, 34, 36, 37, case	005025
26 to 27 thru 31, 33, 34, 36, 37, case	005026
27 to 28 thru 31, 33, 34, 36, 37, case	005027
28 to 29 thru 31, 33, 34, 36, 37, case	005028
29 to 30, 31, 33, 34, 36, 37, case	005029
30 to 31, 33, 34, 36, 37, case	005030
31 to 33, 34, 36, 37, case	005031
33 to 34, 36, 37, case	005032
34 to 36, 37, case	005033
36 to 37, case	005034
37 to case	005193

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

(2) position LG:

Pin to Pin	Test Code No.
1 to 4, 5, 9, 10, 12, 13, 14, 16, 18, 19, 20, 25 thru 31, 36, case	005035
4 to 5, 9, 10, 12, 13, 14, 16, 18, 19, 20, 25 thru 31, 36, case	005036
5 to 9, 10, 12, 13, 14, 16, 18, 19, 20, 25 thru 31, 36, case	005037
9 to 10, 12, 13, 14, 16, 18, 19, 20, 25 thru 31, 36, case	005038
10 to 12, 13, 14, 16, 18, 19, 20, 25 thru 31, 36, case	005039
12 to 13, 14, 16, 18, 19, 20, 25 thru 31, 36, case	005040
13 to 14, 16, 18, 19, 20, 25 thru 31, 36, case	005041
14 to 16, 18, 19, 20, 25 thru 31, 36, case	005042
16 to 18, 19, 20, 25 thru 31, 36, case	005043
18 to 19, 20, 25 thru 31, 36, case	005044
19 to 20, 25 thru 31, 36, case	005045
20 to 25 thru 31, 36, case	005046
25 to 26 thru 31, 36, case	005047
26 to 27 thru 31, 36, case	005048
27 to 28 thru 31, 36, case	005049
28 to 29 thru 31, 36, case	005050
29 to 30, 31, 36, case	005051
30 to 31, 36, case	005052
31 to 36, case	005053
36 to case	005194

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

(3) position HG

Pin to Pin	Test Code No.
2 to 3, 5, 6, 7, 8, 14, 15, 16, 18, 19, 20, 21, 22, 24, 30, 31, 33, 34, 36, case	005054
3 to 5, 6, 7, 8, 14, 15, 16, 18, 19, 20, 21, 22, 24, 30, 31, 33, 34, 36, case	005055
5 to 6, 7, 8, 14, 15, 16, 18, 19, 20, 21, 22, 24, 30, 31, 33, 34, 36, case	005056
6 to 7, 8, 14, 15, 16, 18, 19, 20, 21, 22, 24, 30, 31, 33, 34, 36, case	005057
7 to 8, 14, 15, 16, 18, 19, 20, 21, 22, 24, 30, 31, 33, 34, 36, case	005058
8 to 14, 15, 16, 18, 19, 20, 21, 22, 24, 30, 31, 33, 34, 36, case	005059
14 to 15, 16, 18, 19, 20, 21, 22, 24, 30, 31, 33, 34, 36, case	005060
15 to 16, 18, 19, 20, 21, 22, 24, 30, 31, 33, 34, 36, case	005061
16 to 18, 19, 20, 21, 22, 24, 30, 31, 33, 34, 36, case	005062
18 to 19, 20, 21, 22, 24, 30, 31, 33, 34, 36, case	005063
19 to 20, 21, 22, 24, 30, 31, 33, 34, 36, case	005064
20 to 21, 22, 24, 30, 31, 33, 34, 36, case	005065
21 to 22, 24, 30, 31, 33, 34, 36, case	005066
22 to 24, 30, 31, 33, 34, 36, case	005067
24 to 30, 31, 33, 34, 36, case	005068
30 to 31, 33, 34, 36, case	005069
31 to 33, 34, 36, case	005070
33 to 34, 36, case	005071
34 to 36, case	005072
36 to case	005195

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

(4) position G

Pin to Pin	Test Code No.
1 to 4 thru 16, 18, 19, 20, 24 thru 34, 36, case	005073
4 to 5 thru 16, 18, 19, 20, 24 thru 34, 36, case	005074
5 to 6 thru 16, 18, 19, 20, 24 thru 34, 36, case	005075
6 to 7 thru 16, 18, 19, 20, 24 thru 34, 36, case	005076
7 to 8 thru 16, 18, 19, 20, 24 thru 34, 36, case	005077
8 to 9 thru 16, 18, 19, 20, 24 thru 34, 36, case	005078
9 to 10 thru 16, 18, 19, 20, 24 thru 34, 36, case	005079
10 to 11 thru 16, 18, 19, 20, 24 thru 34, 36, case	005080
11 to 12 thru 16, 18, 19, 20, 24 thru 34, 36, case	005081
12 to 13 thru 16, 18, 19, 20, 24 thru 34, 36, case	005082
13 to 14 thru 16, 18, 19, 20, 24 thru 34, 36, case	005083
14 to 15 thru 16, 18, 19, 20, 24 thru 34, 36, case	005084
15 to 16, 18, 19, 20, 24 thru 34, 36, case	005085
16 to 18, 19, 20, 24 thru 34, 36, case	005086
18 to 19, 20, 24 thru 34, 36, case	005087
19 to 20, 24 thru 34, 36, case	005088
20 to 24 thru 34, 36, case	005089
24 to 25 thru 34, 36, case	005090
25 to 26 thru 34, 36, case	005091
26 to 27 thru 34, 36, case	005092
27 to 28 thru 34, 36, case	005093
28 to 29 thru 34, 36, case	005094
29 to 30 thru 34, 36, case	005095
30 to 31 thru 34, 36, case	005096
31 to 32 thru 34, 36, case	005097
32 to 33, 34, 36, case	005098
33 to 34, 36, case	005099
34 to 36, case	005100
36 to case	005196

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

(5) position L

Pin to Pin	Test Code No.
2 to 3, 4, 6, 7, 8, 9, 10, 12, 13, 14, 17, 22, 23, 24, 25, 27, 28, 29, 33, 34, 36, case	005101
3 to 4, 6, 7, 8, 9, 10, 12, 13, 14, 17, 22, 23, 24, 25, 27, 28, 29, 33, 34, 36, case	005102
4 to 6, 7, 8, 9, 10, 12, 13, 14, 17, 22, 23, 24, 25, 27, 28, 29, 33, 34, 36, case	005103
6 to 7, 8, 9, 10, 12, 13, 14, 17, 22, 23, 24, 25, 27, 28, 29, 33, 34, 36, case	005104
7 to 8, 9, 10, 12, 13, 14, 17, 22, 23, 24, 25, 27, 28, 29, 33, 34, 36, case	005105
8 to 9, 10, 12, 13, 14, 17, 22, 23, 24, 25, 27, 28, 29, 33, 34, 36, case	005106
9 to 10, 12, 13, 14, 17, 22, 23, 24, 25, 27, 28, 29, 33, 34, 36, case	005107
10 to 12, 13, 14, 17, 22, 23, 24, 25, 27, 28, 29, 33, 34, 36, case	005108
12 to 13, 14, 17, 22, 23, 24, 25, 27, 28, 29, 33, 34, 36, case	005109
13 to 14, 17, 22, 23, 24, 25, 27, 28, 29, 33, 34, 36, case	005110
14 to 17, 22, 23, 24, 25, 27, 28, 29, 33, 34, 36, case	005111
17 to 22, 23, 24, 25, 27, 28, 29, 33, 34, 36, case	005112
22 to 23, 24, 25, 27, 28, 29, 33, 34, 36, case	005113
23 to 24, 25, 27, 28, 29, 33, 34, 36, case	005114
24 to 25, 27, 28, 29, 33, 34, 36, case	005115
25 to 27, 28, 29, 33, 34, 36, case	005116
27 to 28, 29, 33, 34, 36, case	005117
28 to 29, 33, 34, 36, case	005118
29 to 33, 34, 36, case	005119
33 to 34, 36, case	005120
34 to 36, case	005121
36 to case	005197

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

(6) position H

Pin to Pin	Test Code No.
1 to 2, 6, 7, 8, 10, 11, 15, 16, 17, 18, 19, 20, 21, 22, 24, 25, 26, 30, 31, 33, 34, case	005122
2 to 6, 7, 8, 10, 11, 15, 16, 17, 18, 19, 20, 21, 22, 24, 25, 26, 30, 31, 33, 34, case	005123
6 to 7, 8, 10, 11, 15, 16, 17, 18, 19, 20, 21, 22, 24, 25, 26, 30, 31, 33, 34, case	005124
7 to 8, 10, 11, 15, 16, 17, 18, 19, 20, 21, 22, 24, 25, 26, 30, 31, 33, 34, case	005125
8 to 10, 11, 15, 16, 17, 18, 19, 20, 21, 22, 24, 25, 26, 30, 31, 33, 34, case	005126
10 to 11, 15, 16, 17, 18, 19, 20, 21, 22, 24, 25, 26, 30, 31, 33, 34, case	005127
11 to 15, 16, 17, 18, 19, 20, 21, 22, 24, 25, 26, 30, 31, 33, 34, case	005128
15 to 16, 17, 18, 19, 20, 21, 22, 24, 25, 26, 30, 31, 33, 34, case	005129
16 to 17, 18, 19, 20, 21, 22, 24, 25, 26, 30, 31, 33, 34, case	005130
17 to 18, 19, 20, 21, 22, 24, 25, 26, 30, 31, 33, 34, case	005131
18 to 19, 20, 21, 22, 24, 25, 26, 30, 31, 33, 34, case	005132
19 to 20, 21, 22, 24, 25, 26, 30, 31, 33, 34, case	005133
20 to 21, 22, 24, 25, 26, 30, 31, 33, 34, case	005134
21 to 22, 24, 25, 26, 30, 31, 33, 34, case	005135
22 to 24, 25, 26, 30, 31, 33, 34, case	005136
24 to 25, 26, 30, 31, 33, 34, case	005137
25 to 26, 30, 31, 33, 34, case	005138
26 to 30, 31, 33, 34, case	005139
30 to 31, 33, 34, case	005140
31 to 33, 34, case	005141
33 to 34, case	005142
34 to case	005198

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

b. No. 2 Switch Positions (J2 Connector)

(1) position A

Pin to Pin	Test Code No.
A to B, C, D, E, F, G, H, J, K, L, M, T, U, V, W, Y, Z, a, c, case	005143
B to C, D, E, F, G, H, J, K, L, M, T, U, V, W, Y, Z, a, c, case	005144
C to D, E, F, G, H, J, K, L, M, T, U, V, W, Y, Z, a, c, case	005145
D to E, F, G, H, J, K, L, M, T, U, V, W, Y, Z, a, c, case	005146
E to F, G, H, J, K, L, M, T, U, V, W, Y, Z, a, c, case	005147
F to G, H, J, K, L, M, T, U, V, W, Y, Z, a, c, case	005148
G to H, J, K, L, M, T, U, V, W, Y, Z, a, c, case	005149
H to J, K, L, M, T, U, V, W, Y, Z, a, c, case	005150
J to K, L, M, T, U, V, W, Y, Z, a, c, case	005151
K to L, M, T, U, V, W, Y, Z, a, c, case	005152
L to M, T, U, V, W, Y, Z, a, c, case	005153
M to T, U, V, W, Y, Z, a, c, case	005154
T to U, V, W, Y, Z, a, c, case	005155
U to V, W, Y, Z, a, c, case	005156
V to W, Y, Z, a, c, case	005157
W to Y, Z, a, c, case	005158
Y to Z, a, c, case	005159
Z to a, c, case	005160
a to c, case	005161
c to case	005199

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

(2) position B

Pin to Pin	Test Code No.
E to F, G, H, J, K, L, M, N, P, R, S, T, V, W, Z, case	005162
F to G, H, J, K, L, M, N, P, R, S, T, V, W, Z, case	005163
G to H, J, K, L, M, N, P, R, S, T, V, W, Z, case	005164
H to J, K, L, M, N, P, R, S, T, V, W, Z, case	005165
J to K, L, M, N, P, R, S, T, V, W, Z, case	005166
K to L, M, N, P, R, S, T, V, W, Z, case	005167
L to M, N, P, R, S, T, V, W, Z, case	005168
M to N, P, R, S, T, V, W, Z, case	005169
N to P, R, S, T, V, W, Z, case	005170
P to R, S, T, V, W, Z, case	005171
R to S, T, V, W, Z, cas e	005172
S to T, V, W, Z, case	005173
T to V, W, Z, case	005174
V to W, Z, case	005175
W to Z, case	005176
Z to case	005200

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

(3) position C

Pin to Pin	Test Code No.
A to B, C, D, G, J, K, L, M, N, P, R, S, T, U, V, case	005177
B to C, D, G, J, K, L, M, N, P, R, S, T, U, V, case	005178
C to D, G, J, K, L, M, N, P, R, S, T, U, V, case	005179
D to G, J, K, L, M, N, P, R, S, T, U, V, case	005180
G to J, K, L, M, N, P, R, S, T, U, V, case	005181
J to K, L, M, N, P, R, S, T, U, V, case	005182
K to L, M, N, P, R, S, T, U, V, case	005183
L to M, N, P, R, S, T, U, V, case	005184
M to N, P, R, S, T, U, V, case	005185
N to P, R, S, T, U, V, case	005186
P to R, S, T, U, V, case	005187
R to S, T, U, V, case	005188
S to T, U, V, case	005189
T to U, V, case	005190
U to V, case	005191
V to case	005192

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

3.7 Indexing. Indexing shall be accomplished by means of a positive detent mechanism. The detent mechanism shall require an input torque of eight plus two minus three inch pounds when selector is rotated through each position both clockwise and counter clockwise. Testing shall be in accordance with 4.4.3. Record torque in accordance with 3.13.

No. 1 Switch			No. 2 Switch		
Position	Rotation	Test Code No.	Position	Rotation	Test Code No.
S to HG	CW	006001	A to B	CW	006013
HG to LG	CW	006002	B to C	CW	006014
LG to G	CW	006003			
G to H	CW	006004			
H to L	CW	006005	C to B	CCW	006017
L to S	CW	006006	B to A	CCW	006018
S to L	CCW	006007			
L to H	CCW	006008			
H to G	CCW	006009			
C to LG	CCW	006010			
LG to HG	CCW	006011			
HG to S	CCW	006012			

3.8 Switch Assembly leakage. The unit shall be purged and filled with 90% nitrogen and 10% helium. The leak rate shall be 1 X 10^{-4} CC/sec maximum at an external pressure of 10 microns when tested as specified in 4.4.4. Record the leak rate in accordance with 3.13. The code no. is 007003.

3.9 Casting. The contractor shall furnish objective evidence (see 6.2) that the casting complies with dwg. 9236827. Testing shall be as specified in 4.4.5.

3.10 Environmental testing. The switch shall comply with MIL-STD-810, visual inspection and failure criteria, section 3. The switch shall also comply with 4.3.3.1 before and after each environmental test. Testing shall be as specified in 4.4.6. Tests shall be conducted in the order specified.

3.10.1 Thermal shock. The switch shall withstand thermal shocks between +160 ± 5°F to -65 ± 5°F for three complete cycles without evidence of external damage (see 6.5) and shall comply with the requirements of 3.5, 3.6 and 3.7 after testing as specified in 4.4.6.1.

3.10.2 Mechanical shock. The switch shall withstand exposure to shock of 50 ± 5 gravity units (g's) peak amplitude, half sine durations of 11 ± 1 milliseconds, applied once in each direction along each of the three (3) perpendicular axes (total of 6 shocks) without evidence of external damage (see 6.5) and shall comply with the requirements of 3.5, 3.6 and 3.7 after testing as specified in 4.4.6.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

3.10.3 Transportation vibration. The switch shall withstand vibration tests along each of three (3) mutually perpendicular axes as specified in Table III without evidence of external damage (see 6.5) and shall be tested as specified in 4.4.6.3. Frequency shall be cycled at a logarithmic rate between 5-500-5 in fifteen (15) minutes. At the completion of this test, the switch shall comply with 3.5, 3.6 and 3.7.

Table III

Vibration test schedule

Frequency (Hz)	Amplitude	Sweep Cycles	
		Ambient -65°F	+160 ± 5°F
5-15	0.4" da	1	1
15-80	5 g	1	1
80-115	0.015" da	1	1
115-500	10 g	1	1

3.10.4 Operational vibration. The switch shall be vibrated at room temperature, -40 + 5°F, and +160 + 5°F in each of three mutually perpendicular axes as specified below without evidence of external damage (see 6.5). During vibration exposure, contact chatter shall be monitored and shall not exceed 10 microseconds with a contact load of 100 ± 10 milliamperes. After testing, the switch shall comply with 3.11, 3.5, 3.6 and 3.7. The vibration test shall be conducted as specified in 4.4.6.4.

a. .06 g /Hertz (Hz) power spectral density (9.3 rms g's minimum) at frequencies ranging from 100 to 1000 Hz, attenuated 6 decibels per octave so that the total frequency enveloped is 50 to 2000 Hz for 10 seconds. The tolerance level shall be ± 3 decibels (Db) between 100 to 1000 Hz and ± 6 Db between 1000 to 2000 Hz.

b. .02 g /Hz power spectral density (5.3 rms g's minimum) at frequencies ranging from 100 to 1000 Hz, attenuated 6 Db so that the frequency enveloped is 50 to 2000 Hz for two (2) minutes. The tolerance level shall be ± 3 Db between 100 to 2000 Hz.

3.11 Current carrying capacity. The maximum allowable voltage drop between terminals listed in Table IV shall not exceed 400 millivolts. The unit shall also be capable of carrying a resistance load of 20 ± 2 amperes for 200 ± 5 milliseconds. After being tested as specified in 4.4.7, the unit shall be tested for compliance with 3.5 and 3.6. Record voltage drop in accordance with 3.13.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

Table IV

Connector	Switch	Position	Terminals	Test Code No.
J1	1	HG	11-14	013001
J2	2	B	A-M	013002

3.12 Life cycling. The unit shall be able to withstand 300 cycles of each switch without degradation of 3.11, 3.5, 3.6 and 3.7. Testing shall be in accordance with 4.4.8.

3.13 Test codes. The contractor shall supply feedback data on punch cards for any item for which coding is required in section 3. The feedback data shall be in accordance with QAI-PA-1.

3.14 Marking. Switches shall be marked in accordance with MIL-STD-130 with the following information:

a. Manufacturers name or trademark.
b. Government drawing number, type designation, and serial number (see 3.4).
c. Date code in accordance with MIL-STD-456.
d. Switch terminals shall be marked as specified in the applicable detail specification or drawing.

The finish or any dimension of the item shall not be altered or damaged by application of marking information. The material used for marking shall not be subject to corrosion, fungus, flaking or similar adverse action which could prevent proper functioning of the switches.

3.15 Soldering. All soldering shall be in compliance with MIL-STD-1460(MU).

3.16 Workmanship.

3.16.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.16.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.16.3 Burrs. Parts shall be free from burrs.

3.16.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.16.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

3.16.6 Electrical. Cable assemblies and wires shall be dressed in such a manner as to prevent pinching or chafing of the wire insulation. Ends of wires shall be free from burrs, sharp edges, or points. All parts shall be free from flux, chips, dirt, grease, rust or foreign material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall submit 8 complete assemblies (see dwg 8879854) for first article testing to the testing facility designated in the invitation for bids or request for proposal.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table V. Tests shall be conducted in order specified in Table V.

Table V

First article inspection and tests

Inspection or Test	Testing Sequence Unit Nos.	Dest	Non-Dest
1. Classification of characteristics (see 4.3.2.1)	all		X
2. Thermal shock (see 3.10.1)	1,4,6,7	X	
3. Transportation vibration (see 3.10.3)	2,3,5,8		X
4. Mechanical shock (see 3.10.2)	1,4,5,8	X	
5. Operational vibration @ +160°F (see 3.10.4)	1,3,6,8	X	
6. Operational vibration @ -40°F (see 3.10.4)	1,2,7,8	X	
7. Circuit resistance (see 3.5)	all		X
8. Insulation resistance (see 3.6)	all		X
9. Indexing (see 3.7)	all		X
10. Combined option selector switch leakage (see 3.8)	all		X
11. Current carrying capacity (see 3.11)	all		X
12. Life cycling (see 3.12)	1,3,4,7	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

4.3.1 Inspection lot formation. All items in each inspection lot shall be from one production line, one shift, one batch of products, one manufacturer of raw material or components, one production method or manufacturing operation. The entire lot shall be submitted as a unit for inspection.

4.3.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table VI and Table VII), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

Table VI
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-72	all	140-141	124	256-259	177	541-549	230
73	72	142	125	260-262	178	550-559	231
74	73	143-144	126	263-265	179	560-569	232
75	74	145	127	266-268	180	570-579	233
76	75	146-147	128	269-271	181	580-590	234
77	76	148-149	129	272-275	182	591-601	235
78	77	150	130	276-278	183	602-613	236
79	78	151-152	131	279-282	184	614-625	237
80	79	153-154	132	283-285	185	626-637	238
81-82	80	155-156	133	286-289	186	638-649	239
83	81	157	134	290-293	187	650-662	240
84	82	158-159	135	294-296	188	663-676	241
85	83	160-161	136	297-300	189	677-690	242
86	84	162-163	137	301-304	190	691-704	243
87	85	164-165	138	305-308	191	705-719	244
88-89	86	166-167	139	309-312	192	720-735	245
90	87	168	140	313-316	193	736-751	246
91	88	169-170	141	317-320	194	752-768	247
92	89	171-172	142	321-324	195	769-785	248
93	90	173-174	143	325-329	196	786-804	249
94-95	91	175-176	144	330-333	197	805-823	250
96	92	177-178	145	334-338	198	824-842	251
97	93	179-180	146	339-342	199	843-863	252
98	94	181-182	147	343-347	200	864-884	253
99-100	95	183-184	148	348-352	201	885-907	254
101	96	185-187	149	353-356	202	908-930	255
102	97	188-189	150	357-361	203	931-955	256
103	98	190-191	151	362-366	204	956-981	257
104-105	99	192-193	152	367-372	205	982-1008	258
106	100	194-195	153	373-377	206	1009-1036	259
107	101	196-197	154	378-382	207	1037-1066	260
108-109	102	198-200	155	383-388	208	1067-1098	261
110	103	201-202	156	389-393	209	1099-1131	262
111	104	203-204	157	394-399	210	1132-1166	263
112-113	105	205-207	158	400-405	211	1167-1204	264
114	106	208-209	159	406-411	212	1205-1243	265
115	107	210-212	160	412-417	213	1244-1285	266
116-117	108	213-214	161	418-424	214	1286-1330	267
118	109	215-217	162	425-430	215	1331-1378	268
119	110	218-219	163	431-437	216	1379-1429	269
120-121	111	220-222	164	438-443	217	1430-1483	270
122	112	223-224	165	444-450	218	1484-1542	271
123-124	113	225-227	166	451-457	219	1543-1605	272
125	114	228-230	167	458-465	220	1606-1673	273
126-127	115	231-232	168	466-472	221	1674-1747	274
128	116	233-235	169	473-480	222	1748-1827	275
129-130	117	236-238	170	481-488	223	1828-1914	276
131	118	239-241	171	489-496	224	1915-2010	277
132-133	119	242-243	172	497-504	225	2011-2115	278
134	120	244-246	173	505-513	226	2116-2232	279
135-136	121	247-249	174	514-521	227	2233-2361	280
137	122	250-252	175	522-530	228	over 2361	298
138-139	123	253-255	176	531-540	229		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

Table VII
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	137 156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Switch (see dwg 8880196 and dwg 8880197).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Soldering in accordance with MIL-STD-1460(MU), incorrect	Visual
Minor:	None defined.	

4.3.2.1.2 Housing, switch (see dwg 8880138).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Flatness of mounting surface incorrect	Gage
	102. Location of mounting holes, incorrect	Gage
	103. Diameter of mounting holes, incorrect	Gage
	104. 'O' ring area surface finish (6 places), incorrect	Visual
	105. Objective evidence of radiograph inspection (see 9236827)	Visual
Minor:	None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

4.3.2.1.3 Switch combined option selector: XM167 (see dwg 8879854).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Sealant on 40 screws missing	Visual
102.	Torque on 40 screws incorrect	Gage
103.	Torque on 5 nuts incorrect	Gage
104.	Major keyway parallel to datum surface (2)	Gage
105.	Any components missing, damaged or improperly assembled	Visual
106.	Cable connector interface, incorrect	Gage
107.	Objective evidence of performance acceptance (dwg 9236832)	Visual
108.	Objective evidence relative to material missing or improper (see 3.1)	Visual
Minor:		
201.	Name plate missing, illegible or incorrect	Visual
202.	Evidence of poor workmanship (see 3.16)	Visual

4.3.2.1.4 Preparation for delivery (see 5).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Preservation, packaging and packing not in accordance with MIL-STD-1169	Visual
102.	Marking not in accordance with MIL-STD-1169	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.16)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

4.3.3 Testing. All tests shall be performed. Tests shall be performed in the order specified below:

Test	Test Classification
a. Circuit resistance	Major
b. Insulation resistance	Major
c. Indexing	Major
d. Combined option selector switch leakage	Major

None of these tests are considered destructive and samples so tested may be returned to the lot.

4.3.3.1 Circuit resistance, insulation resistance, indexing, and switch assembly leakage. Each switch shall be tested in accordance with 4.4.1 through 4.4.4. If any item fails to comply with 3.5 through 3.8, the item shall be rejected and removed from the lot.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL). Els for assemblies are listed on the Equipment Tabulation, ET-8879854. When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

4.4.1 Circuit resistance. The switch shall be tested on an approved four terminal volt-ammeter measuring equipment to determine compliance with 3.5. The magnitude of the direct current (dc) through the contacts shall be 100 + 10 milliamperes (ma) and the open circuit test voltage shall not exceed 32 volts direct current (vdc). Separate voltage and current hookup wiring shall be used at each terminal in order not to include the effect of hookup wiring on measurement values. Activation of switches for purpose of improving contact surfaces prior to actual measurement of resistance shall not be permitted.

4.4.2 Insulation resistance. The insulation resistance shall be measured on approved equipment at a potential of 500 + 50 vdc and current shall not exceed 5 milliamperes (ma). The potential shall be applied for a minimum of 5 seconds while testing to determine compliance with 3.6.

4.4.3 Indexing. The switch shall be mounted on a suitable fixture and be engaging an approved wrench, the torque required to rotate the switch from one position to another throughout the switch range and in either direction shall comply with the requirements of 3.7.

4.4.4 Switch assembly leakage. The switch shall be tested in accordance with MIL-STD-202, Method 112, Test Condition C, Procedure IV with a reduced pressure of 10 micron for one minute minimum; perforation of the unit is not a requirement.

4.4.5 Casting. Radiographic inspections shall be accomplished in accordance with MIL-C-6021. The four mounting flanges shall be Class 1B, Grade B, and the remaining portion of the housing shall be Class 1B, Grade C. The X-ray films and related records shall be arranged to maintain individual casting identities.

4.4.6 Environmental testing (see 3.10).

4.4.6.1 Thermal shock. The switch shall be placed in an approved temperature chamber stabilized at +160 + 5°F (see 6.4) and the switch shall remain at this temperature for a minimum period of four hours. At the conclusion of this period, and within 5 minutes, the switch shall be transferred to another approved chamber stabilized at -60 + 5°F (see 6.4). The switch shall remain at this temperature for a minimum period of four hours. This constitutes one cycle. The number of complete cycles shall be three. At the conclusion of the third cycle, the switch shall be removed from the test chamber, returned to room temperature, and within a period of one hour test for compliance with 3.10.1.

4.4.6.2 Mechanical shock. The switch shall be mounted securely on a fixture capable of being readily positioned along each direction along its mutually perpendicular axes. The mounted switch shall then be installed on a shock producing device and tested to the levels and tests as specified in 3.10.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

4.4.6.4 Operational vibration. The switch shall be mounted securely on a fixture capable of being readily positioned along each direction along its mutually perpendicular axes. The mounted switch shall then be installed on a vibrator and vibrated to the levels and tests as specified in 3.10.4. During vibration testing, contact chatter shall be monitored utilizing approved equipment which will record contact chatter as specified in 3.10.4. After vibration testing, test for compliance with 3.10.4.

4.4.7 Current carrying capacity. The current carrying capacity shall be measured with an approved electrical tester using a voltage of 37 vdc maximum. The maximum voltage drop between the applicable terminal pins of J1 and J2 connectors shall not exceed the value specified in 3.11. The current between the terminal pins shall be 5 + 0.25 amperes for a duration of fifteen + one minutes. The unit shall be subjected to a resistive load of 20 + 2 amperes for 200 + 5 milliseconds without showing evidence of damage (see 6.5). The unit shall then be tested to determine compliance with 3.11.

4.4.8 Life cycling. With the unit at room temperature mount the open selector on a fixture capable of rotating each switch of the assembly through 300 complete switching cycles. The switch shall meet the requirements of 3.11, 3.5, 3.6 and 3.7 after meeting requirements of 3.12.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The switch shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.1.2 Level C. The switch shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.2 Packing.

5.2.1 Levels A and C. The switch shall be packed in accordance with the applicable instructions contained in MIL-STD-1169(MU).

5.3 Marking. Marking shall be in accordance with MIL-STD-1169(MU).

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 will be delivered as identified on a numbered DD Form 1664 when required on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-T.

6.4 Temperature stabilization. The temperature is considered stabilized when the greatest peaks (both highest and lowest) continually observed over 5 minutes min. do not exceed the nominal temperature plus tolerance specified.

6.5 External damage. Characteristics such as obliterated markings, damaged finish exposing base metal, damaged wire insulation, rust and cracks that are detectable by visual examination, shall be considered cause for rejection.

6.6 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-1201A Amendment 4 dated 21 June 1973.

Custodian:
Army - PA

Preparing activity:
Army - PA

Project No. 1135 - A136

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

U.S.MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-N-Q
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.