INCH-POUND

MIL-W-48757 (AR)
AMENDMENT 5
16 DECEMBER 1988

SUPERSEDING
AMENDMENT 4
1 July 1983

MILITARY SPECIFICATION

WARHEAD SECTION, GM, HE, XM251
SPARE PARTS FOR

This Amendment forms a part of Military Specification MIL-W-4-48757 (PA), dated 28 March 1975, and is approved for use within the US Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title: Change to read "WARHEAD SECTIONS, GM, HE: M251 AND M251A1 SPARE PARTS FOR".

1.1 Change to read: "This specification covers spare parts for Warhead Sections, GM, HE: M251 and M251A1."

2.1 SPECIFICATION: Add the following:

"MIL-B-45887 - Bolt, Tee

FEDERAL

QQ-Z-325 - Zinc Plating (Electrodeposited)

QQ-P-461 - Plating, Cadmium (Electrodeposited)".

AMSC N/A

FSC 1340

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

PAGE 2

*2.1 DRAWINGS: Change "US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND" to "US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER", and add the following:

9293477 - Screw, Telescope Tube
8848472 - Bag, Packing, Ammunition for Gasket
9267741 - Gasket, Fuze
9208333 - Latch, Assembly
9267743 - Seal, Metallic, Lead and Wire
8831171 - Washer
8836202 - Spring, Clevis
9208290 - Clevis
9208303 - Nut, Adjust
9208775 - Clevis Assembly

Drawing 8883534: Change title to read "Bag, Packing for Repair Parts".

2.2 In the listing of ASTM's add the following:

"ASTM-B 117-73 - Salt Spray (Fog) Testing".

PAGE 3

*3.2 Line 2: Add "9208303" to the series of drawings.

Line 3: Add "9267741, 9267741, 9267743, 9293477, 8831171, 8836202, 9208290, 9208303 and 9208775" to the series of drawings.

Add new paragraph as follows:

"3.2.1 Tee bolt (Dwg. 9237322). The tee bolt shall comply with all requirements specified in MIL-B-45887. However, First Article requirements specified herein shall apply".

PAGE 4

3.4.5, Line 5: Change "... more than eight (8) percent." to "... less than five (5) percent."

PAGE 5

*4.3.1 Listing:

Change quantity of Spring, Latch (8831279) from "2" to "9".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

Change quantity of Spring, Torsion (9208238) from "1" to "9".

Delete the line "Bolt, tee" in its entirety.

Add the following:

Washer	MS27183-7	4
Pin, Lever	8831277	4
Rivet, Shoulder	8833389	4
Lever, Latch	9208320	4
Pin, Spring	9208681	4
Lever, Locking	9208690	4
Latch, Base Assembly	9208708	4
Hook, Latch	9208758	4
Arm, Hook	9208759	4
Nut, Clinch	9283989-1	4
Nut, Clinch	9283989-2	4
Bolt, Tee	9237322	13 (plated) 10 (unplated)
Gasket, Fuze	9267741	4
Seal, Metallic, Lead and Wire	9267743	4
Seal, Aft Section	9267740	4
Screw, Telescope Tube	9293477	4
Washer	8831171	4
Spring, Clevis	8836202	4
Clevis	9208290	4
Nut, Adjust	9208303	4
Clevis Assembly	9208775	4

PAGE 7

*Table I, Sheet 1, "Notes" block, Add:

"*Samples cut from part

**Samples cut form part, transverse of welded joint."

PAGE 8

*Table I, "Spring, Latch", Add:

"Salt Spray 4 3.2 4.5.9/4.4.3.1"

"Spring Torsion", Add:

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T19:38Z
Check the source to verify that this is the currentversion before use.

4.4.3.7 Add Major 105:

"Salt Spray 4 3.2 4.5.9/4.4.3.1"

PAGE 9

Table I, "Bolt, Tee": Change to read as follows:

Bolt, Tee (Dwg, 9237322)			
Examination for Defects (Note 1)	10	3.2.1	MIL-B-45887
Continuous Grain Flow Lines (Note 1)	3	3.2.1	MIL-B-45887
Hardness (Notes 2 and 3)	10	3.2.1	MIL-B-45887
Tensile Load (Note 2)	10	3.2.1	MIL-B-45887

Notes:
1. Examination for defects and continuous grain flow shall be performed on the plated sample of thirteen (13).
2. The hardness and tensile load examination shall both be performed on the unplated sample of ten (10).
3. Hardness shall be checked on the shaft (above the threads and on the end) and on the cross tee, but not on the bearing surface.

*Table I, Add:

"Screw, Telescope Tube (Dwg 9293477)			
Examination for defects	1	3.2	4.4.2.26
Gasket, Fuze (Dwg 9267741)			
Examination for Defects	1	3.2	4.4.2.27
Seal, Metallic, Lead and Wire (Dwg 9267743)			
Wire diameter, improper	1	3.2	Gage
Wire not tinned	1	3.2	Visual
Washer (MS 27183-7)	4	3.2	4.5.9/ 4.4.3.1
Salt Spray			
Pin, Lever (Dwg 881277)	4	3.2	4.5.9/ 4.4.3.1
Salt Spray			
Rivet, Shoulder (Dwg 8833389)	4	3.2	4.5.9/ 4.4.3.1
Salt Spray			

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

Pin, Spring			
(Dwg 9208681)	4	3.2	4.5.9/
Salt Spray			4.4.3.1
Lever, Latch			
(Dwg 9208320)	4	3.2	4.5.9/
Salt Spray			4.4.3.1
Lever, Locking			
(Dwg 9208690)	4	3.2	4.5.9/
Salt Spray			4.4.3.1
Latch Base Assembly			
(Dwg 9208708)	4	3.2	4.5.9/
Salt Spray			4.4.3.1
Hook, Latch			
(Dwg 9208708)	4	3.2	4.5.9/
Salt Spray			4.4.3.1
Arm Hook			
(Dwg 9208759	4	3.2	4.5.9/
Salt Spray			4.4.3.1
Nut, Clinch			
(Dwg 9283989-1)	4	3.2	4.5.9/
Salt Spray			4.4.3.1
Nut, Clinch			
(Dwg 9283989-2)	4	3.2	4.5.9/
Salt Spray			4.4.3.1
Washer			
(Dwg 8831171)			
Examination for Defects	2	3.2	4.4.2.29
Spring, Clevis			
(Dwg 8836202)			
Examination for Defects	2	3.2	4.4.2.30
Salt Spray	4	3.2	4.5.9/4.4.3.1
Clevis			
(Dwg 9208290)			
Examination for Defects	2	3.2	4.4.2.31

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

and the amendment were made. This was done as convenience only

Nut, Adjust			
(Dwg 9208303)			
Examination for Defects	2	3.2	4.4.2.32
Salt Spray	4	3.2	4.5.9/4.4.3.1
Clevis Assembly			
(Dwg 9208775)			
Examination for Defects	2	3.2	4.4.2.33
Salt Spray	4	3.2	4.5.9/4.4.3.1"

PAGE 36

Add the included sheet - Paragraph 4.4.2.26.

Add the included sheet - Paragraph 4.4.2.27.

Add the included sheet - Paragraph 4.4.2.28.

* Add the included sheet - Paragraph 4.4.2.29.

* Add the included sheet - Paragraph 4.4.2.30.

* Add the included sheet - Paragraph 4.4.2.31.

* Add the included sheet - Paragraph 4.4.2.32.

* Add the included sheet - Paragraph 4.4.2.33.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9293477
4.4.2.26	Screw, Telescope Tube				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Locking element missing or improperly assembled		100%	3.2	Visual
102	Pitch diameter		0.40%	3.2	Gage
103	Major diameter		0.40%	3.2	Gage
104	Distance from head to end		0.40%	3.2	Gage
105	Length of turned down diameter		0.40%	3.2	Gage
106	Turned down diameter		0.40%	3.2	Gage
107	Width of chamfer		0.40%	3.2	Gage
108	True position of turned down diameter		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:38Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9267741
4.4.2.27	Gasket, Fuze				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Thickness		0.40%	3.2	Gage
102	Location of mounting holes		4.5.10	3.2	Gage
103	Distance from mounting hole to radius large hole		4.5.10	3.2	Gage
104	Distance from mounting hole to side large hole		4.5.10	3.2	Gage
105	Length of large hole		4.5.10	3.2	Gage
106	Width of large hole		4.5.10	3.2	Gage
107	Distance from mounting hole to radius of small hole		4.5.10	3.2	Gage
108	Distance from mounting hole to side of small hole		4.5.10	3.2	Gage
109	Length of small hole		4.5.10	3.2	Gage
110	Width of small hole		4.5.10	3.2	Gage
111	Radius of telescope tube cutout, min.		4.5.10	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:38Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8848472-4
4.4.2.28	Bag, Packing, Ammunition for Gasket				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
101	Length of bag, min.		0.40%	3.2	Gage
102	Width of bag, min.		0.40%	3.2	Gage
103	Length of stiffener, min.		0.40%	3.2	Gage
104	Width of stiffener, min.		0.40%	3.2	Gage
105	Thickness, min.		0.40%	3.2	Gage
106	Stiffener (2) missing		0.40%	3.2	Visual
107	Stiffener (2) not taped properly		0.40%	3.2	Visual
108	Bag damaged or improperly sealed		0.40%	3.2	Visual
109	Marking illegible, missing or incorrect		0.40%	3.2	Visual
Minor	None defined				

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:38Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.29	Washer	1	1	8831171
				NEXT HIGHER ASSEMBLY: 0908775

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Inside diameter		0.65%	3.2	Gage
202	Length		0.65%	3.2	Gage
203	Outside diameter		0.65%	3.2	Gage
204	Thickness		0.65%	3.2	Gage
205	Protective finish		0.65%	3.2	Visual
206	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:38Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8836202
4.4.2.30	Spring, Clevis				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Spring embrittlement (5)		Acc. 0 Rej. 1	3.7	4.5.8
102	Solid height		0.40%	3.2	Gage
103	Test for compressive load at lengths (2)		0.40%	3.2	Gage
Minor					
201	Inside diameter, min.		0.65%	3.2	Gage
202	Outside diameter, max.		0.65%	3.2	Gage
203	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:38Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9208290
4.4.2.31	Clevis				NEXT HIGHER ASSEMBLY 9208775
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Width of cutout slot		0.40%	3.2	Gage
102	Pitch diameter of thread		0.40%	3.2	Gage
103	Diameter of large hole		0.40%	3.2	Gage
Minor					
201	Hardness		0.65%	3.2	Gage
202	Outside diameter		0.65%	3.2	Gage
203	Diameter of small hole		0.65%	3.2	Gage
204	Overall length		0.65%	3.2	Gage
205	Distance from end to center of large hole		0.65%	3.2	Gage
206	Length from end to shoulder		0.65%	3.2	Gage
207	Protective finish		0.65%	3.2	Visual
208	Length of cutout slot		0.65%	3.2	Gage
209	Thread length, min.		0.65%	3.2	Gage
210	Chamfers missing (2)		0.65%	3.2	Visual
211	True position of large hole		0.65%	3.2	Gage
212	True position of small hole		0.65%	3.2	Gage
213	Evidence of poor workmanship		0.65%	3.9	Visual

REMARKS:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:38Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 of 1		DRAWING NUMBER 9208303
4.4.2.32	Nut, Adjust				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Inside diameter		0.40%	3.2	Gage
102	Pitch diameter of threads		0.40%	3.2	Gage
103	Presence of locking elements (2)		0.40%	3.2	Visual
104	Length from beginning of thread to end of undercut		0.40%	3.2	Gage
Minor					
201	Overall length		0.65%	3.2	Gage
202	Chamfer missing		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.2	Visual
204	Thread undercut diameter		0.65%	3.2	Gage

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:38Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9208775
4.4.2.33	Clevis Assembly				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Presence of pin springs		0.40%	3.2	Visual
102	Presence of washer		0.40%	3.2	Visual
103	Presence of nut		0.40%	3.2	Visual
104	Pin spring flush or below surface of clevis		0.40%	3.2	Visual
Minor					
201	Distance from pin spring end to small diameter of clevis		0.65%	3.2	Gage
202	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:38Z
Check the source to verify that this is the current version before use.

4.4.3 Delete in its entirety and substitute the following:

"4.4.3 Testing.

4.4.3.1 Salt spray (see QQ-Z-325 or QQ-P-416 as applicable). Four (4) of each of the following parts from each part plating lot shall be subjected to the salt spray test: MS27183-7, 8831277, 8831279, 8833389, 9208238, 9208320, 9208681, 9208690, 9208708, 9208758, 9208759, 9283989, 8836202, 9208303, and 9208775. If any part from any part plating lot fails to comply with the applicable specification requirement, the parts from that plating lot shall be rejected. This test will not be performed on a part plating lot which has been previously tested in first article (see 4.3.1)."

PAGE 38

Add new paragraph as follows:

"4.5.9 Salt spray. The test shall be conducted for 96 hours with a 5 percent salt solution in accordance with ASTM-B-117-73. This is a destructive test. Parts so tested shall not be returned to the lot."

Add new paragraph as follows:

"4.5.10 Dimensional control of standard parts. In place of the normal sampling associated with the Classification of Defects, and with the approval of the Contracting Officer, a sample of at least ten (10) parts shall be dimensionally inspected to qualify the tool used in the stamping process for use in production. In addition, a random sample of five (5) parts shall be selected from the last portion of each hour's production for dimensional inspection as a control of the tool during production. If any defective parts are found during qualification of the tool, the tool producing the defective part shall not be used in production.

If any defective parts are found when inspection is performed for control of the tool, the tool producing th defective part shall be removed from production. Further, that portion of production since the last tool control check shall be returned to the contractor for corrective action.

All tools removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the Contracting Officer to substantiate the request."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

5.1.1, Line 2: After "external wrenching nut", add: "screw, telescope tube".

Line 9, Add: "The fuze gasket; latch assembly; and seal, metallic lead and wire; shall be preserved and packaged in accordance with Dwg. 8848472-4."

5.2.1, Line 2: After "external wrenching nut", add: "screw, telescope tube; gasket, fuze; latch assembly; seal, metallic lead and wire;".

5.3, Line 2: After "8808932", add: "8848472".

6.1, Line 2: Change "...XM251." to...M251 and M251A1".

6.3, Line 3: Change "...ATTN: DRDAR-QAR-I, US Army Armament Research and Development Command...." to "...AMSMC-QAR-I(D), US Army Armament, Munitions and Chemical Command ...".

6.4 Delete in its entirety.

6.5 Delete in its entirety.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of his document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1340-A685)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.