The documentation and process conversion measures necessary to comply with this document shall be completed by 23 October 2021.

INCH-POUND

MIL-PRF-19500/466D
w/AMENDMENT 1
23 July 2021
SUPERSEDING
MIL-PRF-19500/466D
27 January 2016

PERFORMANCE SPECIFICATION SHEET

TRANSISTOR, PNP, SILICON, POWER,
THROUGH HOLE, TYPES 2N5683 AND 2N5684,
QUALITY LEVELS JAN, JANTX, AND JANTXV

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for PNP, silicon, power transistors. Three levels of product assurance (JAN, JANTX, and JANTXV) are provided for each device.

1.2 Package outlines. The device package outlines are as follows: similar to TO-3 in accordance with figure 1 for all encapsulated device types.

1.3 Maximum ratings. Unless otherwise specified, T_C = +25°C.

Types	P_T (1)		$R_{\theta JC}$	V_{CEO}	V_{EBO}	I_B	I_C	T_J and T_{STG}	V_{CBO}
	T_C = +25°C	T_C = +100°C							
	W	W	°C/W	V dc	V dc	A dc	A dc	°C	V dc
2N5683	300	171	.584	-60	-5	-15	-50	-65 to +200	-60
2N5684	300	171	.584	-80	-5	-15	-50	-65 to +200	-80

(1) Between T_C = +25°C and T_C = +200°C, linear derating factor (average) = 1.715 W/°C.

Comments, suggestions, or questions on this document should be addressed to DLA Land and Maritime, ATTN: VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to Semiconductor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A

FSC 5961

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:15Z
Check the source to verify that this is the current version before use.

1.4 Primary electrical characteristics.

Types	h_{FE2} (1)		h_{FE3} (1)		C_{obo}		h_{fe}		$V_{BE(sat)}$ (1)	
	V_{CE} = -2 V dc I_C = -25 A dc		V_{CE} = -5 V dc I_C = -50 A dc		V_{CB} = -10 V dc I_E = 0 0.1 MHz ≤ f ≤ 1 MHz		V_{CE} = -5 V dc I_C = -10 A dc f = 1 kHz		I_C = -25 A dc I_B = -2.5 A dc	
	Min	Max	Min	Max	Min pF	Max pF	Min	Max	Min V dc	Max V dc
2N5683	15	60	5			2,000	15			-2.0
2N5684	15	60	5			2,000	15			-2.0

Types	$V_{CE(sat)1}$		$V_{CE(sat)2}$		Switching			
	I_C = -25 A dc I_B = -2.5 A dc (1)		I_C = -50 A dc I_B = -10 A dc (1)		t_{on}		t_{off}	
					(see table I and figures 2 and 3 herein)			
	Min V dc	Max V dc	Min V dc	Max V dc	Min µs	Max µs	Min µs	Max µs
2N5683		-1.0		-5.0		1.5		3.0
2N5684		-1.0		-5.0		1.5		3.0

(1) Pulsed (see 4.5.1).

1.5 Part or Identifying Number (PIN). The PIN is in accordance with MIL-PRF-19500, and as specified herein. See 6.4 for PIN construction example and 6.5 for a list of available PINs.

1.5.1 JAN certification mark and quality level for encapsulated devices. The quality level designators for encapsulated devices that are applicable for this specification sheet from the lowest to the highest level are as follows: “JAN”, “JANTX”, and "JANTXV".


1.5.2 Device type. The designation system for the device types of transistors covered by this specification sheet are as follows.

1.5.2.1 First number and first letter symbols. The transistors of this specification sheet use the first number and letter symbols "2N".

1.5.2.2 Second number symbols. The second number symbols for the transistors covered by this specification sheet are as follows: "5683" and "5684".

1.5.3 Lead finish. The lead finishes applicable to this specification sheet are listed on QPDSIS-19500.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:15Z
Check the source to verify that this is the current version before use.



Ltr	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
CD		.875		22.22	3
CH	.250	.328	6.35	8.33	
HR	.495	.525	12.57	13.34	
HR_1	.131	.188	3.33	4.78	6
HT	.060	.135	1.52	3.43	
LD	.057	.063	1.45	1.60	4, 5, 9
LL	.312	.500	7.92	12.70	4, 5, 9
L_1		.050		1.27	5, 9
MHD	.151	.161	3.84	4.09	7
MHS	1.177	1.197	29.90	30.40	
PS	.420	.440	10.67	11.18	
PS_1	.205	.225	5.21	5.72	5
S_1	.655	.675	16.64	17.15	

NOTES:
1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. Body contour is optional within zone defined by CD.
4. These dimensions shall be measured at points .050 inch (1.27 mm) to .055 inch (1.40 mm) below seating plane. When gauge is not used, measurement shall be made at seating plane.
5. Both terminals.
6. At both ends.
7. Two holes.
8. Terminal 1 is the emitter, terminal 2 is base. The collector shall be electrically connected to the case.
9. LD applies between L_1 and LL. Lead diameter shall not exceed twice LD within L_1.
* 10. In accordance with ASME Y14.5, diameters are equivalent to ϕx symbology.
11. The seating plane of the header shall be flat within .001 inch (0.03 mm) concave to .004 inch (0.10 mm) convex inside a .930 inch (23.62 mm) diameter circle on the center of the header and flat within .001 inch (0.03 mm) concave to 0.006 inch (0.15 mm) convex overall.

FIGURE 1. Physical dimensions, TO-3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:15Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-750 - Test Methods for Semiconductor Devices.

(Copies of these documents are available online at https://quicksearch.dla.mil).

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturers list before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

3.4 Interface and physical dimensions. Interface and physical dimensions shall be as specified in MIL-PRF-19500, and on figure 1.

3.4.1 Lead finish. Lead finish shall be solderable in accordance with MIL-PRF-19500, MIL-STD-750. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2).

3.5 Marking. Marking shall be in accordance with MIL-PRF-19500.

3.6 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4, and table I.

3.7 Electrical test requirements. The electrical test requirements shall be as specified in table I.

3.8 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:15Z
Check the source to verify that this is the current version before use.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

c. Conformance inspection (see 4.4 and table I and table II).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500.

4.2.1 Group E qualification. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not request the performance of table III tests, the tests specified in table III herein that were not performed in the prior revision shall be performed on the first inspection lot of this revision to maintain qualification.

* 4.3 Screening (JANTX and JANTXV levels). Screening shall be in accordance with table IV of MIL-PRF-19500, and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen	Measurement
	JANTX and JANTXV levels
(1) 3c	Thermal impedance (see 4.3.2)
11	I_{CEX1} and h_{FE2}
12	See 4.3.1
13	Subgroup 2 of table I herein; ΔI_{CEX1} = ±100 percent of initial value or -1.0 µA dc, whichever is greater. Δh_{FE} = ±25 percent of initial value

(1) Shall be performed anytime after temperature cycling, screen 3a; and does not need to be repeated in screening requirements.

* 4.3.1 Power burn-in conditions. Power burn-in conditions are as follows: Adjust P_T to achieve T_J = +187.5°C ± 12.5°C, $V_{CB} \geq$ -10 V dc. NOTE: No heat sink or forced air cooling on the devices shall be permitted.

4.3.2 Thermal impedance. The thermal impedance measurements shall be performed in accordance with method 3131 of MIL-STD-750 using the guidelines in that method for determining I_M, I_H, t_H, t_{MD}, t_{SW}, (and V_H where appropriate). See table III, group E, subgroup 4 herein.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500, and as specified herein.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-PRF-19500, and table I herein. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in table VIB (JAN, JANTX, and JANTXV) of MIL-PRF-19500 and 4.4.2.1 herein. Delta measurements shall be in accordance with table II herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:15Z
Check the source to verify that this is the current version before use.

4.4.2.1 Quality levels JAN, JANTX and JANTXV, table E-VIB of MIL-PRF-19500.

Subgroup	Method	Condition
B3	1037	For solder die attach, $V_{CB} \geq -10$ V dc. No heat sink shall be permitted.
B3	1026	For eutectic die attach adjust P_T to achieve +175°C minimum. $V_{CB} \geq -10$ V dc, $T_A \leq +35°C$

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table VII of MIL-PRF-19500, and as follows. Delta measurements shall be in accordance with table II herein.

Subgroup	Method	Condition
C2	2036	Tension: Test condition A weight = 10 pounds, t = 15 seconds.
C5	3131	See 4.3.2, $R_{\theta JC} = 0.584$.
C6	1026	For eutectic die attach adjust P_T to achieve +175°C minimum. $V_{CB} \geq -10$ V dc, $T_A \leq +35°C$.
C6	1037	For solder die attach, $V_{CB} \geq -10$ V dc. No heat sink shall be permitted. $T_A \leq +35°C$.

4.4.4 Group E inspection. Group E inspection shall be conducted in accordance with the conditions specified for subgroup testing in table IX of MIL-PRF-19500 and as specified in table III herein. Delta measurements shall be in accordance with table II herein.

4.5 Methods of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in section 4 of MIL-STD-750.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:15Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 1						
Visual and mechanical examination	2071					
Subgroup 2						
Thermal impedance 2/	3131	See 4.3.2	$Z_{\theta JX}$			°C/W
Collector to emitter breakdown voltage	3011	Bias condition D; I_C = -200 mA dc, pulsed (see 4.5.1)	$V_{(BR)CEO}$			
2N5683				-60		V dc
2N5684				-80		V dc
Collector to emitter cutoff current	3041	Bias condition D,	I_{CEO}		-5.0	µA dc
2N5683		V_{CE} = -30 V dc				
2N5684		V_{CE} = -40 V dc				
Emitter to base cutoff current	3061	Bias condition D, V_{EB} = -5 V dc, I_C = 0	I_{EBO}		-5.0	µA dc
Collector to emitter cutoff current	3041	Bias condition A, V_{BE} = +1.5 V dc,	I_{CEX1}		-5.0	µA dc
2N5683		V_{CE} = -60 V dc				
2N5684		V_{CE} = -80 V dc				
Collector to base cutoff current	3036	Bias condition D,	I_{CBO}		-5.0	µA dc
2N5683		V_{CB} = -60 V dc				
2N5684		V_{CB} = -80 V dc				
Base to emitter saturated voltage	3066	Test condition A, I_C = -25 A dc, I_B = -2.5 A dc, pulsed (see 4.5.1)	$V_{BE(sat)}$		-2.0	V dc
Base to emitter saturated voltage	3066	Test condition B, V_{CE} = -2 V dc, I_C = -25 A dc, pulsed (see 4.5.1)	V_{BE}		-2.0	V dc
Collector to emitter saturated voltage	3071	I_C = -25 A dc, I_B = -2.5 A dc, pulsed (see 4.5.1)	$V_{CE(sat)1}$		-1.0	V dc
Collector to emitter saturated voltage	3071	I_C = -50 A dc, I_B = -10 A dc, pulsed (see 4.5.1)	$V_{CE(sat)2}$			
2N5683					-5.0	V dc
2N5684					-5.0	V dc

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:15Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 2 - Continued						
Forward-current transfer ratio	3076	V_{CE} = -2 V dc, I_C = -5 A dc, pulsed (see 4.5.1)	h_{FE1}	30		
Forward-current transfer ratio	3076	V_{CE} = -2 V dc, I_C = -25 A dc, pulsed (see 4.5.1)	h_{FE2}	15	60	
Forward - current transfer ratio	3076	V_{CE} = -5 V dc, I_C = -50 A dc, pulsed (see 4.5.1)	h_{FE3}	5		
Subgroup 3						
High-temperature operation		T_A = +150°C				
Collector – emitter cutoff current 2N5683 2N5684	3041	Bias condition A, V_{BE} = +1.5 V dc V_{CE} = -60 V dc V_{CE} = -80 V dc	I_{CEX2}		-50	µA dc
Low-temperature operation		T_A = -55°C				
Forward – current transfer ratio	3076	V_{CE} = -2.0 V dc, I_C = -25 A dc, pulsed (see 4.5.1)	h_{FE4}	7		
Subgroup 4						
Pulse response:	3251	Test condition A except test circuit and pulse requirements per figures 2 and 3 herein.				
Turn - on time		V_{CC} = -30 V dc, I_C = -25 A dc, I_{B1} = -2.5 A dc	t_{on}		1.5	µs
Turn - off time		V_{CC} = -30 V dc, I_C = -25 A dc, I_{B1} = I_{B2} = -2.5 A dc	t_{off}		3.0	µs
Storage time		V_{CC} = -30 V dc, I_C = -25 A dc, I_{B1} = I_{B2} = -2.5 A dc	t_s		2.0	µs

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:15Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 4 - Continued						
Magnitude of common emitter small-signal short-circuit forward-current transfer ratio	3306	V_{CE} = -10 V dc, I_C = -5 A dc, f = 1 MHz	$\|h_{fe}\|$	2.0	20	
Small - signal short circuit forward-current transfer ratio	3206	V_{CE} = -5 V dc, I_C = -10 A dc, f = 1.0 kHz	h_{fe}	15		
Output capacitance (open circuit)	3236	V_{CB} = -10 V dc, I_E = 0, 0.1 MHz ≤ f ≤ 1.0 MHz	C_{obo}		2,000	pF
Subgroup 5						
Safe operating area (dc operation)	3051	T_C = +25°C t = 1 s, 1 cycle, (see figure 4 and figure 5)				
Test 1 (Both device types)		V_{CE} = -6 V dc, I_C = -50 A dc				
Test 2 (Both device types)		V_{CE} = -30 V dc, I_C = -10 A dc				
Test 3 2N5683		V_{CE} = -50 V dc, I_C = -560 mA dc				
2N5684		V_{CE} = -60 V dc, I_C = -640 mA dc				
Safe operating area (switching)	3053	Load condition C, (unclamped inductive load) see figure 6, T_C = +25°C duty cycle ≤ 10 percent, R_S = 0.1 Ω, $t_r = t_f$ ≤ 500 ns				
Test 1		tp = 5 ms, (vary to obtain I_C), R_{BB1} = 10 Ω, V_{BB1} = -20 V dc, R_{BB2} = ∞, V_{BB2} = 0, V_{CC} = -50 V dc, I_C = -20 A dc, L = 1 mH 3/				

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:15Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 5 - Continued						
Test 2		tp = 5 ms, (vary to obtain I_C), R_{BB1} = 100 Ω, V_{BB1} = -10 V dc, R_{BB2} = ∞, V_{BB2} = 0, V_{CC} = -50 V dc, I_C = -1.5A dc, L = 80 mH 4/				
Safe operating area (switching)		Clamped inductive load, condition B, T_A = +25°C, V_{CC} = -50 V dc, (See figures 7 and 8)				
2N5683		Clamp voltage = -60 V dc				
2N5684		Clamped voltage = -80 V dc				
Electrical measurements		See table I, subgroup 2 herein				
Subgroups 6 and 7						
Not applicable						

1/ For sampling plan, see MIL-PRF-19500.
2/ This test required for the following end-point measurements only:
Group B, subgroups 2 and 3 (JAN, JANTX, and JANTXV).
Group C, subgroup 2 and 6.
Group E, subgroup 1.
3/ L = 1 mH Sanford Miller CK-50, 50A, .002 Ω, or equivalent.
4/ L = 80 mH (2 each Signal Transformer CH-6, 6A) 0.4 Ω, or equivalent.

TABLE II. Groups B, C, and E delta measurements. 1/ 2/ 3/

Step	Inspection	MIL-STD-750		Symbol	Limits		Unit
		Method	Conditions		Min	Max	
1.	Forward-current transfer ratio	3076	V_{CE} = -2 V dc; I_C = -25 A dc; pulsed (see 4.5.1)	Δh_{FE2}	±25%		

1/ The delta measurements for table VIB (JAN, JANTX, and JANTXV) of MIL-PRF-19500 are subgroups 3 and 6, see table II herein, step 1.
2/ The delta measurement for table VII of MIL-PRF-19500 is subgroup 6, see table II herein, step 1.
3/ The delta measurements for table IX of MIL-PRF-19500 are subgroups 1 and 2, see table IV herein, step 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:15Z
Check the source to verify that this is the current version before use.

TABLE III. Group E inspection (all quality levels) for qualification and re-qualification only.

Inspection	MIL-STD-750		Sample Plan
	Method	Conditions	
Subgroup 1			45 devices c = 0
Temperature cycling	1051	500 cycles minimum	
Hermetic seal Fine leak Gross leak	1071		
Electrical measurements		See table I, subgroup 2 and table II herein.	
Subgroup 2			45 devices c = 0
Blocking life	1048	Test temperature = +125°C; V_{CB} = 80 percent of rated; T = 1,000 hours.	
Electrical measurements		See table I, subgroup 2 and table II herein.	
Subgroup 4			Sample size N/A
Thermal impedance curves		See MIL-PRF-19500.	
Subgroup 8			45 devices c = 0
Reverse stability	1033	Condition B.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:15Z
Check the source to verify that this is the current version before use.




FIGURE 2. Turn-on (t_{on}) time test circuit.




FIGURE 3. Turn-off (t_{off}) time test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:15Z
Check the source to verify that this is the current version before use.




FIGURE 4. Maximum safe operating area graph (continuous dc) for 2N5683.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:15Z
Check the source to verify that this is the current version before use.




FIGURE 5. Maximum safe operating area graph (continuous dc) for 2N5684.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:15Z
Check the source to verify that this is the current version before use.





FIGURE 6. Safe operating area for switching between saturation and cutoff (unclamped inductive load).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:15Z
Check the source to verify that this is the current version before use.



L = 2.0 mH (2 each 1 mH
Sanford Miller CK-50, 50A)
R = .002 Ω

Procedure:
1. With switch S1 closed, set the specified test conditions.
2. Open S1. Device fails if clamp voltage is not reached.
3. Perform specified endpoint tests.

FIGURE 7. Clamped inductive sweep test circuit.




FIGURE 8. Safe operating area for switching between saturation and cutoff (clamped inductive load).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:15Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory. The notes specified in MIL-PRF-19500 are applicable to this specification.)

6.1 Intended use. Semiconductors conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Packaging requirements (see 5.1).


c. Lead finish (see 3.4.1).

d. The complete PIN, see 1.5 and 6.5.

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML-19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from DLA Land and Maritime, ATTN: VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil. An online listing of products qualified to this specification may be found in the Qualified Products Database (QPD) at https://assist.dla.mil.

6.4 PIN construction example.

6.4.1 Encapsulated devices The PINs for encapsulated devices are constructed using the following form.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:15Z
Check the source to verify that this is the current version before use.

6.5 List of PINs.

6.5.1 List of PINs for encapsulated devices. The following is a list of possible PINs for encapsulated devices available on this specification sheet.

PINs for devices of the base quality level	PINs for devices of the "TX" quality level	PINs for devices of the "TXV" quality level
JAN2N5683	JANTX2N5683	JANTXV2N5683
JAN2N5684	JANTX2N5684	JANTXV2N5684

6.6 Request for new types and configurations. Requests for new device types or configurations for inclusions in this specification sheet should be submitted to: DLA Land and Maritime, ATTN: VAC, Post Office Box 3990, Columbus, OH 43218-3990 or by electronic mail at Semiconductor@dla.mil or by facsimile (614) 693-1642 or DSN 850-6939.

* 6.7 Amendment notations. The margins of this specification are marked with asterisks to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
* Navy - SH
Air Force - 85
NASA - NA
DLA - CC

Review activities:
Army - AR, MI, SM
Navy - AS, MC
Air Force - 19

Preparing activity:
DLA - CC

(Project 5961-2021-070)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:15Z
Check the source to verify that this is the current version before use.