A-A-2213
July 18, 1984

COMMERCIAL ITEM DESCRIPTION

LAMP, INCANDESCENT (Elliptical Reflector)

The General Services Administration has authorized the use of this commercial item description.

This description covers elliptical reflector lamps for general lighting.

Salient characteristics.

The lamps shall have the characteristics that are listed in Table I. The bulb shall be inside frosted.

TABLE I - Lamp Characteristics

Type	Lamp Code	Watts	Volts	Base	Bulb	Filament Design	Max. Overall Length (inches)	Rated Average Life (hours)	Approx. Initial Lumens*
1	50ER30	50	120	Medium	ER-30	CC-6	6-1/4	2,000	525
2	50ER30	50	130	Medium	ER-30	CC-6	6-1/4	2,000	525
3	75ER30	75	120	Medium	ER-30	CC-6	6-1/4	2,000	850
4	75ER30	75	130	Medium	ER-30	CC-6	6-1/4	2,000	850
5	120ER40	120	120	Medium	ER-40	CC-6	7-3/8	2,000	1,475
6	120ER40	120	130	Medium	ER-40	CC-6	7-3/8	2,000	1,475

*Initial lumen ratings are based upon 100 hour photometry reading at rated lamp watts.

The lamps shall be in accordance with ANSI C78.100.

The issue of ANSI C78.100 in effect on the date of the solicitation shall be used to determine compliance with these requirements.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practical.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

FSC 6240

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:20Z
Check the source to verify that this is the current version before use.

Preproduction inspection. One package of lamps, produced using the same tooling, production, and assembly methods that are used for production lots, shall be submitted for examination and test in accordance with the above requirements. Documentation consisting of the certification and test data shall be presented for examination during performance of the preproduction inspection. Failure of the preproduction samples to pass the examination of one or more of the tests, the lack of required documentation, or failure of the documentation to substantiate conformance to the requirements of this CID shall be cause for rejection.

Notes. ANSI Standard C78.100 is available from the American National Standards Institute, Inc., 1430 Broadway, New York, New York 10018.

The commercial item certification clause is not required when this commercial item description is used for procurement.

Avoid contact of hot glass bulb with liquid or metal, because glass may shatter.

The lamp should not be used in equipment where the base temperature will exceed 500 degrees F.

The lamp should be shielded against moisture falling on the bulb.

Military Coordinating Activity

None. DoD has waived coordination on this commercial item description until further notice.

PREPARING ACTIVITY:
GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:20Z
Check the source to verify that this is the current version before use.