MIL-F-60044A (MU)
9 October, 1968
Superseding
MIL-F-60044 (MU)
1 June 1964

MILITARY SPECIFICATION

FUZE, BASE DETONATION, M62A2 LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type of artillery fuze designated as Fuze, BD, M62A2.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition and Special Weapons, General Specification for
MIL-I-45607 - Inspection Equipment; Supply and Maintenance of

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105).
MIL-STD-109 - Quality Assurance Terms and Definitions.
MIL-STD-331 - Fuze and Fuze Components, Environmental and Performance Tests for.
MIL-STD-1167- Ammunition Data Card
MIL-STD-1168- Lot Numbering of Ammunition
MIL-STD-1235- Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes.

FSC: 1390

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:06Z
Check the source to verify that this is the current version before use.

DRAWINGS

ARMY

8886414 - Fuze, Base Detonating, M62A2, Assembly.
8886963 - Container Packing Ammunition for Fuze, BD, M62A2
8886964 - Box, Packing, Ammunition for Fuze, BD, M62A2

PUBLICATIONS

ARMY

ET-8886414-Equipment Tabulation

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material.-Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Assembly.-The assembly shall comply with all requirements specified in Drawing (dwg.) 8886414 and with all requirements specified in applicable specifications.

3.3 Jolt.-The assembly shall comply with the requirements of Standard MIL-STD-331.

3.4 Jumble.-The assembly shall comply with the requirements of Standard MIL-STD-331.

3.5 Transportation vibration.-The assembly shall comply with requirements of Standard MIL-STD-331.

3.6 Functioning (proving ground).-The fuze shall cause the cartridge to function with high order detonation without evidence of a premature burst when tested as specified in 4.3.5. (A premature burst is defined as functioning of the shell in flight before impact.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:06Z
Check the source to verify that this is the current version before use.

3.7 Workmanship.-All parts shall be fabricated and finished in a thorough, workmanlike mannner and all manufacturing, processing, and assembling operations shall be correctly performed. All parts shall be clean and free of burrs, sharp edges, unblended radii, surface defects, cracks, chips, slivers, cuts, dirt, grease, rust, and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat, legible, and sharply defined.

3.8 Arming and Non-Arming (Loaded Slider)

3.8.1 Non-Arming-The slider shall not arm when spun at 2350 revolutions per minute, minimum.

3.8.2 Arming-The slider shall arm when spun at 3650 revolutions per minute, maximum.

3.9 Static functioning.-The fuze shall detonate high order when tested in accordance with 4.3.7.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified within this specification.

b. Number of units of product inspected.

c. Results obtained, by defect code, for all inspections performed.

d. Drawing, specification number and date, together with an identification and date of changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:06Z
Check the source to verify that this is the current version before use.

e. Certificates of conformance on all material purchased by the contractor when such material is controlled by Government or commercial specifications referenced in any of the contractual documents.

f. Number of items in the lot.

g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 Inspection Provisions

4.2.1 Lot formation.-The term "lot" as used throughout this specification refers to an inspection lot, which is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance of the lot with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the lot has been produced by one manufacturer, in one unchanged process using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions. Changes to the process, specifications, or drawings, not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of the lot. Inspection lots shall comply with MIL-STD-105. Unless otherwise approved by the contracting officer, the inspection lot size of end items deliverable under the contract shall be not less than the smallest weekly estimate of quantities contractually scheduled for production during the contract period nor more than the largest monthly quantity contractually scheduled for delivery during the contract period. Inspection lots of components or subassemblies, other than the items of delivery, shall be homogeneous and of a size mutually convenient to both the contractor and the Government inspector. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each lot shall contain:

a. Detonators of one lot interfix number from one manufacturer.

b. Tetryl of one lot interfix number from one manufacturer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:06Z
Check the source to verify that this is the current version before use.

c. Metal parts of one lot interfix number from one manufacturer.

4.2.2 Examination.-Inspection for Critical defects (and Major defects, when so specified), shall be 100 percent. Sampling plans and procedures for Major and Minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity AQL's and sampling plans may be applied to individual characteristics listed using an AQL of 0.65 percent for each Minor defect and an AQL of 0.40 percent for each Major defect, except where 100 percent inspection is specified. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.4.

4.2.2.1 Body loading assembly (see dwg. 8837309 covering a detail of dwg. 8886414).

Categories	Defects	Method of Inspection	Code No. (See 6.2)
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Charge missing	Visual	01001
Minor:	AQL 1.00 percent		
201.	Booster charge above flush	Straight-edge	01002
202.	Evidence of poor workmanship (see 3.7)	Visual	01003

4.2.2.2 Slider loading assembly (see dwg. 8837311 covering a detail of dwg. 8886414)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Charge missing	Visual	02001
Minor:	AQL 1.00 percent		
201.	Charge above flush or obviously below allowable max. depth	Visual	02002
202.	Evidence of poor workmanship (see 3.7)	Visual	02003

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:06Z
Check the source to verify that this is the current version before use.

4.2.2.3 Assembly, prior to staking head (see dwg. 8886414)

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Firing pin in the armed position	Visual	03001
2.	Restraining spring missing	Visual	03002
3.	Detonator holder missing but detonator present	Visual	03003
Major:	AQL 0.65 percent		
101.	Detonator loose	Visual-Manual	03004
102.	Any component missing (other than critical components)	Visual	03005
103.	Detonator inverted	Visual	03006
104.	Firing pin or other component damaged to extent that function may be impaired	Visual	03007
Minor:	AQL 1.00 percent		
201.	Retaining screw or detonator holder loose or not staked	Visual-Manual	03008
202.	Evidence of poor workmanship (see 3.7)	Visual	03009

4.2.2.4 Assembly (see dwg. 8886414)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Concentricity of outside diameter with pitch diameter of thread including perpendicularity on the shoulder	Gage	04012
Minor:	AQL 2.50 percent		
201.	Length under flange, max.	Gage	04001
202.	Total length, max.	Gage	04002
203.	Head or booster cup loose on application of 50 inch pound disassembly torque	Gage	04003

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:06Z
Check the source to verify that this is the current version before use.

204.	Component damaged to extent that function is impaired	Visual	04004
205.	Stake missing	Visual	04005
206.	Evidence of poor workmanship (see 3.7)	Visual	04006

4.2.2.5 Sealed fiber container (see dwg. 8886963)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Container cut or damaged through all impregnated asphalt layers	Visual-Manual	05001
102.	Tape incomplete or badly wrinkled	Visual	05002
103.	Metal end loose or distorted	Visual	05003
Minor:	AQL 2.50 percent		
201.	Gap in excess of 1/8 inch between cover and body	Visual-Manual	05004
202.	Contents loose when shaken	Manual	05005
203.	Tear tab length incorrect	Scale	05006
204.	Color of tape incorrect	Visual	05007
205.	Marking misleading or unidentifiable	Visual	05008

4.2.2.6 Sealed wood packing box (see dwg. 8886964)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Box damaged to the extent that contents are exposed or liable to be exposed	Visual	06001
102.	Hardware or strapping missing, broken or loose	Visual-Manual	06002
103.	DOD symbol misleading or unidentifiable	Visual	06003

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:06Z
Check the source to verify that this is the current version before use.

Minor:	AQL 2.50 percent		
201.	Hardware or strapping improperly assembled	Visual	06004
202.	Car seal missing, unsealed or improperly positioned	Visual	06005
203.	Contents loose	Visual	06006
204.	Handle missing or insecure	Visual-Manual	06007
205.	Marking misleading or unidentifiable	Visual	06008

4.2.3 Testing

4.2.3.1 Specific gravity and binder lubricant content of booster lead charge, booster charge, and slider charge (see dwg. 8837311) Major defect, Code No. 07001.-The contractor shall provide adequate controls to assure the compliance of each lot with the requirements. The contractor shall test, for verification, at least once for each requirement in every 8 hours production or portion thereof. Failure of a sample to comply with a requirement shall be cause for rejection of the 8 hours production represented by the sample.

4.2.3.2 Jolt and jumble (see 3.3 and 3.4) Critical defect, Code No. 04008.-Twelve of the assembled fuzes from each lot shall be subjected to the jolt test specified in Standard MIL-STD-331 except that after test, the fuzes shall not be disassembled but shall be subjected to the jumble test specified in Standard MIL-STD-331 and then disassembled to determine compliance with the requirements. If any assembly fails to comply with the requirements the lot shall be rejected. The test shall be performed as specified in 4.3.3. The assemblies subjected to these tests shall not be returned to the lot.

4.2.3.3 Transportation vibration (see 3.5) Major defect, Code No. 04009.-The sampling plan for this test for each lot shall be in accordance with Standard MIL-STD-105, code letter D, and AQL of 1.50 percent. The test shall be performed as specified in 4.3.4.

4.2.3.4 Functioning (see 3.6) Major defect, Code No. 04010

4.2.3.4.1 Beginning with the first production lot produced and continuing until three consecutive lots have complied with the acceptance criteria specified herein, a sample of 125 fuze assemblies shall be selected for this test. If there are any premature bursts or if 5 or more assemblies fail to function "high order," the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:06Z
Check the source to verify that this is the current version before use.

4.2.3.4.2 After three consecutive lots have met the criteria of 4.2.3.4.1, a sample of 50 fuze assemblies shall be selected from each lot for this test. If there are any premature bursts or of 3 or more assemblies fail to function "high order," the lot shall be rejected.

4.2.3.5 Slider non-arming - Critical defects; Code No. 02004 and slider arming - Major defect (see dwg. 8886414).-These tests shall be performed 100 percent. Any assembly which fails to comply with the requirement shall be classed defective and removed from the lot. The tests shall be performed as specified in 4.3.6 using equipment specified in 4.2.4.

4.2.3.6 Check test for deterioration.-If the total elapsed time between original acceptance of a detonator and the assembly of this lot into the fuzes exceeds two years, or if the detonators in the lot have been exposed to adverse conditions, however brief, at any time since previous tests, they shall be subjected to, and must comply with the check test for deterioration specified in the applicable item specification, immediately before the components are assembled into the fuzes. The test shall be performed by the contractor (see 6.4) on detonators selected by the Government inspector.

4.2.3.7 Static functioning (see 3.9) Major Defect - Code No. 04011.-Twenty-five loaded fuze assemblies shall be randomly selected from each lot for testing in accordance with 4.3.7. If any fuze fails to detonate high order, the lot shall be rejected.

4.2.4 Inspection Equipment.-Equipment Tabulation Number ET-8886414 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in 6.3.

4.2.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.2.4.2 Supply and maintenance.-Supply and maintenance of the equipment listed in the ET shall be in accordance with Specification MIL-I-45607.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:06Z
Check the source to verify that this is the current version before use.

4.2.4.3 Government use of contractor's inspection equipment.- the contractor shall make available to the Government all inspection equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment and verification of its accuracy, shall be supplied by the contractor for the performance of examination or test by the Government.

4.3 Test methods and procedures

4.3.1 Determination of binder lubricant content of tetryl (graphite).-Transfer a sample of approximately 5 grams of the tetryl, accurately weighed, to a 250 ml. beaker. Add 100 ml. of acetone and heat to dissolve the tetryl. Filter the solution through a tared filtering crucible and wash the residue in the crucible with two 25 ml. portions of acetone. Dry the crucible at 100 degrees Centigrade (C.) for 1 hour, cool in a desiccator and weigh. Calculate the increase in weight as percentage of graphite. If the analysis indicates that the graphite content does not exceed the required amount by more than .25 of 1 percent, the tetryl may be reblended and resubmitted for test.

4.3.2 Determination of specific gravity

4.3.2.1 Booster lead charge.-Accurately weigh the empty body (see dwg. 8837309) in air and also when completely immersed in water, and record the weights. Load the body with the booster lead charge and accurately weigh in air and then in water and record the results. Calculate the specific gravity of the charge as follows:

Specific gravity of booster lead charge=C-A divided by [(C-A)-(D-B)] where:

A = weight of unloaded component in air.
B = weight of unloaded component in water.
C = weight of loaded component in air.
D = weight of loaded component in water.

4.3.2.2. Booster charge.-The same procedure specified in 4.3.2.1 shall be used except that a body complete with booster lead charge shall be substituted for the unloaded component and the loaded component shall be the body loading assembly (see dwg. 8837311).

4.3.2.3 Slider charge.-The same procedure specified in 4.3.2.1 shall be used except that a slider shall be substituted for the body.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:06Z
Check the source to verify that this is the current version before use.

4.3.3 Jolt and jumble.-The fuze assemblies shall be tested in accordance with the procedure specified in Standard MIL-STD-331, except that after completion of the jolt test, the assemblies shall not be disassembled but shall be subjected to the jumble test and then disassembled to determine compliance with the requirements.

4.3.4 Transportation vibration.-The fuze assemblies shall be tested in accordance with Standard MIL-STD-331 for compliance with the requirements.

4.3.5 Functioning.-Fuze assemblies shall be assembled in the 165MM HEP Cartridge, M123 loaded with spotting charge. The propelling charge shall be adjusted to give the standard service velocity. The rounds shall be fired from the weapon for which the round is standard against a 1 1/2 or 2 inch thick mild steel plate placed 400 plus 5 feet from the muzzle of the weapon. (see 6.5)

4.3.6 Slider arming and non-arming tests.-The assembly, prior to assembling the head and detonator holder assembly, shall be assembled in a centrifuge. The fuze assembly shall arm when the centrifuge is rotated at the max. arming speed specified and shall not arm when the centrifuge is rotated at the minimum non-arming speed specified. The arming test shall be performed first. The test equipment shall be in accordance with 4.2.4.

4.3.7 Static functioning.-The slider shall be armed by inserting a plug into the slider cavity in the fuze body and reassembling the slider, slider spring and retaining screw. The firing pin assembly shall be removed and replaced by a firing pin guide plug. A hole shall be drilled through the fuze head in line with the hole in the firing pin guide plug and detonator holder to receive the firing pin. The modified fuze assembly shall be mounted in a suitable fixture with the booster end down. The firing pin shall be lowered into the fuze and held slightly above the detonator holder by a shear wire. A weight shall be dropped on the firing pin in such a manner as to shear the wire and detonate the fuze.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging

5.1.1 Level C.-The fuze assemblies shall be preserved and packaged in accordance with dwg. 8886963.

5.2 Packing

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:06Z
Check the source to verify that this is the current version before use.

5.2.1 Level C.-The container shall be packed in accordance with dwg. 8886964.

5.2.2 Marking.-Marking shall be in accordance with dwgs. 8886963 and 8886964.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data cards.-Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the inspection Equipment Lists (EL) referenced on the applicable ET in accordance with the instructions of paragraphs 6.3.1 through 6.3.5.

6.3.1 Inspection equipment lists (EL).-Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings or Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.2 Inspection equipment list codes.-The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment.
MU - Army design, mandatory for use.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:06Z
Check the source to verify that this is the current version before use.

contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications; mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to MIL-D-1000, Category E, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high contrast reproductions. Contractors shall submit two copies of final designs as a flat set. Designs shall be submitted for approval as specified in 6.3.5.

6.3.5 Submission of contractor designs.-All submitted designs shall contain a reference to the applicable five digit Code Number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND12. All other designs of inspection equipment shall be approved by the inspection element of the agency administering

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:06Z
Check the source to verify that this is the current version before use.

the contract; submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished normally within one month after receipt.

6.4 Cost of deterioration check test.-The test shall be conducted at Government expense without cost to the supplier who loaded the detonator or the supplier assembling the detonator into the fuze, and shall not constitute a basis for rejection against either suppliers except where deterioration has occurred as a direct result of carelessness in handling, storage, etc. permitted while the detonator lot was under the responsibility of either supplier.

6.5 Submission of test data and ammunition data cards.-In addition to the normal distribution of records, when the fuze is procured by the Army Munitions Command, one copy of all ballistic test data and ammunition data cards shall be forwarded to each of the following: Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND2 and SMUPA-DC3, Dover, New Jersey.

Custodian:
Army-MU

Preparing activity:
Army-MU

Project Number 1390-A654

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:06Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:06Z
Check the source to verify that this is the current version before use.