MIL-G-80176B
15 November 1982
SUPERSEDING
MIL-G-80176A
31 May 1974

MILITARY SPECIFICATION
GRINDING MACHINES, ABRASIVE BELT, PLATEN, WET AND DRY TYPE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers wet and dry, vertical and combination vertical and horizontal, floor mounting, abrasive belt, platen type grinding machines of the types, classes and sizes classified in 1.2, with equipment and accessories specified herein.

1.2 Classification. This specification covers abrasive belt grinding machines of the following types, classes and sizes. The type, class and size required for a specific procurement shall be as specified (see 6.2.1).

Type I - Dry
  Class A (Combination Vertical/Horizontal Platen)
    Size 4 - 4" (102 mm) belt width
    Size 6 - 6" (152 mm) belt width
    Size 10 - 10" (254 mm) belt width

Type II - Wet
  Class A (Combination Vertical/Horizontal Platen)
    Size 6 - 6" (152 mm) belt width
    Size 10 - 10" (254 mm) belt width

  Class B (Vertical Platen)
    Size 4 - 4" (102 mm) belt width
    Size 6 - 6" (152 mm) belt width
    Size 8 - 8" (203 mm) belt width
    Size 10 - 10" (254 mm) belt width

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Industrial Plant Equipment Center, Memphis, Tennessee, 38114, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 3419

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:44Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form, form a part of this specification to the extent specified herein.

STANDARDS

FEDERAL

FED-STD-H28 - Screw-Thread Standards for Federal Services

MILITARY

MIL-STD-1188 - Commercial Packaging of Supplies and Equipment

(Copies of specifications, standards, drawings and publications required by supplier in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.

2.1.2 Other Government documents, drawings and publications. The following other Government documents form a part of this specification to the extent specified herein.

U. S. DEPARTMENT OF LABOR

OSHA 2206 - General Industry, OSHA Safety and Health Standards (29 CFR 1910)

(Applications for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC, 20402.)

2.2 Other publications. The following other documents form a part of this specification to the extent specified herein.

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

ANSI B11.9 - Safety Requirements for the Construction, Care and Use of Grinding Machines
ANSI/NFPA.79 - Electrical Standards for Metal Working Machine Tools
ANSI/ASTM E-380/IEEE 268 - Metric Practices

(Application for copies should be addressed to the American National Standards Institute, ATTN: Sales Dept., 1430 Broadway, New York, NY, 10018.

2.3 Order of precedence. In the event of a conflict between the text of

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:44Z
Check the source to verify that this is the current version before use.

this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2.1), the contractor shall furnish one complete grinding machine for first article inspection and approval (see 4.2 and 6.3).

3.2 Design. The machine shall be new and one of the manufacturer's current models capable of flat grinding, deburring, chamfering and rounding in accordance with the requirements herein. The machine shall include all components, parts and features necessary to meet the performance requirements herein. All parts subject to wear, breakage and distortion shall be accessible for adjustment, repair or replacement.

3.2.1 Reclaimed materials. The machine manufacturer is encouraged to use reclaimed materials to the maximum extent possible without jeopardizing the chemical composition and physical properties of the materials originally selected for the machine construction.

3.2.2 Controls. All operating controls shall be located conveniently to the operator except as otherwise specified herein.

3.2.3 Safety measures. Covers or other safety devices shall be provided for all parts of the machine that present safety hazards. The safety devices shall not interfere with operations of the machine and shall be removable to facilitate inspection, maintenance and repair. Except as otherwise specified by the preparing activity, the machine shall comply with the standards promulgated under OSHA applicable to the machine itself. In addition, the machine shall comply with all of the requirements of ANSI B11.9 that are designated therein as the responsibility of the machine manufacturer. Additional safety and health requirements shall be as specified (see 6.2.1 and 6.4).

3.2.4 Measurement systems. Unless otherwise specified, either the U.S. Customary System of Units (US) or the International System of Units (SI) may be used in the design and construction of the machine. When only one system of measurements is acceptable, the particular system required shall be as specified (see 6.2.1). In this specification, all measurements, dimensions, sizes and capacities are given in the U.S. Customary System of Units (US). These measurements may be converted to the International System of Units (SI) through the use of the conversion factors and methods specified in ANSI/ASTM E 380.

3.2.5 Lubrication. Means shall be provided for lubrication of all sliding and moving parts, except where sealed bearings are used. Recirculating systems, when provided, shall include filters which are cleanable or replaceable. Each lubricant reservoir shall have means for determining the fluid level. All oil holes, grease fittings and filler caps shall be readily accessible.

3.2.6 Interchangeability. To provide for replacement of worn parts, all parts shall be manufacturered to definite dimensions and tolerances which

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:44Z
Check the source to verify that this is the current version before use.

will permit installation of replacement parts without modification of part or machine.

3.3 Construction. The machine shall be constructed of parts which are new, without defects and are free of repair. The structure shall be capable of withstanding all forces encountered during the operation of the machine to its maximum rating and capacity without permanent distortion.

3.3.1 Castings and forgings. All castings and forgings shall be free of scale and mismatching. No process such as welding, peening, plugging or filling with paste shall be used for reclaiming any defective part.

3.3.2 Welding, brazing or soldering. Welding, brazing or soldering shall be employed only where specified in the original design. None of these operations shall be employed as a repair measure for any defective part.

3.3.3 Fastening devices. All screws, pins, bolts and similar fasteners which affect machine operation or prevent loss of fluids shall be installed with means of preventing loss of tightness. Fasteners that are subject to removal or adjustment shall not be swaged, peened or staked.

3.3.4 Surfaces. All surfaces shall be cleaned and free of sand, dirt, fins, sprues, flash, scale, flux and other harmful or extraneous materials. All edges shall be either rounded or beveled unless sharpness is required to perform a necessary function. Except as otherwise specified herein, the condition and finish of all surfaces shall be in accordance with the manufacturer's standard commercial practice.

3.3.5 Painting. Unless otherwise specified (see 6.2.1), the machine shall be painted in accordance with the manufacturer's standard commercial practice.

3.3.6 Threads. All threaded parts used on the machine and its related attachments and accessories shall conform to FED-STD-H28 and the applicable "Detailed Standard" section referenced therein.

3.3.7 Plates. All words on instruction and indicating plates shall be in the English language. Characters shall be engraved, etched, embossed or stamped in boldface on a contrasting background.

3.4 Components. Machines covered by this specification shall consist essentially of a floor mounting base, pedestal or stand, a frame, an abrasive belt, a belt drive system, a platen and a worktable or other holding device. Type I machines shall have provisions for connection to a dust collection system. Type II machines shall have a coolant system.

3.4.1 Base, pedestal or stand. A fabricated or cast base, pedestal or stand shall rigidly support the machine at a convenient working height.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:44Z
Check the source to verify that this is the current version before use.

The base, pedestal or stand shall have means for securely fastening the machine to the floor.

3.4.2 Frame. The machine frame shall have provisions for mounting the worktable, the workrest, the platen, the abrasive belt drive system, the abrasive belt and the hood and side guards. The frame for Class A machines shall be designed so that the machine can be operated in both the horizontal and vertical positions. The frame for Class B machines shall be designed for vertical operation.

3.4.3 Hood and side guards. The machine shall have a hood and side guard which will minimize the discharge of abrasive dust, abraded metal and water spray toward the operator. The hood and side guards shall enclose the abrasive belt and the belt drive system to the extent that only the normal working areas of the belt and platen are exposed. The side guards shall be readily removable or mounted on hinges to provide access to the interior of the machine to facilitate cleaning the interior and changing the abrasive belt.

3.4.4 Abrasive belt. The machine shall be designed for operation with an abrasive belt of the width specified in Table I. When specified (see 6.2.1), the belts of the proper length and width shall be furnished in the quantity, grit type and grit size specified.

3.4.5 Abrasive belt drive system. The abrasive belt drive system shall consist of an electric motor conforming to 3.4.11, a pair of abrasive belt pulleys and either a direct drive coupling or a belt drive system. The mechanism shall have means for adjusting the tension of the drive belts, when utilized, and for adjusting the tension and tracking alignment of the abrasive belt and pulleys. The abrasive belt pulleys shall be dynamically balanced for operation at the designed belt speed and shall be mounted on fully-enclosed, permanently sealed and lubricated, anti-friction bearings. All driving components shall be capable of transmitting full motor torque to the abrasive belt without slippage.

3.4.6 Platen. The platen length, width and working area above the table surface shall conform to the requirements of Table I. Unless otherwise specified, the platen shall be constructed of the material normally furnished by the manufacturer on his standard commercial machine.

3.4.7 Worktable (or other type worksupport device). Unless otherwise specified, the machine shall have the standard type worktable or other worksupport device specified in 3.4.7.1 through 3.4.7.1.3 as required for the size machine being procured. When specified (see 6.2.1), size 6 and sizes 8 machines shall have one of the optional worktables described in paragraphs 3.4.7.2.1 through 3.4.7.2.2.

3.4.7.1 Standard worktables (or other type worksupport device).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:44Z
Check the source to verify that this is the current version before use.

3.4.7.1.1 Size 4 machines. All size 4 machines shall have a workrest that assists the operator in holding the workpiece in the proper grinding position. The workrest shall extend across the entire width of the abrasive and platen and shall be adjustable to allow the workrest to be positioned within 1/32 inch of the belt face.

3.4.7.1.2 Size 6 and 10 machines. All size 6 and 10 machines shall have a tilting type worktable. The table shall tilt up not less than 15 degrees and down not less than 45 degrees.

3.4.7.1.3 Size 8 machines. All size 8 machines shall have a stationary (fixed) table with options available for automatic or semi-automatic table (see 3.4.7.2.2). Size 8 machines that are normally equipped with an automatic or semi-automatic table shall not be required to have options.

3.4.7.2 Optional worktables. When specified (see 6.2.1), size 6 and 8 machines shall have the type worktable described in 3.4.7.2.1.1, 3.4.7.2.2.1 or 3.4.7.2.2.2 in lieu of the standard worktable described in 3.4.7.1.2 and 3.4.7.1.3.

3.4.7.2.1 Optional worktables for Type II Class B size 6 machines.

3.4.7.2.1.1 Manual oscillating, manual infeeding worktable. When a manual oscillating and infeeding worktable is required to be furnished on size 6 machines, the worktable shall oscillate radially about a horizontal axis perpendicular to the platen work surface. The angle of oscillation shall not be less than 15 degrees clockwise and counterwise from the horizontal position. The table shall have a manual or power feed mechanism with an adjustable stop which will stop the infeed movement at any point within 1/2-inch of the platen. The worktable surface shall be not smaller than 8 x 10 inches. Means shall be provided for securely attaching workpiece or workpiece holding fixtures to the worktable surface.

3.4.7.2.1.2 Manual oscillating with counterweights and power infeeding worktable. When a manual oscillating, power infeeding worktable is required, the worktable shall oscillate radially about a horizontal axis perpendicular to the platen work surface, through an angle of not less than 30 degrees clockwise and counterclockwise from the horizontal. The oscillating mechanism shall have counterweights which oscillate with the table and assist in sustaining the oscillating motion. The table shall have a pneumatic or hydraulic infeed mechanism that will feed the table toward the platen through a distance of not less than 0.375 inches. The table shall tilt away from the platen through an angle of not less than 45 degrees to facilitate loading, inspection and unloading of the workpiece. The worktable size shall conform to the requirements of Table I. Means shall be provided for securely fastening workpiece or workpiece holding fixtures to the table surface.

3.4.7.2.2 Optional worktables for Type II Class B size 8 machines.

3.4.7.2.2.1 Power infeeding, horizontal sliding worktable. When a power infeeding horizontal sliding worktable is required to be furnished on size 8 machines, the worktable shall be mounted on ways which allow the table to infeed in a direction perpendicular to the platen work surface, and slide

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:44Z
Check the source to verify that this is the current version before use.

horizontally in a direction parallel to the platen work surface. The design of the table shall permit loading a workpiece on half of the table surface while a workpiece mounted on the other half is being ground. The infeed distance shall be not less than 0.400 inch and the horizontal sliding distance shall be not less than 10 inches. The size of the worktable surface shall be not less than 13 x 28 inches. Means shall be provided for securely attaching workpiece or workpiece holding fixtures to the table surface.

3.4.7.2.2.2 Power reciprocating manual infeed type worktable. When a power reciprocating, manual infeed type worktable is required, the worktable shall be mounted on ways which allow the table to infeed in a direction perpendicular to the platen surface and reciprocate in a direction parallel to the platen surface. The infeed motion of the table shall be manually powered by an electric motor having a continuous duty rating of not less than 1/4 horsepower. The reciprocation rate shall be variable over a range of 11 or less, to 22 or more, strokes per minute. The reciprocating stroke length shall be infinitely variable over a range of 0 to not less than 8 inches. The table shall tilt back away from the platen through an angle of not less than 45 degrees to facilitate loading, inspection and unloading of the workpiece. The worktable surface shall be not smaller than 10 x 15 inches. Means shall be provided for securely attaching workpiece or workpiece holding fixtures to the table surface.

3.4.8 Exhaust outlet. Type I machines (dry) shall have a cylindrical exhaust outlet, not less than 3 inches in diameter, which can be connected to a dust collection system. When specified (see 6.2.1), a dust collection system complete with motorized blower, flexible ducts and a dust collection container shall be furnished.

3.4.9 Coolant system. All Type II machines shall have a coolant system consisting of a sump or reservoir, a power driven pump and all necessary piping. The sump or reservoir shall have sufficient capacity to permit full flow of coolant. The system shall have means for draining and cleaning and shall include a strainer or baffle which is easily removable for cleaning. Means shall be provided to permit the operator to direct and control the amount of coolant.

3.4.10 Electrical system. Unless otherwise specified (see 6.2.1), the electrical system shall conform to all requirements in this paragraph. The system shall conform to the requirements of ANSI/NFPA-79. Each machine shall draw all of its electrical power from a single 230/460 volt, 3 phase, 60 Hz circuit having a fused safety disconnect switch. The grinder shall be initially wired for operation on 230 volts. An identified terminal for grounding the machine when installed shall be mounted in or near the disconnect switch. The terminal shall be suitable for connecting the size grounding conductor specified in Table 240/A of ANSI/NFPA-79 for the disconnect fuse rating.

3.4.11 Motors. Motors shall have ball or roller bearings. Continuous

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:44Z
Check the source to verify that this is the current version before use.

duty horsepower ratings shall conform to the requirements of Table I. Unless otherwise specified (see 6.2.1), each motor shall meet the requirements of a totally enclosed, fan cooled (TEFC) motor.

3.5 Sizes and capacities. The sizes and capacities of the grinder shall conform to the requirements of Table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:44Z
Check the source to verify that this is the current version before use.

TABLE I

SIZES AND CAPACITIES

	TYPE I - DRY			TYPE II - WET					
	Class A - Combination Horizontal/Vertical Platen			Class A - Combination Horizontal/Vertical Platen		Class B - Vertical Platen			
	Size 4	Size 6	Size 10	Size 6	Size 10	Size 4	Size 6	Size 8	Size 10
Abrasive Belt:									
Drive Motor, Horsepower	1/2	1-1/2	5	3	7-1/2	1-2	5	5	7-1/2
Belt Width, Inches	4	6	10	6	10	4	6	8	10
Belt Speed, SFPM	1800	3400	3400	3300	3400	1800	3400	2500	3400
Platen:									
Size, Width x Length, Inches	4 x 6	6 x 11	10 x 20	6 x 12	10 x 20	4 x 6	6 x 9	9 x 12	10 x 16
Work Area Above Table, Surface Inches	4 x 6	6 x 11	10 x 16	6 x 9	10 x16	4 x 6	6 x 9	9 x 12	10 x 16
Standard Work Table:									
Type Table	Workrest	Tilting	Tilting	Tilting	Tilting	Workrest	Tilting	Stationary	Tilting
Size, Inches	------	7 x 11	9 x 16	7 x 10	9 x 16	------	8 x 10	11 x 14	9 x 16
Coolant Tank Capacity, Gal.	------	------	------	15	25	5	25	25	25

NOTE: Requirements shall be not less than those shown.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:44Z
Check the source to verify that this is the current version before use.

3.6 Accuracy and performace.

3.6.1 Square and beveled edges. Machines with tilting tables shall be capable of grinding square and beveled edges within an accuracy of ± 1 1/2 degrees of the desired angle. Machines with fixed tables shall be capable of grinding square edges to an accuracy of 90 ± 1 1/2 degrees.

3.6.2 Square-cut and mitered ends. Machines with protractor type work guides shall be capable of grinding square-cut and mitered ends to an accuracy of ± 1 1/2 degrees of the desired angle.

3.6.3 Free-hand grinding. All machines shall be capable of free-hand deburring, chamfering and rounding of edges.

3.7 Standard equipment. Unless otherwise specified (see 6.2.1), each machine shall be furnished with all standard equipment, including all maintenance tools, normally furnished by the machine manufacturer.

3.8 Optional equipment. Optional equipment shall be furnished as specified (see 6.2.1). Any optional equipment required shall be fully described.

3.9 Lubrication chart or plate. Unless otherwise specified (see 6.2.1), a lubrication chart or plate shall be permanently and securely attached to each machine. If a chart is furnished, it shall be placed in a transparent plastic folder, or permanently sealed between clear plastic sheets, with suitable means for mounting. The following information shall be furnished on the chart or plate:

Points of application
Service interval
Type of lubricant
Viscosity
Military or Federal Specifications covering above lubricants

3.10 Nameplate. Unless otherwise specified (see 6.2.1), a corrosion-resistant metal nameplate identifying the machine shall be securely attached to each machine. The nameplate shall contain the information listed below. If the machine is a special model, the model designation shall include the model of the basic standard machine and a suffix identified in the manufacturer's records. The captions listed may be shortened or abbreviated, provided the entry for each caption is clear as to its identity.

Nomenclature
Manufacturer's name
Manufacturer's model designation
Manufacturer's serial number
Power input (volts, total amps, phase, frequency)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:44Z
Check the source to verify that this is the current version before use.

Contract Number or Order Number
National Stock Number or Plant Equipment Code
Date of manufacture

3.11 Technical data. Technical data shall be furnished as specified (see 6.2.2).

3.12 Workmanship. Workmanship of the machine and accessories shall be of a quality equal to that of the manufacturer's commercial equipment of the type specified herein.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified in the contract or order. The supplier may utilize his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification when such action is deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When first article inspection is required, it shall be applied to the first article submitted in accordance with 3.1. Unless otherwise specified (see 6.2.1), first article inspection shall consist of the examination in 4.5 and all tests in 4.6. Failure to pass the examination of one or more first article tests shall be cause for rejection.

4.4 Quality conformance inspection. Quality conformance inspection shall be applied to each item prior to being offered for acceptance under the contract, unless otherwise specified (see 6.2.1). Quality conformance inspection shall consist of the examination in 4.5 and the test in 4.6.1 and 4.7. Failure of the item to pass the examination or test shall be cause for rejection.

4.5 Examination. The machine and equipment shall be examined to determine compliance with all requirements specified herein.

4.6 Tests.

4.6.1 Operational test. The machine shall be operated at no load for

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:44Z
Check the source to verify that this is the current version before use.

Contract Number or Order Number
National Stock Number or Plant Equipment Code
Date of manufacture

3.11 Technical data. Technical data shall be furnished as specified (see 6.2.2).

3.12 Workmanship. Workmanship of the machine and accessories shall be of a quality equal to that of the manufacturer's commercial equipment of the type specified herein.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified in the contract or order. The supplier may utilize his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification when such action is deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When first article inspection is required, it shall be applied to the first article submitted in accordance with 3.1. Unless otherwise specified (see 6.2.1), first article inspection shall consist of the examination in 4.5 and all tests in 4.6. Failure to pass the examination of one or more first article tests shall be cause for rejection.

4.4 Quality conformance inspection. Quality conformance inspection shall be applied to each item prior to being offered for acceptance under the contract, unless otherwise specified (see 6.2.1). Quality conformance inspection shall consist of the examination in 4.5 and the test in 4.6.1 and 4.7. Failure of the item to pass the examination or test shall be cause for rejection.

4.5 Examination. The machine and equiment shall be examined to determine compliance with all requirements specified herein.

4.6 Tests.

4.6.1 Operational test. The machine shall be operated at no load for

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:44Z
Check the source to verify that this is the current version before use.

not less than 30 minutes. Proper operation of all controls, motors and adjusting mechanisms shall be verified during the trial period.

4.6.2 Performance tests. Each class and size machine shall be required to successfully perform the flatness test described in 4.6.2.1. The manufacturer shall also demonstrate that the machine is capable of free-hand grinding, grinding square and beveled edges, and grinding square-cut and mitered ends in accordance with the accuracy requirements of 3.6.1, 3.6.2 and 3.6.3. The manufacturer may use any available scrap metal of any composition in performing these demonstrations.

4.6.2.1 Flatness test. With the machine in operation, the raw edges at the open end of a standard 4-inch octagonal electric outlet box shall be hand-held against the abrasive belt until not less than 1/16 inch of metal is removed from all edges. The ground surface shall then be held against a flat surface plate, and the flatness shall be inspected by attempting to insert a 0.003-inch feeler gauge between the ground surface and the surface plate. The feeler gauge shall not enter at any point around the periphery.

4.7 Inspection of preparation for delivery. Preservation, packaging, packing and marking shall be inspected to determine compliance with the requirements of Section 5.

5. PACKAGING

5.1 Preservation, packing and marking. Unless otherwise specified (see 6.2.1), preservation, packing and marking shall conform to the requirements of MIL-STD-1188.

6. NOTES

6.1 Intended use. The belt grinders covered by this specification are intended for use in secondary finishing operations, such as flat grinding, deburring, chamfering, rounding of edges and free-hand grinding.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number and date of this specification
b. Class and size machine required (see 1.2)
c. First article approval, if required (see 3.1 and 4.3)
d. Specify exceptions and additional safety and health requirements (see 3.2.3 and 6.3)
e. If measuring and indicating devices are required to be graduated in a specific measurements system (US or SI), state required system (see 3.2.4)
f. Painting, if different (see 3.3.5)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:44Z
Check the source to verify that this is the current version before use.

g. Abrasive belts, if required, specify quantity, grit type and size (see 3.4.4)
h. Optional worktables, if required, specify type (see 3.4.7.2.1 or 3.4.7.2.2)
i. Dust collecting system, if required (see 3.4.8)
j. Electrical equipment, if different (see 3.4.10)
k. Type of enclosure for motors, if different (see 3.4.11)
l. Standard equipment, if different (see 3.7)
m. Optional equipment, if required, fully describe optional equipment required (see 3.8)
n. Lubrication chart, if different (see 3.9)
o. Nameplate, if different (see 3.10)
p. First article inspection, if different (see 4.3)
q. Quality conformance, if different (see 4.4)
r. Required level of preservation, packaging and packing (see 5.1)
s. Additional marking, if required (see 5.1)

6.2.2 Contract data requirements. Required technical data such as operators' manuals, parts lists, foundation and anchor bolt plans, wiring diagrams and other instructions for operation and maintenance as identified on a numbered DD Form 1664, should be specified on a DD Form 1423 incorporated into the contract.

6.3 First article. When a first article is required, it shall be tested and approved under appropriate provision of 7-104.55 of the Defense Acquisition Regulation. The first article should be a preproduction item from the contractor's current inventory. The contracting officer should include specific instructions in all procurement instruments regarding arrangements for examinations, tests and approval of the first article.

6.4 Safety and health requirements. Paragraph 3.2.3 requires compliance only with those OSHA requirements that concern the machine itself. It does not require compliance with those OSHA requirements that concern "the machine in its operating environment" such as noise levels, radiation levels, electromagentic emissions, noxious vapors, air contaminants, heat, etc. Since OSHA limits the total level of these hazards in the environment (and does not limit the hazard level of individual machines in the environment) the requesting activity is advised to analyze the existing hazard levels in the proposed operating environment, and specify additional machine requirements that will integrate the new machine into its future operating environment. If specific point-of-operation guarding is required, as in most cases, the guard configuration is dependent on the size and configuration of workpieces. The above, and any other additional safety and health requirements, should be specified in detail under 6.2.1(d).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:44Z
Check the source to verify that this is the current version before use.

6.5 Size relation to previous issues.

MIL-G-80176B	MIL-G-80176A
Type I - Dry	(New Title)
Class A - Combination Vertical/ Horizontal Platen	Class I - Light Duty (Dry Type)
Size 4 - 4" belt width in inches	Size 4 - 4" belt width in inches
Size 6 - 6" belt width in inches	Size 6 - 6" belt width in inches
Size 10-10" belt width in inches	Size 10-10" belt width in inches
Type II - Wet	(New Title)
Class A - Combination Vertical/ Horizontal Platen	Class II - Medium Duty (Wet Type)
Size 6 - 6" belt width in inches	Size 6 - 6" belt width in inches
Size 10-10" belt width in inches	Size 10-10" belt width in inches
Class B - Vertical Platen	Class III - Heavy Duty (Wet Type)
Size 4 - 4" belt width in inches	(New Size)
Size 6 - 6" belt width in inches	Size 6 - 6" belt width in inches
Size 8 - 8" belt width in inches	Size 8 - 8" belt width in inches
Size 10-10" belt width in inches	(New Size)

Custodians:
Army - AL
Navy - SH
Air Force - 99

Preparing Activity:
DLA-IP

Project Number:
3419 - 0196

Review Activities:
Army - AL
Navy - SH
Air Force - 99
DSA - GS

User Activity:
Navy - AS, OS, MC, YD

59

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:44Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-G-80176B, Grinding Machines, Abrasive Belt, Platen, Wet and Dry Type

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1426
1 OCT 76

EDITION OF 1 JAN 72 MAY BE USED UNTIL EXHAUSTED

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:44Z
Check the source to verify that this is the current version before use.

FOLD

DEFENSE LOGISTICS AGENCY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL

FIRST CLASS PERMIT NO. 4966 WASHINGTON D. C

POSTAGE WILL BE PAID BY THE DEFENSE LOGISTICS AGENCY

Commander
Defense Industrial Plant Equipment Center
ATTN: DIPEC-TES
Memphis, Tennessee 38114

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:44Z
Check the source to verify that this is the current version before use.