MILITARY SPECIFICATION

PELLET, SMOKE MARKER FOR CARTRIDGE, 105MM: APERS-T, XM546

1. SCOPE

1.1 This specification covers Pellet, Smoke Marker, made for use in Cartridge, 105MM: APERS-T, XM546.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-636 - Boxes, Fiber
PPP-F-320 - Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes
PPP-T-45 - Tape, Gummed, Paper, Reinforced
UU-T-106 - Tape, Pressure-Sensitive Adhesive, Paper, Drafting

MILITARY

MIL-B-117 - Bags, Interior Packaging
MIL-B-2427 - Boxes, Ammunition Packing; Wood, Nailed
MIL-C-2439 - Container, Ammunition, Fiber, Spirally Wound
MIL-A-2550 - Ammunition and Special Weapons, General Specification for
MIL-I-45607- Inspection Equipment, Supply and Maintenance of

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:06Z
Check the source to verify that this is the current version before use.

DRAWINGS

ARMY

8796522 - Marking Diagram and Sealing for Wood Packing Boxes
9230453 - Pellet, Smoke Marker

PUBLICATIONS

ARMY

ET-9230453 - Equipment Tabulation

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material.-Material shall be in accordance with the applicable drawings and specifications.

3.2 Pellet.-The pellet shall comply with all requirements specified on Drawing (dwg.) 9230453 and all requirements specified in the applicable drawings and specifications.

3.3 Compositions.-No ingredients other than those specified shall be utilized and no ingredients shall be omitted.

3.4 Moisture content.-The moisture content of the smoke charge composition and the igniter charge composition shall not exceed the applicable drawing requirements when tested in accordance with 4.4.1.

3.5 Static functioning

3.5.1 Delay.-The delay in functioning shall not exceed 0.25 seconds when tested in accordance with paragraph 4.4.2.

3.5.2 Duration.-The smoke emission shall be maintained for a minimum of 2.0 seconds when tested as specified in paragraph 4.4.2.

3.6 Ballistic functioning.-The pellet shall generate black smoke within 80 feet of projectile first function and trail smoke for a distance of 1000 feet, minimum, when tested as specified in 4.2.3.

3.7 Workmanship.-The pellet shall be fabricated in a thorough workmanlike manner. The pellet shall be free of dirt, chips and other foreign matter and shall not exhibit excessive cavitation or broken interfaces. All packing components shall be dry.

Source: https://assist.dla.mil -- Downloaded: 20260-23T01:06Z
Check the source to verify that this is the current version before use.

3.8 First article.-This specification makes provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified within this specification.
b. Number of units of product inspected.
c. Results obtained, by defect code, for all inspections performed.
d. Drawing, specification number and date, together with an identification and date of changes.
e. Certificates of conformance on all material purchased by the contractor when such material is controlled by Government or commercial specifications referenced in any of the contractual documents.
f. Number of items in the lot.
g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First Article Inspection

4.2.1 Submission.-The contractor shall submit a first article sample as designated by the contracting officer for

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:06Z
Check the source to verify that this is the current version before use.

evaluation in accordance with the provisions of 4.2.2. The first article sample shall consist of 40 pellets separately packaged in quantities of 10 units each which have been produced by the contractor or furnished by a supplier and which have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample, including statements of findings for materials, processes and tests. A sample containing known defects will not be submitted unless specifically authorized, by the Contracting Officer. A first article sample, or portion thereof, as directed by the contracting officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect product uniformity as determined by the Government.

4.2.2 Inspections to be performed.-Pellets from three (3) containers will be subjected by the Government to any or all of the examinations or tests specified in 4.3.2 and 4.3.3 of this specification and any or all requirements of the applicable drawings. The inspection shall take place prior to insertion into the static test fixture. After inspection has been completed and the pellets provisionally accepted, the remaining container of 10 pellets shall be sent to a Government Proving Ground for ballistic testing.

4.2.3 Ballistic Test.-Each of the ten (10) pellets selected for this test shall be inserted into an appropriate fuze adapter, assembled into a complete round using a zone 7 propellant charge, and conditioned to 70 degrees Fahrenheit. The fuze shall be set to function at a 1000 meter range and the round shall be fired in a relatively horizontal trajectory in a weapon for which the round was designed. The height of the projectile at the point of fuze function should be approximately 50 meters above the terrain as an aid to observation. Each pellet shall generate black smoke within 80 feet of the projectile first function and exhibit a trail of smoke from first appearance to termination at least 1000 feet long as verified by appropriate measuring equipment such as engineering transits or other equivalent means.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:06Z
Check the source to verify that this is the current version before use.

4.2.4 Rejection.-If any assembly or component fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an assembly or component to comply with any of the stated requirements.

4.3 Inspection Provisions

4.3.1 Lot formation.-The term "lot" as used throughout this specification refers to an inspection lot, which is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance of the lot with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the lot has been produced by one manufacturer, in one unchanged process using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions. Changes to the process, specifications, or drawings, not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of the lot. Inspection lots shall comply with MIL-STD-105. Unless otherwise approved by the contracting officer, the inspection lot size of end items deliverable under the contract shall be not less than the smallest weekly estimate of quantities contractually scheduled for production during the contract period nor more than the largest monthly quantity contractually scheduled for delivery during the contract period. Inspection lots of components or subassemblies, other than the items of delivery, shall be homogeneous and of a size mutually convenient to both the contractor and the Government inspector. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each lot of pellets shall be prepared using individual ingredients from one manufacturer and shall contain the same proportion of ingredients.

4.3.2 Examination.-Inspection for Critical defects (and Major defects, when so specified), shall be 100 percent. Sampling plans and procedures for Major and Minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:06Z
Check the source to verify that this is the current version before use.

procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to individual characteristics listed using an AQL of 0.65 percent for each Minor defect and an AQL of 0.40 percent for each Major defect, except where 100 percent inspection is specified. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 Pellet (see dwg. 9230453).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.0 percent		
101.	Weight of igniter charge	Scale	01001
102.	Length of side of hole, minimum (min.)	Gage	01002
103.	Large diameter, maximum (max.) ...	Gage	01003
104.	Thickness, max.	Gage	01004
105.	Location of square hole	Gage	01005
Minor:	AQL 2.5 percent		
201.	Igniter charge surface coverage	Visual	01006
202.	Length of side of hole, max.	Gage	01007
203.	Large diameter, min.	Gage	01008
204.	Thickness, min.	Gage	01009
205.	Evidence of poor workmanship (see 3.7)	Visual	01010

4.3.2.2 Fiber tube container, prior to placing in intermediate packaging (see 5.1.1).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Aluminum wrap incomplete or torn to extent contents are exposed (prior to insertion into fiber tube container)	Visual	02001

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:06Z
Check the source to verify that this is the current version before use.

102.	Sealing strips improperly applied to coin wrap	Visual	02002
103.	Fiber tube container torn, cut or punctured	Visual	02003
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.7)	Visual	02004

4.3.2.3 Fiberboard container after sealing in barrier bag and prior to placing in wooden box (see 5.1.2).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Barrier bag torn or exposing inner fiber box container	Visual	03001
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.7)	Visual	03002

4.3.2.4 Sealed wood packing box (see 5.2).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Box damaged	Visual	04001
102.	ICC nomenclature improper	Visual	04002
103.	Contents loose	Visual	04003
104.	Strapping broken	Visual	04004
Minor:	AQL 0.65 percent		
201.	Marking improper	Visual	04005

4.3.3 Testing

4.3.3.1 Moisture content - Major defect.-Moisture content of smoke charge composition, Code No. 05001 and moisture content of igniter charge composition, Code No. 05002.-The contractor

Source: https://assist.dla.mil -- Downloaded: 202610-23T01:06Z
Check the source to verify that this is the current version before use.

M

shall provide adequate controls to assure the compliance of each lot with the applicable requirement. The contractor shall test a minimum of one randomly selected sample from each 8 hours of production. Composite samples shall not be used in determining compliance. Failure to comply with the applicable requirement shall be cause for rejection of the parent quantity from which the sample was drawn. Testing shall be performed as specified in 4.4.1.

4.3.3.2 Static functioning.-This test shall be conducted using equipment in accordance with 4.3.4.

4.3.3.2.1 Delay - Major defect - Code No. 05003.

4.3.3.2.1.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirement, fifty sample pellets shall be randomly selected from each lot and tested in accordance with 4.4.2 If one or more sample pellets fail to meet the requirement of 3.5.1,the lot shall be rejected.

4.3.3.2.1.2 After the three consecutive lots have met the criteria of 4.3.3.2.1.1, twenty-five sample pellets shall be randomly selected from each lot and tested in accordance with 4.4.2. If one or more sample pellets fail to meet the applicable requirement, the lot shall be rejected.

4.3.3.2.2 Duration - Major defect - Code No. 05004.-The samples selected for delay will also be observed for duration. If any sample pellet fails to meet the requirement of 3.5.2, the lot shall be rejected.

4.3.4 Inspection Equipment.-Equipment Tabulation Number ET-9230453 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in 6.3.

4.3.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

Source: https://assist.dla.mil -- Downloaded: 202640-23T01:06Z
Check the source to verify that this is the currentversion before use.

4.3.4.2 Supply and maintenance.-Supply and maintenance of the equipment listed in the ET shall be in accordance with Specification MIL-I-45607.

4.3.4.3 Government use of contractor's inspection equipment.- The contractor shall make available to the Government all inspection equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment and verification of its accuracy, shall be supplied by the contractor for the performance of examination or test by the Government.

4.4 Test methods and procedures

4.4.1 Moisture content.-The moisture content of the smoke charge composition and the igniter charge composition shall be determined by carefully weighing about 10 grams to within 0.2 milligrams of the composition to be tested and placing it in a tared stoppered weighing dish. The uncovered specimen shall be heated to a temperature of 55 plus or minus 2 degrees Centigrade at an absolute pressure of 80 plus or minus 10mm of Mercury for 6 hours. The dish shall then be covered and allowed to cool to room temperature in a desiccator. The loss in weight of the specimen shall then be used in the moisture content computation as follows:

$$\text{Percent Moisture} = \frac{A\ 100}{B}$$

where:

A = loss in weight, grams
B = weight of sample, grams

4.4.2 Static functioning.-The sample pellet shall be tested in the appropriate test fixture. After completion of the test, the time elapsed (delay time) from initiation of the squib to the point midway between the initial (zero amplitude) level and the amplitude level of the peak flame intensity shall be measured. The total time from pellet initiation to termination of smoke emission shall be taken.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:06Z
Check the source to verify that this is the current version before use.

5.1.1 Unit Packaging

5.1.1.2 Level C - Twenty (20) pellets shall be coin wrapped in minimum .001 thick aluminum foil with approximately 2 1/2 turns (wraps) having tuck ends folded to provide complete closure of both ends. A polyethylene disc constructed of minimum 30 mil polyethylene or a polyethylene coated paper disc of .030 inch thickness shall be placed between each pellet and over each end. A piece of one inch wide tape shall be placed across each end and extend approximately 2 inches onto body of foil wrapper. Another piece of tape shall be used to cover the entire side seam of the foil wrapper. Tape shall meet requirements of Specification UU-T-106, Type I or II. Sealed wrappers shall be placed in chipboard or boxboard tubes meeting requirements of paragraph 3.3 of Specification MIL-C-2439. Chipboard tubes shall be 8 7/8 - 1/16 long by 1 15/16 + 1/16 diameter with a .060 + .005 wall thickness.

5.1.2 Intermediate Packaging

5.1.2.1 Level C - Twenty (20) unit packages shall be placed horizontally in a fiberboard box in a 10 by 1 by 2 layer arrangement. A fiberboard separator shall be placed between layers and filler shall be added on top of contents as required to provide a tight pack. The box shall conform to Specification PPP-B-636, Type CF, Class Domestic, Style CSSC, Grade 200. The box size shall be approximately 21 1/4 by 8 7/8 by 4 5/8 inches deep inside dimensions. Separator and fillers shall be made from same materials as the fiberboard boxes and shall be cut to the inside size of the box dimension minus 1/16 inch. The boxes shall be closed with PPP-T-45, Class B, gummed, kraft tape, 2 inch width applied over the full length of all top and bottom seams of the box with approximately 2 inch extension of tape onto end panels and around all corners of the box. The fiberboard box shall be inserted into a barrier bag conforming to MIL-B-117, Type I, Class E. All excess air shall be exhausted from the bag and the bag opening closed by heat-sealing. The bag size shall be approximately 15 by 28 3/4 inches.

5.2 Packing

5.2.1 Level C - Two intermediate packages (800) markers shall be packed in Type I, Class 1, Grade C wood box conforming to requirements of Specification MIL-B-2427. Fillers consisting of PPP-F-320, Type CF, Class Domestic, Grade 200 fiberboard shall be added between the contents and the interior sides and ends of the box and on top of the box contents as required for a tight pack. Wood box size shall be approximately 22 1/8 by 18 3/4 by 5 3/8 inches deep inside dimensions.

Source: https://assist.dla.mil -- Downloaded: 20260-23T01:06Z
Check the source to verify that this is the current version before use.

End fillers shall be approximately 17 3/4 by 5 1/8 inches. Side fillers shall be approximately 22 by 5 1/8 inches. Top fillers shall be approximately 22 by 17 3/4 inches. Boxes shall be closed and strapped in accordance with instructions contained in the Appendix of the box specification.

5.3 Marking.-Each chipboard tube, fiberboard box and barrier bag shall be marked by labeling, stamping or stenciling with the following information:

(QTY) PELLET, SMOKE MARKER
Lot No.
Packed (mo/yr)

All letters shall be upper case. Size of letters and numbers - minimum 1/4 inch. Ink shall be black, commercial grade. Labels shall be gummed or ungummed white paper. Ungummed labels shall be applied to tubes and boxes with commercial adhesive. Wood box shall be marked in accordance with Drawing 8796522. The DOT marking shall be "SMOKE SIGNALS".

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Ammunition data cards shall be prepared for each lot in accordance with MIL-STD-1167.
c. Provisions for the submission of First Article Samples.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the referenced inspection Equipment Lists (EL) in accordance with the instructions of paragraphs 6.3.1 through 6.3.5.

6.3.1 Inspection equipment lists.-Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings of Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.2 Inspection equipment list codes.-The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:06Z
Check the source to verify that this is the current version before use.

CD - Contractor design on controlled contractor format and/or commercial equipment.
MU - Army design, mandatory for use.

6.3.3 Army design.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications; mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format that the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to MIL-D-1000, Category E, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high contrast reproductions. Contractors shall submit one copy of final designs as a rolled set. Designs shall be submitted for approval as specified in 6.3.5.

6.3.5 Submission of contractor designs.-All submitted designs shall contain a reference to the applicable 5 digit Code

Source: https://assist.dla.mil -- Downloaded: 202610-23T01:06Z
Check the source to verify that this is the current version before use.

Number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND2. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract; submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished normally within one month after receipt.

Custodian:
Army-MU

Preparing activity:
Army-MU

Project Number: 1315-A-580

Source: https://assist.dla.mil -- Downloaded: 202640-23T01:06Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT

$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)* | DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:06Z
Check the source to verify that this is the current version before use.