MIL-T-60647(MU)
18 July 1968
SUPERSEDING
FA-PD-MI-2682
7 July 1965

MILITARY SPECIFICATION
THRUSTER, CARTRIDGE ACTUATED: M5A2
REMANUFACTURED METAL PARTS ASSEMBLY

1. SCOPE

1.1 This specification covers Thruster, Cartridge Actuated, M5A2, Remanufactured Metal Parts Assembly. The assembly will ultimately be loaded and used in conjunction with other propellant actuated devices in aircrew emergency escape systems.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Military

MIL-A-2550	- Ammunition and Special Weapons, General Specification for

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-1167	- Ammunition Data Card

DRAWINGS

Munitions Command

F8594747	- Thruster, Cartridge Actuated, M5A2, Metal Parts Assembly
C8797741	- Container, Ammunition, Fiber, M347, for Thruster, Cartridge Actuated, M20A1, M25 or M5A2
C8797742	- Box, Packing, Ammunition, for Thruster, Cartridge Actuated, M20A1, M25 or M5A2 in Fiber Container, M347

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:52Z
Check the source to verify that this is the current version before use.

not have equivalent operational performance characteristics across military

DRAWINGS (Cont'd)

IEL-8594747 - Index of Inspection Equipment List for Thruster, Cartridge Actuated, M5A2, Metal Parts Assembly

(Copies of specifications, standards and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications.- The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bid or request for proposal shall apply.

ASA B46.1 - Surface Texture, Surface Roughness, Waviness and Lay

(Application for copies should be addressed to the American Standards Association, 10 East 40th Street, New York N.Y. 10016.)

3. REQUIREMENTS

3.1 General.- Materials, parts and assemblies shall comply with the requirements specified on the applicable drawings and referenced specifications.

3.2 Material.- Components for remanufacture may be obtained from thruster Model M5A2. All components from earlier model types will have to be modified in accordance with M5A2 model.

3.3 Hydrostatic pressure.- The body and head shall withstand a constant internal pressure of 8000 pounds per square inch (psi), minimum, for 15 seconds, minimum, without application of any external load and shall show no evidence of leakage or mechanical failure (see 6.2).

3.4 Structural strength.- The assembled thruster shall withstand a static tensile force of 2000 pounds, minimum, for 15 seconds, minimum, between mounting points without unlocking and without mechanical failure (see 6.2).

3.5 Metal parts assembly.- Parts shall be combined to produce an assembly which conforms to the requirements of the metal parts assembly drawing. All threaded joints shall be assembled with sufficient torque to lightly bottom components.

3.5.1 The remanufactured thruster metal parts assembly shall contain the following new components: O-Rings, shear pin, piston lock spring, and set screws.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:52Z
Check the source to verify that this is the current version before use.

3.5.2 The remanufactured thruster metal parts assembly shall be assembled with a firing pin that is in accordance with Drawing C8593864.

3.5.3 Trunnion rotation.- Upon completion of assembly, the trunnion shall be free to rotate 360 degrees.

3.5.4 End sleeve rotation.- Upon completion of assembly and after structural strength test, the end sleeve shall be free to rotate 360 degrees in a clockwise direction.

3.6 Protective finish.- Protective finish shall be in accordance with the applicable specifications and drawings and shall apply to all surfaces of the components regardless of contour configuration. Remanufactured exterior components shall have the existing protective finish stripped and the specified protective finish reapplied (see 6.4).

3.7 Residual magnetism.- The metal parts assembly shall not deflect the indicator of the compass more than three degrees in either direction when passed in front of the compass at a distance of 6 inches (see 6.3).

3.8 Workmanship.- The requirements for workmanship are as specified on the applicable drawings, referenced specifications and the following:

3.8.1 Metal defects.- All components shall be free from cracks, splits, or other metal defects.

3.8.2 Burr.- The part shall not have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.8.3 Foreign matter.- No part or assembly shall contain chips, dirt, grease, rust, corrosion or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 20261O-23T00:52Z
Check the source to verify that this is the current version before use.

4.1.1 Quality assurance terms and definitions.- Reference shall be made to MIL-STD-109 to define Quality Assurance terms used.

4.1.2 Inspection.- Inspection shall be in accordance with MIL-A-2550 and as specified herein.

4.2 Inspection provisions.

4.2.1 Lot.

4.2.1.1 Submission of product.- Unless otherwise specified by the contracting officer, formation of lots and presentation of lots shall be in accordance with the "Submission of Product" provisions of MIL-STD-105.

4.2.1.2 Size of lot.- The shipping lots of metal parts assemblies shall consist of 1200 thrusters, maximum, provided the homogeneity of remanufacturing process has been retained throughout the inspection lot. A smaller lot may be shipped upon approval of the contracting officer.

4.2.2 Examination.- The roughness comparison specimens prescribed in ASA B46.1 shall be used as a basis of comparison for surface roughness determination. Four power (4X) magnification may be used in performing visual examination for such defects as burr and foreign matter.

4.2.2.1 Reclaimed parts.- Examination of reuseable parts, which require no reprocessing, shall be limited to inspection of defects that require visual type inspection. One hundred per-cent examination shall be performed for all such defects. All nonconforming parts shall be either reprocessed or rejected.

4.2.2.2 Reprocessed parts.- One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects contained herein, using the sampling plan and associated criteria in Table I and Table II. For an individual defect (single characteristic) the criteria in Table I shall be used. For total defects within a major or minor group, the criteria in Table II shall be used. All nonconforming material shall be rejected.

TABLE I

Lot Size	Sample Size	Major		Minor	
		Accept	Reject	Accept	Reject
1 - 300	100% Examination				
301 - 1300	110	1	2	2	3
1301 - 3200	150	2	3	3	4
3201 - 8000	225	3	4	4	5
8001 - 22000	300	4	5	5	6

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:52Z
Check the source to verify that this is the current version before use.

TABLE II

Total Allowable Defects Per Sample Size

Sample Sizes for Major Defects Number of Defects in Class	110	150	225	300
2 - 3	1	2	3	4
4 - 7	2	3	4	5
8 - 19	3	4	5	7
20 - 43	4	5	8	10
over 43	6	8	11	14

Sample Sizes for Minor Defects Number of Defects in Class	110	150	225	300
2 - 3	2	3	4	5
4 - 7	3	4	5	7
8 - 16	4	5	8	10
17 - 48	6	8	11	14
over 48	8	11	17	20

4.2.2.3 Key, Drawing C8593857 covering a detail of Drawing F8594747.

Defect	Method of Inspection
CRITICAL	
None defined	
MAJOR	
101. Metal defective	Visual
102. Protective finish inadequate or defective	Visual
103. Burr or sharp corner	Visual
104. Foreign matter	Visual
MINOR	
None defined	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:52Z
Check the source to verify that this is the current version before use.

4.2.2.4 Guide, Firing Pin, Drawing D8593863 covering a detail of Drawing F8594747.

Defect	Method of Inspection
CRITICAL	
None defined	
MAJOR	
101. Metal defective	Visual
102. Protective finish inadequate or defective	Visual
103. Burr or sharp corner	Visual
104. Foreign matter	Visual
MINOR	
None defined	

4.2.2.5 Pin, Firing, Drawing D8593864 covering a detail of Drawing F8594747.

Defect	Method of Inspection
CRITICAL	
None defined	
MAJOR	
101. Metal defective	Visual
102. Protective finish inadequate or defective	Visual
103. Burr or sharp corner	Visual
104. Foreign matter	Visual
MINOR	
None defined	

4.2.2.6 Body, Drawing D8594480 covering a detail of Drawing F8594747.

Defect	Method of Inspection
CRITICAL	
None defined	

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:52Z
Check the source to verify that this is the current version before use.

4.2.2.6 (Cont'd)

Defect	Method of Inspection
MAJOR	
101. Thread damaged or not full	Visual
102. Metal defective	Visual
103. Protective finish inadequate or defective	Visual
104. Burr or sharp corner	Visual
105. Foreign matter	Visual
MINOR	
None defined	

4.2.2.7 Trunnion, Drawing D8594482 covering a detail of drawing F8594747.

CRITICAL	
None defined	
MAJOR	
101. Diameter of lugs	Gage
102. Metal defective	Visual
103. Protective finish inadequate or defective	Visual
104. Burr or sharp corner	Visual
105. Foreign matter	Visual
MINOR	
None defined	

4.2.2.8 Retainer, Cartridge Drawing D8594483 covering a detail of Drawing F8594747.

CRITICAL	
None defined	
MAJOR	
101. Thread damaged or not full	Visual
102. Metal defective	Visual
103. Protective finish inadequate or defective	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:52Z
Check the source to verify that this is the current version before use.

4.2.2.8 (Cont'd)

Defect	Method of Inspection
MAJOR	
104. Burr or sharp corner	Visual
105. Foreign matter	Visual
MINOR	
None defined	

4.2.2.9 Screw, Buffer, Drawing D8594485 covering a detail of Drawing F8594747.

CRITICAL	
None defined	
MAJOR	
101. Thread damaged or not full	Visual
102. Metal defective	Visual
103. Protective finish inadequate or defective	Visual
104. Burr or sharp corner	Visual
105. Foreign matter	Visual
MINOR	
None defined	

4.2.2.10 Sleeve, End, Drawing D8594488 covering a detail of Drawing F8594747.

CRITICAL	
None defined	
MAJOR	
101. Thread damaged or not full	Visual
102. Metal defective	Visual
103. Protective finish inadequate or defective	Visual
104. Burr or sharp corner	Visual
105. Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T00:52Z
Check the source to verify that this is the currentversion before use.

4.2.2.10 (Cont'd)

Defect	Method of Inspection
MINOR	
None defined	
4.2.2.11 Head, Drawing F8594749 covering a detail of Drawing F8594747.	
CRITICAL	
None defined	
MAJOR	
101. Thread damaged or not full	Visual
102. Metal defective	Visual
103. Protective finish inadequate or defective	Visual
104. Burr	Visual
105. Foreign matter	Visual
MINOR	
None defined	
4.2.2.12 Piston, Drawing F8594750 covering a detail of Drawing F8594747.	
CRITICAL	
None defined	
MAJOR	
101. Thread damaged or not full	Visual
102. Metal defective	Visual
103. Protective finish inadequate or defective	Visual
104. Burr or sharp corner	Visual
105. Foreign matter	Visual
MINOR	
None defined	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:52Z
Check the source to verify that this is the current version before use.

4.2.2.13 Assembly, Drawing F8594747, less all component parts except Guide 8593863, Firing Pin 8593864 and O-Ring MS29513-12.

Defect	Method of Inspection
CRITICAL	
1. Protrusion of the firing pin	Gage
MAJOR	
101. Any part missing	Visual
102. Metal defective	Visual
103. Protective finish inadequate or defective	Visual
104. Burr	Visual
105. Foreign matter	Visual
MINOR	
None defined	

4.2.2.14 Metal Parts Assembly, Drawing F8594747.

CRITICAL	
None defined	
MAJOR	
101. Trunnion not free to rotate 360 degrees	Manual
102. End sleeve not free to rotate 360 degrees	Manual
103. Any part missing, except as otherwise classified	Visual
104. Improper assembly	Visual
105. Thread damaged or not full	Visual
106. Marking missing, incorrect or illegible	Visual
107. Burr	Visual
108. Foreign matter	Visual
MINOR	
201. Shipping cap or plug missing	Visual
202. Protective finish inadequate or defective	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:52Z
Check the source to verify that this is the current version before use.

4.2.2.15 Container, Fiber, Drawing C8797741.

Defect		Method of Inspection
CRITICAL		
	None defined	
MAJOR		
	None defined	
MINOR		
201.	Gap between body and cover, max.	Manual
202.	Contents loose	Manual
203.	Metal ends loose or distorted	Manual
204.	Cut or damaged through all impregnated layers	Visual

4.2.2.16 Box, Packing, Drawing C8797742.

CRITICAL		
	None defined	
MAJOR		
	None defined	
MINOR		
201.	Contents loose	Manual
202.	Hardware missing, loose, broken or improperly engaged	Manual & Visual
203.	Strapping missing, loose, broken or improperly assembled	Manual & Visual
204.	Contents of box exposed	Visual
205.	Box damaged	Visual
206.	Marking misleading or unidentifiable	Visual
207.	Number of units incorrect	Visual

4.2.3 Inspection testing.- The following tests shall be performed in accordance with the provisions of 4.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:52Z
Check the source to verify that this is the current version before use.

4.2.3.1 Hydrostatic pressure.- Each body and each head shall be subjected to an internal hydrostatic pressure. Failure of any unit to comply with the requirements of 3.3 shall be cause for rejection of the unit.

4.2.3.2 Structural strength.- Each thruster shall be subjected to the structural strength test. Failure of any thruster to comply with the requirements of 3.4 shall be cause for rejection of the thruster.

4.2.3.3 Protective finish.- The number of units for protective finish tests shall be in accordance with the applicable MIL-Standard. Failure of any sample to comply with the requirements shall be cause for rejection of the lot.

4.2.3.4 Residual magnetism.- Each assembly shall be subjected to the test for excessive residual magnetism. Failure of any unit to comply with the requirements of 3.7 shall be cause for rejection of the assembly.

4.2.4 Inspection equipment.- The examination and tests shall be made using equipment listed on IEL-8594747.

4.3 Test methods and procedures.

4.3.1 Hydrostatic pressure.- The body and head, assembled or individually, shall be subjected to an internal hydrostatic pressure in accordance with the requirements of 3.3. The testing device used shall internally seal the body and end cap, as applicable, at each end without applying any axial load other than that applied by liquid pressure. This test shall be performed prior to the application of protective finish.

4.3.2 Structural strength.- The thruster shall be subjected to the structural strength test in accordance with the requirements of 3.4. The test shall be performed in the specified fixture in conjunction with a tensile testing machine or other device.

4.3.3 Protective finish.- Test procedures for protective finish shall be in accordance with the requirements referenced on the component drawing.

4.3.4 Residual magnetism.- The assembly shall be tested for excessive residual magnetism in an area free of local magnetic effects by placing the assembly 6 inches from and at the same height as the compass, in a north-south horizontal position (head end at south) with the compass set in an east-west heading. The assembly shall be moved slowly past the compass for its entire length, rotated 90 degrees in the horizontal position about its longitudinal axis and moved slowly back past the compass. This procedure shall be repeated for each 90 degree rotation of the thruster.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:52Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking - Level A.- Packing and marking shall be in accordance with Drawings C8797741 and C8797742.

5.2 Data cards.- Data card information shall be as specified in MIL-STD-1167.

6. NOTES

6.1 Ordering data.- Procurement documents should specify the title, number and date of this specification.

6.2 A "mechanical failure" is defined as any deformation or breakage of a part, the occurrence of which is other than a design function.

6.3 When remanufacturing and loading of assembly is performed by the same facility, the requirement of 3.7 is waived and the residual magnetism performed on the loaded assembly only.

6.4 Remanufactured exterior components are as follows: Head, body, trunnion and end sleeve.

6.5 Supersession data.- This specification includes the requirements of Purchase Description FA-PD-MI-2682 dated 7 July 1965.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1377-A162

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:52Z
Check the source to verify that this is the currentversion before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

( ) DIRECT GOVERNMENT CONTRACT ( ) SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

( ) YES ( ) NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:52Z
Check the source to verify that this is the current version before use.

1 0 — CHANNEL 2

FOLD

Department of the Army

Frankford Arsenal
Philadelphia, Pa. 19137

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
Department of the Army

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-N1100
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:52Z
Check the source to verify that this is the current version before use.