METRIC

DOD-I-63274A
AMENDMENT 1
23 January 1984

MILITARY SPECIFICATION

INSERT, SCREW THREAD-THIN WALL, LOCKED IN, METRIC,

GENERAL SPECIFICATION FOR

This amendment forms a part of Military Specification DOD-I-63274A, dated 14 February 1983, and is approved for use by all Department and Agencies of the Department of Defense.

Page 3

3.3.1.2, line 2: Delete "cleaned and descaled" and substitute "cleaned, descaled and passivated".

Page 7

Table II, delete the two right hand columns in their entirety and substitute the following:

"

Minimum Shear Engagement Area mm^2	Minimum Resistance to Pullout kN
25.44	4.32
49.73	8.45
63.32	10.8
87.28	14.8
95.29	16.2
128.20	21.8
198.10	33.7
264.70	45
321.30	54.6
423.00	72
478.20	81
632.50	108
659.00	112
864.50	147

Page 13

4.6.3.2, delete in its entirety and substitute the following: "4.6.3.2 Cleaning, descaling and passivation inspection. Sample inserts shall be inspected for cleaning, descaling and passivation in accordance with ASTM A380 and 3.3.1.2."

FSC 5340

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

Custodians:
Army - AR
Navy - OS
Air Force - 99

Review activities:
Army - AV, MI
Air Force - 11
DLA - IS

User activities:
Army - ME, AT, CR
Navy - MC

Preparing activity:
Army - AR

(Project 5340-1581)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.