INCH-POUND

MIL-F-70807A (AR)
AMENDMENT 3
28 March 2001
SUPERSEDING
AMENDMENT 2
04 June 1996

MILITARY SPECIFICATION

FUZE, PD, M745
(LESS BOOSTER AND LEAD)

This amendment forms a part of MIL-F-70807A (AR), dated 25 May 1994, and is approved for use by the U.S. Army Armament Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

3.6.1.5: Delete in its entirety and substitute:

"3.6.1.5 Spring, gear latch (destructive, non-arming). With the zigzag body in the forward (up) position, the spring, gear latch shall prevent jackscrew withdrawal with 0.70 ± 0.05 psig air pressure applied to the turbine in accordance with 4.5.4.5 for at least three (3) seconds. The S & A shall have passed this test if either of the following criteria are met:

a. The jackscrew setting does not exceed 0.659 inch. This dimension applies with the zigzag locked down and the rotor assembly in the fully seated (toward the barrier) position, or

b. If the jackscrew setting exceeds 0.659 inch, the S & A shall not arm when subjected to
an air pressure of 0.206 + .000/-.006 psig for five (5) seconds minimum. This test shall be conducted with the zigzag locked down and the S & A placed in the tester of 4.4.4.1.1.

The S & A device need not be operable but shall be in the safe position following this test."

AMSC N/A FSC 1390
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:03Z
Check the source to verify that this is the current version before use.

4.4.2.1, Delete in its entirety and substitute:

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE		SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Fuze, PD, M745 (Less Booster and Lead)			11927103
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	NEXT HIGHER ASSEMBLY 11927102 / INSPECTION METHOD REFERENCE
Critical				
1	S&A in the armed position	100%	3.3	Gage/Probe
2	Premature function during ballistic test	(a)(b)	3.4	4.5.2
Major				
101	Overall length	Level III	3.3	Gage
102	Worm shaft drive and alternator shaft not engaged	Level III	3.4	Radiograph
103	Ballistic test Charge 0, 45 deg QE, 120mm, 70 F, n=18 Charge 0, 45 deg QE, 60mm, 145 F, n=18 Charge 0, 45 deg QE, 120mm, -50 F, n=18 Charge 1, 45 deg QE, 60mm, -50 F, n=18 Charge 4, 45 deg QE, 120mm, 145 F, n=18 Charge 4, 45 deg QE, 120mm, 70 F, n=18	(a)(c)	3.4	4.5.2
Minor				
201	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:
(a) After loading with boosters and leads, the fuzes shall be assembled to 60mm and 120mm cartridges and conditioned and fired as above.
(b) Any premature function shall be cause for immediate test suspension for failure analysis and lot rejection.
(c) A total of three (3) or more duds or an early function shall be cause for lot rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:03Z
Check the source to verify that this is the current version before use.

PAGE 13

4.4.2.4, M101, Change From: ...100%; To: Level II.

PAGE 35

* 4.4.2.25, Delete Minor 202 in its entirety.

PAGE 36

4.4.2.26, Major 104: Delete “gage” and substitute “visual”.

PAGE 37

4.4.2.27, Major 101: Delete "freon" and substitute "toluene".

NOTES: Delete "(a) Draw ... greater than .030 inch ... between 11.3% and 13.6% ...". and substitute "(a) Draw ... greater than .100 inch ... between 18.2% and 23.4 % ...".

PAGE 38

* 4.4.2.28:

Delete Major 102 in its entirety.

Major 103, delete “Shoulder diameter” and substitute “Outside shoulder diameter”

Minor 204, delete “204 … (3 places) … ” and substitute “ 204 … (4 places) …”

PAGE 39

4.4.2.29, Major 101: Delete “worm drive shaft gap too small” and substitute “depth of worm drive shaft too large”.

PAGE 41

* 4.4.2.31, Major 106, delete “106 … Primer cage … ” and substitute “ 106 … Detonator cage …”

PAGE 49

* 4.4.2.38, Minor 203, delete “203 Length from barrier shoulder to rear end … ” and substitute “ 203 .795 length …”

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:03Z
Check the source to verify that this is the current version before use.

PAGE 50

* 4.4.2.39:

Delete Major 107, 109 and 110 in their entirety.

Delete Minor 206 in its entirety.

Add Minor 208 as follows:

"Minor 208 Height of longer legs (2 places) …Level V … 3.3 … Gage"

PAGE 53

4.5.2, Delete in its entirety and substitute the following:

"4.5.2 Ballistic test. The fuzes shall be assembled to 60mm, HE, M720, 60mm, WP, M722, 120mm, WP, M929, 120mm, HE, M933 cartridges or 120mm, HE, M57 as appropriate and available. The rounds shall be fired as soon as practical after removal from the conditioning chamber. The round shall be fired from a 60mm, Light Weight Company Mortar System (LWCMS), M224 mortar or a 120mm, M121 Carrier mounted mortar (a 120mm M120 towed mortar (ground mount) may be used with prior approval from the Government) at appropriate quadrant elevation (QE) and charges."

The margin of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1390-0883)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:03Z
Check the source to verify that this is the current version before use.