MIL-C-50785A (AR)
AMENDMENT 1
09 October 1992

**MILITARY SPECIFICATION**

**CIRCUIT CARD ASSEMBLY, SIGHT CURRENT GENERATOR GENERAL SPECIFICATION FOR**

This amendment forms a part of MIL-C-50785A (AR), dated 15 May 1990, and iS aPPrOVed for Use by the U.s. Army Armament, Munitions, and Chemical Command, and IS available for use by all Departments and Agencies of the Department of Defense.

**PAGE 2**

2.1.1: Delete the following military specifications:

"MIL-s-45743 - 'Soldering. Manual TYPe Hi9h reliabilityt Electrical and Electronic Equipment
MIL-S-46844 - Soldering, Bath Soldering of Printed Wiring Assemblies"

2.1.2: Add the following drawing:

"12950877 - Requirements for Soldering Electrical and Electronic Assemblies"

*PAGE* **3**

3.2: Delete "e. soldering electrical connections".

3.3.1: Delete in its entirety and substitute the following:

'3.3.1 Vibration The circuit card assemblies when mounted in a normal service condition (or equivalent) shall not suffer damage and shall meet the requirements of 3.4 and 3.5 after exposure to the equivalent of 6000 miles of track-laying vehicle operational vibration as defined by MIL-STD-810 narrowband random-on-random data for equipment installed on the deck of the M113 armored personnel carrier. Normal service condition is defined by Sight Current Generator Drawing 12000239 and Isolator Drawing 10545465."



**DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.**

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:37Z
Check the source to verify that this is the current version before use.

3.3.3, 3.3.3.1 and 3.3.3.2: **Delete** in their entirety and substitute the following:

"3.3.3 Altitude operating. The circuit card assemblies shall meet the requirements of 3.4 and 3.5 during and after exposure to barometric pressure encountered at 10,000 feet above sea level (20.6 inches of Hg) ."

PAGE 4

3.7: **Delete in its entirety and substitute the following:**

"3.7 Soldering. All soldering shall be in accordance with the requirements of Note 2 of Drawing 12950877."

PAGE 9

4.7.1.1: Delete first sentence and substitute the following:

"4.7.1.1 Vibration. This test shall be performed **as** specified in Method 514, Category 8, Procedure I of **MIL-STD-810 and paragraph 3.3.1 herein."**

**4.7.1.2, first sentence: Change "516.3 to 516".**

**4.7.1.3: Delete in its entirety and substitute the following:**

**4.7.1.3 Altitude operating. This test shall be performed as specified** in Procedure II, Method 500 of **MIL-STD-810. The operational checkout shall be as specified in 4.7.2 and 4.7.3 for compliance with 3.3.3."**

PAge **10**

4.7.1.4.1, first sentence: Change "501.2" to "501".

4.7.1.4.2, first sentence: Change "502.2" to "502".

4.7.1.5, first sentence: Change ● 507.2' to '507'.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:37Z
Check the source to verify that this is the current version before use.

Add new paragraph 4.8 as follows:

"4.8 Soldering. Soldering processes shall be inspected by certified inspectors to the requirements and acceptance criteria of Note 2 of Drawing 12950877 as specified in paragraph 3.7."

Custodian:
Army-AR

Preparing activity:
Army

(Project 1285-A857)



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:37Z
Check the source to verify that this is the current version before use.