MILITARY SPECIFICATION
INITIATOR, PROPELLANT ACTUATED, DELAY, M113
ASSEMBLY

This amendment forms a part of Military Specification MIL-I-50714(MU), 7 May 1971.

Paragraph 3.5 delete and substitute:

"3.5 The assembled initiator, less the firing mechanism shall withstand 14 PSI internal-external pressure differential with a maximum permissable leak rate of 1 x 10^{-4} cubic centimeters per seconds."

Paragraph 4.3.2 delete Table II and substitute:

TABLE II

		Major		Minor	
Lot Size	Sample Size	Accept	Reject	Accept	Reject
1- 300	100% examination	-	-	-	-
301- 800	50	0	1	1	2
801- 1,800	90	1	2	2	3
1,801-10,000	200	2	3	3	4

Paragraph 4.2.3.4.1, line 3 delete "4.3.3.1.1" and substitute "4.3.4.1.1".

Paragraph 4.3.4.1, line 4 delete "4.3.3.1.1" and substitute "4.3.4.1.1".

Add the following new paragraph:

6.4 Storage and Shipping Information

Explosive Hazard Classification - Class I
Storage Compatibility - Group B, E, or N
Department of Transportation (DOT) Hazard - Class C
DOT Marking - "Explosive Power Device - Class C- Handle Carefully, Keep Fire Away"

Custodian:

Army - MU

Preparing activity:

Army - MU(FA)

Project No. 1377-A493

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:35Z
Check the source to verify that this is the currenversion before use.