MILITARY SPECIFICATION

CARTRIDGES, PERCUSSION AND ELECTRIC PRIMED, 20-MM FOR GUNS, M3, M24, AND M24A1

This amendment forms a part of Military Specification MIL-C-11255A, 31 January 1952, and has been approved by the Departments of the Army, the Navy and the Air Force.

Page 1, paragraph 1.2: Delete and substitute:

"**1.2 Classification.**—Cartridges shall be of the following grades, as specified (see 6.1):

Grade A—Cartridges which contain a minimum allowable percentage of defectives (visual, dimensional, and firing defects) and the required ballistic quality.

Grade B — Cartridges which contain a greater allowable percentage of defectives than grade A; or which fail to comply with grade A requirements upon first submission for acceptance but meet grade B requirements (except that grade A cartridges may be retested for dry velocity, wet velocity, and pressure, without penalty with respect to grade provided retest complies with requirements); or which fail to comply with grade B requirements upon first submission but meets acceptance requirements upon retest.

Page 1, paragraph 2.1:

List of Military specifications: Add:

"MIL-C-20367—Case, Cartridge, Brass, M21A1, for 20-mm. Hispano Gun 1A1."

List of U. S. Army specifications: Delete:

"50 - 46 - 2 — Case, Cartridge, Brass, M21A1, for 20-mm. Hispano Gun 1A1."

List of drawings, arms and equipment: Delete:

"FB - 22278 — Gage, Airspace, Small Arms Ammunition," and substitute:

"FB - 22274 — Gage, Airspace, Small Arms Ammunition."

Page 5, paragraph 3.3: Delete and substitute:

"**3.3 Projectile extraction.**—The force required to extract the projectile from case shall be not less than 1200 pounds nor more than 2000 pounds. Of the sample tested as specified in 4.3, not more than one cartridge shall require a force of less than 1000 pounds to extract the projectile from the case."

Page 5, paragraph 3.5: Delete and substitute:

"**3.5 Waterproofing.**—The average velocity of the cartridge after submergence in water as specified in 4.5 shall not vary from the average velocity of the same lot by more than 100 feet per second. Failure to meet the requirements shall not be counted against the cartridge, as the results are for information purposes only to check waterproofing."

Page 5, paragraph 3.6: Delete and substitute:

"**3.6 Pressure.**—The maximum chamber pressure shall not exceed 46,000 p.s.i. The maximum average chamber pressure plus three standard deviations shall not exceed 53,000 p.s.i."

270718—53—(98)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:47Z
Check the source to verify that this is the current version before use.

Page 5, table II: Delete and substitute:

TABLE II—*Basic velocity and standard deviation.*

Cartridge	Basic velocity ±50 f.p.s.	Standard Deviation
Armor Piercing Tracer, M95	2680	40
Electric, Armor Piercing Tracer, M95	2680	40
Incendiary, M96	2710	40
Electric, Incendiary, M96	2710	40
High Explosive Incendiary, M97	2680	40
Target Practice, M99	2680	40
Armor Piercing Incendiary (T21E1), M330	2670	40
Elecric Armor Piercing Incendiary (T21E1) M330	2670	40

Page 6, paragraph 3.7: Delete and substitute:

"3.7 Accuracy.—The average of the figures of merit of all targets obtained at 600 yards shall not exceed 30.0 inches. For ranges less than 600 yards, the average of the figures of merit shall not exceed that proportion of 30.0 inches that the range bears to 600 yards."

Page 6, paragraph 3.12, line 3: Delete "0.002 second" and insert "0.005 second."

Page 7, paragraph 4.1.2.4: Add: "Retests shall consist of twice the number of cartridges shown in table IV."

Page 8, paragraph 4.9: Add: "(For photographs of incendiary flashes see group IV, Drawing D769129.)"

Custodians:
Army—Ordnance Corps
Navy—Bureau of Ordnance
Air Force

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:47Z
Check the source to verify that this is the current version before use.