MIL-C-11263B(MU)
5 August 1969
SUPERSEDING
MIL-C-11263A (CmlC)
23 January 1957

MILITARY SPECIFICATION

CARRIER, FIELD PROTECTIVE MASK, M11

1. SCOPE

1.1 This specification covers one type of protective mask carrier.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

QQ-S-781 - Steel, Strapping, Flat.
TT-W-00572 - Wood Preservative, Water-Repellent.
CCC-C-419 - Cloth, Cotton, Duck, Unbleached, Plied-Yarns, (Army and Numbered).
PPP-B-621 - Boxes; Wood, Nailed and Lock Corners.
PPP-B-636 - Box, Fiberboard.

MILITARY

MIL-B-2427 - Boxes, Ammunition Packing; Wood, Nailed.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

FSC 4240

Source: https://assist.dla.mil -- Downloaded: 202610-17T15:47Z
Check the source to verify that this is the current version before use.

DRAWINGS

US ARMY MUNITIONS COMMAND

EDGEWOOD ARSENAL

DL5-4-313 - Carrier, Field Protective Mask, M11.
D150-2-1 - Marking Diagram for Shipping Containers.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies of these ratings, rules and regulations should be addressed to Uniform Classification Committee, 202 Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606.)

AMERICAN TRUCKING ASSOCIATIONS, INC.

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., 1616 P Street, N. W., Washington, D. C. 20036.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Reinforcing strip (Dwg. B5-4-321). When rubber-coated duck is used for the reinforcing strip it shall consist of 7.90 ounces (oz.), minimum, per square yard (sq. yd.) undyed cotton army duck conforming to CCC-C-419, coated approximately the same on both sides with a cured natural or synthetic rubber compound. The coated duck shall have a minimum weight of 21 oz. per sq. yd. and shall not be tacky to the touch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:47Z
Check the source to verify that this is the current version before use.

3.1.2 Other components. All other materials and components used in the manufacture and assembly of the carrier shall conform to the specifications and drawings forming a part of this specification.

3.2 Manufacture and assembly. The components and subassemblies of the carrier shall be manufactured and assembled as specified on Drawing D5-4-313 and subsidiary drawings listed thereon.

3.3 Stitching. All rows of stitching shall be straight or regular lines, free from loose stitches or thread loops. When stitching is not of continuous thread, each thread end or break shall be backstitched (whenever practicable) for not less than 2 inches. All seams and hems shall be backstitched at the ends to prevent raveling. The stitching shall be reinforce where and as indicated on the respective drawings.

3.4 Fastener attachment. The male and female components of all fastener shall be securely attached to the carrier in such a manner that the pressur used neither weakens nor injures the fabric.

3.5 Preproduction. Prior to the start of regular production a preproduction lot of carriers shall be produced for inspection in accordance with 4.3.

3.6 Marking. The finished carrier shall be legibly and indelibly marked as specified on Drawing D5-4-314.

3.7 Workmanship. The carrier shall be free from damage such as tears, cuts, and holes. It shall be free from foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5, for which specific inspection has not been provided in this specification, have been satisfied.

Source: https://assist.dla.mil -- Downloaded: 202610-17T15:47Z
Check the source to verify that this is the currentversion before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Preproduction inspection (see 4.3).

(b) Quality conformance inspection (see 4.4).

4.3 Preproduction inspection.

4.3.1 Sample. A preproduction sample of 25 carriers shall be produced using the same methods, materials, and equipment as will be used during regular production.

4.3.2 Inspection procedure. The preproduction sample shall be inspected for all the requirements of the drawings and this specification.

4.3.3 Acceptance/rejection criteria. The preproduction sample shall comply with all the requirements of this specification to be acceptable.

4.4 Quality conformance inspection.

4.4.1 Lotting. A lot shall consist of the carriers produced by one manufacturer, at one plant, from the same type of material, under essentially the same manufacturing conditions, and offered for acceptance at one time.

4.4.2 Sampling. Sampling shall be conducted in accordance with MIL-STD-105.

4.4.3 Inspection procedure. The sample carriers shall be inspected in accordance with the classification of defects and with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:47Z
Check the source to verify that this is the current version before use.

4.4.3.1 Classification of defects.

(a) Carrier, field protective mask, M11 (Dwg. D5-4-313)

Categories		Defects
Critical:		None defined
Major:	AQL 1.0 percent defective	
101		Inability of carrier to properly contain all contents
102		Damage
103		Harness incorrect, or located or attached incorrectly
104		Marking incorrect
105		Hardware incorrect, nonfunctioning, or located or attached incorrectly
106		Contamination (grease or oil)
Minor:	AQL 2.5 percent defective	
201		Seams turned incorrectly
202		Stitching incorrect
203		Reinforcing missing, incorrect, or located incorrectly
204		Stiffener missing, incorrect, or located incorrectly
205		Pocket, bottom or side, incorrect, or located or attached incorrectly (not affecting functioning)
206		Anti-dim strap incorrect, or located or attached incorrectly (not affecting functioning)
207		Hardware coating missing, inadequate or incorrect
208		Marking missing or illegible
209		Contamination (other than 106)

5. PREPARATION FOR DELIVERY.

5.1 Packing, level A. Fifty carriers shall be packed within a class 2, style 2, 2 1/2, or 4 nailed wood box, conforming to PPP-B-621. The box shall be closed and strapped in accordance with the appendix of the box specification. Strapping conforming to type I, class B of QQ-S-781, shall be used. The box and the finished wood parts thereof, shall be completely immersed for a minimum of three minutes in a water repellent wood preservation conforming to composition A of TT-W-00572 and then dried. Prior to packing the items in the box, the treated wooden box shall meet the preservative dryness requirement specified in MIL-B-2427.

5.1.1 Packing, level B. Fifty carriers shall be packed within a style RSC, fiberboard box conforming to V3C of PPP-B-636. The box shall be closed and sealed in accordance with the appendix thereto.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:47Z
Check the source to verify that this is the current version before use.

5.1.2 Packing, level C. Carriers shall be packed to insure carrier acceptance and safe delivery to the first domestic destination. Shipping containers shall be in compliance with Uniform Freight Classification rules or National Motor Freight Classification rules.

5.3 Marking. In addition to any special marking required by the contract or order, unit packages shall be marked in accordance with MIL-STD-129. Shipping containers shall be marked in accordance with D150-2-1. All markings on the shipping containers shall be clear, legible and permanent after the application of the wood preservative specified in 5.1.

6. NOTES

6.1 Intended use. This carrier is intended for use with the M9A1 Protective Mask.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Selection of applicable level of packing.
( )
(d) Preproduction.

(1) Time allowed for supplier submission of samples for Government test and evaluation after award of contract.
(2) Name and address of test facility and shipping instructions when testing is performed by the Government.
(3) Time required for the Government to notify the supplier whether or not to proceed with production.

Custodians:

Army - MU

Preparing activity:

Army - MU(EA)

Project No. 4240-A398

Source: https://assist.dla.mil -- Downloaded: 202640-17T15:47Z
Check the source to verify that this is the current version before use.

TO DETACH FORM - CUT ON THIS LINE

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 202640-17T15:47Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

OFFICIAL BUSINESS

Commanding Officer
Edgewood Arsenal
ATTN: SMUEA-QAES
Edgewood Arsenal, Maryland 21010

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:47Z
Check the source to verify that this is the current version before use.