MIL-C-11272/11A
7 January 1970
SUPERSEDING
MIL-C-11272/11
10 August 1960

MILITARY SPECIFICATION

CAPACITORS, FIXED, GLASS DIELECTRIC,

STYLE CY31

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

INACTIVE FOR DESIGN AFTER DATE OF THIS SPECIFICATION. USE MIL-C-23269.

1. SCOPE

1.1 This specification covers the detail requirements for style CY31, axial-radial lead, glass-dielectric (vitreous enamel), fixed capacitors.

2. APPLICABLE DOCUMENTS

2.1 The following document, of the issue in effect on date of invitation for bids or request for proposal, forms a part of this specification to the extent specified herein.

SPECIFICATION

MILITARY

MIL-C-11272 Capacitors, Fixed, Glass Dielectric, General Specification for.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)


3. REQUIREMENTS

3.1 **Requirements.** Requirements shall be in accordance with MIL-C-11272, and as specified herein.

3.2 **Design and construction.** Capacitors shall be of the design, construction, and physical dimensions specified on figure and in table I.

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:51Z
Check the source to verify that this is the current version before use.



INCHES	MM	INCHES	MM	INCHES	MM	INCHES	MM
.001	.03	.031	.79	.062	1.57	.700	17.78
.004	.10	.037	.94	.156	3.96	.797	20.24
.015	.38	.040	1.02	.219	5.56	.812	20.62
						1.125	28.58

NOTES:
1. Dimensions are in inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
3. The lead diameter shall be $.037\ ^{+.004}_{-.001}$ for capacitance values below 2200 pF, and $.040\ ^{+.004}_{-.001}$ for capacitance values above 2000 pF.
4. For any value above 2000 pF, this dimension shall be $.219\ ^{+.062}_{-.031}$.

Style CY31 capacitors.

Source: https://assist.dla.mil -- Downloaded: 202610-17T15:51Z
Check the source to verify that this is the current version before use.

TABLE I. *Style CY31.*

Type designation 1/	Capacitance	DC rated voltage	Capacitance tolerances available
	pF	*volts*	*(±)*
CY31C112-	1,100	500	FGJ
CY31C122-	1,200	500	FGJ
CY31C132-	1,300	500	FGJ
CY31C152-	1,500	500	FGJ
CY31C162-	1,600	500	FGJ
CY31C182-	1,800	500	FGJ
CY31C202-	2,000	500	FGJ
CY31C222-	2,200	500	FGJ
CY31C242-	2,400	500	FGJ
CY31C272-	2,700	500	FGJ
CY31C302-	3,000	500	FGJ
CY31C332-	3,300	500	FGJ
CY31C362-	3,600	300	FGJ
CY31C392-	3,900	300	FGJ
CY31C432-	4,300	300	FGJ
CY31C472-	4,700	300	FGJ
CY31C512-	5,100	300	FGJ
CY31C562-	5,600	300	FGJ

1/ Complete type designation will include an additional letter symbol to indicate capacitance tolerance.

3.3 Life.

3.3.1 *For qualification inspection.* Capacitors shall meet the following requirements, as applicable:

(a) At 25°C:
  (1) Insulation resistance – 100,000 megohms or 100 ohmfarads, whichever is less.
  (2) Dissipation factor – Shall not exceed 0.002.
(b) At 125°C:
  (1) Insulation resistance – 10,000 megohms or 10 ohmfarads, whichever is less.
  (2) Dissipation factor – Shall not exceed 0.003.

3.3.2 *For quality conformance inspection.*

3.3.2.1 *Performance check.* Capacitors shall meet the following requirements:

(a) Insulation resistance – 100,000 megohms or 100 ohmfarads, whichever is less.
(b) Dissipation factor – Shall not exceed 0.002.

3.4 Quality factor (Q). The Q shall be not less than 2,000.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:51Z
Check the source to verify that this is the current version before use.

3.5 Temperature coefficient and capacitance drift. The temperature coefficient and capacitance drift shall be within the limits specified in table II.

TABLE II. *Temperature coefficient and capacitance drift.*

Temperature coefficient	Capacitance drift (-55° to +125°C)
Parts/million/°C 105 ± 25	0.1 percent or 0.1 pF, whichever is greater.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection shall be in accordance with MIL-C-11272.

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery shall be in accordance with MIL-C-11272.

6. NOTES

6.1 Notes. In addition to the notes specified herein, the notes specified in MIL-C-11272 are applicable to this specification.

Custodians:
Army – EL
Navy – EC
Air Force – 11

Review activities:
Army – EL
Navy – EC, SH
Air Force – 11, 17, 85
DSA – ES

User activities:
Army –
Navy –
Air Force – 19

Preparing activity:
Air Force – 11

Agent:
DSA – ES

(Project 5910-0994-12)

Source: https://assist.dla.mil -- Downloaded: 202610-17T15:51Z
Check the source to verify that this is the currentversion before use.