MIL-C-52128C
AMENDMENT 2
8 April 1982
SUPERSEDING
INT. AMENDMENT l(ME)
12 May 1981

MILITARY SPECIFICATION

CRUSHER, JAW, DIESEL-ENGINE AND ELECTRIC-MOTOR-DRIVEN,

75-TON-PER-HOUR CAPACITY

This amendment forms a part of Military Specification MIL-C-52128C, dated 26 June 1980, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Under SPECIFICATION, MILITARY, add:

"MIL-B-52919 - Belts, V: Industrial Drive, Narrow Type.

MIL-E-52929 - Enamel, Alkyd, Camouflage, Flash Dry."

Under STANDARDS, MILITARY, delete, "MIL-STD-100" and substitute "DOD-STD-100", "delete MIL-STD-423 and MIL-STD-424".

PAGE 5

Under AMERICAN NATIONAL STANDARDS INSTITUTE, INC., delete: "B55.1 - Specification for Multiple V-Belt Drives." and add:

"B29.3 - Double-Pitch Power Transmission Roller Chains and Sprockets."

PAGE 6

Delete:

"RUBBER MANUFACTURERS ASSOCIATION, INC.

Engineering Standard, Specification for Drives Using Narrow V-Belts (3V, 5V, and 8V Cross Sections).

(Application for copies should be addressed to the Rubber Manufacturers Association, Inc., 444 Madison Avenue, New York, NY 10022)."

FSC 3820

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:08Z
Check the source to verify that this is the current version before use.

PAGE 9

3.5, line 4, delete "MIL-STD-100" and substitute "DOD-STD-100."

PAGE 1 0

After 3.8.1.4 add new paragraph:

* "3.8.1.5 Oil sampling valve. An oil sampling valve shall be provided on the engine. The valve shall be manually operated and shall automatically close after release. It shall be made of material resistant to corrosion such that it will not contaminate the sample. The discharge port of the valve shall be covered with a captive chained cap conforming to SAE J514. The valve shall be located in such a way as to insure that personnel will not be exposed to danger when taking oil samples with the engine running. The location of the oil tap shall be such that when samples are taken, it shall be a true representation of oil that is flowing while the engine is running."

PAGE 13

3.9.1, delete entirely and substitute;

"3.9.1 Chain drives. Unless otherwise specified herein, chains and sprockets used in drive trains shall be in accordance with ANSI B29.1 or ANSI B29.3, as applicable. Chain drives shall be installed with idlers and other methods for providing adjustment."

PAGE 31

3.25, line 3, delete "color as specified" and substitute "Unless otherwise specified (see 6.2), the final coat shall be lusterless forest green in accordance with MIL-E-52929. "

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - ME

Preparing activity:
Army - ME

Review activities:
Army - AT
DLA – CS

Project 3820-0172

User activity:
Navy - MC

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:08Z
Check the source to verify that this is the current version before use.