MILITARY SPECIFICATION

DITCHING MACHINE: DIESEL-ENGINE-DRIVEN;

WHEEL-MOUNTED; LADDER

Page 3

2.1, under STANDARDS, Military, add:
"MIL-STD-209 - Slinging Eyes and Attachments for Lifting and Tying Down Military Equipment."

Page 17

3.11, lines 8 through 11, delete the sentence: "The temperature rise. . . . . during all operations specified herein."

Page 19

3.11.9, lines 1 through 4, delete the first sentence "The reservoir . . . . . plate requirements." and substitute "The reservoir shall conform to MIL-R-52602 except for the requirements for materials, suction port, return port, air vent, instruction plate, filling method; and the level indicator may be either visual- or dipstick-type."; line 7, delete "consist of" and substitute "include".

Page 25

3.15, lines 3 and 4, delete "stationary and moving conditions:" and substitute "conditions, as well as the moving conditions indicated in J919:".

Page 32

3.20.9, line 2, delete "batteries" and substitute "starting motor".

Page 38

3.24, line 5, after "specified in 4.6.2.10" change the period to a comma and add: "and shall comply with the static load and dimensional requirements of MIL-STD-209."

3.25, lines 3 and 4, delete "photographic plate." and substitute "style 1, composition C, of type I, grade A, class 1 material."; line 5, delete "photographic plate," and substitute "composition C, of type I, grade A, class 1 material,".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:07Z
Check the source to verify that this is the current version before use.

3.26, line 4, delete "photographic plate." and substitute "composition C, of type I, grade A, class 1 material."

Page 40

3.33, line 4, delete "or a varnish having a" and substitute "with".

Custodian:

Army - ME

Preparing activity:

Army - ME

Project No. 3805-A062

☆ U. S. GOVERNMENT PRINTING OFFICE: 1971-433-699/7726

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:07Z
Check the source to verify that this is the current version before use.