MILITARY SPECIFICATION

PUMPING ASSEMBLY, LIQUID BULK TRANSFER, DIESEL-ENGINE-DRIVEN,

350 GPM CAPACITY, 275 TOTAL HEAD, WHEEL MOUNTED

This amendment forms a part of MIL-P-52144E(ME), dated 4 June 1985, and is approved for use within the USA Belvoir Research, Development, and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 14

4.5.2.2, table I, line 1, column 2 delete "X" and substitute "-" for individual pump testing.

PAGE 20

5.2, delete in its entirety and substitute the following:

"5.2 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2). Preservatives applied to the interior surfaces of the pump, connecting components and any other surface that normally contacts the liquid being transferred, shall be harmless should their residual material, after evaporation, be inadvertently ingested by personnel."

5.2.1, delete in its entirety and substitute the following:

"5.2.1 Level A. Preservatives identified herein by "P" numbers shall conform to the corresponding symbols and applicable specifications in MIL-P-116."

5.2.1.3, delete the first sentence in its entirety and substitute the following:

"The pump shall be drained and dried. Interior surfaces of the pump and connecting piping shall then be coated with type P-14 preservative."

5.2.1.4, add the following sentence at the end of the paragraph:

"Engines with liquid cooling systems shall have the cooling system preserved by the water and antifreeze procedure as specified therein."

Custodian:
Army - ME

Preparing activity:
Army - ME

Review activity:
DLA - CS

Project 4320-A267

AMSC N/A

FSC 4320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:08Z
Check the source to verify that this is the current version before use.