MIL-P-52144E(ME)
AMENDMENT 2
28 March 1988
SUPERSEDING
AMENDMENT 1
16 April 1987

MILITARY SPECIFICATION

PUMPING ASSEMBLY, LIQUID BULK TRANSFER, DIESEL-ENGINE-DRIVEN,

350 GPM CAPACITY, 275 TOTAL HEAD, WHEEL MOUNTED

This amendment forms a part of MIL-P-52144E(ME), dated 4 June 1985, and is approved for use within the USA Belvoir Research, Development, and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 10

* 3.27, add the following new sentence at the end of the paragraph:

"Top coat in accordance with MIL-C-46168 shall not be applied to engine manifolds, exhaust pipes, mufflers and other parts subject to high temperatures."

PAGE 14

4.5.2.2, table I, line 1, column 2 delete "X" and substitute "-" for individual pump testing.

PAGE 20

5.2, delete in its entirety and substitute the following:

"5.2 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2). Preservatives applied to the interior surfaces of the pump, connecting components and any other surface that normally contacts the liquid being transferred, shall be harmless should their residual material, after evaporation, be inadvertently ingested by personnel."

AMSC N/A FSC 4320

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:08Z
Check the source to verify that this is the current version before use.

5.2.1, delete in its entirety and substitute the following:

"5.2.1 Level A. Preservatives identified herein by "P" numbers shall conform to the corresponding symbols and applicable specifications in MIL-P-116."

5.2.1.3, delete the first sentence in its entirety and substitute the following:

"The pump shall be drained and dried. Interior surfaces of the pump and connecting piping shall then be coated with type P-14 preservative."

* Line 5, delete "left open" and substitute "closed".

* 5.2.1.4, add the following sentences at the end of the paragraph:

"Engines with liquid cooling systems shall have the cooling system preserved by the water and antifreeze procedure as specified therein. See 5.2.1.11 for alternate fuel tank interior treatment."

PAGE 21

* After paragraph 5.2.1.10, add the following new paragraph:

"5.2.1.11 Fuel tank. The interior of fuel tanks shall be treated with rust-preventing fog oil conforming to MIL-L-21260, grade 30, prior to the airtight sealing of all fuel tank openings in preparation for shipment or storage."

The margins of the amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletion) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - ME

Preparing activity:
Army - ME

Review activity:
DLA - CS

Project 4320-A283

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:08Z
Check the source to verify that this is the current version before use.