INCH-POUND

MIL-P-52144E(ME)
AMENDMENT 3
31 October 1994
SUPERSEDING
AMENDMENT 2
28 March 1988

MILITARY SPECIFICATION

PUMPING ASSEMBLY, LIQUID BULK TRANSFER, DIESEL-ENGINE-DRIVEN,

350 GPM CAPACITY, 275 TOTAL HEAD, WHEEL MOUNTED

This amendment forms a part of MIL-P-52144E(ME), dated 4 June 1985, and is approved for use within the USA Belvoir Research, Development, and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 1.2, delete in its entirety and replace with the following:

"1.2 Classification. Pumping assemblies shall be of the following types and styles, as specified (see 6.2, and 6.10):

Type I - Pumping Assembly, POL.

Style A - Without regulator (TA13229E8400).
Style B - With Regulator (TA13229E8402).

Type II - Pumping Assembly, Water (TA13229E8401)."

* 2.1.1, Under SPECIFICATIONS, FEDERAL, delete:

"QQ-S-781 - Strapping, Steel, and Seals."

PAGE 2

* 2.1.1, Under SPECIFICATIONS, MILITARY, delete the following "MIL-G-1086" and "MIL-I-20241" in their entirety.

* Under SPECIFICATIONS, MILITARY, add the following:

"MIL-R-6855 - Rubber, Synthetic, Sheets, Strips, Molded or Extruded Shapes, General Specification for."
"MIL-I-24391 - Insulation Tape, Electrical, Plastic, Pressure-Sensitive."

AMSC N/A FSC 4320
DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:08Z
Check the source to verify that this is the current version before use.

PAGE 3

* 2.1.2, under DRAWINGS, ME, delete in their entirety and replace with the following:

"TA13229E8400 - Pumping Assembly, POL, 4 Inch, Diesel-Engine-Driven, 350 GPM Capacity, 275 Ft. Total Head, Wheel Mounted, Noise Enclosed.
TA13229E8402 - Pumping Assembly, POL, 4 Inch, Diesel-Engine-Driven, 350 GPM Capacity, 275 Ft. Total Head, Wheel Mounted, Noise Enclosed with Regulator.
TA13229E8401 - Pumping Assembly, Water, 4 Inch, Diesel-Engine-Driven, 350 GPM Capacity, 275 Ft. Total Head, Wheel Mounted, Noise Enclosed."

2.2, Under AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM), add the following:

"D 3953 - Specification for Strapping, Flat Steel and Seals."

PAGE 4

* 3.1, lines 4 and 5, delete "TA13220E1070, TA13226E2289, or TA13225E9200" and replace with "TA13229E8400, TA13226E8402, or TA13229E8401".

PAGE 5

* 3.4, delete paragraph in its entirety and replace with the following:

"3.4 Gaskets. All cork and rubber composition gaskets shall conform to MIL-C-6183, type optional, class I, grade B, except that the gasket between the intermediate and pump volute and the gasket on which the discharge check valve seats, shall be synthetic rubber conforming to MIL-R-6855, class I. Synthetic rubber gasket material shall meet all the requirements of MIL-R-6855, class I."

* 3.5, delete the first sentence and replace with "Unless otherwise specified, all threaded fasteners shall be steel and zinc coated in accordance with MIL-STD-171, finish 1.9.2.3."

PAGE 10

3.27, add the following new sentence at the end of the paragraph: "Top coat in accordance with MIL-C-46168 shall not be applied to engine manifolds, exhaust pipes, mufflers and other parts subject to high temperatures."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:08Z
Check the source to verify that this is the current version before use.

PAGE 12

4.4.1, delete in its entirety and replace with the following:

"4.4.1 Sampling. sampling for examination and tests shall be in accordance with MIL-STD-105. Sample size shall be determined by using MIL-STD-105, table I and table IIa. A lot shall be accepted when zero defects are found and rejected when one or more defects are found."

* 4.4.2, delete the last sentence and replace with the following: "Presence of one or more defects shall be cause for rejection."

* 4.4.3.2, delete the last sentence and replace with the following: "Failure of any test shall be cause for rejection."

PAGE 14

4.5.2.2, table I, line 1, column 2 delete "X" and substitute "-" for individual pump testing.

PAGE 19

* 4.7.2.2, delete in its entirety and replace with the following:

"4.7.2.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105. Sample size shall be determined by using MIL-STD-105, table I and table IIa. A lot shall be accepted when zero defects are found and rejected when one or more defects are found."

* 4.7.2.3, delete the last sentence and replace with the following: "Presence of one or more defects shall be cause for rejection."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:08Z
Check the source to verify that this is the current version before use.

5.2, delete in its entirety and replace with the following:

"5.2 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2). Preservatives applied to the interior surfaces of the pump, connecting components and any other surface that normally contacts the liquid being transferred, shall be harmless should their residual material, after evaporation, be inadvertently ingested by personnel."

5.2.1, delete in its entirety and replace with the following:

"5.2.1 Level A. Preservatives identified herein by "P" numbers shall conform to the corresponding symbols and applicable specifications in MIL-P-116."

5.2.1.3, delete the first sentence in its entirety and replace with the following: "The pump shall be drained and dried. Interior surfaces of the pump and connecting piping shall then be coated with type P-14 preservative."

Line 5, delete "left open" and substitute "closed".

5.2.1.4, add the following sentences at the end of the paragraph: "Engines with liquid cooling systems shall have the cooling system preserved by the water and antifreeze procedure as specified therein. See 5.2.1.11 for alternate fuel tank interior treatment."

* 5.2.1.10, delete in its entirety and replace with:

"5.2.1.10 Other components. Components removed that will not fit in the toolbox shall be secured to the pump in a protected location that will not increase cubage or interfere with lifting or towing of the pump. Components shall be secured using soft annealed wire or strapping conforming to ASTM D3953, type 1 or type 2, size as applicable. Finish of strapping shall be zinc coated, grade optional."

After paragraph 5.2.1.10, add the following new paragraph:

"5.2.1.11 Fuel tank. The interior of fuel tanks shall be treated with rust-preventing fog oil conforming to MIL-L-21260, grade 30, prior to the airtight sealing of all fuel tank openings in preparation for shipment or storage."

* 5.3.1, delete the fifth, sixth and seventh sentences and replace with:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:08Z
Check the source to verify that this is the current version before use.

"The straps shall conform to ASTM D3953, Type 1 or 2, size as applicable. Finish of strapping shall be zinc coated, grade optional."

PAGE 22

* 6.2.j, delete in its entirety.

PAGE 23

Add the following new paragraph:

* "6.10 Superseding data. This specification covers two types and two styles of pumping assemblies which have been updated to include noise enclosures. The old pumping assemblies will only be used as follows:

"Type I - Pumping Assembly, POL

Style A (TA13220E1070)-
Inactive for new design, use for procurement of repair parts only.

Style B (TA13226E2289)-
Inactive for new design, use for procurement of repair parts only.

Type II - Pumping Assembly, Water

(TA13225E9200)-
Inactive for new design, use for procurement of repair parts only."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - ME

Preparing activity:
Army - ME

Review activity:
DLA - CS

Project 4320-A377

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:08Z
Check the source to verify that this is the current version before use.