MILITARY SPECIFICATION

TRAINING AID, PERSONAL DECONTAMINATION KIT

This amendment forms a part of MIL-T-51469B(EA), dated 9 October 1986, and is approved for use within the Chemical Research, Development and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

3.3 and 3.4: Delete in their entirety.

PAGE 4

3.14: Delete in its entirety.

3.15: Change title from "Ampoule screen" to "Tube glass screen".

Add new paragraph 3.17 as follows:

"3.17 Decon 2 packet solution content. The pad in the decon 2 packet shall contain 3.6 to 5.2 g of a solution consisting of 12 ± 2 percent by weight 2-propanol conforming to TT-I-735, with the remainder water conforming to Drawing 5-77-2267 when tested as specified in 4.4.4.12."

PAGE 5

4.3.2.2, Table I Preproduction Inspection:

Delete the requirements for "Ampoule leakage," "Ampoule Fill" and "Ampoule Tip" in their entirety.

Add a new requirement as follows:

Requirement: "Decon 2 packet solution content (3.17)"
Sample size: "10 (1 per kit)"
Accept/reject criteria: "Acc 0, Rej 1"
Test paragraph: "4.4.4.12"

AMSC N/A FSC 6910

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:01Z
Check the source to verify that this is the current version before use.

Change title of requirement for "Ampoule screen" to "Tube glass screen".

Delete "***Same sample packets used for ampoule leakage test may be used."

PAGE 7

Table II:

Delete the requirements for "Ampoule Leakage," "Ampoule Fill" and "Ampoule Tip" in their entirety.

Change title of requirement for "Ampoule screen" to "Tube glass screen".

Add a new requirement:

Requirement: "Decon 2 packet solution content (3.17)"
Sample size: "15, prior to assembly in training aids"
Accept/reject criteria: "Acc 1, Rej 2"
Test paragraph: "4.4.4.12"

Delete "***Same sample packets used for ampoule leakage test may be used."

PAGE 8

4.4.4.1: Delete in its entirety.

PAGE 9

4.4.4.2 and 4.4.4.9: Delete in their entirety.

4.4.4.10: Change title from "Ampoule screen" to "Tube glass screen".

Add new paragraph 4.4.4.12 as follows:

"4.4.4.12 Decon 2 packet solution content. Weigh the packet to the nearest 0.01 g. Open the packet and remove the towelette (pad) and nylon mesh with glass tubes enclosed. Place the pad, nylon mesh with glass tubes and opened packet in the air circulating oven and dry at 105° ± 2°C for 60 ± 5 minutes. Weigh the entire packet, nylon mesh with glass tubes and pad to the nearest 0.01 g. Calculate the weight of the solution on the pad as follows:

$$\text{Weight of solution} = A - B$$

where: A = Weight of packet 2 (pad, nylon mesh with glass tubes and packet) before drying, in grams, and
B = Weight of packet 2 (pad, nylon mesh with glass tubes and packet) after drying, in grams."

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:01Z
Check the source to verify that this is the current version before use.

Custodian:

Army - EA

Preparing activity:

Army - EA

(Project No. 6910-A007)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:01Z
Check the source to verify that this is the current version before use.