COMMERCIAL ITEM DESCRIPTION

BELT, ABRASIVE
(COATED CLOTH, POWER MACHINE)

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification P-B-172.

This commercial item description covers commercial and industrial quality coated abrasive cloth belts and bands for power sanding wood, metal and other materials.

Salient characteristics:

Belt tolerances

Width	Length (total inside measurement)
Under 6 inches ± 1/16	Under 40 inches ± 1/8
6 inches and over	40 to 167 inches ± 1/4
40 grit size and finer ± 1/16	168 inches and over ± 3/8
36 grit size and coarser ±	

Conditioning. Dimensions shall be measured after belts have been conditioned at least 24 hours at $75^{\circ} \pm 5^{\circ}$ F and 50 ± 2 percent relative humidity.

Backing material. The coated abrasive shall be fabricated from cotton grey cloth or synthetic cloth, waterproof or nonwaterproof as specified, conforming to the following requirements:

Minimum backing tensile breaking strength (lbs/in)

Cloth type	Warp direction	Filling direction
Jeans ("J")	90	40
Drills ("X")	130	50

Abrasive. The cloth shall be coated on one side with abrasive quality silicon carbide, aluminum oxide or garnet as specified. The abrasive grain shall contain not more than 5 percent extraneous material.

Grit sizes. Coated abrasive cloth shall be in the following grit sizes as specified:

"X" weight cloth - 400, 320, 280, 240, 220, 180, 150, 120, 100, 80, 60, 50, 40, 36, 24
"J" weight cloth - 150, 120, 100, 80, 60

Grading. The grading, control and tolerances of the abrasive grain shall be in accordance with ANSI B74.18.

Open coat. The abrasive grain shall be evenly dispursed over 50 to 70 percent of the backing surface.

Closed coat. The abrasive grain shall completely and uniformly cover the surface of the backing.

Adhesive. The making and sizing coats of adhesive shall be glue or a comparable adhesive, synthetic resin or waterproof as specified.

Bonds. The types of adhesive bonds shall be glue bond or equivalent, resin or glue or equivalent, resinbond or waterproof.

Splices. The coated abrasive belt shall be joined to form a smooth, continuous nonseparating surface under normal working conditions.

Identification. The coated abrasive belt shall be identified by:

(a) Kind of abrasive grain (generic name, trade name or identification marking).
(b) Grit size
(c) Backing weight, "X" for drills, "J" for jeans, with exception of waterproof drills
(d) Open coat identification, if applicable
(e) Belt size
(f) Directional arrow
(g) Manufacturer's name or trademark

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:11Z
Check the source to verify that this is the current version before use.

Workmanship. The abrasive belt shall be free from imperfections which may impair durability or serviceability.

The issue of ANSI B74.18 in effect on the date of the solicitation shall be used to determine compliance with this requirement.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same product sold in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Regulatory requirements. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Packaging, packing, and marking. The items shall be packaged in accordance with normal commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with the National Motor Freight Classification and Uniform Freight Classification. Shipping containers shall be marked as specified in the contract or order.

ANSI standards are available from the American National Standards Institute, 1430 Broadway, New York, NY 10018.

MILITARY INTERESTS

Military Coordinating Activity:

Air Force - 99

Custodians

Army - MR
Air Force - 99

Review Activity:

DSC - IS

User Activities:

Navy - SD, SH
Army - ME

CIVIL AGENCY COORDINATING ACTIVITY:

JFK

Preparing Activity:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:11Z
Check the source to verify that this is the current version before use.