[METRIC]

A-A-2303A
October 18, 1993
SUPERSEDING
A-A-2303
July 24, 1985

COMMERCIAL ITEM DESCRIPTION

RULER, STEEL (BUSINESS FORMS)

The General Services Administration has authorized the use of this Commercial Item Description, for all Federal agencies.

1. SCOPE:

A. This commercial item description covers a double-sided, four-edged, stainless steel, 16 inch, business form rulers. These rulers are commonly used in the layout of forms, particularly data processing forms.

2. Salient characteristics.

A. The material shall be series 300 stainless steel alloy, suitable for the purpose intended.

B. The ruler shall be of the following dimensions:

Length of ruler	41.28 ± 0.16cm (16-1/4 ± 1/16 inch)
Length of displays	See accuracy paragraph
Width of ruler	3.18 ± 0.16 cm (1-1/4 ± 1/16 inch)
Thickness of ruler	0.081 ± 0.013 cm (0.032 ± 0.005 inch)

Beneficial comments, recommendations, additions, deletions, clarification, etc. and any data which may improve this document should be sent to:

General Services Administration
Engineering Branch (2FYEE), Rm. 20-130
26 Federal Plaza
New York, NY 10278
Attn: Charles E. Smith

FSC 7510

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:21Z
Check the source to verify that this is the current version before use.

C. Required displays The four edges shall display the following scales. The order of scales shall be in accordance with the supplier's commercial practice. Incremental marking shall be at the edge to insure accuracy in use.

1/12 and 1/6 inch	0 to 16 inches
1/32 and 1/16 inch	0 to 16 inches
1/10 inch	0 to 16 inches
Metric scale	0 to 405 millimeters

D. There shall be groups of file holes in diameters of 1.11 ± 0.010 cm, (7/16 ± 0.004 inch) and 0.792 0.010 cm, (5/16 ± 0.004 inches), arranged so that the holes in the same diameters may be paired at 6.99 ± 0.010 cm, (2-3/4 ± 0.004 inches) and 10.79 ± 0.010 cm, (4-1/4 ± 0.004 inch) centers.

E. There shall be a minimum of 22 line holes 0.475 ± 0.010 cm, (3/16 ± 0.004 inches) in diameter, spaced on 1.27 ± 0.010 cm, (1/2 ± 0.004 inches) centers.

F. Additional displays, other than required herein, may appear on the rulers, so long as these additional displays are regular commercial practice.

G. The overall length of each display shall have a cumulative error of no more than +0.013 -0.025 cm, (+ 0.005 - 0.010 inch) cumulative. The individual measure between each increment on any of the displays shall be correct to ± 0.013 cm within (± 0.005 inches) .

H. All of the displays on these stainless steel rulers shall be acid-etched, black epoxy filled characters.

I. Workmanship. The finished rulers shall exhibit no evidence of jagged or rough work. The rulers shall be free from defects which may affect its serviceability, durability, and appearance.

3. Quality Assurance

A. Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the government. The Government reserves the right to perform any of the inspections set forth in the Commercial Item Description, where such inspections are deemed necessary to assure that supplies and services conform to the prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:21Z
Check the source to verify that this is the current version before use.

B. Each lot of rulers shall be inspected for conformance to the requirements herein. Sampling for inspection shall be in accordance with MIL-STD-105 using the plans specified below.

C. Visual characteristics - Inspection Level S-2 with an Acceptable Quality Level (AQL) of 4.0 percent defective. The sample unit shall be one ruler.

D. Dimensional characteristics - Inspection Level S-2 with an Acceptable Quality Level (AQL) of 4.0 percent defective. The sample unit shall be one ruler.

E. Packaging, Packing, and Marking - Inspection Level S-2 with an AQL of 4.0 percent defective. The sample unit shall be one fully prepared shipping container.

4. Preparation for delivery

Packaging, packing and marking shall be as specified in the contract or purchase order.

5. Regulatory Requirements

The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable in accordance with paragraph 23.403 of the Federal Acquisition Regulation.

6. Application for copies of technical documents referenced herein:

The issue date in effect on date of invitation for bids or request for proposal shall apply.

A. Military Specifications:

MIL-STD-105 - Sampling Procedures and Table for Inspection by Attributes.

Available from: Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094

B. Federal Acquisition Regulation:

Available from: Superintendent of Documents, Government Printing Office (GPO), Washington, DC 20402

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:21Z
Check the source to verify that this is the current version before use.

Notes:
A. Ordering Data:

Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

1) Packaging, packing and marking.

No Official DOD Interest
Has Been Registered

Preparing Activity:
GSA/FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:21Z
Check the source to verify that this is the current version before use.