INCH-POUND

A-A-2512A
May 16, 2002
SUPERSEDING
A-A-2512
April 1, 1987

COMMERCIAL ITEM DESCRIPTION

BRUSHES, WIRE, ROTARY, CUP, TWISTED TUFT

The General Services Administration has authorized the use of this Commercial Item Description by all federal agencies.

1. SCOPE. This Commercial Item Description covers brushes for use with pneumatic or electric tools in the standard or heavy-duty removal of rust, scale, paint, or burrs from all types of metal surfaces.

2. CLASSIFICATION. Unless otherwise specified brushes shall conform to the following types, classes, and styles.

2.1 Type I. Brass.
- Class 1. Threaded arbor.
- Class 2. Unthreaded arbor hole.
  - Style A. Twisted tuft, standard duty.
  - Style B. Twisted tuft, heavy duty.

2.2 Type II. Stainless Steel
- Class 1. Threaded arbor.
- Class 2. Unthreaded arbor hole.
  - Style A. Twisted tuft, standard duty.
  - Style B. Twisted tuft, heavy duty.

2.3 Type III. High carbon tempered steel.
- Class 1. Threaded arbor.
- Class 2. Unthreaded arbor hole.
  - Style A. Twisted tuft, standard duty.
  - Style B. Twisted tuft, heavy duty.



Figure 1. Type I
Twisted tuft. (Regular duty.)



Figure 2. Type II
Twisted tuft. (Heavy duty.)

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data that may improve this document should be sent to: General Services Administration, Federal Supply Service, Hardware SuperStore, 6FEE, 1500 Bannister Rd., Bldg.# 6, Kansas City, Missouri 64131.

FSC 5130

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:23Z
Check the source to verify that this is the current version before use.

3. SALIENT CHARACTERISTICS.

3.1 Design. The brushes shall be of the cup shaped design, and for use with pneumatic or electric portable grinders.

3.1.1 Body. The body shall be of steel overall and constructed in such a manner as to insure an even distribution of the wire throughout the brush to provide good balance for minimal vibration at max rated free speed R.P.M. Provisions shall be made for securely holding the fill wire in place and to prevent the wire from detaching due to flex during use or at rated free speed RPM. Where welded construction is used, the wire shall not be burned, broken, or affected in any way by the welding process.

3.1.2 Arbor. As specified the brush shall either possess a threaded arbor or an unthreaded through hole of specified size to fit a mandrel. The threaded arbor shall have a 5/8-11 NC female thread in accordance with the current version of Federal Standard H28. To minimize vibration the threaded arbor shall be mounted to the body in a manner that when brush is installed on a grinder the brush runs true. The unthreaded-hole type brush shall also have the hole centered in the brush to run true on a mandrel.

3.1.3 Style A. Standard duty tufted wire. As specified, the crimped wire shall be of brass, stainless, high carbon tempered steel of specified diameter and wire-points (density). Tufts shall consist of a single row of U-shaped fill wire passed through or around the retainer and twisted tightly to prevent untwisting during use. The regular-duty twisted tuft wire brush shall be similar to figure 1.

3.1.4 Style B. Heavy duty tufted wire. As specified, the crimped wire shall be of brass, stainless, or high carbon tempered steel of specified diameter and wire-points (density). Tufts shall consist of two rows of U-shaped fill wire passed through or around the retainer and twisted tightly to prevent untwisting during use. The heavy-duty twisted tuft wire brush shall be similar to figure 2.

3.2 Identification marking. The tool shall be marked with the Maximum Safe Free Speed, (RPM or MSFS), the words "Wear Eye Protection", the manufacturer's name or identifying symbol and the state or country of manufacture, unless otherwise specified. All identification markings shall be etched, engraved, molded, or indented directly on the item's surface in such a manner that it remains clearly legible throughout the life of the item.

3.3 Workmanship. Details of workmanship shall be in accordance with the best commercial practices. Paints, coatings, plating, and finishes shall be smooth, adherent, continuous and not stained or discolored. External surfaces shall be free of tool and gouge marks, nicks, or other surface imperfections. The item shall be free from manufacturing workmanship defects (e.g. sharp or rough external edges, corners, or surfaces) and material workmanship defects (e.g. pits, rips, fins, burrs, tears, nodules, cracks, or blisters), which may adversely impact the item's serviceability, durability, safety, or appearance.

4. REGULATORY REQUIREMENTS.

4.1 Recovered materials. The supplier/manufacturer is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4.2 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified (using conversion tables contained in the latest revision of Federal Standard 376) and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch- pound units, a request should be made to the contracting officer to determine if the product is acceptable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:23Z
Check the source to verify that this is the current version before use.

5. PRODUCT CONFORMANCE.

5.1 Safety. The brushes shall comply with American National Standards Institute (ANSI) standard B165.1-1991, Safety Requirements for the design, Care and Use of Power Driven Brushing Tools.

5.2 Product Conformance. The products provided shall meet the salient characteristics of this Commercial Item Description, conform to the supplier's own drawings, specifications, standards and quality assurance practices, and the same product and offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

5.3 Responsibility for inspection. Unless otherwise specified, the supplier is responsible for the performance of all inspection requirements and may use any commercial facilities (including the supplier's own facilities) suitable for performance of the inspection requirements, unless disapproved by the Government. The Government reserves the right to perform any inspections deemed necessary to assure the item conforms to the specified requirements.

6. PACKAGING. Requirements of preservation, packing, packaging, and marking of packages shall be as specified in the contract or order.

7. NOTES. (This section contains information of a general or explanatory nature that is not mandatory.)

7.1 Addresses for obtaining copies of referenced documents:

Federal Acquisition Regulation (FAR): Government Printing Office, Superintendent of Documents, Washington, DC 20401-9371

GSA Specification Section (3FP-E), Suite 8100, 470 L'Enfant Plaza, SW, Washington, DC, 20407.

American National Standards Institute (ANSI), Washington, DC Headquarters, 1819 L Street, NW, 6th Fl., Washington, DC, 20036

7.2 National Stock Numbers (NSNs). The following NSNs correspond to the types, classes, and styles specified in this CID. This list may not be indicative of all possible NSNs associated with this CID.

NSN	Type	Class	Style	Wire diameter (inches)	Trim length (inches)	Fill material	Wire point min.	Arbor style (inches)	Max RPM
5130-00-473-6443	III	1	B	0.0204	1-1.625	Steel	2888	5/8-11 UNC	7000
5130-00-807-3010	III	1	A	0.0204	1.375-1.875	Steel	2300	5/8-11 UNC	6000
5130-00-293-2857	III	1	A	0.014	1-1.625	Steel	5000	5/8-11 UNC	6000
5130-00-278-0822	III	1	A	0.035	1.375-1.875	Steel	1600	5/8-11 UNC	6000
5130-00-293-2504	III	1	B	0.0204	1.375-1.875	Steel	7300	5/8-11 UNC	6000
5130-00-293-2863	III	1	B	0.014	1.375-1.875	Steel	14000	5/8-11 UNC	6000
5130-00-293-2859	III	1	B	0.035	1.375-1.875	Steel	2300	5/8-11 UNC	6000
5130-00-278-6633	III	2	A	0.0204	1-1.625	Steel	2300	.500-hole	6000
5130-00-293-2860	III	1	A	0.035	1-1.625	Steel	1000	5/8-11 UNC	6000

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:23Z
Check the source to verify that this is the current version before use.

7.3 Ordering data. The contract order should specify the following (in inches):

(A) Title, number, and date of Commercial Item Description.
(B) Type, class, and style.
(C) Brush outside diameter.
(D) Wire diameter.
(E) Wire point minimum. (Wire density)
(F) Arbor size. (Threaded or unthreaded)
(F) Wire trim-length.
(G) Max RPM. (Free-speed)
(H) Preservation, packing, packaging, required.

7.4 Key words. Wire cup brushes, twisted tuft.

MILITARY INTERESTS:

NONE: DoD has no registered interest in revisions and amendments to this Commercial Description until further notice.

Preparing Activity:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:23Z
Check the source to verify that this is the current version before use.