[METRIC]
A-A-2744A
August 18, 1993
SUPERSEDING
A-A-2744
October 22, 1991

COMMERCIAL ITEM DESCRIPTION

RAZOR, SAFETY, DISPOSABLE

The General Services Administration has authorized the use of this commercial item description, for all federal agencies.

This commercial item description covers a disposable safety razor designed to remove hair from skin.

Salient Characteristics: RAZOR, SAFETY, DISPOSABLE

Classification:

Type I - Single Blade
Type II - Twin Blade

Class 1 - Fixed Head
Class 2 - Pivoting head

Materials:

Handle and Razor Head. The material shall be polystyrene, polypropylene, or styrene-butadiene.

Protective Cap. The protective cap shall be manufactured of transparent or translucent plastic.

Blade Material. Cutting blade(s) shall be fabricated from corrosion resistant steel containing 0.62 to 0.72 percent carbon, 0.15 to 0.25 percent silicon, 0.90 to 1.10 percent manganese, 12.0 to 14.0 percent chromium, and maximums of 0.040 percent phosphorus and 0.040 percent sulfur. As an alternate, the corrosion resistant steel shall contain 0.53 to 0.70 percent carbon, 0.15 to 0.50 percent silicon, 0.20 to 0.80 percent manganese, 12.0 to 14.70 percent chromium, and maximums of 0.030 percent phosphorous and 0.025 percent sulfur.

DISTRIBUTION STATEMENT: Approved for public release Distribution is unlimited.

FSC 8530

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.

Design and Construction

Handle. The handle shall be serrated or grooved to provide suitable gripping surface and reduce slippage. The handle diameter (when round) shall be 6 mm. (0.24 inch) minimum. Handle width, across flats, (when rectangular) at the smallest cross-section, shall be 6 mm. (0.24 inch) minimum.

Razor Head. The razor head shall be designed to position the blade(s) at an angle that provides a close, nick free shave with minimal pressure, in accordance with industry standards for disposable safety razor manufacture. There shall be no movement of the blade(s) in the razor head. The razor head length shall be a minimum of 38 mm. (1.5 inches). For fixed head razors (Class 1), the razor head shall be attached to the handle by any means that prevents movement of the head or removal of the head without destruction of the attaching mechanism. For pivoting head razors (Class 2), the razor head shall be attached to the handle to facilitate a pivot angle of from 25 to 42 degrees in a direction perpendicular to the cutting edge of the blade(s). The long axis of the razor head must remain rigid and perpendicular to the handle.

Finish of the blade. The cutting edge of the blade shall be bilaterally ground and honed to razor sharpness. The final honed bevels shall be flat, smooth, and continuous throughout the entire length of the blade. Except for the extreme 1.6 mm (0.063 in) at either end, the cutting edge shall be free from micro-cracks, and no more than 5% of the edge length shall show nicks, notches, or unhoned portions when viewed microscopically, at 100 diameters. The remainder of the blade shall have a smooth and bright, polished finish. The entire blade shall be free from rust, scale, burrs, pits and cracks. The finished blade shall be coated with a fluorocarbon-telomer coating such as polytetrafluoroethylene or shall have a fine silicon fluid coating.

Hardness of the blade. When tested in accordance with ASTM E18, E92, E140, or equivalent British standard Method, cutting blades shall be uniformly hardened to 85 - 93 on the Rockwell N scale using a 15 Kgf load.

Overall length of razor. The overall length of the razor shall be 101 mm (4 in) with a tolerance of plus or minus 6 mm (0.24 in).

Protective cap. The protective cap shall be designed to provide a friction fit and completely cover the cutting edges of the blade(s).

Identification marking. The razor shall be permanently and legibly marked with the name or trademark of the manufacturer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.

Workmanship. The safety razor shall be free from defects which detract from its appearance or impair its serviceability.

Unit. Box (BX).

Type I and Type II. One (1) unit shall be a box containing seventy-two (72) packages of five (5) razors of the same type and class totaling three hundred sixty (360) razors.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, providing they fall within the tolerances specified and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the specification preparing activity for changes to this document.

Regulatory Requirements.

Federal Food, Drug and Cosmetic Act. If the product covered by this document has been determined by the U.S. Food and Drug Administration to be under its jurisdiction, the offeror/contractor shall comply, and be responsible for compliance by its subcontractors/suppliers, with the requirements of the Federal Food, Drug and Cosmetic Act, as amended, and regulations promulgated thereunder. In addition, the offeror/contractor shall comply, and be responsible for compliance by its subcontractors/suppliers, with the requirements of all other applicable Federal, State and local statutes, ordinances, and regulations.

Recovered materials. The offeror/contractor is encouraged to use recovered materials in accordance with the Federal Acquisition Regulation, Subpart 23.4 to the maximum extent practical.

Preservation, packaging, packing, labeling and marking. Unless otherwise specified, preservation, packaging and packing shall be to the degree of protection to preclude damage to containers and/or contents thereof under normal shipping conditions, handling, etc. involving shipment from the supply source to the receiving activity, plus reshipment from receiving activity, and shall conform to applicable carrier's rules and regulations. Intermediate and external package quantities and labeling and marking shall be specified in the contract and or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.

Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a)Title, number, and date of this commercial item description.
(b)Type and Class of razor.
(c)National Stock Number

MILITARY INTERESTS:

Military Coordinating Activity:

MC
GS
SA

CIVIL AGENCY COORDINATING ACTIVITIES:

DOJ-BOP
BIA
FSRS

PREPARING ACTIVITY:

FSS-GSA

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.