[Metric]
A-A-2900
August 19, 1996

COMMERCIAL ITEM DESCRIPTION
MOISTENER, PAPER SEALING, WELL TYPE

The General Services Administration has authorized the use of this commercial item description, by all federal agencies and replaces Federal Specification GG-M-565 which is canceled.

1. Scope: This Commercial Item Description covers brush, well-type paper sealing moisteners.

2. Salient Characteristics:

2.1 Porcelain shall be uniformly glazed, except for the bottom of the cup, and one side of the roller for a distance of not more than 1.3 cm (1/2 inch) from the axle housing. The glaze shall be free from crazing, cracking, chips, and bare spots.

2.2 The cover with guide arm, and the brush ferrule shall be fabricated from aluminum alloy, or corrosion-resistant steel. The cup shall be fabricated from wrought aluminum alloy, corrosion-resistant steel, aluminum or zinc-base die casting. Corrosion-resistant steel shall be in accordance with normal commercial practice.

2.3 The thickness of cast parts shall be not less than 2.5 mm (0.10 inch), and the brush shall be not less than 0.4 mm (0.015 inch). The thickness of metals other than casting and brush ferrule shall be not less than 0.6 mm (0.025 inch).

2.4 The finish of corrosion-resistant steel shall be No. 4 general purpose polished finish, or No. 6 dull satin finish. Finish of aluminum or zinc-base die casting shall be baked-on enamel. The color shall be as specified in the contract or ordering data.

2.5 The brush filler shall be composed of at least 50% by weight of natural color hog bristle and the remainder natural color horsehair or other animal hair or bristle of similar character. Filler material shall be straightened and sterilized by a commercially acceptable method and shall weigh 14 g ± 1.8 g (1/2 oz ± 1/16 oz).

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to General Services Administration, Federal Supply Service, Engineering Branch, 26 Federal Plaza, New York, NY 10278.

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

2.6 Moistener shall be of the non-adjustable (stationary) brush type. Moistener shall be sturdily constructed and suitable for the purpose intended. The moistener shall consist of a cup (water reservoir), brush unit, and a cover (lid) with guide arm. Moistener shall be constructed to permit the brush to extend within the cup containing water, and water shall be drawn up to the top of the brush by capillary action to moisten envelope flaps, gummed labels and similar items requiring water for sealing purposes. Moistener shall be equipped with rubber, cork, or felt feet or base to prevent marring of furniture. A sufficient amount of water shall be transferred to the labels for the labels to adhere and remain firmly fixed to the paper.

2.7 The cup shall have an inside length to accommodate the brush unit width, and shall have an inside depth to accommodate the brush unit length when the brush unit is positioned in the cup at not more than a 45° angle from the vertical. The cup shall have an inside width at the top of not less than 5.7 cm (2 1/4 inch). The brush unit shall be supported at one height.

2.8 The filler material shall have a chiseled trim by cupping, forming or by machine chiseling. The filler shall be 70% top size with no more than 5% shorts 2.5 cm (1 inch) or less. The filler extending out of the ferrule shall be 4.4 cm (1 3/4 inch) with a minus tolerance of 0.3 cm (1/8 inch), and shall extend 0.9 cm 3/8 inch), with a minus tolerance of 0.16 cm (1/16 inch), from the edge of the guide arm. The over-all dimensions of the brush shall be not less than 7.3 cm (2 7/8 inch) wide and 0.7 cm (5/16 inch) thick at the top of the ferrule, and 5.7 cm (2 1/4 inch) long. Unless otherwise specified, the brush filler shall be set in pure rubber, synthetic rubber, or thermosetting resin base, and secured with a ferrule. The ferrule shall be not less than 1.3 cm (1.2 inch) wide, and shall be interlocked and soldered, lock-seamed and punched, soldered, welded, or held together with a minimum of 3 metal rivets. Replacement brushes shall be furnished as specified in the contract or ordering instructions.

2.9 The cover and guide arm shall be made of metal. The cover shall encompass the top of the cup, except for the exposed brush filler, and shall clip or snap on the cup. The guide arm shall be not less than 2.2 cm (7/8 inch) wide, and of sufficient length to equal the width of the exposed brush unit. The guide arm shall be constructed to guide items to be moistened for contact with the exposed brush area.

2.10 Workmanship. The moistener shall be free from defects or imperfections of manufacture which may affect their durability, appearance, serviceability or which may present a hazard to the user.

3. Regulatory Requirements: The offerer/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

4. Quality Assurance Requirements:

4.1 Product Conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards and quality assurance practices and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

5. Packaging:

5.1 Preservation, packing, and marking shall be specified in the contract or order.

6. Notes:

6.1 Source of Documents. Issues of the following documents, in effect on the date of invitation for bids or request for proposal form a part of this document to the extent specified herein.

6.1.1 Federal Acquisition Regulation (FAR) may be obtained from the Superintendent of Documents, Government Printing Office, Washington. DC 20402.

6.2 National Stock Number Listing (NSN's). The following is a list of nsn's assigned which correspond to this CID. The list may not be indicative of all possible nsn's associated with the CID.

7520-00-530-6050

MILITARY INTERESTS:

NONE: DoD has no registered interest in revisions and amendments to this Commercial Item Description until further notice.

Preparing Activity:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.