[INCH-POUND]
A-A-2920
November 24, 1995

COMMERCIAL ITEM DESCRIPTION

RAKE (ASPHALT, ROAD)

The General Services Administration has authorized the use of this Commercial Item Description as a replacement for the Type II-Road Rake specified in GGG-R-0080 for all federal agencies.

1. SCOPE. This Commerical Item Description covers a road rake used in road building, paving work, and gravel work.

2. CLASSIFICATION

Not applicable.

3. SALIENT CHARACTERISTICS.

3.1 Material. Material used in the construction of the rake shall be of uniform quality and free from defects that may affect the serviceability, durability, or safety of the rake.

3.2. Design. The rake shall consist essentially of a long wood handle with a steel rake head, steel shank and steel tangs for moving asphalt and gravel.

3.3 Handle. The rake handle shall be of Ash wood. All portions of the handle shall be smoothly finished and shall be adequately covered with two durable coats of transparent lacquer, varnish or with one coat of water base latex emulsion after surface treatment utilizing heat, (both, flame treating or charring). The coating shall be applied in such a manner to permit visual inspection of the wood and to prevent absorption of water.

3.4 Handle dimensions. The overall length and width diamension shall be in accordance with Table II.

3.5 Head dimensions. The number of teeth and the dimensions of depth, and thickness dimensions shall be in accordance with table II.

3.6 Hardness of head and teeth. The head and teeth of the rake shall be HRB 90 minimum, when tested in accordance with ASTM E-18.

Benefical comments, recommendations, addtions, deletions, clarifications, etc. and any data which may improve this document should be sent to: General Service Administration, Federal Supply Service, Tools and Appliances Center (6FETE-CO), Washington, DC 20406

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

3.7 Head and shank. The rake head and shank shall be formed in one piece from steel. The top and th ends of the head shall be square-edged to semi-round. The rake shall have a single central shank which shall be forced into the handle and reinforced with a ferrule.

3.8 Nails and rivets. Nails and rivets for attachment of the handle or ferrule shall be steel, oval or round head, not less than 0.115 inch body diameter and not less than 27/32 inch overall length. When any rivet or nail extends entirely through the opposite side of the ferrule, its end shall be neatly headed over the ferrule.

3.9 Teeth. The teeth shall be straight within 1/8 inch. The length of the teeth shall be 3-1/8 inches, or greater, from the tip to the bottom of the radius. The spacing between the teeth shall be 7/8 inches or greater, when measured 2 inches from the tip.

3.10 Ferrule. A steel tubular ferrule 4-1/8 inches long or greater shall be provided. The ferrule shall be tapered and fastened to the handle with at least one nail or rivet. The seam of the ferrule shall be closed by a continuous weld.

3.11 The rake shall conform to the test loads and dimensions specified in Table II.

Table II.

Head				Handle				Test Loads		
Teeth	Depth		Thickness	Width		Length		Handle	Tooth	Shank
Number	inches		inches	inches		inches		Lbs	Lbs	Lbs
	Min	Max	± 1/32	Min	Max	Min	Max			
14	3-1/8	4-1/16	3/8	15-1/4	16	65	67	500	100	2

3.12 Workmenship. Details of workmanshipshall be in accordance with the best commerical practice. Paints, coatings, plating, and finishes shall be smooth, adherent, continuous, and not stained or discolored. External surfaces shall be free of tool and gouge marks, nicks, or other surface imperfections. The item shall be free from manufacturing workmanship defects (e.g. sharp or rough external edges, corners, or surfaces) and material workmanship defects (e.g. pits, rips, fins, burrs, tears, nodules, cracks, blisters) which may adversely impact the item's serviceability, durability, safety, or appearance.

3.11 Identification marking. The rake shall be marked with the manufacturer's name or identification symbol, and the state or country of manufacture, unless otherwise specified. All identification markings shall be engraved, etched, molded, or indented directly on the item's surface in such a manner that it remains clearly legible throughout the life of the item.

4. REGULATORY REQUIREMENTS.

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulations (FAR).

4.2 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified (using conversion tables contained in the latest revision of Federal Standard 376) and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

5. QUALITY ASSURANCE PROVISIONS.

5.1 Contractor certification. The contractor shall provide certification and maintain substantiating evidence that all items being offered for acceptance meet the requirements of this Commercial Item Description and conform to the manufacturer's drawings, specifications, standards, and quility assurance practices. The Government reserves the right to require proof of such conformence prior to first delivery and thereafter as provided for under the provisions of the contracr.

5.2 Responsibility for inspection. Unless otherwise specified, the contractor is reponsible for the performance of all inspection requirements and may use any commercial facilities (including the contractor's facilities) suitable for performance of the inspection requirements, unless disapproved by the Government. The Government reserves the right to perform any inspections deemed necessary to assure the item conforms to the specified requirements.

5.3 Bid sample(s). When a bid sample requirement is specified in the solicitation, the bid sample(s) shall be inspected for all salient characteristics. A failure of any bid sample to meet the salient characteristics shall be cause for rejection.

5.4 First article sample(s). When a first article requirement is specified in the contract, the first article sample(s) shall be inspected for all salient charactertics. A failure of any first article sample to meet the salient characteristics shall be cause for rejection.

6. PACKAGING.

Preservation, packing, packaging and marking shall be as specified in the contract or order.

7. NOTES.

(This section contains information of a general or explanatory nature that is not mandatory.)

7.1 Addresses for obtaining copies of referenced docouments.

Federal Specifications: Federal Supply Service Bureau, Specification Section, Suit 8100, 470 L'Enfant Plaza, SW,
Washington, DC, 20407.

Federal Acquisition Regulations (FAR): Government Printing Office Superintendent of Documents, Washington DC 20401-9371.

ANSI/ASQC Z1.4: American Society for Quality Control, PO Box 3005, 611 E. Wisconsin Ave., Milwaukee, WI 43201-4606.

ASTM E18: American Society For Testing Materials, 1916 Race St., Philadelphia, PA 19103

7.2 Ordering data. Purchasers should select the preferred options permitted herein and should include the following information in procurement documents:

(a) Title, number, and date of this Commercial Item Description.

(b) When applicable, the appropriate NSN.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:27Z
Check the source to verify that this is the currenversion before use.

(c) If bid samples are required and the number of samples required.

(d) If first article samples are required and the number of samples required.

(e) If lot sampling is required and the applicable lot sampling requirements.

For example, the following typical lot sampling requirements would be specified in the contract.

Sampling for inspection. Sampling for inspection (both examinations and testing) shall be in accordance with ANSI/ASQC Z1-4.

Inspection. Each sample rake shall be tested for all salient characteristics. The Inspection Level shall be S-2 with an Acceptible level of 2.5 expressed in term of defects per hundred units.

What preservation, packing, packaging and marking are required.

7.3 National Stock Numbers (NSNs). The following NSN is associated with this CID. This list may not be indicative of all possible NSNs associated with this CID.

NSN 5120-00-224-9239

Militiaty Interest:
None: DOD has no registered
interest in revisions and notices
to this Commercial Item Description until further notice.

Preparing Activeity
GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:27Z
Check the source to verify that this is the currentversion before use.