INCH-POUND

A-A-2930A
August 6, 2003
SUPERSEDING
A-A-2930
April 1, 1996

COMMERCIAL ITEM DESCRIPTION

REAMER, HAND, TAPER PIN

The General Services Administration has authorized the use of this commercial item description by all federal agencies.

1. SCOPE. This commercial item description covers taper pin hand reamers used in reaming hole diameters to specified tolerances.


2. CLASSIFICATION.

Type 1 – Straight Fluted
Type 2 – Spiral Fluted


3. SALIENT CHARACTERISTICS.

3.1 Type 1.

3.1.1 Design. The hand reamer shall have straight flutes, straight round shank with squared end, and shall be right-hand and ground. The reamer shall be similar to Figure 1(A), and conform to the dimensions specified in ASME B94.2, Table 24 and it's applicable tolerances.



(A) Taper Pin Hand Reamer, Straight Flutes



(B) Taper Pin Hand Reamer, Spiral Flutes
Figure 1.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data which may improve this document should be sent to: General Services Administration, Federal Supply Service, Hardware SuperStore (6FEE), 1500 E. Bannister Rd Bldg. #6, Kansas City, Missouri 64131.

FSC 5110

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:27Z
Check the source to verify that this is the current version before use.

3.2 Type 2.

3.2.1 Design. The hand reamer shall have spiral flutes, straight round shank with squared end, and shall be left-hand-and-ground. The reamer shall be similar to Figure 1(B), and conform to the dimensions specified in ASME B94.2, Table 24 and it's applicable tolerances.

3.3 Material. The hand reamer shall be made of molybdenum base types M1, M2, M7, or M10 high speed steel.

3.4 Construction. The cutting section shall taper 1/4 inch per foot. The cutting edges shall be properly relieved and the flutes shall provide for chip clearance. Flute spacing shall be in accordance with the manufacturer's standard practice. The shank shall be integral or joined to the reamer by welding, and shall be concentric with the cutting edges within 0.001 inch total indicator reading (tir) as measured between centers.

3.5 Hardness. The full length of the cutting edges of the reamer shall be hardened and tempered to a Rockwell hardness value from C61 to C67. When required to be tested, the reamer shall be tested for hardness in accordance with ASTM E18.

3.6 Performance. The reamer shall cut freely and produce smooth and accurate holes when subjected to hand reaming a minimum of 25 holes in a steel plate of at least 1/2 inch thickness. The testing steel shall conform to FED-STD-66, AISI Number 4140 or 4150, and shall have a Brinell hardness value from 235 to 285. The starting holes shall be 0.002 to 0.003 inch smaller than the small diameter of the finish-reamed hole.

3.7 Workmanship. Details of workmanship shall be in accordance with the best commercial standards and practices. Paints, coatings, platings, and finishes shall be smooth adherent, continuous, and not stained or discolored. External surfaces shall be free from manufacturing workmanship defects (e.g. sharp or rough external edges, corners or surfaces) and material workmanship defects (e.g. pits, rips, fins, burrs, tears nodules, cracks, blisters) which may adversely impact the item's serviceability, durability, safety, or appearance.

3.8. Identification Marking. The reamer shall be marked with the manufacturer's name or identifying symbol, and the state or country of manufacture, unless otherwise specified. All identification markings shall be engraved, etched, molded, or indented directly on the item's surface in such a manner that it remains clearly legible throughout the life of the item. The reamer shall be marked with the words 'High Speed' or the abbreviation 'HS'.

4. REGULATORY REQUIREMENTS.

4.1 Recovered Materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal acquisition Regulation (FAR).

4.2 Metric Products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified (using conversion tables contained in the latest revision of Federal Standard 376) and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch- pound units, a request should be made to the contracting officer to determine if the product is acceptable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

5. PRODUCT CONFORMANCE.

5.1 Product Conformance. The product provided shall meet the salient characteristics of this Commercial Item Description, conform to the producer's own drawing, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

5.2 Responsibility for Inspection. Unless otherwise specified, the contractor is responsible for the performance of all inspection requirements and may use any commercial facilities (including the contractor's own facilities) suitable for performance of the inspection requirements, unless disapproved by the Government. The Government reserves the right to perform any of the inspections deemed necessary to assure the item conforms to the specified requirements.

6. PACKAGING. Preservation, packaging and marking shall be as specified in the contract or order.

7. NOTES. This section contains information of a general or explanatory nature that is not mandatory.

7.1 Source of Documents.

American Society for Testing and Materials (ASTM), 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959.

Federal Acquisition Regulation (FAR): Government Printing Office, Superintendent of Documents, Washington DC. 20401-9371.

General Services Administration, Specification Section (3FP-E), Suite 8100, 470 L'Enfant Plaza, SW, Washington, DC 20407.

American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

7.2 Ordering data. Purchasers should select the preferred options permitted herein and should include the following information in procurement documents.

a. Title, number, and date of Commercial Item Description.
b. Type and reamer size.
c. Packaging requirements.

7.3 National Stock Numbers (NSN's). A list of NSN's assigned that correspond to this CID. The list may not be indicative of all possible NSN's associated with the CID.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

7.3.1 Type 1.

Reamer Size	National Stock Number	Reamer Size	National Stock Number	Reamer Size	National Stock Number
7/0	5110-00-253-3152	0	5110-00-243-2004	6	5110-00-253-3176
6/0	5110-00-253-3154	1	5110-00-243-2005	7	5110-00-253-3178
5/0	5110-00-253-3156	2	5110-00-243-2006	8	5110-00-555-1205
4/0	5110-00-253-3158	3	5110-00-253-3170	9	5110-00-253-3182
3/0	5110-00-253-3160	4	5110-00-253-3172	10	5110-00-253-3184
2/0	5110-00-243-2003	5	5110-00-243-2007		

7.3.2 Type 2.

Reamer Size	National Stock Number	Reamer Size	National Stock Number	Reamer Size	National Stock Number
7/0	5110-00-253-3151	0	5110-00-253-3163	6	5110-00-253-3175
6/0	5110-00-253-3153	1	5110-00-253-3165	7	5110-00-253-3177
5/0	5110-00-253-3155	2	5110-00-253-3167	8	5110-00-253-3179
4/0	5110-00-253-3157	3	5110-00-253-3169	9	5110-00-253-3181
3/0	5110-00-253-3159	4	5110-00-253-3171	10	5110-00-253-3183
2/0	5110-00-253-3161	5	5110-00-253-3173		

7.4 Key words. Reamer, Hand, Taper Pin

MILITARY INTERESTS:
NONE: DoD has no registered interest
in revisions and amendments to this
Commercial Item Description until further notice.

Preparing Activity:
GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.