MILITARY SPECIFICATION

ACTUATOR,EXPLOSIVE, LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of Actuator, Explosive which is used on the Nike Hercules warhead section.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-810	- Environmental Test Methods.
MIL-STD-1168	- Lot Numbering of Ammunition.
MIL-STD-1169	- Packaging, Packing and Marking for Shipment of Inert Ammunition Components.

DRAWINGS

ORDNANCE

8804257	- Explosive Actuator.
8804258	- Cup.
8804259	- Powder Charge Sub-assembly.
8804262	- Plug Insulator.
8804263	- Disc Solid.
8804264	- Igniter Assembly.
8804265	- Piston.
8804266	- Body.
8804267	- Pin Contact.
EL-8828870	- Equipment Lists.

FSC: 1135

>/S

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this purchase description. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

INTERSTATE COMMERCE COMMISSION

49 CFR 71-78 - Interstate Commerce Commision Rules and Regulations for the Transportation of Explosives and Other Dangerous Articles.

(The Interstate Commerce Commision regulations are now a part of the Code of Federal Regulations (1949 Edition-Revised 1950) available from the Superintendent of Documents, Government Printing Office, Washington 25, D.C. Orders for the above publication should cite "49 CFR 71-78 (Rev. 1950).")

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The explosive actuator shall comply with all requirements specified on the drawing (dwg) 8804257, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

3.4 Serialization. The contractor shall assign serial numbers as required by drawings. The contractor may select any number which complies with the drawing requirement. These numbers shall not be duplicated.

3.5 Bridge wire weld. The bridge wire after welding to the pins shall be capable of a prefire test without evidence of damage or deterioration such as loosening, breaking foreign matter, burning, or necking down when tested as specified in 4.4.2.

3.6 Resistance. The resistance of the bridge wire circuits shall be 4.5 $\pm$ 0.5 ohms when tested as specified in 4.4.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

3.7 Insulation resistance. The insulation resistance of all circuits in the assembly shall be 50 megohms minimum when tested as specified in 4.4.4.

3.8 Non-firing. The explosive actuator shall not actuate when subjected to 100 ± 5 milliamperes when tested as specified in 4.4.5.

3.9 Environmental testing. The explosive actuator shall comply with MIL-STD-810, visual inspection and failure criteria, section 3. The explosive actuator shall also comply with 3.8 and 3.6 before and after each environmental test. Testing shall be as specified in 4.4.6. Tests shall be conducted in the order specified.

3.9.1 Vibration. The explosive actuator shall show no evidence of electrical or mechanical damage, as evidenced by cracking, splitting, or loosening of components. When vibrated in the three mutually perpendicular planes with frequencies varying from 8 to 55 Hertz (Hz) at a constant double amplitude of 0.036 inch and from 55 to 500 Hz constant acceleration of 10 g, and shall comply with the requirements of 3.8 and 3.6 when tested as specified in 4.4.6.1.

3.9.2 Impact shock. The explosive actuator shall withstand three impact shocks of 60 g in each of the three mutually perpendicular axis and three impact shock of 100 g, and shall comply with the requirements of 3.8 and 3.6 when tested as specified in 4.4.6.2.

3.9.3 Low temperature and low pressure. The explosive actuator shall show no evidence of electrical or mechanical damage, as evidenced by cracking, chipping, or distorting, and shall meet the requirements of 3.9.1 and 3.9.2 in that order after subjection to a barometric pressure of two inches of mercury and during subjection to a -65 ± 5°F., and shall comply with the requirements of 3.8 and 3.6 when tested as specified in 4.4.6.3.

3.9.4 Low temperature. The explosive actuator shall show no evidence of electrical or mechanical damage, as evidenced by cracking, chipping, or distorting, and shall meet the requirements of 3.8, 3.6 and 3.9.1 in that order and after subjection to a temperature of -80 ± 5°F., shall comply with the requirements of 3.8 and 3.6 when tested as specified in 4.4.6.4.

3.10 Functional tests.

3.10.1 Firing. The explosive actuator shall be capable of firing when subjected to a current of 565 ± 15 milliamperes when tested as specified in 4.4.7.1.

3.10.2 Explosive force. The force exerted by the explosive actuator shall be tested as specified in 4.4.7.2.

3.11 Workmanship.

3.11.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.11.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

3.11.3 Burrs. Parts shall be free from burrs.

3.11.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.11.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

3.11.6 Electrical. Cable assemblies and wires shall be dressed in such a manner as to prevent pinching or chafing of the wire insulation. Ends of wires shall be free from burrs, sharp edges, or points. All parts shall be free from flux, chips, dirt, grease, rust or foreign material.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall submit 10 complete assemblies (see dwg 8804257) for first article testing to the testing facility designated in the invitation for bids or request for proposal.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table I. Tests shall be conducted in order specified in Table I.

Table I

First article inspection and tests

Inspection or Test	Dest	Non-Dest
1. Classification of characteristics (see 4.3.2.1)		X
2. Bridge wire weld (see 3.5)		X
3. Resistance (see 3.6)		X

Source: https://assist.dla.mil -; Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Inspection or Test	Dest	Non-Dest
4. Insulation resistance (see 3.7)		X
5. Non-firing (see 3.8)		X
6. Vibration (see 3.9.1)	X	
7. Impact Shock (see 3.9.2)	X	
8. Low temperature and low pressure (see 3.9.3)	X	
9. Low temperature (see 3.9.4)	X	
10. Function (see 3.10)	X	

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table II and Table III), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Table II
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-72	all	140-141	124	256-259	177	541-549	230
73	72	142	125	260-262	178	550-559	231
74	73	143-144	126	263-265	179	560-569	232
75	74	145	127	266-268	180	570-579	233
76	75	146-147	128	269-271	181	580-590	234
77	76	148-149	129	272-275	182	591-601	235
78	77	150	130	276-278	183	602-613	236
79	78	151-152	131	279-282	184	614-625	237
80	79	153-154	132	283-285	185	626-637	238
81-82	80	155-156	133	286-289	186	638-649	239
83	81	157	134	290-293	187	650-662	240
84	82	158-159	135	294-296	188	663-676	241
85	83	160-161	136	297-300	189	677-690	242
86	84	162-163	137	301-304	190	691-704	243
87	85	164-165	138	305-308	191	705-719	244
88-89	86	166-167	139	309-312	192	720-735	245
90	87	168	140	313-316	193	736-751	246
91	88	169-170	141	317-320	194	752-768	247
92	89	171-172	142	321-324	195	769-785	248
93	90	173-174	143	325-329	196	786-804	249
94-95	91	175-176	144	330-333	197	805-823	250
96	92	177-178	145	334-338	198	824-842	251
97	93	179-180	146	339-342	199	843-863	252
98	94	181-182	147	343-347	200	864-884	253
99-100	95	183-184	148	348-352	201	885-907	254
101	96	185-187	149	353-356	202	908-930	255
102	97	188-189	150	357-361	203	931-955	256
103	98	190-191	151	362-366	204	956-981	257
104-105	99	192-193	152	367-372	205	982-1008	258
106	100	194-195	153	373-377	206	1009-1036	259
107	101	196-197	154	378-382	207	1037-1066	260
108-109	102	198-200	155	383-388	208	1067-1098	261
110	103	201-202	156	389-393	209	1099-1131	262
111	104	203-204	157	394-399	210	1132-1166	263
112-113	105	205-207	158	400-405	211	1167-1204	264
114	106	208-209	159	406-411	212	1205-1243	265
115	107	210-212	160	412-417	213	1244-1285	266
116-117	108	213-214	161	418-424	214	1286-1330	267
118	109	215-217	162	425-430	215	1331-1378	268
119	110	218-219	163	431-437	216	1379-1429	269
120-121	111	220-222	164	438-443	217	1430-1483	270
122	112	223-224	165	444-450	218	1484-1542	271
123-124	113	225-227	166	451-457	219	1543-1605	272
125	114	228-230	167	458-465	220	1606-1673	273
126-127	115	231-232	168	466-472	221	1674-1747	274
128	116	233-235	169	473-480	222	1748-1827	275
129-130	117	236-238	170	481-488	223	1828-1914	276
131	118	239-241	171	489-496	224	1915-2010	277
132-133	119	242-243	172	497-504	225	2011-2115	278
134	120	244-246	173	505-513	226	2116-2232	279
135-136	121	247-249	174	514-521	227	2233-2361	280
137	122	250-252	175	522-530	228	over 2361	298
138-139	123	253-255	176	531-540	229		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Table III
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Plug, Insulator (see dwg 8804262 covering a detail of dwg 8804264).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Diameter of holes, max.	Gage
	102. Distance between holes	Gage
	103. Length overall	Gage
	104. Length of small diameter	Gage
	105. Small diameter	Gage
	106. Large diameter	Gage
	107. Objective evidence relative to material missing or improper (see 3.1)	Visual
Minor:		
	201. Evidence of poor workmanship (see 3.11)	Visual

4.3.2.1.2 Pin, contact (see dwg 8804267 covering a detail of dwg 8804267).

Critical:	None defined.	
Major:		
	101. Diameter of body of pin, min.	Gage
	102. Objective evidence relative to material missing or improper (see 3.1)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Minor:

201.	Distance from head to end of pin	Gage
202.	Diameter of head	Gage
203.	Length of head	Gage
204.	Radius missing or inadequate	Visual
205.	Evidence of poor workmanship (see 3.11)	Visual

4.3.2.1.3 Ignitor assembly (see dwg 8804264 covering a detail of dwg 8804257).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Bridge wire broken or not properly welded	Visual
102.	Pins improperly cemented in body	Visual
103.	Objective evidence relative to material missing or improper (see 3.1)	Visual
Minor:		
201.	Bridge wire not properly covered	Visual
202.	Bond inadequate	Visual
203.	Evidence of poor workmanship (see 3.11)	Visual

4.3.2.1.4 Cup (see dwg 8804258 covering a detail of dwg 8804259).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Overall length of cup	Gage
102.	End wall thickness	Gage
103.	Inside diameter	Gage
104.	Outside diameter	Gage
105.	Objective evidence relative to material missing or improper (see 3.1)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Minor:
201. Radius missing or inadequate.....Visual
202. Evidence of poor workmanship (see 3.11).....Visual

4.3.2.1.5 Powder charge sub-assembly (see dwg 8804259 covering a detail of dwg 8804257).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Weight of charge (prior to assembly)...	Balance
102.	Retaining disc or cup crack or split...	Visual
103.	Objective evidence relative to material missing or improper (see 3.1).....	Visual
Minor:		
201.	Lacquer missing or inadequate.....	Visual
202.	Paper disc missing from cup.....	Visual
203.	Evidence of poor workmanship (see 3.11).....	Visual

4.3.2.1.6 Disc, solid (see dwg 8804263 covering a detail of dwg 8804257).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Diameter of disc.....	Gage
102.	Disc damaged.....	Visual
103.	Objective evidence relative to material missing or improper (see 3.1).....	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.11).....	Visual

4.3.2.1.7 Piston (see dwg 8804265 covering a detail of dwg 8804257).

Critical: None defined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Major:

101.	Large outside diameter of piston	Gage
102.	Diameter of undercut	Gage
103.	Width of undercut	Gage
104.	Diameter of piston body	Gage
105.	Concentricity of large outside diameter with body diameter	Gage
106.	Length from small end to shoulder	Gage
107.	Length, extreme, over the two large shoulders	Gage
108.	Objective evidence relative to material missing or improper (see 3.1)	Visual

Minor:

201.	Piston damaged	Visual
202.	Finish improper	Visual
203.	Radius missing	Visual
204.	Evidence of poor workmanship (see 3.11)	Visual

4.3.2.1.8 Body (see dwg 8804266 covering a detail of dwg 8804257).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	

Major:

101.	Inside diameter of body below shoulder	Gage
102.	Inside diameter of body above shoulder	Gage
103.	Diameter of hole in end	Gage
104.	End wall thickness	Gage
105.	Diameter of body	Gage
106.	Concentricity of hole with inside diameter below shoulder	Gage
107.	Objective evidence relative to material missing or improper (see 3.1)	Visual

Minor:

201.	Small outside diameter	Gage
202.	Length of small outside diameter	Gage
203.	Length from top of body to shoulder on inside diameter to bottom of body	Gage
204.	Length from shoulder on inside diameter to bottom of body	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

205. Radius missing.....Visual
206. Finish improper.....Visual
207. Evidence of poor workmanship (see 3.11).....Visual

4.3.2.1.9 Explosive actuator (MC-727) (see dwg 8894257).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Height	Gage
102.	Piston projected below body, max	Gage
103.	Any component or operation missing	Visual
104.	Objective evidence relative to material missing or improper (see 3.1)	Visual
Minor:		
201.	Marking misleading or unidentifiable	Visual
202.	Pin holes in ignitor assembly	Visual
203.	Radius missing	Visual
204.	Serialization improper or missing	Visual
205.	Evidence of poor workmanship (see 3.11)	Visual

4.3.2.1.10 Preparation for delivery (see 5).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Preservation and packaging not in accordance with MIL-STD-1169	Visual
102.	Packing not in accordance with 49 CFR 71-78	Visual
103.	Marking not in accordance with MIL-STD-129	Visual
Minor:	None defined.	

4.3.3 Testing. All tests shall be performed. Tests shall be performed in the order specified below:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Test	Test Classification
a. Bridge wire weld	Critical
b. Resistance	Critical
c. Insulation resistance	Critical
d. Non-firing	Critical
e. Vibration	Major
f. Impact shock	Major
g. Low temperature and low pressure	Major
h. Low temperature	Major
i. Function	Major

Of these tests, (e) through (i) are considered destructive and samples so tested shall not be returned to the lot. Destructive samples are over and above the deliverable quantity of items required by the contract.

4.3.3.1 Bridge wire weld, resistance and insulation resistance. Each explosive actuator shall be tested in accordance with 4.4.2, 4.4.3 and 4.4.4. If any item fails to comply with 3.5, 3.6 and 3.7, the item shall be rejected and removed from the lot.

4.3.3.2 Non-firing, vibration, impact shock, low temperature and low pressure, low temperature and function. A sample shall be selected at random in accordance with Table IV. The sample shall be tested in accordance with 4.4.5, 4.4.6.1, 4.4.6.2, 4.4.6.3, 4.4.6.4 and 4.4.7. If any item fails to comply with 3.8, 3.9.1, 3.9.2, 3.9.3, 3.9.4 and 3.10, the lot shall be rejected.

Table IV

Number Required to be Delivered	Sample Size for No Failures
2-8	1
9-15	2
16-25	3
26-40	5
41-65	8
66-110	13
111-180	22
181-300	26
301-and over	MIL-STD-105 (AQL 0.25 percent)

For Destructive Testing.
Lot Size Required = Number Required to be Delivered + Sample Size.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL) (see EL-8828870). When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Test tolerances. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy.

4.4.2 Bridge wire weld. The bridge wire assembly shall be connected into a circuit of 10 volts, 40 microfarad. The bridge wire shall glow with an even luminescence. After cooling, the bridge wire shall be visually examined under a 10 power glass for the following conditions.

a. Loosening: Bridge wire insecurely welded to the pins.
b. Breaking: Wire is continuous without breaking.
c. Burning or necking down: Wire burned or reduced in area.
d. Foreign matter: Stray weld metal between pins.

4.4.3 Resistance. The bridge wire resistance shall be measured by means of a circuit such that the current flowing through the bridge wire is 25 milliamperes maximum. The bridge wire resistance shall be 4.5 + 0.5 ohms.

4.4.4 Insulation resistance. The insulation resistance shall be measured by applying 500 ± volts dc between the shorted contact pins and the case for one second minimum. The insulation, resistance shall be 50 megohms minimum.

4.4.5 Non-firing. A current of 100 ± 5 milliamperes shall be passed through the bridge wire for a period of five minutes ± 15 seconds. The explosive actuator shall not fire under these conditions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

4.4.6 Environmental testing (see 3.9).

4.4.6.1 Vibration. Prior to beginning this test, the explosive actuator shall be mounted with the contact pins plugged into a rigid block. The explosive motor shall be inclosed in and restrained by a thin metallic cyclindrical cup or can which is accured to the block into which the explosive motor is plugged. A hole shall be provided in the bottom of the cup so that the piston is free to extend when and if the motor is actuated. Several motors may be mounted on the same block, but each motor shall be provided with individual restraining cups. The explosive actuator shall be vibrated through a frequency range of 8 to 500 to 8 Hertz (Hz) in 15-minute cycles for a period of 60 minutes in the longitudinal axis at an applied double amplitude of 0.036 inch in the frequency range of 8 to 55 (Hz) and at an applied constant acceleration of 10 g in the 55 to 500 (Hz) range. Upon completion of the test, the explosive actuator shall be tested as specified in 4.4.5 and 4.4.3.

4.4.6.2 Impact shock. Prior to beginning this test, mount per 4.4.6. The explosive actuator shall be subjected to three 60 g impact shock impulses applied in each direction along each of three mutually perpendicular axis for a total of 18 impact shocks. Each shock impulse shall have a duration of 3 ± 1 milliseconds. Also, the explosive actuator shall be subjected to three 100 g impact shocks with piston end down, having a duration of 3 ± 1 milliseconds. Upon completion of the test, the explosive actuator shall be tested as specified in 4.4.5 and 4.4.3.

4.4.6.3 Low temperature and low pressure. The explosive actuator shall be placed in a suitable test chamber and the temperature shall be reduced and stabilized (see 6.4) -65 ± 5°F. The barometric pressure shall be reduced to 2 inches of mercury absolute within 15 minutes of placing the explosive actuator in the chamber. The conditions shall be maintained for four hours, after which time the assembly shall be returned to atmospheric pressure and tested as specified in 4.4.5 and 4.4.3.

4.4.6.4 Low temperature. The explosive actuator shall be placed in a suitable test chamber and the temperature shall be reduced and stabilized at -80 ± 5°F. for 20 hours, after which time the actuator shall be returned to atmospheric pressure and tested as specified in 4.4.5 and 4.4.3.

4.4.7 Functional tests.

4.4.7.1 Firing. The explosive actuator shall fire when a current of 565 ± 15 milliamperes is passed through the bridge wire for a period of 2 + 0.0, -0.2 milliseconds.

4.4.7.2 Explosive force. The explosive actuator shall move a 7 + 4 -0 gram weight vertically upward through a distance of 5/16 ± 1/64 inches against a constant force of 21 ± 1 pounds within 30 milliseconds of application of firing pulse.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The explosive actuator shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169.

5.1.2 Level C. The explosive actuator shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169.

5.2 Packing. The explosive actuator shall be packed in accordance with Interstate Commerce Commission. Regulations for Transportation of Explosive and other Dangerous Articles, paragraph 73.66 (see Code of Federal Regulations 49 CFR 71-78).

5.3 Marking. Marking shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1).

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 will be delivered as identified on a numbered DD Form 1664 when required on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-T.

6.4 Temperature stabilization. The temperature is considered stabilized when the greatest peaks (both highest and lowest) continually observed over 5 minutes min. do not exceed the nominal temperature plus tolerance specified.

Custodian:
Army - PA

Preparing activity:
Army - PA

Project No. 1135-A185

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

U.S.MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-N-Q
Dover, New Jersey 07801

FOLD