MIL-M-63283A(AR)
30 April 1981
SUPERSEDING
MIL-M-63283(AR)
27 June 1978

MILITARY SPECIFICATION

MOUNT ASSEMBLY, SUB-CALIBER, UNIVERSAL: M179 (INCLUDING MANTLET ADAPTER ASSEMBLY)

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains requirements not covered by the drawings, and provides quality assurance provisions for the fabrication, assembling and packing for Mount Assembly, Sub-Caliber, Universal: M179. (Includes Mantlet Adapter Assembly) (See 6.5)

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-S-12109	- Solenoid, Electrical; Gun-Firing Mechanisms.
MIL-S-45743	- Soldering, Manual Type, High Reliability, Electrical and Electronic Equipment.
MIL-A-48078	- Ammunition, Standard Quality Assurance Provisions, General Specification For.

FSC 1005

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

SUPPLEMENTARY QUALITY ASSURANCE PROVISIONS (SQAP)

SQAP 8720102 - Controller Assembly, Single Shot.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-1460 - Soldering of Electrical Connections and Printed Wiring Assemblies, Procedures for.

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

11828578 - Mount Assembly, Sub-Caliber, Universal: M179.

11828599 (See 6.5) - Wiring Harness Assembly for XM1 to (M179).

PACKAGING DATA SHEET

11828578 - Mount Assembly, Sub-Caliber, Universal: M179.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM E 18 - Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials.

ASTM B 117 - Salt Spray (Fog) Testing.

(Application for copies should be addressed to: American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings, specifications and standards.

3.2 Parts. All parts shall be in accordance with the applicable drawings, specifications and standards.

3.3 Mount assembly. The mount assemblies shall comply with all requirements specified on Drawing (Dwg) F-11828578, all associated drawings, and with all requirements specified in applicable specifications and standards.

3.4 Mantlet mounting (See 6.5). Parts for mantlet mounting shall comply with all requirements specified on the applicable drawings, and all applicable specifications and standards.

3.5 Wiring harness assembly (See 6.5). The Wiring Harness Assembly shall comply with all requirements specified on Dwg. B11828599, all associated drawings, and all applicable specifications and standards.

3.6 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.7 Welding. All welds shall be reasonably smooth and free of craters. They shall exhibit characteristics of good fusion, penetration, and soundness of deposit representative of good welding practice. The process shall be such as to prevent warpage and distortion. There shall be no crack in or near welded areas.

3.8 Workmanship. All parts and assemblies shall be fabricated and assembled in a thorough, workmanlike manner. They shall be free of burrs, chips, weld spatter, sharp edges, chipped edges, gouges, cracks, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agents. All required markings shall be neat and sharply defined. External threads shall be full, complete and undamaged for their entire length. All soldering shall be performed in a thorough, workmanlike manner with no evidence of burning or charring.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item.

a. First article inspection (See 4.3).

b. Quality conformance inspection (See 4.4).

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawings	Quantity
Sub-Caliber Universal Mount Assembly, M179	F11828578	15
Pull Cable Assembly	D11828580	15
Wiring Harness Assembly	D11828588	15
Stud	B11828560	10
Block, Angle	C11828563	10
Block, Stationary	C11828565	10
Insert	B11828577	10
Stud Block Assembly	D11828567	10
Bracket (Weldment)	C11828564	10
Brace	C11828573	10
Saddle	F11828575	10

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:32Z
Check the source to verify that this is the currentversion before use.

Brace and Magazine (Weldment)	D11833434	10
Brace, Strap	C11828569	10
Bolt, Eye	D11828570	10
Strap Assembly	F11828571	10
Pintle (Weldment)	D11828568	10
* Bar, Cross	D9335637	10
* Brace	D9335639	10
* Bracket	C9335640	10
* Wiring Harness Assembly	B11828599	15
* Shim	C11828600	10

* When applicable (See 6.5)

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

TABLE I. FIRST ARTICLE INSPECTION.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63283A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 5		DRAWING NUMBER
	Mount Assembly, Sub-Caliber, Universal: M179				See below
					NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Pull Cable Assembly (Dwg. D11828580)				
	Examination for defects	15		3.2	4.4.2.1
	Wiring Harness Assembly (Dwg. D11828588)				
	Examination for defects	15		3.2	4.4.2.2
	Stud (Dwg. B11828560)				
	Examination for defects	10		3.2	4.4.2.3
	Salt spray test (Note 1)	10		3.2	4.5.4
	Block, Angle (Dwg. C11828563)				
	Examination for defects	10		3.2	4.4.2.4
	Salt spray test (Note 1)	10		3.2	4.5.4
	Block, Stationary (Dwg. C11828565)				
	Examination for defects	10		3.2	4.4.2.5

NOTES: 1. Any evidence of salt deposits or corrosion following completion of salt spray test shall cause the sample to be classed defective.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

TABLE I. FIRST ARTICLE INSPECTION.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63283A(AR)

PARAGRAPH	TITLE: Mount Assembly, Sub-Caliber, Universal: M179		SHEET 2 OF 5		DRAWING NUMBER: See below NEXT HIGHER ASSEMBLY: ---
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Insert (Dwg. B11828577)				
	Examination for defects	10		3.2	4.4.2.6
	Salt spray test (Note 1)	10		3.2	4.5.4
	Stud Block Assembly (Dwg. D11828567)				
	Examination for defects	10		3.2	4.4.2.7
	Salt spray test (Note 1)	10		3.2	4.5.4
	Bracket (Weldment) (Dwg. C11828564)				
	Examination for defects	10		3.2	4.4.2.8
	Salt spray test (Note 1)	10		3.2	4.5.4
	Brace (Dwg. D11828573)				
	Examination for defects	10		3.2	4.4.2.11
	Saddle (Dwg. F11828575)				
	Examination for defects	10		3.2	4.4.2.13

NOTES: 1. Any evidence of salt deposits or corrosion following completion of salt spray test shall cause the sample to be classed defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

TABLE I. FIRST ARTICLE INSPECTION.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63283A(AR)

PARAGRAPH	TITLE		SHEET	DRAWING NUMBER
	Mount Assembly, Sub-Caliber, Universal: M179		3 OF 5	See below
				NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Brace & Magazine (Weldment) (Dwg. D11833434)				
	Examination for defects	10		3.2	4.4.2.14
	Salt spray test (Note 1)	10		3.2	4.5.4
	Brace, Strap (Dwg. C11828569)				
	Examination for defects	10		3.2	4.4.2.15
	Salt spray test (Note 1)	10		3.2	4.5.4
	Bolt, Eye (Dwg. D11828570)				
	Examination for defects	10		3.2	4.4.2.16
	Hardness (Note 2)	10		3.2	4.5.3
	Salt spray test (Note 1)	10		3.2	4.5.4
	Strap Assembly (Dwg. F11828571)				
	Examination for defects	10		3.2	4.4.2.17
	Pintle (Weldment) (Dwg. D11828568)				
	Examination for defects	10		3.2	4.4.2.18
	Salt spray test (Note 1)	10		3.2	4.5.4

NOTES: Note 1: Any evidence of salt deposits or corrosion following completion of the salt spray test shall cause the sample to be classed defective.

Note 2: If any part fails to comply with the hardness requirement specified on the applicable drawing it shall be classed defective.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil - Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

TABLE I. FIRST ARTICLE INSPECTION.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63283A(AR)

PARAGRAPH	TITLE		SHEET 4 OF 5		DRAWING NUMBER
	Mount Assembly, Sub-Caliber, Universal: M179				See below
					NEXT HIGHER ASSEMBLY ---
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Bar, Cross (when applicable - See 6.5) (Dwg. 9335637)				
	Examination for defects	10		3.2	4.4.2.19
	Salt spray test (Note 1)	10		3.2	4.5.4
	Brace (when applicable - See 6.5) (Dwg. D9335639)				
	Examination for defects	10		3.2	4.4.2.20
	Salt spray test (Note 1)	10		3.2	4.5.4
	Bracket (when applicable - See 6.5) (Dwg. C9335640)				
	Examination for defects	10		3.2	4.4.2.21
	Salt spray test (Note 1)	10		3.2	4.5.4
	Wiring Harness Assembly (when applicable - See 6.5) (Dwg. B11828599)				
	Examination for defects	15		3.2	4.4.2.22
	Shim (when applicable - See 6.5) (Dwg. C11828600)				
	Examination for defects	10		3.2	4.4.2.23
	Salt spray test (Note 1)	10		3.2	4.5.4

NOTES:
1. Any evidence of salt deposits or corrosion following completion of salt spray test shall cause the sample to be classed defective.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete
Source: https://assist.dla.mil -- Downloaded: 2026-01-25T02:32Z
Check the source to verify that this is the current version before use.

TABLE I. FIRST ARTICLE INSPECTION.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE: Mount Assembly, Sub-Caliber, Universal: M179		SHEET 5 OF 5		DRAWING NUMBER: See below NEXT HIGHER ASSEMBLY: ---
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Mount Assembly, Sub-Caliber, Universal: M179 (Dwg. F11828578) Examination for defects	15		3.2	4.4.2.24

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil - Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

4.4. Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of Mount Assemblies shall contain:

a. Parts of one lot interfix number from one manufacturer.

b. Controller assemblies, Single Shot, of one lot interfix number from one manufacturer accepted in accordance with Supplementary Quality Assurance Provisions (SQAP) 8720102.

c. Solenoids of one lot interfix number from one manufacturer accepted in accordance with MIL-S-12109.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:32Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET OF		DRAWING NUMBER
4.4.2.1	Pull Cable Assembly		1 1		11828580
					NEXT HIGHER ASSEMBLY 11828578
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside diameter of cable loop at clip end, minimum (min)		0.65%	3.2	Gage
102	Burr, sliver or raised metal on handle		0.65%	3.8	Visual-Manual
103	Cable defective (cut at end of handle or cut or worn between clips)		0.65%	3.2	Visual
104	Part of clip missing or loose (2 clips)		0.65%	3.2	Visual-Manual
105	Pull Test	Note 1		3.2	4.5.1
Minor					
201	Outside width of handle across ends (6.62)		1.50%	3.2	Gage
202	Total height of handle (3.42)		1.50%	3.2	Gage
203	Outside diameter of handle pipe		1.50%	3.2	Gage
204	Inside radius of bends of handle		1.50%	3.2	Gage
205	Distance between cable loop and clip		1.50%	3.2	Gage
206	Length to clip (handle end) (8.37)		1.50%	3.2	Gage
207	Distance between clip and end of cable (1.00) (2 places)		1.50%	3.2	Gage
208	Length from handle to end loop (96.50)		1.50%	3.2	Scale
209	Incorrectly assembled		1.50%	3.2	Visual
210	Poor workmanship (excluding 102)		2.50%	3.8	Visual

NOTES:

1. Twenty (20) assemblies shall be selected from each lot for this test. If any assembly fails to comply with the breaking strength requirement, the lot shall be rejected.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63283A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11828588
4.4.2.2	Wiring Harness Assembly				NEXT HIGHER ASSEMBLY 11828578
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Total length		0.65%	3.2	Gage
102	Contact pin missing or damaged (pin bent)		0.65%	3.2	Visual
103	Cable damaged (cuts, frayed, insulation damaged, etc.)		0.65%	3.2	Visual
104	Terminal washer missing (female end)		0.65%	3.2	Visual
105	Sleeve missing (male end)		0.65%	3.2	Visual
106	Solder workmanship poor)		0.65%	Note 1	Visual
107	Continuity and resistance		Note 2	3.2	4.5.2
108	Female terminal assembly crimp missing or unsatisfactory		0.65%	3.2	Visual
Minor					
201	Poor workmanship (excluding 106)		2.50%	3.8	Visual

NOTES:
1. MIL-STD-1460, Section 5.3
2. This test shall be performed 100%. Any assembly which fails to comply with the specified requirement shall be classed defective and removed from the lot.

DRD\R-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Stud		11828560
			NEXT HIGHER ASSEMBLY 11828566

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter, min.		0.65%	3.2	Gage
102	Major diameter, min.		0.65%	3.2	Gage
103	Hardness	Note 1		3.2	4.5.3
Minor					
201	Length, min.		1.50%	3.2	Gage
202	Poor workmanship		2.50%	3.8	Visual

NOTES:
1. Five (5) studs shall be selected from each heat treat batch and subjected to the hardness test. If any stud fails to comply with the hardness requirement specified on the applicable drawing, the heat treat batch shall be rejected.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63283A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11828563
4.4.2.4	Block, Angle				NEXT HIGHER ASSEMBLY 11828566
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter thread		0.65%	3.2	Gage
102	Minor diameter, max		0.65%	3.2	Gage
103	Height of end of taper (.50)		0.65%	3.2	Gage
104	Distance between slot and side (1.75)		0.65%	3.2	Gage
105	Distance between slot and adjacent side (.75)		0.65%	3.2	Gage
Minor					
201	Width of slot, min		1.50%	3.2	Gage
202	Length of slot		1.50%	3.2	Gage
203	Distance between side and threaded groove		1.50%	3.2	Gage
204	Total length		1.50%	3.2	Gage
205	Total width		1.50%	3.2	Gage
206	Letters or figures incorrectly located, missing, or illegible		1.50%	3.2	Visual
207	Paint on angled surface or bottom		1.50%	3.2	Visual
208	Threads damaged		1.50%	3.2	Visual
209	Protective finish missing or damaged		1.50%	3.2	Visual
210	Poor workmanship		2.50%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63283A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Block, Stationary				11828565
					NEXT HIGHER ASSEMBLY 11828567
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of set screw groove, min (.43)		0.65%	3.2	Gage
102	Depth of set screw groove, min (.25)		0.65%	3.2	Gage
103	Width of insert recess (1.000)		0.65%	3.2	Gage
104	Length of insert recess		0.65%	3.2	Gage
105	Location of insert recess and set screw groove (.93)		0.65%	3.2	Gage
106	Pitch diameter of stud hole thread, max		0.65%	3.2	Gage
107	Minor diameter of stud hole thread, max		0.65%	3.2	Gage
Minor					
201	Pitch diameter of stud hole thread, min		1.50%	3.2	Gage
202	Location of stud hole from sides		1.50%	3.2	Gage
203	Height to top of taper (1.12)		1.50%	3.2	Gage
204	Width (2.00)		1.50%	3.2	Gage
205	Length		1.50%	3.2	Gage
206	Poor workmanship		2.50%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil - Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63283A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11828577
4.4.2.6	Insert				NEXT HIGHER ASSEMBLY 11828566
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness, max.		0.65%	3.2	Gage
102	Length, max.		0.65%	3.2	Gage
103	Width, max.		0.65%	3.2	Gage
104	Diameter groove, min.		0.65%	3.2	Gage
Minor					
201	Protective finish missing or damaged		1.50%	3.2	Visual
202	Chamfer missing (8)		1.50%	3.2	Visual
203	Poor workmanship		2.50%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER 11828567
4.4.2.7	Stud Block Assembly		NEXT HIGHER ASSEMBLY 11828566

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of hex screw hole threads, max, (2)		0.65%	3.2	Gage
102	Minor diameter of screw hole threads, max, (2)		0.65%	3.2	Gage
103	Insert recess length, min.		0.65%	3.2	Gage
104	Insert recess width, min.		0.65%	3.2	Gage
105	Insert recess depth, min.		0.65%	3.2	Gage
106	Location of "0" fix line		0.65%	3.2	Gage
107	Location of hex screw holes from sides and end (2)		0.65%	3.2	Gage
108	Weld unsatisfactory		0.65%	3.7	Visual
109	Crack in or near weld area		0.65%	3.7	Visual
110	Marking or stamping incorrect or unsatisfactory		0.65%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63283A(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 11828567
cont'd	Stud Block Assembly				NEXT HIGHER ASSEMBLY 11828566
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Block length, min (4.75)		1.50%	3.2	Gage
202	Block thickness, min. (.50)		1.50%	3.2	Gage
203	Diameter of set screw groove (.43)		1.50%	3.2	Gage
204	Location of groove		1.50%	3.2	Gage
205	Pitch diameter of screw hole threads, min (2)		1.50%	3.2	Gage
206	Protective finish missing or damaged		1.50%	3.2	Visual
207	Paint on block or angled surface		1.50%	3.2	Visual
208	Poor workmanship		2.50%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete.
Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63283A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER 11828564
4.4.2.8	Bracket (Weldment)		NEXT HIGHER ASSEMBLY 11828566

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Functional test (see Dwg note)		100%	3.2	Manual
102	Location of set screw slots (2)		0.65%	3.2	Gage
103	Distance between uprights for specified depth				
104	Diameter of upright hex screw holes, min (2)		0.65%	3.2	Gage
105	Pitch diameter threaded groove, max		0.65%	3.2	Gage
106	Minor diameter threaded groove, max		0.65%	3.2	Gage
107	Location of "o" fix line		0.65%	3.2	Gage
108	Weld unsatisfactory		0.65%	3.7	Visual
109	Crack in or near weld area		0.65%	3.7	Visual
110	Marking or stamping incorrect or unsatisfactory		0.65%	3.8	Visual
Minor					
201	Pitch diameter threaded groove, min		1.50%	3.2	Gage
202	Length of base plate, max		1.50%	3.2	Gage
203	Width of base plate, max		1.50%	3.2	Gage
204	Perpendicularity of uprights to specified surface		1.50%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil - Downloaded: 202610-23T02:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63283A(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 11828564
cont'd	Bracket (Weldment)				NEXT HIGHER ASSEMBLY 11828566
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
205	Distance between threaded groove and side of base		1.50%	3.2	Gage
206	Protective finish missing or damaged		1.50%	3.2	Visual
207	Paint on inner face of uprights or base bottom		1.50%	3.2	Visual
208	Poor workmanship		2.50%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:32Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63283A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11828566
4.4.2.9	T & E Assembly				NEXT HIGHER ASSEMBLY 11828578
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Part missing		0.65%	3.2	Visual
102	Part damaged		0.65%	3.2	Visual
103	Assembly improper		0.65%	3.2	Visual
104	Stud thread damaged		0.65%	3.2	Visual
105	Crack in weld or near weld area		0.65%	3.7	Visual
Minor					
201	Lettering or stamping illegible or missing		1.50%	3.8	Visual
202	Poor workmanship		2.50%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil - Downloaded: 202610-23T02:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63283A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11828572
4.4.2.10	Spacer				NEXT HIGHER ASSEMBLY 11833434
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Width		0.65%	3.2	Gage
102	Thickness		0.65%	3.2	Gage
Minor					
201	Length		1.50%	3.2	Gage
202	Poor workmanship		2.50%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63283A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 11828573
4.4.2.11	Brace				NEXT HIGHER ASSEMBLY 11833434
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Distance between largest hole and second smallest hole (12.25)		0.65%	3.2	Gage
102	Diameter of largest hole (1.000)		0.65%	3.2	Gage
103	Diameter of second smallest hole (.53)		0.65%	3.2	Gage
104	Diameter of smallest hole (.50)		0.65%	3.2	Gage
105	Location of three holes on midline (1.75)		0.65%	3.2	Gage
106	True position of four threaded holes		0.65%	3.2	Gage
107	Minor diameter of four threaded holes		0.65%	3.2	Gage
108	Distance between four threaded holes and side (.75)		0.65%	3.2	Gage
109	Distance between two threaded holes and end (1.50) (each pair)		0.65%	3.2	Gage
110	Distance between threaded holes and smallest hole (10.25)		0.65%	3.2	Gage
111	Vee notch missing from end		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63283A(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 11828573
cont'd	Brace				NEXT HIGHER ASSEMBLY 11833434
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Length, max.		1.50%	3.2	Gage
202	Width		1.50%	3.2	Gage
203	Distance from end to largest hole		1.50%	3.2	Gage
204	Thickness		1.50%	3.2	Gage
205	Poor workmanship		2.50%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63283A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11828574
4.4.2.12	Magazine				NEXT HIGHER ASSEMBLY 11833434
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length of braces, min (2) (1.00)		0.65%	3.2	Gage
102	Welds unsatisfactory		0.65%	3.7	Visual
103	Crack in weld or near weld area		0.65%	3.7	Visual
Minor					
201	Height, max.		1.50%	3.2	Gage
202	Inside length, min. (5.50)		1.50%	3.2	Gage
203	Inside width, min.		1.50%	3.2	Gage
204	Location of braces		1.50%	3.2	Gage
205	Poor workmanship		2.50%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63283A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 11828575
4.4.2.13	Saddle				NEXT HIGHER ASSEMBLY 11828578
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR (100%)	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Profile of part Including: Radius underside (1.00) (2 places), distance between vee notch and each end radius (6.6) Thickness (1.00) Angle of bend between middle hole and threaded hole (.43) (2)		0.65%	3.2	Gage
102	Pitch diameter of threaded hole (2)		0.65%	3.2	Gage
103	Minor diameter of threaded hole (2)		0.65%	3.2	Gage
104	Diameter of holes near middle (.656) (2)		0.65%	3.2	Gage
105	True position of holes near middle (2)		0.65%	3.2	Gage
106	Width (3.00)		0.65%	3.2	Gage
107	Vee notch missing		0.65%	3.2	Visual
108	Spot face missing from hole (4)		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63283A(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 11828575
cont'd	Saddle				NEXT HIGHER ASSEMBLY 11828578
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Width of slot (2) (.63)		1.50%	3.2	Gage
202	Depth of slot (2)		1.50%	3.2	Gage
203	Location of threaded holes (2)		1.50%	3.2	Gage
204	Finish on noted surfaces improper		1.50%	3.2	Visual
205	Poor workmanship		2.50%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63283A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11833434
4.4.2.14	Brace & Magazine (weldment)				NEXT HIGHER ASSEMBLY 11828578
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Perpendicularity of specified surface with surface "B" (zone C-4)		0.65%	3.2	Gage
102	Perpendicularity of specified surface with surface "B" (zone C-7)		0.65%	3.2	Gage
103	Part missing		0.65%	3.2	Visual
104	Part improperly assembled		0.65%	3.2	Visual
105	Weld improper or poor weld workmanship		0.65%	3.2 & 3.7	Visual
106	Crack in weld between brace and spacer, spacer and magazine, or brace, spacer and magazine and gusset (either side)		0.65%	3.7	Visual
Minor					
201	Height of magazine (7.12)		1.50%	3.2	Gage
202	Distance between magazine and brace end (3.31)		1.50%	3.2	Gage
203	Distance between gusset and end of magazine		1.50%	3.2	Gage
204	Protective finish missing or damaged		1.50%	3.2	Visual
205	Marking missing, incorrect or illegible		1.50%	3.2	Visual
206	Poor workmanship		2.50%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63283A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11828569
4.4.2.15	Brace, strap				NEXT HIGHER ASSEMBLY 11828571
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of hole, min		0.65%	3.2	Gage
Minor					
201	Radius, max		1.50%	3.2	Gage
202	Width of sides, max (4)		1.50%	3.2	Gage
203	Location of hole		1.50%	3.2	Gage
204	Protective finish missing or damaged		1.50%	3.2	Visual
205	Poor workmanship		2.50%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil - Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63283A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11828570
4.4.2.16	Bolt, Eye				NEXT HIGHER ASSEMBLY 11828571
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR ,100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter, min.		0.65%	3.2	Gage
102	Major diameter, min		0.65%	3.2	Gage
103	Width of eye, min.		0.65%	3.2	Gage
104	Threads damaged		0.65%	3.8	Visual
105	Hardness	Note 1	---	3.2	4.5.3
106	Crack in weld or near weld area		0.65%	3.7	Visual
Minor					
201	Length thread face to eye, min		1.50%	3.2	Gage
202	Thread length		1.50%	3.2	Gage
203	Weld unsatisfactory		1.50%	3.7	Visual
204	Protective finish missing or damaged		1.50%	3.2	Visual
205	Poor workmanship		2.50%	3.8	Visual

NOTES: 1. Five (5) eye bolts shall be selected from each heat treat batch and subjected to the hardness test. If any bolt fails to comply with the hardness requirement specified on the applicable drawing, the heat treat batch shall be rejected.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11828571
4.4.2.17	Strap Assembly				NEXT HIGHER ASSEMBLY 11828578
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Flange weld unsatisfactory		0.65%	3.7	Visual
102	Improperly assembled		0.65%	3.2	Visual
103	Nut or brace missing (either end)		0.65%	3.2	Visual
104	Tensile test	Note 1		3.2	4.5.5
105	Crack in weld or near weld area		0.65%	3.7	Visual
Minor					
201	Distance between bolts, min		1.50%	3.2	Gage
202	Poor workmanship		2.50%	3.8	Visual

NOTES:
1. Twenty (20) assemblies shall be selected from each lot for this test. If any assembly fails to comply with the specified requirements, the lot shall be rejected.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 11828568
4.4.2.18	Pintle (Weldment)				NEXT HIGHER ASSEMBLY 11828578
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of base hole, min.		0.65%	3.2	Gage
102	Distance between side plates, min (see note 5)		0.65%	3.2	Gage
103	Perpendicularity of specified sides to datum A		0.65%	3.2	Gage
104	Diameter of side plate holes, min (2)		0.65%	3.2	Gage
105	Location of side plate holes (1.50) (2)		0.65%	3.2	Gage
106	True position of side plate holes (2)		0.65%	3.2	Gage
107	Location of base hole		0.65%	3.2	Gage
108	Functional test (see dwg. note)		0.65%	3.2	Manual
109	Total height		0.65%	3.2	Gage
110	Weld unsatisfactory		0.65%	3.7	Visual
111	Crack in weld or near weld area		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:32Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63283A(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 11828568
cont'd	Pintle (Weldment)				NEXT HIGHER ASSEMBLY 11828578
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Width, max (3.37)		1.50%	3.2	Gage
202	Length, max (3.00)		1.50%	3.2	Gage
203	Height of weldment, max.		1.50%	3.2	Gage
204	Protective finish missing or damaged		1.50%	3.2	Visual
205	Paint on bottom of base		1.50%	3.2	Visual
206	Finish on specified surface of sides improper		1.50%	3.2	Visual
207	Protective finish onprohibited area (see note 5)		1.50%	3.2	Visual
208	Poor workmanship (excluding 111)		2.50%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63283A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9335637
4.4.2.19	Bar, Cross (Note 1)				NEXT HIGHER ASSEMBLY 11828578
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter, brace mounting holes (.766) (8)		0.65%	3.2	Gage
102	True position of brace mounting holes (8)		0.65%	3.2	Gage
103	Diameter brace and magazine mounting holes (.650) (2)		0.65%	3.2	Gage
104	True position of brace and magazine mounting holes (2)		0.65%	3.2	Gage
105	Length		0.65%	3.2	Gage
106	Distance between brace mounting holes and middle (5.87) (4)		0.65%	3.2	Gage
107	Distance between holes and side (1.00) (10)		0.65%	3.2	Gage
108	Location of brace and magazine mounting holes from middle (1.00) (2)		0.65%	3.2	Gage
Minor					
201	Width		1.50%	3.2	Gage
202	Marking missing, incorrect or illegible		1.50%	3.2	Visual
203	Protective finish missing or damaged		1.50%	3.2	Visual
204	Poor workmanship		2.50%	3.8	Visual

NOTES:

1. When applicable (See 6.5)

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9335639
4.4.2.20	Brace (Note 1)				NEXT HIGHER ASSEMBLY 11828578
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of holes (3)		0.65%	3.2	Gage
102	Location of holes from side (1.00) (3)		0.65%	3.2	Gage
103	Location of lower hole from end (1.00)		0.65%	3.2	Gage
104	True position of hole		0.65%	3.2	Gage
105	Height (7.37)		0.65%	3.2	Gage
106	Parallelism of specified surfaces		0.65%	3.2	Gage
Minor					
201	Length (20.75)		1.50%	3.2	Scale
202	Width (2.00)		1.50%	3.2	Gage
203	Protective finish missing or damaged		1.50%	3.2	Visual
204	Poor workmanship		2.50%	3.8	Visual

NOTES:

1. When applicable (See 6.5)

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil - Downloaded: 202640-23T02:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63283A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9335640
4.4.2.21	Bracket (Note 1)				NEXT HIGHER ASSEMBLY 11828578
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter end holes (2) (.656)		0.65%	3.2	Gage
102	Diameter center hole (.766)		0.65%	3.2	Gage
103	True position of end holes		0.65%	3.2	Gage
104	True position of middle hole		0.65%	3.2	Gage
Minor					
201	Location of end holes		1.50%	3.2	Gage
202	Width (3.50)		1.50%	3.2	Gage
203	Length		1.50%	3.2	Gage
204	Protective finish missing or damaged		1.50%	3.2	Visual
205	Poor workmanship		2.50%	3.8	Visual

NOTES:
1. When applicable (See 6.5)

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11828599
4.4.2.22	Wiring Harness Assembly for M1 to M179) (Note 1)				NEXT HIGHER ASSEMBLY 11828578
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Continuity and resistance		Note 2	3.2	4.5.2
102	Length		0.65%	3.2	Gage
103	Any component missing or damaged (including cable insulation)		0.65%	3.2	Visual
104	Crimp of lug or terminal assembly missing or unsatisfactory		0.65%	3.2	Visual
105	Solder workmanship poor		0.65%	Note 3	Visual
Minor					
201	Poor workmanship (excluding 105)		2.50%	3.8	Visual

Note 1. When applicable (See 6.5)
Note 2. This test shall be performed 100%. Any assembly which fails to comply with the specified requirement shall be classed defective and removed from the lot.
Note 3. See MIL-S-45743.

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63283A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11828600
4.4.2.23	Shim (Note 1)				NEXT HIGHER ASSEMBLY 11828578
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Width of cutouts (2)		0.65%	3.2	Gage
102	True position of cutouts (2)		0.65%	3.2	Gage
103	Distance between cutouts and side (.75) (2)		0.65%	3.2	Gage
Minor					
201	Length (3.50)		1.50%	3.2	Gage
202	Protective finish missing or damaged		1.50%	3.2	Visual
203	Poor workmanship		2.50%	3.8	Visual

NOTES:

1. When applicable (See 6.5)

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63283A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11828578
4.4.2.24	Mount Assembly, Sub-Caliber, Universal: M179				NEXT HIGHER ASSEMBLY ——
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Screw or nut loose		0.65%	3.2	Manual
102	Part missing		0.65%	3.2	Visual
103	Incorrectly assembled		0.65%	3.2	Visual
104	Part damaged (crack in or near weld area, etc.)		0.65%	3.2 & 3.7	Visual
Minor					
201	Protective finish damaged (bare areas)		1.50%	3.2	Visual
202	Marking or stamping missing or unidentifiable		1.50%	3.2	Visual
203	Slivers or sharp edges		1.50%	3.8	Visual
204	Evidence of corrosion on coated part		1.50%	3.8	Visual
205	Poor workmanship (excluding 104)		2.50%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil - Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the Paragraph/Inspection Method column in the tables starting with Paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.2 herein.

4.5 Test methods and procedures.

4.5.1 Pull test of pull cable assembly. The pull test shall be performed as specified on the applicable drawing. Test procedures and equipment shall have prior approval of the Government.

4.5.2 Continuity and resistance test of wiring harness assembly. The continuity and resistance test shall be performed as specified on the applicable drawing. Test procedures and equipment shall have prior approval of the Government.

4.5.3 Hardness. This test shall be performed as specified in ASTM E 18. Each heat treat batch shall remain segregated until completion of all required tests.

4.5.4 Salt spray test (first article only). This test shall be performed as specified in ASTM B 117. Test procedures and equipment shall have prior approval of the Government.

4.5.5 Tensile test of strap assembly. The strap assembly shall be subjected to the tensile test specified on the applicable drawing. Test procedures and equipment shall have prior approval of the Government.

5. PACKAGING

5.1 Preservation, packaging and packing. The mount assembly, and the associated parts and assemblies specified on Dwg. F11828578, shall be preserved, packaged and packed in accordance with Packaging Data Sheet (PDS) 11828578.

5.2 Marking. Marking of the packaging and packing shall be in accordance with PDS 11828578.

5.3 Shipping. When components from more than one lot are shipped at one time, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. See MIL-A-48078.

6.2 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs as required to Commander, ARRADCOM, ATTN: DRDAR-QAA-I, Dover, NJ 07801. Request letter of submittal state contractor, contract number, specification number, item nomenclature and classification of defects and test paragraph.

6.3 Submission of results of contractor-conducted examinations and tests. Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of examinations or tests to: Commander, ARRADCOM, ATTN: DRDAR-QAA-S, Dover, NJ 07801.

6.4 Data cards. (See MIL-A-48078). When data cards are required, their distribution shall include the address specified in 6.3.

6.5 Mantlet mounting. Drawings and quality assurance requirements in this document relative to mantlet mounting apply only when the contract includes these parts.

6.6 Drawings. Drawings and SQAP's listed in Section 2 of this specification under the heading "US Army Armament Research and Development Command" (ARRADCOM) may also include drawings and SQAP's prepared by and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities are now under the cognizance of ARRADCOM.

6.7 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

Project 1005-A606

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:32Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament R&D Command
ATTN: DRDAR-QAT-M
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE MIL-M-63283A (AR): Mount Assembly, Sub-Caliber, Universal: M179 (Including Mantlet Adapter Assembly)

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:32Z
Check the source to verify that this is the current version before use.