MIL-STD-1391C

5 October 1984

SUPERSEDING
MIL-STD-1391B
23 May 1977

MILITARY STANDARD

PROVISIONS FOR EVALUATING QUALITY OF

OVERCOATS, MEN'S

FSC 8405

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF DEFENSE

WASHINGTON, D. C. 20301

Provisions for Evaluating Quality of Men's Overcoats

MIL-STD-1391

1. This Military Standard is approved for use by all Departments and Agencies of the Department of Defense.

2. Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Officer in Charge, Navy Clothing and Textile Research Facility, 21 Strathmore Road, Natick, MA 01760-2490 by using the self-addressed Standardization Document Improvement Proposed (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

FOREWORD

This standard provides a standardized procedure for evaluating quality of overcoats procured by the Department of Defense.

The objectives of this standard are to:

a. Provide standard descriptions for defects.
b. Standardize examination requirements.
c. Reduce the size of each specification.

Specifications for overcoats in this standard are:

MIL-O-2414(NU)	- Overcoat, Man's, Enlisted
MIL-O-19664(MC)	- Overcoat, Man's, Wool, Serge, Green
MIL-O-43537(GL)	- Overcoat, Man's, Wool, Army Green 44, With Removable Liner
MIL-O-82250(NU)	- Overcoat, Man's (Officer's Type)

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

CONTENTS

PARAGRAPH		PAGE
1.	SCOPE	1
1.1	Purpose	1
1.2	Application	1
1.2.1	Model form	1
2.	REFERENCED DOCUMENTS	1
2.1	Issues of documents	1
3.	DEFINITIONS	2
3.1	Fabric Defects	2
3.2	Knots and Slubs	2
3.3	Quality Assurance Terms	2
3.4	Open Seam	2
3.5	Defective Button	2
3.6	Outside-Inside	2
3.7	Raw Edge	2
4.	GENERAL	2
5.	SAMPLE AND INSPECTION PROVISIONS	3
5.1	End Item Examination	3
5.2	Dimensional Examination	3
5.3	Packaging Inspection	3
6.	INSPECTION	5
6.1	Initiation of Inspection	5
6.2	Continuation of Inspection	5
6.3	Switching Procedures	5
6.3.1	Normal to Tightened	5
6.3.2	Tightened to Normal	5
6.3.3	Normal to Reduced	6
6.3.4	Reduced to Normal	6

TABLES

NUMBER		PAGE
I	Sampling Provisions	4
II	Classification of Defects	6
III	Selected Defects	30

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 Purpose.- The purpose of this standard is to provide standardized provisions for evaluating the quality of overcoats.

1.2 Application.- This standard will be made applicable to contracts by references in the appropriate overcoat specifications. These documents require: (a) as a final step in the contractors production control plan before formation of a lot, each overcoat shall be buttoned on a model form and examined for selected defects and (b) an overcoat containing a selected defect shall not be included in the end item lot. Selected defects are those defects listed in Table II as asterisk (*) in the point value column. The selected defects are also listed individually in Table III.

1.2.1 Model form. The model forms (for the selected defects examination specified in 1.2, and for examination of defects XI through XXVIII in table II, Classification of defects) shall be men's forms conforming to the measurements specified below. The coat sizes listed shall be examinaed on the appropriate model form size as specified below.

	Model form			
Overcoat size	Model form size	Chest 1/	Waist 1/	Seat-Hip 1/
30, 31	30	32	26	32
32, 33	32	34	28	34
34, 35	34	36	30	36
36, 37	36	38	32	38
38, 39	38	40	34	40
40, 41	40	42	36	42
42, 43	42	44	38	44
44, 45	44	46	40	46
46, 47	46	48	42	48
48, 50	48	50	44	50

1/ Tolerances (+ 1/2 inch)

2. REFERENCED DOCUMENTS

2.1 Issues of documents.- The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this standard to the extent specified herein.

STANDARD

FEDERAL

FED-STD-4 - Glossary of Fabric Imperfections

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

MIL-STD-109 - Quality Assurance Terms and Definitions

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. DEFINITIONS

3.1 Fabric defects.- The fabric defect definitions applicable to the standard are described in FED-STD-4.

3.2 Knots and slubs.- Only knots and slubs that exceed the limits specified in the basic cloth specification shall be scored as defects in evaluating quality of the overcoat.

3.3 Quality assurance terms.- Definitions of quality assurance terms shall be in accordance with MIL-STD-105 and MIL-STD-109.

3.4 Open seam.- The seam shall be classified open when one or more stitches joining a seam are broken or when two or more continuous skipped or runoff stitches occur. Double stitched seams are considered open when one or both rows of stitching are open.

3.5 Defective button.- A button shall be considered defective when it has a sharp, rough, cracked or split edge; scratches, dent, blemishes, imbedded foreign matter, loose shank, loose shell; badly shaded or poorly plated.

3.6 Outside-inside.- The terms "outside" and "inside" as used in this standard for defects I, II and IV are defined as follows:

Outside - Any part of overcoat that is visible when the completely buttoned overcoat is observed on the model form (including undersleeve)

Inside - Any part of overcoat that is not visible when the completely buttoned overcoat is observed on the model form.

The terms "outside" and "inside" as used in this standard for any defects other than I, II and IV are defined as follows:

Outside - Any part, seam or stitching that appears on the outer overcoat. This includes under the collar (including undercollar), under the shoulder loops, under the pocket flaps and in the back vent.

Inside - Any part, seam or stitching that does not appear on the outer overcoat.

3.7 Raw edge.- A raw edge is defined as any edge not finished as specified including any protruding edge on the outside of the overcoat.

4. GENERAL

4.1 This standard contains the provisions for end item examination, dimensional examination and the packaging inspection for overcoats. If there are any inconsistencies between the requirement of the appropriate specification and the provisions of the standard, the specification shall control. This standard

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

assigns to the listed defects, point values of 1, 2 or 3 depending on degree of severity. The higher point values are assigned to those defects having more detrimental effect on the appearance or serviceability of the item. The defects indicated by an asterisk (*) in the Point Value column of Table II are those defects having the most detrimental effect on appearance or serviceability of the item.

5. SAMPLE AND INSPECTION PROVISIONS

5.1 End item examination.- The overcoats shall be examined and all defects shall be penalized as indicated in table II of this standard. The sample size shall be as specified in Table I. The sample unit shall be one finished overcoat. The lot shall be unacceptable if:

a. The point value for 3 & 2 point defects exceeds the applicable maximum acceptable point value

OR

b. The point value for total (3, 2 & 1 point) defects exceeds the applicable maximum acceptable point value

OR

c. The number of selected defects (asterisk * defect) exceeds the maximum allowed for the sample size (see Table I).

5.2 Dimensional examination.- The appropriate number of overcoats determined from the table below, shall be examined for conformance to the dimensional requirements cited in the table of measurements of the appropriate overcoat specification. When a measurement deviates from a dimension and tolerance specified, the overcoat shall be penalized one point. Each sample unit shall also be penalized one point when the sleeves are uneven in length by 1/2 inch (12.70 mm) or more. The lot shall be unacceptable if the total point value resulting from this examination exceeds the maximum acceptable point value. Each size of overcoat present in the lot shall be represented in the sample selected for this examination.

Dimensional Examination Sampling Provisions

Lot Size	Sample Size	Maximum Acceptable Point Values
Up thru 500	8	0
501 thru 3200	13	1
3201 thru 35,000	20	2
35,001 and up	32	3

5.3 Packaging inspection.- An examination shall be made to determine that preservation packaging, packing and marking requirements are in compliance with section 5 of the appropriate specification. Defects listed below shall be scored one point. The sample size for this examination shall be five shipping containers fully prepared for delivery with the exception that they need not be closed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot shall be unacceptable if one or more points are scored for this examination.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect, illegible; of improper size, location, sequence or method of application.
Materials	Any component missing, damaged, or not as specified.
Workmanship	Inadequate application of components, such as; incomplete closure of container flaps, loose strapping, improper taping, inadequate stapling. Bulged or distorted container.
Content	Number of intermediate packages or overcoats per shipping container is more or less than required. Number of overcoats per intermediate package is more or less than required. 1/ Size shown on one or more overcoats not as specified on shipping container. 1/

1/ For this defect, one intermediate package from each shipping container in the sample shall be examined.

Table I - Sampling Provisions

	Lot size	Sample size	Maximum Acceptance Number for Selected Defects (*defect)	Maximum Acceptable Point Value: 3 & 2 point defects	Maximum Acceptable Point Value: 3,2,& 1 point defects
Normal Inspection	Up thru 90	20	0	5 points	11 points
	91 thru 150	32	0	7 points	17 points
	151 thru 280	50	0	11 points	22 points
	281 thru 500	80	0	14 points	31 points
	501 thru 1200	125	1	23 points	44 points
	1201 thru 3200	200	1	29 points	60 points
	3201 thru 10,000	315	2	42 points	91 points
	10,001 thru 35,000	500	3	60 points	135 points
	35,001 and over	800	5	91 points	203 points
Tightened Inspection	Up thru 90	20	0	4 points	8 points
	91 thru 150	32	0	5 points	12 points
	151 thru 280	50	0	8 points	17 points
	281 thru 500	80	0	11 points	23 points
	501 thru 1200	125	1	17 points	35 points
	1201 thru 3200	200	1	22 points	52 points
	3201 thru 10,000	315	2	36 points	77 points
	10,001 thru 35,000	500	3	54 points	115 points
	35,001 and over	800	5	81 points	173 points

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

Table I - Sampling Provisions (cont'd)

	Lot size	Sample size	Maximum Acceptance Number for Selected Defects (*defect)	Maximum Acceptable Point Value	
				3 & 2 point 1/ defects	3, 2,& 1 point defects
Reduced Inspec-tion	Up thru 280	20	0	3-7 points	11 points
	281 thru 500	32	0	6-12 points	20 points
	501 thru 1200	50	0	10-16 points	24 points
	1201 thru 3200	80	0	12-21 points	39 points
	3201 thru 10,000	125	1	21-30 points	52 points
	10,001 thru 35,000	200	1	27-37 points	77 points
	35,001 and over	315	2	37-48 points	115 points

1/ If the first value is exceeded but the second value has not been exceeded, accept the lot but reinstate normal inspection (see 6.3.4b). The second value is the maximum acceptable point value.

6. INSPECTION.- Inspection shall be as specified in MIL-STD-105, except where otherwise indicated in this document.

6.1 Initiation of inspection.- Normal inspection will be used at the start of inspection unless otherwise directed by the procurement quality assurance element administrating the contract.

6.2 Continuation of inspection.- Normal, tightened or reduced inspection shall continue unchanged on successive lots except where switching procedures in 6.3 require change.

6.3 Switching procedures

6.3.1 Normal to tightened.- When normal inspection is in effect, tightened inspection shall be instituted when two out of five consecutive lots have been rejected on original inspection (i.e., ignoring resubmitted lots for this procedure).

6.3.2 Tightened to normal.- When tightened inspection is in effect, normal inspection shall be instituted when five consecutive lots have been considered acceptable on original inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

6.3.3 Normal to reduced.- When normal inspection is in effect, reduced inspection shall be instituted providing that all of the following conditions are satisified:

a. The preceding 10 lots have been on normal inspection and none have been rejected on original inspection; and

b. The total number of points for 3 and 2 point defects in the sample from the preceding 10 lots is equal to or less than sixty percent of the total maximum acceptable point values for 3 or 2 point defects from the preceding 10 lots; and

c. The total number of points for 3, 2 and 1 point defects in the sample from the preceding 10 lots is equal to or less than seventy-five percent of the total maximum acceptable point values for 3, 2 and 1 point defects from the preceding 10 lots; and

d. Production is at a steady rate; and

e. Reduced inspection is considered desirable by the procurement quality assurance element administrating the contract.

6.3.4 Reduced to normal.- When reduced inspection is in effect, normal inspection shall be instituted if any of the following occur on original inspection:

a. A lot is rejected; or

b. A lot is considered acceptable but exceeds the applicable first value (see 1/ to table I); or

c. Production becomes irregular or delayed; or

d. Other conditions warrant that normal inspection be instituted.

Table II - Classification of Defects

A. GENERAL DEFECTS	Point Value
I. MATERIAL DEFECT AND WORKMANSHIP DAMAGE	
a. Hole, cut, tear, smash, mend, burn, scorched area or open place:	
1. On outside	3
2. On inside or on liner longest dimension in any direction:	
(a) -up to 1/4 inch (6.35mm) inclusive	1
(b) -more than 1/4 inch (6.35mm)	2

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

Table II - Classification of Defects (cont'd)

	Point Value
I. MATERIAL DEFECT AND WORKMANSHIP DAMAGE (cont'd)	
b. Loose yarn, snagged thread, misweave, area of no dye penetration, dye streak, missing yarn, broken yarn, thin place, shade bar or woven in waste; more than 1/4 inch (6.35mm) (largest dimension in any direction):	
1. On outside	2
2. On liner	1
c. Permanent fold, pleat or crease in cloth (when caught in seaming or stitching):	
1. On outside	3
2. On liner	1
d. Needle chew on outside	
1. Up to 1/4 inch (6.35mm) inclusive	2
2. More than 1/4 inch (6.35mm)	3
e. Knot or slub (see 3.2 on outside)	2
II SHADED PART	
a. On outside:	
1. Any part shaded (except parts which may be cut from ends)	3
2. Variation in shade within a part (except parts which may be cut from ends)	3
3. Part cut from ends badly shaded	1
4. Undercollar parts not matching each other	1
b. On inside or liner:	
1. Any part badly shaded (except sleeve linings)	1
2. Sleeve lining part badly shaded, pairs not matching each other	1
III PRESSING (Overcoat, with or without liner)	
a. Omitted or poorly pressed (unless otherwise classified)	2
b. Excess gloss	1
c. Lapel, front or collar edge bulky, or not pressed solid	1
d. Lapels not roll pressed	1
e. Armhole seam not pressed open across top (when applicable)	2

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

Table II - Classification of Defects (cont'd)

	Point Value
III PRESSING (Overcoat, with or without liner) (cont'd)	
f. Wrinkle, crease or basting thread or ticket impression not removed	1
g. Sleeve not roll pressed or creased	2
h. Armhole stretched	3
i. Collar breakline not creased as specified	1
j. Armhole not blocked or poorly blocked	1
k. Body, liner or lining, front darts, yoke, or pleats, back pleats, and bellows pleat not pressed smooth and flat	1
l. Inside of armhole not creased or not creased solid	1
m. Pressing impressions under lapels, collar, pocket welts or flaps, half belt sections and vent not removed	1
n. One or more seams not pressed open or not turned to the side specified	1
o. Belt not pressed	1
IV CLEANNESS	
a. Spot or stain on outside (largest dimension in any direction):	
1. -up to 3/8 inch (9.52mm) inclusive	1
2. -more than 3/8 inch (9.52mm) up to 3/4 inch (19.05mm) inclusive	2
3. -more than 3/4 inch (19.05mm)	3
b. Any marking exposed or visible on outside	3
c. More than 3 ends not trimmed to 1/4 inch or less on outside	2
d. More than 5 ends not trimmed to 1/4 inch or less on inside	2
e. Two or more shade or size tickets on overcoat	1
f. Basting thread (including monofilament thread or fragments of monofilament thread) not completely removed from outside	1
V COMPONENT AND ASSEMBLY	
a. Any component part or operation omitted (unless otherwise classified herein)	3
b. Any component not as specified (type, size, color, etc)	3
c. Any component part tight, twisted, distorted, pleated or full (unless otherwise classified herein)	2
d. Any operation not as specified (unless otherwise classified herein)	1
e. The edge of any component part required to be forced out having folds of more than 1/8 inch (3.17mm) (unless otherwise classified herein)	2
f. Any wool parts assembled with the face side on the underside (unless otherwise specified)	3
g. Any inside part assembled with the face side (as specified) on the underside	1

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

Table II - Classification of Defects (cont'd)

	Point Value
VI CUTTING	
a. Any component part not cut in accordance with specified pattern, directional lines on patterns or not in accordance with specification requirements	3
b. Twill line of any outside part not running in specified direction	3
c. Any outside component part not cut in the same direction of nap	3
VII SEAM AND STITCHING	
a. Accuracy of seaming:	
1. Seam puckered (unless otherwise classified herein)	1
2. Seam irregular, pleated or wavy (unless otherwise classified herein)	2
3. Part of overcoat or liner caught in any unrelated operation or stitching	2
4. Blindstitching, tacking or hand felling of armhole exposed on outside	1
5. Machine felling or hand felling (other than around armhole) exposed for a distance of 3/8 inch (9.52mm) or more	1
6. End of stitching when not caught in another seam or stitching not finished as specified	1
7. Stitching overlapping end of thread break less than 1/2 inch (12.70mm)	1
8. End of a continuous line of stitching overlapped less than 1/2 inch (12.70mm) (except labels)	1
9. Not specified color thread used on outside	2
10. Needle perforations visible on outside	2
b. Gage of stitching and seam allowance:	
1. Edge, top or raised stitching sewn too close to edge resulting in damage to cloth	3
2. Width of seam allowance not as specified by 1/16 inch (1.58mm) or more. (score only when condition exists on more than 1/2 the length of the seam)	1
3. Irregular or not within range specified or varies more than 1/16 inch (1.58mm) when no range is specified. (score only when condition exists on more than 1/2 the length of the seam)	1

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

Table II - Classification of Defects (cont'd)

	Point Value
VII SEAM AND STITCHING (cont'd)	
c. Open seam (see para. 3.4)	
1. On outside (excluding lower edge of undercollar):	
(a) -more than 3/4 inch (19.05mm)	3
(b) -more than 1/2 inch (12.70mm) up to 3/4 inch (19.05mm) inclusive	2
(c) -up to 1/2 inch (12.70mm) inclusive	1
2. On inside and liner machine felling and hand felling (other than hand felling around armhole)	
(a) -more than 3/4 inch (19.05mm) up to 2 inches (5.08cm) (inclusive)	1
(b) -more than 2 inches (5.08cm)	2
3. On inside and liner: stitch type 301 and hand felling around armhole	
(a) -up to 2 inches (5.08cm) inclusive	1
(b) -more than 2 inches (5.08cm)	2
d. Raw edge:	
1. On outside (excluding permitted raw edges):	
(a) -up to 1/2 inch (12.70mm) inclusive	1
(b) -more than 1/2 inch (12.70mm) up to 3/4 inch (19.05mm) inclusive	2
(c) -more than 3/4 inch (19.05mm)	3
2. On inside and liner (excluding raw edge of binding not required to be turned under)	
(a) 3/8 inch (9.52mm) up to 2 inches (5.08cm) inclusive	1
(b) more than 2 inches (5.08cm)	2
e. Seam and stitch type:	
1. Not specified seam or stitch type	3
2. Any line of stitching omitted or insecure	2
3. Any line of stitching not beginning or ending where specified (unless otherwise classified herein)	1
4. Looper thread of 401 stitch type on outside	3

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

Table II - Classification of Defects (cont'd)

	Point Value
VII SEAM AND STITCHING (cont'd)	
f. Stitch tension:	
1. Loose tension resulting in a loose seam:	
(a) -up to 1/2 inch (12.70mm) inclusive	1
(b) -more than 1/2 inch (12.70mm) up to 3/4 inch (19.05mm) inclusive	2
(c) -more than 3/4 inch (19.05mm)	3
2. Loosely exposed loops of lower or top thread on edge, top or raised stitching	2
3. Tight tension (stitches break when normal strain is applied in the direction of the seam or stitching)	3
g. Stitches per inch (score only when condition exists on more than 1/2 the length of seam):	
1. -more than the maximum specified	1
2. -less than the minimum specified:	
(a) by one or two stitches	1
(b) by three or more stitches	2
h. Runoff, skipped or broken stitch:	
1. Joining seam - use (Open seam) classification	-
2. Edge, top or raise stitching (more than 1/4 inch) (6.35mm)	1
i. Bartack, backtack, tack or tacking (except buttonhole bartack):	
1. Missing, insecure, misplaced, not serving intended purpose or not specified size or type	1
2. Loose stitch tension	1
VIII BUTTONHOLE	
a. Misplaced or not positioned as specified	3
b. Omitted, added, not specified type or not finished as specified	3
c. Gimp omitted; uncut; finished length not as specified or end of gimp not pulled through to underside	2

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

Table II - Classification of Defects (cont'd)

	Point Value
VIII BUTTONHOLE (cont'd)	
d. Incomplete stitching, stitching not securely caught in fabric, bulky appearance or stitches not uniform	2
e. Ragged edges, i.e., yarn or thread on inside of buttonhole not trimmed to less than 1/4 inch	2
f. Broken stitch or two or more skipped stitches	2
g. Buttonhole stitching extending beyond bartack	2
h. Bartack missing, loose or misplaced (not serving intended purpose)	2
i. Stitches per buttonhole or bartack less than specified by:	
1. -one to three stitches	1
2. -four or more stitches	2
j. Buttonhole stitching not covering gimp for a distance of more than 1/8 inch (3.17mm)	1
k. Ends of buttonhole in bartack area are uneven in length by more than 1/8 inch (3.17mm)	2
IX BUTTONS (see para. 3.5)	
a. Omitted, broken or defective	2
b. Part of garment pleated or puckered by button sewing	1
c. Misplaced, loose; not attached as specified; or insecurely sewn	1
d. Tacking stitches omitted or insecure (hand sewn)	1
e. Button sewn with eagle or anchor in other than specified direction	1
f. Shank wrapping (when required) omitted, loosely wrapped or not specified shank length	2
g. Stitching on button not locked at end of cycle (tug at loose end of the thread when accessible to determine whether it will ravel)	1
X BUTTON LOOP	
a. Omitted or insecure	1
b. Misplaced or not attached as specified	2
c. Length or width not as specified	1

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

Table II - Classification of Defects (cont'd)

	Point Value
B. DETAILED DEFECTS (OVERCOAT BUTTONED ON FORM)	
XI ALIGNMENT OF BUTTONS, (INCLUDING ANCHOR BUTTON, BUTTONHOLES AND BUTTON LOOPS)	
a. Not aligned, causing a bulge or twist when buttoned:	
1. On front	2
2. On half belt or tab for sleeve, collar, vent or lapel	1
b. Button on left front not in horizontal alignment with corresponding button on right front by:	
1. More than 1/2 inch (12.70mm), but not more than 1 inch (2.54cm), inclusive	2
2. More than 1 inch (2.54cm)	3
c. Spacing between front buttonholes varying more than 1/4 inch (6.35mm)	1
XII LENGTH OF BUTTONED FRONTS	
a. Left front shorter than right front at bottom corner by:	
1. More than 1/4 inch (6.35mm) to 1/2 inch (12.70mm) inclusive	1
2. More than 1/2 inch (12.70mm)	2
b. Left front bottom corner longer than right front at bottom by:	
-More than 1/2 inch (12.70mm)	1
c. Bottom corner of right front exposed below bottom edge of left front by:	
1. More than 1/4 inch (6.35mm) to 1/2 inch (12.70mm) inclusive	1
2. More than 1/2 inch (12.70mm)	2
d. Fronts uneven at neck when buttoned by more than 1/4 inch (6.35mm)	2

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

Table II - Classification of Defects (cont'd)

	Point Value
XII CONSTRUCTION OF FRONTS	
a. Front not properly shaped or constructed causing left front to swing to the right or left by more than 2 inches (5.08cm) from an imaginary perpendicular line drawn from forward edge of top button to bottom of overcoat with overcoat buttoned (measure horizontally at bottom of coat from imaginary line to front edge of left front)	2
b. Left front rolling outward below bottom front button, when buttoned	2
c. Fronts puckered, twisted or not smooth, having a wavy appearance	3
XIV FRONT FACING	
a. Short, tight, or twisted, causing puckers or twist on fronts	3
b. Long, causing bottom corner of front to curl up	3
c. Exposed along edge of left front	1
d. Fullness on facing between buttons and buttonholes or between buttonhole or buttons and front edge	1
e. Tacking at back edge of facing to interlining omitted or insecure	1
f. Front exposed along facing at lapel edge (facing seam not rolled to the underside	2
XV COLLAR (construction and setting)	
a. Collar setting	
1. Short, i.e., causing puckers on back or front along edge of collar or pulling lapel breakline causing front to roll out	3
2. Long, i.e., setting away from neck collar not fitting neck, or lapel rolling higher than 2 inches (5.08cm) above top front button or buttonhole when measured along front edge	3
3. Collar not properly set, causing a curve or bulge on creaseline at joining to gorge seam	3
4. Tight at joining to gorge seam of front or facing or undercollar across back causing fullness on lapel or fullness or pleat across outside of back	2
5. Collar off center by more than 1/4 inch (6.35mm) with shoulder seam matching	2

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

Table II - Classification of Defects (cont'd)

	Point Value
XV COLLAR (construction and setting) (cont'd)	
b. Collar edge	
1. Collar edge short across shoulders, causing collar to rise above creaseline by:	
a. More than 1/4 inch (6.35mm) to 1/2 inch (12.70mm) inclusive	2
b. More than 1/2 inch (12.70mm)	3
2. Irregular or wavy	1
3. Outer edge of undercollar exposed beyond outer edge of top collar (score only when condition exists on more than 1/2 the length of seam)	2
4. Undercollar edge more than 1/8 inch (3.17mm) from topcollar edge (score only when condition exists on more than 1/2 the length of seam)	1
5. Collar edge short across shoulders causing distortion or pulling on topcollar	2
c. Topcollar	
1. Tight, i.e., causing edges to curl or bulge on undercollar	2
2. Twisted, i.e., having a diagonal twist	3
3. Full, i.e., having puckers or pleats	3
4. Full, i.e., topcollar folds 1/8 inch (3.17mm) or more above creased edge or breakline of undercollar	2
5. Seam joining topcollar and topcollar stand exposed beyond edge of breakline	3
6. Puckers or pleats on topcollar at joining to topcollar stand	2
7. Finished collar width at center back not as specified (measured from fold to outer edge of topcollar)	2
d. Topcollar stand	
1. Stitching of collar stand and topcollar not extending beyond side sections of undercollar	1
2. Tight, puckered or pleated at joining to topcollar	2
e. Undercollar	
1. Interlining pleated, affecting smoothness of topcollar	2
2. Interlining tight or twisted, causing puckers on undercollar	2

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

Table II - Classification of Defects (cont'd)

	Point Value
e. Undercollar (cont'd)	
3. Tight at joining to fronts or back causing puckers or pleats on outside at neck	3
4. Center seam from center back seam:	
a. More than 1/4 inch (6.35mm) to 3/8 inch (9.52mm) inclusive	1
b. More than 3/8 inch (9.52mm)	2
5. Lower raw edge of undercollar not enclosed within felling stitches for more than 3/4 inch (19.05mm)	1
6. Blindtacking at corner of collar or lapel exposed on outside of overcoat	1
7. Tacking on corner of undercollar to lapel omitted or insecure	1
8. Undercollar distorted or pleated at joining seam to coat	2
f. Undercollar stand	
1. Width not as specified (measure from breakline to bottom edge of undercollar at center)	1
2. Collar stand row of stitching through undercollar and collar interlining omitted	2
3. Tight, puckered or pleated at joining to undercollar	2
g. Gorge seam	
1. Not straight	2
2. Any portion of seam not spread open and pressed flat (when applicable)	2
3. Back end of seam not back of or is less than 1 inch (2.54cm) back of lapel breakline	1
4. Length of seam on outside not uniform with other side by 3/8 inch (9.52mm) or more (measured from collar breakline to end of gorge seam at notch)	1
5. Tacking of gorge seam omitted or insecure	1
XVI LAPEL AND COLLAR	
a. Lapel facings	
1. Twisted, short or tight causing lapel to curl out or twist	3
2. Fullness (not smooth and flat)	2
3. Pleated or puckered	3

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

Table II - Classification of Defects (cont'd)

	Point Value
b. Lapel edges	
1. Irregular, wavy or not properly forced out	2
2. Front part exposed on lapel edge	2
3. Tape set on too tight causing puckering at edges	2
c. Lapel and collar shapes (ends, points, and steps)	
1. Twisted, short or tight causing collar or lapel to curl out	*
2. Misshapen or distored - any point varying from finished shaper by:	
a. 1/4 inch (6.35mm) or more but less than 1/2 inch (12.70mm)	3
b. 1/2 inch (12.70mm) or more	*
3. Not uniform in size or shape, varying from matching part by:	
a. 1/4 inch (6.35mm) or more but less than 1/2 inch (12.70mm)	2
b. 1/2 inch (12.70mm) or more	*
4. Matching parts uniform but varying from finished pattern shaper by:	
a. 1/4 inch (6.35mm) or more but not more than 3/8 inch (9.52mm)	1
b. More than 3/8 inch (9.52mm)	2
5. Gap between top edge of lapels and ends of collar not uniform with other side by more than 1/4 inch (6.35mm) (when measured at the outer edge of collar/lapel)	3
6. Collar end lapped over top edge of lapel on one or both sides	3
7. Notch length not within specified tolerances or not uniform within 1/4 inch (6.35mm) from one side to the other	3
d. Bridle tape	
1. Misplaced, not serving intended purpose	2
2. Loose, causing breakline not to lie flat	2
3. Tight, causing puckers or pleats along breakline	3
XVII TABS (sleeve, collar, lapel, and vent)	
a. End poorly shaped or ends not of uniform shape or size	1
b. Tight, loose or distorted when buttoned	1

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

Table II - Classification of Defects (cont'd)

	Point Value
XVII TABS (sleeve, collar, lapel, and vent) (cont'd)	
c. Bottom edge of sleeve tabs not uniformly positioned from bottom edge of sleeve by more than 3/8 inch (9.52mm)	1
d. Irregular in width by 3/16 inch (4.76mm) or more	1
e. Finished length or width not as specified	1
f. Misplaced	1
g. Edge not fully forced out	1
h. Construction other than specified	1
i. Omitted or insecurely attached	3
j. Felling stitches on serged edge of lapel tab not caught through interlining	2
XVIII WELT AND FLAP TYPE POCKETS	
a. General	
1. Poorly shaped, not uniformly positioned, or not uniform in shape or size by more than 1/4 inch (6.35mm) with corresponding point on matching part	2
2. Irregular in width by 3/16 inch (4.76mm) or more	2
3. Notch exposed at end of welt or raw edge at corner	3
4. Out of alignment or misplaced by: 1/	
a. More than 1/2 inch (12.70mm) to 3/4 inch (19.05mm) inclusive	2
b. More than 3/4 inch (19.05mm) to 1 inch (2.54cm) inclusive	3
c. More than 1 inch (2.54cm)	*
5. Finished length or width not as specified	1
6. Front at corner of pocket opening pleated or distorted	1
7. Top back edge of welt or flap not equidistant from side seam by more than 3/4 inch (19.05mm)	1
b. Welt type pockets	
1. Welt misplaced, i.e., right welt on left front and left welt on right front	3
2. Back edge of welt short, causing puckers on front or back edge too loose causing welt to gap	2
3. Tape, reinforcement piece or interlining omitted	2
4. Tape stitching exposed and visible on outside	1
5. One or both ends of welt pleated	1
6. Material twill lines of welt not running in same direction or angle by more than 1/8 inch (3.17mm) as twill lines of front	2

1/ Following local points shall be measured in the examination for this condition:
1. Flap: Top corner of flap nearest front edge of coat and front edge of flap just before the curved corner.
2. Patch pocket: Bottom of straight edge nearest front edge of coat.
3. Welt pocket: Top corner of pocket nearest front edge of coat.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

Table II - Classification of Defects (cont'd)

	Point Value
XVIII WELT AND FLAP TYPE POCKETS (cont'd)	
b. Welt type pockets (cont'd)	
7. Diagonal or reinforcing row of stitching on corners of welt, omitted or insecure	2
8. Front under width of welt at one or both ends puckered or pleated	1
9. Notch or binding not caught in stitching on underside at end of welt	2
10. Topstitching along welt crooked, not parallel to pocket or misplaced	
11. Decorative stitching at welt ends missing, misplaced, or not as specified	1
c. Flap type pockets	
1. Lining tight or twisted causing flap to curl or twist	2
2. Fullness on outside of flap	2
3. Top edge of welt at corner opening 3/16 inch (4.76mm) or more below seam joining flap to front	2
4. Edge of flap not properly forced out or lining exposed	1
5. Flap set on crookedly	2
XIX SWORD SLIT OPENING	
a. Omitted or misplaced	3
b. Assembly reversed, i.e., facing stitched to front edge of underarm seam of left forepart and flap stitched to back underarm seam of left forepart	3
c. Flap too large causing puckers or pleats on foreparts	1
d. Width of flap varies more than 1/8 inch (3.17mm) from finished shaper	1
e. One or both ends insecurely tacked	2
f. Flap lining tight or twisted, causing fullness or twist on outside of flap	2
XX HAND OPENING	
a. One or both ends not completely caught in stitching ends of welt	2
b. Finished piping less than 1/4 inch (6.35mm) or more than 3/8 inch (9.52mm) wide	1
c. Length of opening not as specified	1
d. Hand felling on lining around pocket opening not performed as specified	1

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

Table II - Classification of Defects (cont'd)

	Point Value
XXI SHOULDER	
a. Construction	
1. Improperly joined or set causing front or back of shoulder to twist	3
2. Shoulder seam curved towards back at armhole seam in lieu of toward the front:	
a. 3/16 inch (4.76mm) to 3/8 inch (9.52mm) inclusive	1
b. More than 3/8 inch (9.52mm)	2
3. Fullness not evenly distributed as specified	2
b. Shoulder pad	
1. Not properly set causing shoulder to twist, pucker or bulge	3
2. Misplaced, not serving intended purpose, i.e., too far back or too far forward, not completely or securely caught in armhole tacking	2
c. Shoulder strap or loop (construction and setting)	
1. General	
a. Poorly shaped or not of uniform shape or size	2
b. Length or width not as specified	2
2. MIL-O-43537(GL) and MIL-O-19664(MC) overcoats:	
a. Pointed or rounded end not specified distance from undercollar joining seam	2
b. Misplaced so that shoulder seam is exposed	3
c. Set with seam on the upper side	3
d. Button or buttonhole exposed beyond collar edge	2
e. Not uniformly placed, one strap is further forward or back from position of other strap by 1/4 inch (6.35mm) or more	2
f. Back edge of strap at collar end more than 1/8 inch (3.17mm) beyond shoulder seam	1
g. Back edge of strap not specified distance from shoulder seam at armhole	1
h. Strap will not lie flat, twists or bulges when buttoned	2
i. Strap buttonhole 1/4 inch (6.35mm) or more off center (MIL-O-19664(MC))	2
j. Buttonhole from rounded edge less than 3/4 inch (1.90cm) or more than 1 1/4 inches (3.17cm) (MIL-O-19664(MC))	2

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

Table II - Classification of Defects (cont'd)

	Point Value
XXI SHOULDER (cont'd)	
c. Shoulder strap or loop (construction and setting) (cont'd)	
3. MIL-O-82250(SA) overcoat:	
a. Tight, loose or distorted when stitched	1
b. Length of loop opening not as specified	2
c. Set with covering stitch on the upper side	2
d. Position of loop not as specified	2
XXII ARMHOLE	
a. Stretched causing excessive fullness on back between shoulder and underarm	2
b. Crooked or puckered seam	2
c. Tape stitching exposed and visible on outside	2
d. Armhole not tacked as specified	2
e. Armhole tacking stitches exposed and visible on outside	2
XXIII SLEEVE HEAD WADDING	
a. Not completely or insecurely tacked	2
b. Misplaced, not serving intended purpose	2
XXIV SLEEVE	
a. Set improperly, causing sleeve to break or twist	*
b. Fullness misplaced	2
c. Tight at armholes, i.e., roll effect not present on front or back of sleeves or causing fold of under-sleeve or on armhole at base of sleeve	3
d. Lower part of top sleeve tight causing front of sleeve not to roll	3
e. Front edge of sleeve either too far front or too far back when measured from a set point on pocket by more than 1 1/2 inches (3.81cm):	
1. MIL-O-43537(GL), MIL-O-82250(SA), and MIL-O-19664(MC) overcoats:	
a. Front of pocket - from center of welt joining seam	3
b. Back of pocket - from lower back corner of welt	3

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

Table II - Classification of Defects (cont'd)

	Point Value
XXIV SLEEVE (cont'd)	
2. MIL-O-2414(SA) overcoat:	
a. From lower end of pocket opening	3
f. Hang of sleeves within above tolerance but in opposite directions; one sleeve too far forward and one sleeve too far back from above set points of measurement on pockets. A tolerance of not more than 1 1/4 inches (3.17cm) is allowed for position of each sleeve	2
g. Sleeve backarm seam not equidistant from shoulder seam by 1/2 inch (12.70mm) or more	2
h. Wigan twisted, tight or pleated causing puckering on outside of sleeve, clearly noticeable	2
i. Bottom edge of wigan not extending to bottom edge of sleeve by more than 1/8 inch (3.17mm) or blindstitch tacking on bottom turn-up to wigan omitted or insecure	2
j. Bottom edge of sleeve uneven by:	
1. 1/4 inch (6.35mm) to 3/8 inch (9.52mm) inclusive	1
2. More than 3/8 inch (9.52mm)	2
k. Position of ornamental sleeve braid not as specified	2
l. Junction of braid at underarm seam staggered more than 1/16 inch (1.58mm)	1
XXV SLEEVE CUFF	
a. Cuff full or twisted	2
b. Point of cuff not uniformly shaped or not forced out to a sharp point	2
c. Height of cuff points on paired sleeves varying by more than 1/4 inch (6.35mm)	2
d. Sleeve or cuff puckered or twisted at joining seam	2
e. Height of cuff at point or at backarm seam or forearm seam not within tolerance specified	2
f. Point not centered between front and back creased edge of sleeve by 3/8 inch (9.52mm) or more	2
g. Top edge of cuff at backarm seam staggered more than 1/8 inch (3.17mm)	2
h. Edge of cuff crooked, irregular or not uniform on either side of point	2
i. Cuff turn-up not specified width	1
j. Pointed end of cuff not seamed and stitched as specified	2
k. Tacking at bottom turn-up of cuff to sleeve omitted or insecure	2

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

Table II - Classification of Defects (cont'd)

	Point Value
XXVI FRONT AND BOTTOM EDGES	
a. Front edge stretched	2
b. Tape set too tight causing puckering on front of bottom edge	2
c. Front edge irregular, bulky, or not fully forced out	2
d. Bottom corner of left front poorly shaped	1
e. Bottom edge stretched or uneven	1
f. Stitching along bottom edge exposed on outside	1
XXVII FITTING	
a. Fitting of body lining, front interlining, and liner:	
-tight, short or twisted causing puckers or twists on outside	3
b. Canvas front too full, causing front to have a wavy appearance or not lie smoothly	3
XXVIII VENT	
a. Not lapped in direction specified	2
b. Outer vent edge stretched or not properly constructed causing vents to open	2
c. Lining, interlining or tape tight, short or twisted causing puckers on vent edge	2
d. Outer vent edge irregular	2
e. Stitching of stay or tape on outer vent exposed and visible on outside	1
f. Bottom turn-up exposed on outside of outer vent edge	1
g. Outer vent shorter than inner vent by:	
1. 1/4 inch (6.35mm) to 1/2 inch (12.70mm) inclusive	1
2. More than 1/2 inch (12.70mm)	2
h. Outer vent longer than inner vent by:	
-more than 1/2 inch (12.70mm)	1
C. DETAILED DEFECTS (OVERCOAT SPREAD OUT ON TABLE)	
XXIX DARTS, PLEATS, AND BELLOWS	
a. Omitted:	
1. On outside	3
2. On inside or liner	2
b. Uneven in length by more than 1/2 inch (12.70mm)	1

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

Table II - Classification of Defects (cont'd)

	Point Value
C. DETAILED DEFECTS (OVERCOAT SPREAD OUT ON TABLE) (cont'd)	
XXIX DARTS, PLEATS, AND BELLOWS (cont'd)	
c. Not properly tapered causing unsightly bulge	1
d. Inside fold of dart or outer fold of pleat not facing direction specified	1
e. Length, depth, location or construction other than specified	2
f. Bellows strip short causing front to pucker or twist	2
g. Bellows pleat twisted	1
h. Bellows pleat not abutted along top edge of hem	2
XXX HEMS (sleeve, yoke and bottom)	
a. Irregular in width by more than 1/8 inch (3.17mm)	1
b. Twisted, puckered or pleated	2
c. Width not as specified	1
d. Tape on bottom turn-up not specified type, width or color	1
e. Not bound, taped or turned under as specified	2
f. Tacking on turn-up of front to front omitted or insecure	1
g. Felling or blindstitching of hem not caught or not securely caught to overcoat	2
h. Step at front hem edge not squared when specified	1
XXXI BELT ASSEMBLY	
a. Belt (general)	
1. Free end or point poorly shaped	2
2. Irregular by more than 1/8 inch (3.17mm) or not of uniform width	1
3. Lining, interlining or underply tight or twisted	2
4. Length or width of finished belt not as specified	2
5. Fullness, twist or pleats on upperside	2
6. Edge stretched or full	2
7. Joining seam off center by 1/4 inch (6.35mm) or more	1
8. Attached with underseam exposed on opposide side to that specified	2
9. Point off center by 1/4 inch (6.35mm) or more	1
10. Joining seam not pressed open	1

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

Table II - Classification of Defects (cont'd)

	Point Value
XXXI BELT ASSEMBLY (cont'd)	
b. Half-belt	
1. Out of horizontal alignment by more than:	
a. 1/2 inch (12.70mm) to 3/4 inch (19.05mm) inclusive	1
b. More than 3/4 inch (19.05mm)	2
2. Position other than specified	2
c. Full belt:	
1. Belt in reversed position, i.e., buckle end of belt on wrong side	1
2. Length of turnback less than specified	1
3. Raw edge not turned under at turnback	1
4. Buckle omitted, defective or not specified type, size, color or finish	3
5. Belt keeper:	
a. Omitted or insecure	2
b. Too short, not permitting belt to lie smoothly or to function freely, opening wider by 1/4 inch (6.35mm) than belt	2
c. Finished width not as specified	1
d. Position not as specified	1
6. Belt loop:	
a. Any omitted	3
b. Misplaced, not attached as specified poorly shaped or set on an angle (more than 3/16 inch (4.76mm) off the perpendicular)	2
c. Length or width not as specified	2
d. Raw ends extending more than 1/4 inch (6.35mm) from stitching	1
e. Irregular in width by more than 1/8 inch (3.17mm)	1
f. Reversed; set with covering stitch or seam on outside	2
g. Out of horizontal alignment by more than 1/2 inch (12.70mm)	1
h. Insecure	2
XXXII VENT	
a. Stay piece or tape on inside of left vent omitted	2
b. Finished length or width of vent or vent lining not as specified	1

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

Table II - Classification of Defects (cont'd)

	Point Value
XXXII VENT (cont'd)	
c. Diagonal row(s) of stitching across top of vent opening omitted, insecure, or not as specified	2
d. Top of right vent lining not folded diagonally or not extending above top of right vent as specified	1
e. Stitching on back seam extends more than 1/2 inch (12.70mm) below diagonal row of stitching on back	1
f. Distance of left vent lining from edge of left vent not as specified	1
g. Top edge of silesia stay not caught in stitching across vent extension	1
h. Turn-back of left vent irregular in width by 1/4 inch (6.35mm) or more	1
i. Folded edge of left vent lining from folded edge of left vent not as specified	1
j. Folded edge of right vent lining exposed beyond raw edge of right vent (score only when condition exists on more than 1/2 the length of seam)	1
k. Blindstitch tacking on back edge of left vent omitted	2
l. Vent overlap 1/4 inch (6.35mm) more or less than specified	1
m. Bottom turn-up exposed on outside of vent	2
XXXIII BINDING	
a. Omitted	3
b. Twisted	1
c. Not securely caught, causing binding to pull away from fabric	3
d. Binding short or tight causing edge of seam to curl and not lie flat	2
e. Stretched causing edge to be wavy in appearance	2
f. End not overlapped as specified	1
g. Not starting or finishing as specified or incomplete	1
h. Not spliced or caught as specified	1
i. Not specified width	1
XXXIV FRONT, BACK (YOKE), VENT AND SLEEVE LINING	
a. Twisted, short or tight causing puckering or twist on outside	2
b. Backstitching at armpit of armhole from forearm seam to side seam omitted or insecure	2
c. Bottom turn-up of sleeve lining not specified distance from lower end of sleeve	1
d. Shoulder seam not lapped as specified	2
e. Welt pocket slash lining opening not as specified	1
f. Sleeve seam out of alignment with sleeve seam at armhole or at bottom of sleeve by more than 3/4 inch (19.05mm)	1

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

Table II - Classification of Defects (cont'd)

	Point Value
XXXIV FRONT, BACK (YOKE), VENT AND SLEEVE LINING (cont'd)	
g. Lining too long, extends below bottom edge of sleeve more than 1/2 inch (12.70mm)	1
h. Tacking of sleeve lining seam to sleeve seam omitted or insecure	2
i. Bottom of front and back yokes staggered 1/2 inch (12.70mm) or more at side seam	1
j. Lower edge of front yoke not completely covering top edge of bellows strip	2
k. Tacking on bottom edge of yoke to side seam omitted or insecure	1
l. Felling on bottom corners of lining and vent omitted or insecure	1
XXXV INSIDE POCKET	
a. Positioned other than specified	3
b. Width of pocket opening or depth of pocket not as specified	2
c. Opening gapped by more than 1/4 inch (6.35mm0 in the center of opening	1
d. Finished width of piping less than 3/16 inch (4.76mm) or more than 1/4 inch (6.35mm)	1
e. Stay or facing omitted	1
f. Tacking along front edge of twill pocket through facing and interlining omitted or insecure	2
g. Tacking on upper or back edges of inside pockets to interlining omitted or insecure	1
XXXVI HANGING POCKET	
a. Stitching on one or both ends of welt not completely caught through specified plies of material, i.e., facing, stay piece or pocketing	3
b. Reversed; finished with face side not on inside of pocket	2
c. Twisted, tight or short; pocket does not lie smoothly	2
d. Depth not as specified	1
e. Seam allowance of twill or corduroy pocket not tacked to interlining as specified	2
f. Back ply not lined on outside with rayon lining	3
g. Tacking along front edges of interlining omitted or insecure	2
h. Row of stitching around edges of pocket adjacent to binding omitted	2

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

Table II - Classification of Defects (cont'd)

	Point Value
XXXVII LINER	
a. Size shown on liner not same as overcoat	1
b. Fronts uneven in length by more than 3/4 inch (19.05mm)	2
c. Slash openings:	
1. One or both omitted	3
2. Out of alignment by more than 1 inch (2.54cm)	2
d. Vents uneven in length by more than 3/8 inch (9.52mm)	1
e. Lining tight or short causing puckering on wool part	2
f. Stitching around edges through wool part and linings before binding operation omitted	1
g. Shoulder seam not pressed open (wool part)	1
h. Ends of binding at top of vent opening not caught in bartack or stitching	2
i. Ends of binding on slash opening not caught in bartack	2
XXXVIII SLIDE FASTENER	
a. Not type, size or finish specified	3
b. Any part of assembly defective	3
c. Overcoat or liner twisted or distorted when slide fastener is engaged	3
d. Stitched too close to metal chain, not permitting slider to pass	3
e. Slide fastener tape stitched on too loosely or tightly causing waviness or puckering	1
f. End of tape not turned under when stitched	2
g. Tape not attached or positioned as specified	2
h. Tape stitched to liner or facings with one row of stitching	2
i. Tapes reversed, slider part on facing when liner is removed from overcoat	2
j. Provision for slide fastener track at back edge of front facing omitted or not constructed as specified (MIL-O-83179USAF)	3
k. Front button stitching caugh through slide fastener track at back edge of facing prohibiting function of the slide fastener	3
XXXIX HANGER LOOP	
a. Omitted	1
b. Misplaced; 1/2 inch (12.70mm) or more off center with center back	1
c. Finished length, width or spread not as specified	1
d. Not specified type or construction	1
e. Insecure	1

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

Table II - Classification of Defects (cont'd)

	Point Value
XL LABEL	
a. Missing, incorrect, or illegible:	
1. Size or combination label	3
2. Identification label	1
b. Not attached as specified	1
c. Misplaced or stitching through printing	1

Table III - Selected defects

LAPEL AND COLLAR SHAPES (ends, points, and steps)
Twisted, short or tight causing collar or lapel to curl out.
Misshapen or distorted, any point varying from finished shaper by 1/2 inch (12.70mm) or more.
Not uniform in size or shape, varying from matching part by 1/2 inch (12.70mm) or more
WELT AND FLAP TYPE POCKETS
Out of horizontal alignment by more than 1 inch (2.54cm).
SLEEVE
Set improperly, causing sleeve to break or twist.

Custodian:
Navy - NU
Army - GL
Air Force - 11

Preparing activity:
Navy - NU

Project No. 8405-0914

Review activities:
Navy - MC
Air Force - 99, 82
DLA - CT

☆U.S. GOVERNMENT PRINTING OFFICE: 1984—505-038/A4812

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Officer in Charge
Navy Clothing & Textile Research Facility
ATTN: Code 50
21 Strathmore Road
Natick, MA 01760

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-STD-1391C	PROVISIONS FOR EVALUATING QUALITY OF OVERCOATS, MEN'S

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:14Z
Check the source to verify that this is the current version before use.