MIL-STD-1636

22 April 1977

MILITARY STANDARD

ADAPTERS, COAXIAL TO WAVEGUIDE
SELECTION OF

FSC 5985

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:48Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF DEFENSE
WASHINGTON, DC 20301

Adapters, Coaxial to Waveguide, Selection of.

MIL-STD-1636

1. This Military Standard is approved for use by all Departments and Agencies of the Department of Defense.

2. Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Naval Electronic Systems Command ATTN: ELEX 5043, Department of the Navy, Washington, DC 20360 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 202610-24T00:48Z
Check the source to verify that this is the currentversion before use.

CONTENTS

Paragraph | Page

1. SCOPE - 1
1.1 Scope - 1
1.2 Purpose - 1

2. REFERENCED DOCUMENTS - 1

3. DEFINITIONS - 1

4. GENERAL REQUIREMENTS - 1
4.1 Selection of adapters - 1
4.2 Criteria for inclusion - 1
4.3 Electrical and physical tolerances - 1
4.4 Detailed requirements - 1

5. DETAILED REQUIREMENTS - 1

6. NOTES - 1

TABLES

I. Coaxial to waveguide adapters (Series N to waveguide-class 1) - 2
II. Coaxial to waveguide adapters (7/8-inch coaxial to waveguide-class 3) - 4
III. Coaxial to waveguide adapters (5/8-inch coaxial to waveguide-class 2) - 5
IV. Coaxial to waveguide adapters (Series TNC to waveguide-class 4) - 6
V. Coaxial to waveguide adapters (SMA coaxial to waveguide-class 5) - 7
VI. Pressurable coaxial to waveguide adapters (Series N to waveguide-class 1 with air fitting) - 9
VII Cross-reference of AN nomenclature to part number - 12

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:48Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:48Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 Scope. This standard provides standard coaxial to waveguide adapters considered by the Department of Defense as standard for use in military equipment and applications.

1.2 Purpose. The purpose of this standard is to:

a. Provide the equipment designer with a list of adapters considered standard for use in military applications.
b. Restrict and minimize the variety of adapters for use in military applications in order to provide effective logistic support of equipment.
c. Establish criteria pertinent to choice and application of adapters for use in military equipment.

2. REFERENCED DOCUMENTS

2.1 Issues of documents. The issues of the following documents in effect on the date of invitation for bids form a part of this standard to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-W-85 - Waveguides, Rigid, Rectangular General Specification for.
MIL-F-3922 - Flanges, Waveguide, General Purpose General Specification for.
MIL-A-22641 - Adapters, Coaxial to Waveguide, General Specification for.

(Copies of specifications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. DEFINITIONS

3.1 The terms used in this standard are those commonly encountered in microwave engineering practice.

4. GENERAL REQUIREMENTS

4.1 Selection of adapters. Adapters to be used in military applications shall be selected from those listed in tables I through VI.

4.2 Criteria for inclusion. The criteria for the selection of adapter types for inclusion in this standard are:

a. The adapter shall be considered by representatives of the Military Departments the best available type for current application.
b. Availability of the adapter shall be reasonably certain.
c. The adapter shall have an approved military specification.

4.3 Electrical and physical tolerances. Adapters used in military applications shall be representative of manufactured lots possessing acceptable material and physical and electrical characteristics and shall in no manner degrade the operational characteristics of the equipment it is used in.

4.4 Detailed requirements. The detailed requirements for adapters listed in this standard are covered by the applicable MIL-A-22641 specification sheet.

5. DETAILED REQUIREMENTS

Not applicable.

6. NOTES

Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:48Z
Check the source to verify that this is the current version before use.

TABLE I. Coaxial to waveguide adapters (Series N to waveguide-class 1).

Part number	Frequency range	VSWR over entire freq. range	VSWR over 50% freq. range	Insertion loss (max)	Waveguide housing	Flange and mounting method	Waveguide and flange mat.	Mating flange
M22641/16-	GHz			dB	M85/			
01	7.05-10.0	1.25:1	1.20:1	0.1	1-069 1-073 (RG-51/U)	M3922/53-002 (UG-51/U) (Cover) Butt	Copper alloy	M3922/59-007 (UG-52B/U)
02	5.85-8.2	1.25:1	1.20:1	0.1	1-063 1-067 (RG-50/U)	M3922/55-001 (UG-344/U) (Cover) Sleeve	Copper alloy	M3922/60-001 (UG-343B/U)
03	3.95-5.85	1.25:1	1.20:1	0.1	1-051 1-055 (RG-49/U)	M3922/57-002 (UG-149A/U) (Cover) Sleeve	Copper alloy	M3922/62-002 (UG-148C/U)
04	2.60-3.95	1.25:1	1.20:1	0.1	1-039 1-043 (RG-48/U)	M3922/56-001 (UG-53/U) (Cover) Sleeve	Copper alloy	M3922/61-002 (UG-54B/U)
05	8.20-12.40	1.25:1	1.20:1	0.2	1-079 1-075 (RG-52/U)	M3922/53-001 (UG-39/U) (Cover) Butt	Copper alloy	M3922/59-006 (UG-40B/U)
06	1.70-2.60	1.25:1	1.20:1	0.05	1-027 1-031 (RG-104/U)	M3922/58-009 (UG-435B/U) (Contact) Butt	Copper alloy	M3922/58-009
07	1.12-1.70	1.25:1	1.20:1	0.05	1-015 1-017 (RG-69/U)	M3922/58-007 (UG-417B/U) (Contact) Butt	Copper alloy	M3922/58-007
08	4.9-7.05	1.25:1	1.20:1	0.1	1-057 1-061 (RG-343/U)	M3922/52-037 (UG-1354/U) (Contact) Butt	Copper alloy	M3922/52-037
09	7.05-10.0	1.25:1	1.20:1	0.1	1-071 (RG-68/U)	M3922/53-004 (UG-138/U) (Cover) Butt	Aluminum alloy	M3922/59-009 (UG-137B/U)
10	5.85-8.2	1.25:1	1.20:1	0.1	1-065 (RG-106/U)	M3922/55-002 (UG-441/U) (Cover) Sleeve	Aluminum alloy	M3922/60-002 (UG-440B/U)
11	3.95-5.85	1.25:1	1.20:1	0.1	1-053 (RG-95/U)	M3922/57-001 (UG-407/U) (Cover) Sleeve	Aluminum alloy	M3922/62-001 (UG-406B/U)
12	2.60-3.95	1.25:1	1.20:1	0.1	1-041 (RG-75/U)	M3922/56-002 (UG-584/U) (Cover) Sleeve	Aluminum alloy	M3922/61-001 (UG-585A/U)
13	8.20-12.4	1.25:1	1.20:1	0.2	1-077 (RG-67/U)	M3922/53-003 (UG-135/U) (Cover) Butt	Aluminum alloy	M3922/59-008 (UG-136B/U)

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:48Z
Check the source to verify that this is the current version before use.

TABLE I. Coaxial to waveguide adapters (Series N to waveguide-class 1). - Continued

Part number	Frequency range	VSWR over entire freq. range	VSWR over 50% freq. range	Insertion loss (max)	Waveguide housing	Flange and mounting method	Waveguide and flange mat.	Mating flange
M22641/16-	GHz			dB	M85/			
14	1.70-2.60	1.25:1	1.20:1	0.1	1-029 (RG-105/U)	M3922/58-010 (UG-437B/U) (Contact) Butt	Aluminum alloy	M3922/58-010
15	1.12-1.70	1.25:1	1.20:1	0.05	1-018 (RG-103/U)	M3922/58-008 (UG-418B/U) (Contact) Butt	Aluminum alloy	M3922/58-008
16	4.90-7.05	1.25:1	1.20:1	0.1	1-059 (RG-344/U)	M3922/52-038 (UG-1355/U) (Contact) Butt	Aluminum alloy	M3922/52-038
17	7.0-11.0	1.25:1	1.20:1	0.2	1-155 (RG-320/U)	M3922/70-001 (UG-1493/U) (Cover) Butt	Copper alloy	M3922/69-001 (UG-1494/U)
18	4.9-7.05	1.25:1	1.20:1	0.1	1-059 1-060 (RG-344/U)	M3922/52-038 (UG-1355/U) (Contact) Butt	Aluminum alloy	M3922/52-038
19	4.9-7.05	1.25:1	1.20:1	0.1	1-061 (RG-343/U)	M3922/52-037 (UG-1354/U) (Contact) Butt	Copper alloy	M3922/52-037
20	2.25-5.5	1.30:1	1.20:1	0.1	4-001 (RG-109/U)	RE-49F554 (UG-509/U) (Cover) Sleeve	Copper alloy	UG-510/U
21	5.0-10.0	1.40:1	1.30:1	0.1	4-003 (RG-110/U)	RE-49F555 (UG-511/U) (Cover) Sleeve	Copper alloy	UG-512/U
22	7.0-11.0	1.10:1	1.10:1	0.2	1-155 (RG-320/U)	M3922/70-001 (UG-1493/U) (Cover) Butt	Copper alloy	M3922/69-001 (UG-1494/U)
23	3.95-5.85	1.065:1	1.03:1	0.1	1-055 (RG-49/U)	M3922/52-013 (UG-1728/U) (Contact) Butt	Copper alloy	M3922/52-013
24	3.95-5.85	1.065:1	1.03:1	0.1	1-053 (RG-95/U)	M3922/52-014 (UG-1729/U) (Contact) Butt	Aluminum alloy	M3922/52-014
25	7.05-10.0	1.065:1	1.03:1	0.1	1-073 (RG-51/U)	M3922/52-019 (UG-1734/U) (Contact) Butt	Copper alloy	M3922/52-019
26	7.05-10.0	1.065:1	1.03:1	0.1	1-071 (RG-68/U)	M3922/52-020 (UG-1735/U) (Contact) Butt	Aluminum alloy	M3922/52-020

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:48Z
Check the source to verify that this is the current version before use.

TABLE II. Coaxial to waveguide adapters (7/8 inch coaxial to waveguide-class 3).

Part number	Frequency range	VSWR over		Insertion loss (max)	Waveguide housing	Flange and mounting method	Wave-guide and flange mat.	Mating flange
		entire freq. range	50% freq. range					
M22641/17-	GHz			dB	MBS/			
01	2.60-3.95	1.30:1	1.25:1	--	1-039 (RG-48/U)	M3922/56-001 (UG-53/U) (Cover) Sleeve	Copper alloy	M3922/61-002 (UG-54B/U)
02	2.60-3.95	1.30:1	1.25:1	--	1-039 (RG-48/U)	M3922/56-001 (UG-53/U) (Cover) Sleeve	Copper alloy	M3922/61-002 (UG-54B/U)
03	2.60-3.95	1.30:1	1.25:1	--	1-041 (RG-75/U)	M3922/56-002 (UG-584/U) (Cover) Sleeve	Aluminum alloy	M3922/61-001 (UG-585A/U)
04	2.60-3.95	1.30:1	1.25:1	--	1-041 (RG-75/U)	M3922/56-002 (UG-584/U) (Cover) Sleeve	Aluminum alloy	M3922/61-001 (UG-585A/U)

Source: https://assist.dla.mil -- Downloaded: 202610-24T00:48Z
Check the source to verify that this is the current version before use.

TABLE III. Coaxial to waveguide adapters (5/8 inch coaxial to waveguide-class 2).

Part number	Frequency range	VSWR over entire freq. range	VSWR over 50% freq. range	Insertion loss (max)	Waveguide housing 1/	Flange and mounting method 2/	Waveguide and flange mat.	Mating flange
M22641/18-	GHz			dB	M85/			
01	5.85-8.20	1.30:1	1.20:1	--	1-063 (RG-50/U)	M3922/55-001 (UG-344/U) (Cover) Sleeve	Copper alloy	M3922/60-001 (UG-343B/U)
02	5.85-8.20	1.30:1	1.20:1	--	1-063 (RG-50/U)	M3922/55-001 (UG-344/U) (Cover) Sleeve	Copper alloy	M3922/60-001 (UG-343B/U)
03	2.60-3.95	1.30:1	1.25:1	--	1-039 (RG-48/U)	M3922/56-001 (UG-53/U) (Cover) Sleeve	Copper alloy	M3922/61-002 (UG-54B/U)
04	2.60-3.95	1.30:1	1.25:1	--	1-039 (RG-48/U)	M3922/56-001 (UG-53/U) (Cover) Sleeve	Copper alloy	M3922/61-002 (UG-54B/U)
05	3.95-5.85	1.30:1	1.20:1	--	1-051 (RG-49/U)	M3922/57-002 (UG-149A/U) (Cover) Sleeve	Copper alloy	M3922/62-002 (UG-148C/U)
06	3.95-5.85	1.30:1	1.20:1	--	1-051 (RG-49/U)	M3922/57-002 (UG-149A/U) (Cover) Sleeve	Copper alloy	M3922/62-002 (UG-148C/U)
07	5.85-8.20	1.30:1	1.20:1	--	1-065 (RG-106/U)	M3922/55-002 (UG-441/U) (Cover) Sleeve	Aluminum alloy	M3922/60-002 (UG-440B/U)
08	5.85-8.20	1.30:1	1.20:1	--	1-065 (RG-106/U)	M3922/55-002 (UG-441/U) (Cover) Sleeve	Aluminum alloy	M3922/60-002 (UG-440B/U)
09	2.60-3.95	1.30:1	1.25:1	--	1-041 (RG-75/U)	M3922/56-002 (UG-584/U) (Cover) Sleeve	Aluminum alloy	M3922/61-001 (UG-585A/U)
10	2.60-3.95	1.30:1	1.25:1	--	1-041 (RG-75/U)	M3922/56-002 (UG-584/U) (Cover) Sleeve	Aluminum alloy	M3922/61-001 (UG-585A/U)
11	3.95-5.85	1.30:1	1.20:1	--	1-053 (RG-95/U)	M3922/57-001 (UG-407/U) (Cover) Sleeve	Aluminum alloy	M3922/62-001 (UG-406B/U)
12	3.95-5.85	1.30:1	1.20:1	--	1-053 (RG-95/U)	M3922/57-001 (UG-407/U) (Cover) Sleeve	Aluminum alloy	M3922/62-001 (UG-406B/U)

1/ Waveguide in accordance with MIL-W-85.
2/ Flange in accordance with MIL-F-3922.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:48Z
Check the source to verify that this is the current version before use.

TABLE IV. Coaxial to waveguide adapters (Series TNC to waveguide-class 4).

Part number	Frequency range	VSWR over		Insertion loss (max)	Waveguide housing	Flange and mounting method	Wave-guide and flange mat.	Mating flange
		entire freq. range	50% freq. range					
M22641/19-	GHz			dB	MBS/			
01	8.20-12.40	1.25:1	1.20:1	--	1-075 1-079 (RG-52/U)	M3922/53-001 (UG-39/U) (Cover) Butt	Copper alloy	M3922/59-006 (UG-40B/U)

Source: https://assist.dla.mil -- Downloaded: 202610-24T00:48Z
Check the source to verify that this is the currentversion before use.

TABLE V. Coaxial to waveguide adapters (SMA coaxial to waveguide-class 5).

Part number	Frequency range	VSWR over entire freq. range	VSWR over 50% freq. range	Insertion loss (max)	Waveguide housing	Flange and mounting method	Wave-guide and flange mat.	Mating flange
M22641/20-	GHz			dB	M85/			
01	2.60-3.95	1.10:1	1.05:1	0.05	1-041 (RG-75/U)	M3922/56-002 (UG-584/U) (Cover) Sleeve	Aluminum alloy	M3922/61-001 (UG-585A/U)
02	2.60-3.95	1.10:1	1.05:1	0.05	1-041 (RG-75/U)	M3922/56-002 (UG-584/U) (Cover) Sleeve	Aluminum alloy	M3922/61-001 (UG-585A/U)
03	8.20-12.40	1.10:1	1.05:1	0.15	1-077 (RG-67/U)	M3922/53-003 (UG-135/U) (Cover) Butt	Aluminum alloy	M3922/59-006 (UG-136B/U)
04	8.20-12.40	1.10:1	1.05:1	0.15	1-077 (RG-67/U)	M3922/53-003 (UG-135/U) (Cover) Butt	Aluminum alloy	M3922/59-008 (UG-136B/U)
05	12.40-18.0	1.10:1	1.05:1	0.20	1-090 (RG-349/U)	M3922/53-006 (UG-1665/U) (Cover) Butt	Aluminum alloy	M3922/59-002 (UG-1666/U)
06	12.40-18.0	1.10:1	1.05:1	0.20	1-090 (RG-349/U)	M3922/53-006 (UG-1665/U) (Cover) Butt	Aluminum alloy	M3922/59-002 (UG-1666/U)
07	2.60-3.95	1.10:1	1.05:1	0.05	1-043 (RG-48/U)	M3922/56-001 (UG-53/U) (Cover) Sleeve	Copper alloy	M3922/61-002 (UG-54B/U)
08	2.60-3.95	1.10:1	1.05:1	0.05	1-043 (RG-48/U)	M3922/56-001 (UG-53/U) (Cover) Sleeve	Copper alloy	M3922/61-002 (UG-54B/U)
09	8.20-12.40	1.10:1	1.05:1	0.15	1-079 (RG-52/U)	M3922/53-001 (UG-39/U) (Cover) Butt	Copper alloy	M3922/59-006 (UG-40B/U)
10	8.20-12.40	1.10:1	1.05:1	0.15	1-079 (RG-52/U)	M3922/53-001 (UG-39/U) (Cover) Butt	Copper alloy	M3922/59-006 (UG-40B/U)
11	12.40-18.0	1.10:1	1.05:1	0.20	1-089 (RG-91/U)	M3922/53-005 (UG-419/U) (Cover) Butt	Copper alloy	M3922/59-001 (UG-541A/U)
12	12.40-18.0	1.10:1	1.05:1	0.20	1-089 (RG-91/U)	M3922/53-005 (UG-419/U) (Cover) Butt	Copper alloy	M3922/59-001 (UG-541A/U)
13	7.0-11.0	1.10:1	1.05:1	0.15	1-158	M3922/70-014 (Cover) Butt	Aluminum alloy	M3922/69-002
14	7.0-11.0	1.10:1	1.05:1	0.15	1-158	M3922/70-014 (Cover) Butt	Aluminum alloy	M3922/69-002
15	12.40-18.0	1.10:1	1.05:1	0.20	1-090 (RG-349/U)	M3922/70-020 (Cover) Butt	Aluminum alloy	- - -

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:48Z
Check the source to verify that this is the current version before use.

TABLE V. Coaxial to waveguide adapters (SMA coaxial to waveguide-class 5). - Continued

Part number	Frequency range	VSWR over		Insertion loss (max)	Waveguide housing	Flange and mounting method	Wave-guide and flange mat.	Mating flange
		entire freq. range	50% freq. range					
M22641/20-	GHz			dB	M85/			
16	12.40-18.0	1.10:1	1.05:1	0.20	1-090 (RG-349/U)	M3922/70-020 (Cover) Butt	Aluminum alloy	---
17	7.0-11.0	1.10:1	1.05:1	0.15	1-155 (RG-320/U)	M3922/70-013 (Cover) Butt	Copper alloy	M3922/69-001 (UG-1494/U)
18	7.0-11.0	1.10:1	1.05:1	0.15	1-155 (RG-320/U)	M3922/70-013 (Cover) Butt	Copper alloy	M3922/69-001 (UG-1494/U)
19	12.40-18.0	1.10:1	1.05:1	0.20	1-089 (RG-91/U)	M3922/70-019 (Cover) Butt	Copper alloy	M3922/59-001 (UG-541A/U)
20	12.40-18.0	1.10:1	1.05:1	0.20	1-089 (RG-91/U)	M3922/70-019 (Cover) Butt	Copper alloy	M3922/59-001 (UG-541A/U)

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:48Z
Check the source to verify that this is the current version before use.

TABLE VI. Pressurable coaxial to waveguide adapters (Series N to waveguide-class 1, with air fitting.

Part number	Frequency range	VSWR over entire freq. range	VSWR over 50% freq. range	Insertion loss (max)	Waveguide housing 1/	Flange and mounting method 2/	Wave-guide and flange mat.	Mating flange
M22641/21-	GHz			dB	MBS/			
001	2.30-4.40	1.15:1	1.08:1	0.05	4-001 (RG-109/U)	M3922/71-13 (Contact) Butt 3/	Copper alloy	UG-509/U RE-F2687361 RE-49F554
002					4-001 (RG-109/U)	M3922/71-01 (Contact) Socket 3/	Copper alloy	UG-509/U RE-F2687361 RE-49F554
003					4-002	M3922/71-14 (Contact Butt 3/	Aluminum alloy	---
004					4-002	M3922/71-02 (Contact) Socket 3/	Aluminum alloy	---
005	4.30-7.35				1-061 (RG-343)	M3922/71-17 (Contact) Butt 3/	Copper alloy	M3922/52-037
006					1-061 (RG-343)	M3922/71-05 (Contact) Socket 3/	Copper alloy	M3922/52-037
007					1-060	M3922/71-18 (Contact) Butt 3/	Aluminum alloy	M3922/52-038
008					1-060	M3922/71-06 (Contact) Socket 3/	Aluminum alloy	M3922/52-038
009	5.0-10.75	1.20:1	1.15:1	0.08	4-003 (RG-110/U)	M3922/71-15 (Contact) Butt 3/	Copper alloy	RE-F-2687362 UG-511/U RE-49F555
010					4-003 (RG-110/U)	M3922/71-03 (Contact) Socket 3/	Copper alloy	UG-511/U RE-F2687362 RE-49F555
011					4-004	M3922/71-16 (Contact) Butt 3/	Aluminum alloy	---
012					4-004	M3922/71-04 (Contact) Socket 3/	Aluminum alloy	---
013	7.0-11.0				1-155 (RG-320/U)	M3922/72-05 (Cover) Butt 3/	Copper alloy	M3922/69-001
014	7.0-11.0	1.20:1	1.15:1	0.08	1-155 (RG-320/U)	M3922/72-01 (Cover) Socket 3/	Copper alloy	M3922/69-001

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:48Z
Check the source to verify that this is the current version before use.

TABLE VI. Pressurable coaxial to waveguide adapters (Series N to waveguide-class 1, with air fitting). - Continued

Part number	Frequency range	VSWR over entire freq. range	VSWR over 50% freq. range	Insertion loss (max)	Waveguide housing 1/	Flange and mounting method 2/	Wave-guide and flange mat.	Mating flange
M22641/21-	GHz			dB	M85/			
015	7.0-11.0	1.20:1	1.15:1	0.08	1-155 (RG-320/U)	M3922/73-05 (Choke) Butt 3/	Copper alloy	M3922/70-001, -013
016					1-155	M3922/73-01 (Choke) Socket 3/		M3922/70-001, -013
017					1-158	M3922/72-06 (Cover) Butt 3/	Aluminum alloy	M3922/69-002
018						M3922/72-02 (Cover) Socket 3/	Aluminum alloy	M3922/69-002
019						M3922/73-06 (Choke) Butt 3/	Aluminum alloy	M3922/52-038
020					1-158	M3922/73-02 (Choke) Socket 3/	Aluminum alloy	---
021	2.30-4.40	1.15:1	1.08:1	0.05	4-001 (RG-109/U)	M3922/71-19 (Contact) Butt 4/	Copper alloy	UG-509/U RE-F2687361 RE-49F554
022					4-001 (RG-109/U)	M3922/71-07 (Contact) Socket 4/	Copper alloy	UG-509/U RE-F2687361 RE-49F554
023					4-002	M3922/71-20 (Contact) Butt 4/	Aluminum alloy	---
024					4-002	M3922/71-08 (Contact) Socket 4/	Aluminum alloy	---
025	4.30-7.35				1-061 (RG-343/U)	M3922/71-23 (Contact) Butt 4/	Copper alloy	M3922/52-037
026					1-061 (RG-343/U)	M3922/71-11 (Contact) Socket 4/	Copper alloy	M3922/52-037
027					1-060	M3922/71-24 (Contact) Butt 4/	Aluminum alloy	M3922/52-038
028					1-060	M3922/71-12 (Contact) Socket 4/	Aluminum alloy	M3922/52-038

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:48Z
Check the source to verify that this is the current version before use.

TABLE VI. Pressurable coaxial to waveguide adapters (Series N to waveguide-class 1, with air fitting). - Continued

Part number	Frequency range	VSWR over entire freq. range	VSWR over 50% freq. range	Insertion loss (max)	Waveguide housing 1/	Flange and mounting method 2/	Waveguide and flange mat.	Mating flange
M22641/21-	GHz			dB	M85/			
029	5.0-10.75	1.20:1	1.15:1	0.08	4-003 (RG-110/U)	M3922/71-21 (Contact) Butt 4/	Copper alloy	UG-511/U RE-F2687362 RE-49F555
030					4-003 (RG-110/U)	M3922/71-09 (Contact) Socket 4/	Copper alloy	UG-511/U RE-F2687362 RE-49F555
031					4-004	M3922/71-22 (Contact) Butt 4/	Aluminum alloy	---
032					4-004	M3922/71-10 (Contact) Socket 4/	Aluminum alloy	---
033	7.0-11.0				1-155 (RG-320/U)	M3922/72-07 (Cover) Butt 4/	Copper alloy	M3922/69-001
034						M3922/72-03 (Cover) Socket 4/		M3922/69-001
035						M3922/73-07 (Choke) Butt 4/		M3922/70-001, 013
036						M3922/73-03 (Choke) Socket 4/		M3922/70-001, 013
037					1-158	M3922/72-08 (Cover) Butt 4/	Aluminum alloy	M3922/69-001, -002
038						M3922/72-04 (Cover) Socket 4/		M3922/69-001, -002
039						M3922/73-08 (Choke) Butt 4/		M3922/70-002, -014
040						M3922/73-04 (Choke) Socket 4/		M3922/70-002, -014

1/ Waveguide in accordance with MIL-W-85.
2/ Flange in accordance with MIL-F-3922.
3/ Air fitting is installed in the broad wall side of the flange.
4/ Air fitting is installed in the narrow wall side of the flange.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:48Z
Check the source to verify that this is the current version before use.

TABLE VII. Cross-reference of AN nomenclature to part number.

AN nomenclature	Part number	AN nomenclature	Part number
	M22641/		M22641/
UG-397/U	16-01	UG-1647/U	18-07
UG-398/U	16-02	UG-1648/U	18-08
UG-399/U	16-03	UG-1649/U	18-09
UG-400/U	16-04	UG-1650/U	18-10
UG-403/U	18-01	UG-1651/U	18-11
UG-404/U	18-06	UG-1652/U	18-12
UG-405/U	17-02	UG-1653/U	16-09
UG-445/U	18-03	UG-1654/U	16-10
UG-446A/U	16-05	UG-1655/U	16-11
UG-520/U	18-02	UG-1656/U	16-12
UG-521/U	18-05	UG-1657/U	16-13
UG-522/U	17-01	UG-1658/U	16-14
UG-523/U	18-04	UG-1659/U	16-15
UG-952/U	16-06	UG-1660/U	16-16
UG-953/U	16-07	UG-1661/U	16-08
UG-1004/U	16-20	UG-1662/U	17-03
UG-1005/U	16-21	UG-1663/U	17-04
UG-1538/U	16-17	UG-1679/U	16-19
UG-1646/U	16-18		

Custodians:
Army - FI
Navy - EC
Air Force - 11

Review activities:
Army - MI, AV
Navy - OS
Air Force - 17, 85, 99
DLA - ES

User activities:
Army - MU
Navy - MC

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5985-0848)

Source: https://assist.dla.mil -- Downloaded: 202640-24T00:48Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
NAVAL ELECTRONIC SYSTEMS COMMAND
WASHINGTON, D.C. 20360

POSTAGE AND FEES PAID
NAVY DEPARTMENT
DOD 316

OFFICAL BUSINESS

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:48Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:48Z
Check the source to verify that this is the current version before use.