MILITARY SPECIFICATION

TRUCKS, ARMORED: PAYROLL DISTRIBUTION, 4x2

This specification is approved for use by all departments and agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers diesel and gasoline engine driven, four-wheel, two-rear-wheel drive, 19,000 pounds gross vehicle weight (GVW), trucks with an armored body. Vehicles procured under this specification are commercial items which shall be warranted by the manufacturer as specified in procurement documents.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS
FEDERAL

O-E-915	- Extinguishers, Fire, Dry-Chemical (Portable).
W-B-131	- Battery, Storage: Vehicular, Ignition, Lighting and Starting.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Tank-Automotive Command, ATTN: DRSTA-GBS.l, Warren, MI 48090, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC-2320

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:16Z
Check the source to verify that this is the current version before use.

MILITARY
MIL-A-27302 - Arrestor, Spark, Exhaust, Internal Combustion Engine.

STANDARDS
MILITARY
MIL-STD-1223 - Non-Tactical Wheeled Vehicles Treatment, Painting, Rustproofing, Identification Marking, and Data Plate Standards.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DEPARTMENT OF TRANSPORTATION (DoT)
Federal Motor Carrier Safety Regulations.
Federal Motor Vehicle Safety Standards.

(Application for copies should be addressed to the Department of Transportation, Federal Highway Administration, Washington, D.C. 20591.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)
Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines.
Noise Emission Standards for Transportation Equipment - Medium and Heavy Trucks.

(Application for copies should reference the Code of Federal Regulations, 40 CFR, and the Federal Register and should be addressed to the Superintendent of Documents, U.S. Covernment Printing Office, Washington, D.C. 20402.)

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN NATIONAL STANDARDS INSTITUTE, INC. (ANSI)
ANSI Standards
ANSI/UL752 - Standard for Bullet Resistant Equipment.

(Application for copies should be addressed to the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:16Z
Check the source to verify that this is the current version before use.

SAE, INC.
SAE Standards and Recommended Practices.

J245	- Engine Rating Code - Spark Ignition.
J537	- Storage Batteries.
J551	- Limits and Methods of Measurement of Radio Interference Characteristics of Vehicles and Devices (20-1000 MHz) (DoD adopted).
J552	- External Electromagnetic Radiation Suppressors.
J588	- Turn Signal Lamps.
J589	- Turn Signal Switch.
J688	- Truck Ability Prediction Procedure.
J816	- Engine Test Code - Spark Ignition and Diesel.

(Application for copies should be addressed to SAE, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

THE TIRE AND RIM ASSOCIATION, INC.
Yearbook.
(Application for copies should be addressed to the Tire and Rim Association, Inc., 3200 W. Market Street, Akron, OH 44313.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Standard vehicle and accessories. Except as specified in 3.1.1 through 3.1.1.7, the vehicle, components, assemblies, and accessories to be delivered under the contract shall be standard or optional items, which meet or exceed the requirements of this specification. All chassis items shall be as represented in the chassis manufacturer's technical data, and special bodies or mounted equipment shall be as represented in the body and equipment manufacturer's technical data. Technical data shall be limited to specifications and technical material identical to that furnished to the authorized company representatives for selection of vehicle models and components, and shall be on file in the engineering offices of the procuring activity, prior to delivery of the items.

3.1.1 Special requirements. In addition to the standard vehicle and components specified in 3.1, the vehicle shall be furnished with special equipment as specified herein.

Source: https://assist.dla.mil -- Downloaded: 202640-23T01:16Z
Check the source to verify that this is the currentversion before use.

3.1.1.1 Painting and marking. As specified by the procuring activity for the appropriate service (see 6.2), treatment, painting, identification marking, and data plates shall be in accordance with MIL-STD-1223. Body interior surfaces shall be treated and painted as specified in 3.5.1.4.

3.1.1.1.1 Instruction plates. A photoetched corrosion resistant plate showing a schematic of the air conditioner and the heater and complete operating instructions shall be fastened on the inside of the vehicle.

3.1.1.2 Rustproofing. When specified (see 6.2), the vehicle shall be rustproofed in accordance with MIL-STD-1223.

3.1.1.3 Drain plugs. All drain plugs installed throughout the vehicle for the purpose of draining lubricants, shall be of the permanent magnet type.

3.1.1.4 Heavy duty cooling system. A heavy duty cooling system shall be furnished that shall maintain engine coolant at a temperature below the boiling point with vehicle loaded to rated GVW and operated at an altitude of 10,000 feet above sea level or in an ambient air temperature of not less than 125 degrees Fahrenheit (°F).

3.1.1.5 Coolant system and indicators. Coolant system shall include a de-aeration system, a surge tank, or a coolant recovery reservoir of not less than two quart capacity. A high coolant temperature or low coolant level alarm buzzer and red indicator warning light shall be provided on the dash instrument panel.

3.1.1.6 Towing devices. Not less than two hooks, loops or pins, for towing the vehicle, shall be furnished on the front of the vehicle.

3.1.1.7 Spark arrester. As specified herein (see 3.4.4), the vehicle shall be furnished with an exhaust system spark arrester.

3.2 General design.

3.2.1 Federal Motor Vehicle Safety Standards. The vehicle and furnished accessories shall comply with all Federal Motor Vehicle Safety Standards in effect on the date of manufacture.

3.2.2 Air pollution control. The vehicle shall comply with EPA Regulations governing Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines in effect on the date of manufacture. In addition, vehicles destined for California shall comply with State of California regulations governing air pollution control in effect on the date of manufacture.

Source: https://assist.dla.mil -- Downloaded: 202640-23T01:16Z
Check the source to verify that this is the currentversion before use.

3.2.3 Sound level. The interior sound level shall conform to Federal Motor Carrier Safety Regulation 393.94. The vehicle exterior sound level shall conform to EPA Noise Emission Standards for Transportation Equipment, Medium and Heavy Trucks.

3.2.4 Curb weight. The curb weight shall include the weight of the chassis and body, with all attachments, accessories, and equipment: full complement of fuel, lubricants, and coolant.

3.2.5 Gross vehicle weight. Gross vehicle weight (GVW) shall consist of curb weight, operator and assistant (weight computed at 175 pounds each), and a payload evenly distributed in the vehicle body load area, to provide not less than the specified GVW.

3.2.5.1 Payload and gross vehicle weight. The distribution of GVW for the purpose of establishing suspension, axle and tire capacities shall be determined with the payload uniformly distributed over the truck body load area. The minimum GVW rating shall be 19,000 pounds, and the minimum payload capacity shall be 2,500 pounds. The GVW rating shall be increased beyond 19,000 pounds, if required, to provide the 2,500 pound payload capacity.

3.2.6 Ratings. Component and vehicular ratings shall not be raised to meet the requirements of this specification. Vehicle ratings shall be manufacturer's published ratings.

3.2.7 Wheelbase. The wheelbase shall be not less than 125 inches.

3.3 Performance.

3.3.1 Speeds. High and low speed requirements shall be met with vehicle loaded to required GVW.

3.3.1.1 High speed gradeability. The vehicle shall ascend a grade of 1.5 percent at 50 miles per hour (mph). Gradeability requirements shall be met with the transmission in direct drive and, when a multispeed axle is furnished, with the axle in high speed range. Gradeability shall be verified with calculations in accordance with SAE J688 (see 6.3).

3.3.1.2 Low speed. Low speed shall be calculated with engine operating at not less than 35 percent of recommended governed speed, and shall provide a vehicle speed of not more than four mph.

3.3.1.3 Maximum geared speed. The maximum geared speed at engine governed speed shall be not less than 55 mph. Conformance to geared speed specified shall be determined by calculating in accordance with the following formula:

$$\text{Maximum geared speed (mph)} = \frac{\text{Governed speed (rpm)}}{\text{Total gear reduction x tire factor (see 6.3)}}$$

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:16Z
Check the source to verify that this is the current version before use.

3.3.2 Service brakes. The service brakes shall control and hold the vehicle, when loaded to required GVW, on a 30 percent grade. The service brakes shall stop the vehicle, loaded to required GVW, within the stopping distance requirements of Federal Motor Carrier Safety Regulation 393.52.

3.4 Chassis components.

3.4.1 Engine. The engine furnished shall be the chassis manufacturer's standard, or optional engine for the commercial model truck which meets or exceeds the requirements of this specification.

3.4.1.1 Diesel engine. Unless otherwise specified (see 3.4.1.2), the vehicle shall be equipped with a liquid cooled, compression ignition, two-stroke or four-stroke cycle diesel engine, with not less than four cylinders. Engine net horsepower used in performance prediction calculations shall be determined in accordance with SAE J816. A fan clutch to reduce fan speed automatically, when not required for engine cooling, shall be provided.

3.4.1.2 Gasoline engine. When specified (see 6.2), the vehicle shall be equipped with a liquid cooled, internal combustion, four-stroke cycle gasoline engine with not less than six cylinders. The engine furnished shall produce the required vehicle performance when operated on unleaded fuel with a research octane rating of 91, at engine speed not more than the manufacturer's recommended operating speed. The engine shall be capable of continuous, warranted operation on unleaded fuel. The rated net torque output of the engine shall be not less than 265 pound feet. Engine net torque ratings and net horsepower used in performance calculations shall be determined in accordance with SAE J245. Unless otherwise specified or required by foreign laws, vehicles for overseas use shall be capable of accepting and operating on leaded gasoline.

3.4.1.3 Oil and fuel filters. A full flow type oil filter shall be furnished. Engine manufacturers standard fuel filter(s) shall be furnished.

3.4.1.4 Governor. An engine governor shall be furnished and set and sealed to limit the engine to the manufacturer's maximum recommended operating speed.

3.4.1.5 Coolant temperature control. Thermostatic control of engine coolant temperature shall be provided. On diesel engine driven vehicles, the control shall include partial thermostatic control of coolant flow through the radiator and thermostatically controlled radiator shutters or complete thermostatic control of all coolant flow through the radiator.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:16Z
Check the source to verify that this is the current version before use.

3.4.1.6 Power plant heaters and fuel warmer. When specified (see 6.2), coolant heater; engine oil heater; and fuel warmer (diesel engine driven vehicles only) shall be provided. Unless otherwise specified (see 6.2), a battery heater shall be provided when power plant heaters are specified. Heaters shall operate on 120-volt alternating current (ac), and shall be wired through a junction block to a single three pronged (male), weatherproof, slave receptacle for receiving external power and grounding vehicle. A three wire connecting cable, 25 feet long and of adequate line capacity to supply power for all heater units simultaneously, shall be furnished. Connecting cable shall include a matching female connector at the vehicle end and a standard, weatherproof, three pronged (two power plus one ground) male connector at the other end. Electrical apparatus shall be in accordance with Federal Motor Carrier Safety Regulation 393.77(c)(7). Electrical insulation of connecting cable shall withstand normal operating stresses in low ambient air temperature (down to minus 60°F) without cracking or loss of dielectric capacity. All heater lead wires shall be installed without interfering with vehicle component operation, and without loose excess wire. Provisions for stowage of the cable shall be provided in the vehicle cab. Heaters shall be furnished as follows:

(a) Coolant heater, 1500-watt minimum rating, shall be installed in the engine block or lower coolant inlet hose. Engine thermostat with an operating range of 170°F to 195°F shall be installed.
(b) Immersion type engine oil heater, 300-watt minimum rating, with 170°F to 195°F thermostat, shall be installed in oil pan through any convenient opening.
(c) Battery heater shall have a capacity adequate to maintain the battery electrolyte at a temperature of not less than 10°F during vehicle exposure in ambient air temperature as low as minus 60°F, and shall embody a thermostat to limit the temperature of the electrolyte to not more than 80°F.
(d) A fuel warmer or pre-heater shall be provided on diesel engine driven vehicles to prevent clogging of fuel filters due to wax crystallization in the fuel. The fuel warmer shall use engine coolant to transfer sufficient heat to the diesel fuel to heat it from an inlet temperature of minus 40°F to an outlet temperature of plus 9°F, with a flow rate not less than the maximum fuel demand of the engine fuel system. A coolant shutoff valve shall be provided for the coolant inlet side of the fuel warmer unit.

3.4.2 Electrical system. The electrical system shall be in accordance with Federal Motor Carrier Safety Regulations 393.27 through 393.31 and 393.33.

Source: https://assist.dla.mil -- Downloaded: 202610-23T01:16Z
Check the source to verify that this is the current version before use.

3.4.2.1 Starting system (diesel engine). For diesel engine driven vehicles, a 12 or 24-volt direct current (dc) starting system, with 12-volt dc lighting system, and not less than an 82 ampere alternator, shall be furnished. Engine starting equipment shall include an ether starting system or glow plug. When specified (see 6.2), if an ether system is furnished in lieu of a glow plug, it shall be of the measured shot type. Measured shot type ether system shall be key operated or manually operated from the driver's compartment, shall have a reservoir of not less than 12 fluid ounces and shall be inoperative with the engine warm.

3.4.2.2 Ignition system (gasoline engine). For gasoline engine driven vehicles, a 12-volt dc ignition system shall be furnished. An alternator of not less than 60 amperes rated capacity, and which provides not less than 16 amperes dc output at normal engine idle speed, shall be furnished.

3.4.2.3 Lighting. All vehicle lights, reflectors, and wiring shall be as specified herein and shall conform to Federal Motor Carrier Safety Regulations 393.12, 393.19, 393.20 and 393.22 through 393.26(d). Lights and reflectors shall not be mounted on vertical surface of rub rails (unless recessed and fully protected) or mounted on vehicle bumpers.

3.4.2.4 Turn signals. Turn signal lamps shall conform to SAE J588. Operating units shall conform to SAE J589, class A, and shall be mounted on the steering column. The vehicle shall be provided with front and side signal units and with single faced rear signal units installed in accordance with SAE J588, except that turn signals shall not be mounted on engine compartment hood. Turn signal operating units shall be self-cancelling type with visible and audible flash indicator.

3.4.2.5 Battery(s). Each battery shall be of a 12-volt potential. The total reserve capacity ratings and the total cold cranking ratings at 0°F, both measured in accordance with SAE J537, shall be not less than specified in table I. The batteries shall be of the maintenance free type having the maintenance free characteristics listed in W-B-131.

TABLE I. Battery(s).

Engine type	Reserve capacity (minutes)	Cold cranking (amperes)
Diesel	320	1200
Gasoline	110	450

3.4.2.6 Radio interference suppression. The vehicle shall be suppressed to limit electromagnetic radiation in accordance with SAE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:16Z
Check the source to verify that this is the current version before use.

J551. Suppressors where used shall conform to SAE J552. Any body equipment emitting radiation shall be suppressed to the same level as the vehicle chassis.

3.4.3 Fuel system. The fuel system shall conform to Federal Motor Carrier Safety Regulations 393.65 and 393.67.

3.4.3.1 Air cleaner. An air cleaner shall be furnished. When equipped with an oil-bath type, oil capacity shall be not less than 1 quart.

3.4.3.2 Fuel tank(s). Fuel tank(s) shall be the vehicle manufacturer's standard. Vehicle shall be equipped with fuel tank(s) of not less than 60 gallon total capacity. When more than one tank is furnished on diesel engine driven vehicles, means shall be provided to assure equalized fuel level in both tanks. When more than one tank is furnished on gasoline engine driven vehicles, a selector valve connecting either tank to engine fuel intake shall be provided and means shall be provided to monitor the fuel level of either tank from a single fuel gage. Fuel tanks shall be shielded by and fit within the perimeter of the body armor.

3.4.4 Exhaust system. The exhaust system shall conform to Federal Motor Carrier Safety Regulation 393.83 and, unless otherwise specified (see 6.2), the vehicle shall be furnished with a spark arrester conforming to the material and performance requirements of MIL-A-27302, except on turbocharged engines. Exhaust system shall discharge to the side behind the rear wheels.

3.4.5 Transmission. A manually shifted transmission shall be provided. Input torque capacity of the transmission shall be at least equal to the maximum torque delivered by the engine. Transmission and axle gear ratios shall be selected to provide the performance specified in 3.3.1. The vehicle shall be provided with not less than five forward speeds and one reverse speed. The transmission shall provide for maximum ease of shifting in all speeds.

3.4.5.1 Clutch. The clutch shall be of the largest capacity offered for the engine and vehicle model furnished, with torque capacity exceeding maximum delivered engine torque.

3.4.6 Drive line components. Drive line components shall be adequate to transmit the maximum delivered torque of the engine, as developed through the maximum gear train reduction.

3.4.7 Frame. The chassis frame shall be the manufacturer's standard for the type of vehicle furnished. The vehicle shall have a

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:16Z
Check the source to verify that this is the current version before use.

frame with reinforcements extending at least from the rear of the front-suspension, rear hanger bracket to the front of the rear spring, front hanger bracket. Reinforcements shall provide sufficient structural strength in the chassis frame through increased resisting bending moment at least equal to the loads imposed with vehicle body loaded to required GVW.

3.4.8 Suspension. The vehicle shall be equipped with a suspension system having a rated capacity at least equal to the load imposed on each member, measured at the ground, with the vehicle loaded to required GVW. Vehicle shall be equipped with hydraulic, double-acting shock absorbers at the front wheels.

3.4.9 Axles. Axle ratings shall be at least equal to the load imposed at each axle, measured at the ground, with the vehicle loaded to required GVW. A single reduction rear axle shall be furnished.

3.4.9.1 Traction control. When specified (see 6.2), the vehicle shall be furnished with traction control on the rear axle. The traction control shall actuate automatically to insure that power is transmitted to the wheels having traction when the opposite wheel loses traction. Maximum traction capabilities shall be maintained at all times under each drive wheel for the life of the vehicle.

3.4.10 Wheels, rims, tires, and tubes. The vehicle shall be equipped with single front and dual rear wheels. Rims and tire ratings shall conform to Tire and Rim Asociation recommendations for the type and size of tires furnished. Rims and disc wheel sizes shall be the same for all wheels on the vehicle. Tire size and load range (ply rating) shall be the same for all tires on the vehicle. When specified (see 6.2), disc type wheels shall be furnished.

3.4.10.1 Tires. Unless otherwise specified (see 6.2), tires shall be tube or tubeless type with highway tread. Tires shall be of the steel belted radial type or, when specified (see 6.2), bias ply. Tires shall be of rated capacity at least equal to the load imposed on each tire, measured at each wheel, at the ground, with the vehicle loaded to required GVW.

3.4.10.2 Inner tubes. When tube type tires are furnished, inner tubes shall be of heavy duty type, and shall be of proper size for tires furnished. Tire flaps shall be provided for tube type tires in accordance with Tire and Rim Association recommendations.

3.4.10.3 Spare wheel assembly. Unless otherwise specified (see 6.2), a spare wheel or rim shall be mounted on a carrier and installed in a readily accessible location on the vehicle. Carrier design shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:16Z
Check the source to verify that this is the current version before use.

enable removal or mounting of spare wheel assembly using only tools specified in 3.4.15.

3.4.10.3.1 Spare tire. Unless otherwise specified (see 6.2), an inflated spare tire mounted on the spare wheel or rim shall be furnished. The spare tire shall be of the same size and tread design and ply rating as the tires furnished on the vehicle.

3.4.11 Brakes. Brakes shall conform to Federal Motor Carrier Safety Regulations 393.40 through 393.43 and 393.45 through 393.52.

3.4.11.1 Vacuum-hydraulic type. Unless otherwise specified (see 3.4.11.2), the vehicle shall be equipped with vacuum assisted, hydraulic actuated, four-wheel, service brakes.

3.4.11.2 Air or air-hydraulic type. When specified (see 6.2), the vehicle shall be equipped with four wheel, air or air-hydraulic type brakes. The braking system, complete with all necessary components, shall include:

(a) Air compressor, unloader-head-type, engine driven and engine lubricated, air or water cooled, and having a capacity of not less than 7 1/4 cubic feet per minute (cfm).
(b) Air storage reservoir(s) with not less than 2,000 cubic inches total capacity, each tank equipped with drain, and with safety and check valves between compressor and last reservoir tank.
(c) Air control valves.
(d) Foot control, suspended or treadle type.
(e) Air pressure gage, visible to the driver.
(f) Low-air-pressure warning, visible and audible.
(g) Service brake stop lamp switch.
(h) Alcohol aspirator with unbreakable transparent container.
(i) Automatic moisture ejector.

3.4.12 Steering. Power steering shall be provided.

3.4.13 Windshield wipers and washers. The vehicle shall be equipped with dual windshield wipers and windshield washers. The windshield wipers shall be multispeed type and operated by either air or electric motor(s).

3.4.14 Bumpers. A heavy duty channel type front bumper shall be provided. Rear end protection shall be provided and shall be in accordance with Federal Motor Carrier Safety Regulations 393.86 (see 3.5.1.5).

Source: https://assist.dla.mil -- Downloaded: 202640-23T01:16Z
Check the source to verify that this is the current version before use.

3.4.15 Tools. Unless otherwise specified (see 6.2), each vehicle shall be furnished with tools required for exchanging a mounted tire assembly with the spare assembly and shall include at least a jack, jack handle and wheelnut wrench. The jack shall be of such closed height as to permit its location under axle, or other satisfactory lift point, at any wheel with the tire flat. The jack, without blocking, shall be capable of raising any wheel of loaded vehicle to a height adequate to permit removal and replacement of wheel and tire assembly. Stowage space of sufficient size to accommodate vehicle jack, hand tools, antiskid chains, warning flares and reflectors shall be furnished for retaining equipment during vehicle operation. Stowage space for these tools may be furnished in the body. When stowage space for these tools is located outside of the body, it shall be waterproof and shall provide for locking with a padlock.

3.4.16 Heater and defroster. A hot water heater shall be provided. Heater shall be of the fresh air type or recirculating type. Discharge outlets shall be provided to direct heated air to floor and to defroster louvers. Heater shall be complete with blower and mounted controls convenient to the driver.

3.4.17 Controls and operating mechanism(s). All controls and operating mechanisms shall be located for left-hand drive. Controls shall be complete and conveniently operable by the driver. Lever controls shall be designed and located to permit easy entrance and exit of operator to and from the driver's compartment. Instruments and controls shall be identified as to their function and installed in a manner to facilitate removal and servicing. Instruments shall be panel mounted. When specified (see 6.2), controls shall be located for right-hand drive.

3.4.17.1 Accessories and equipment. Chassis equipment shall be complete with all accessories furnished as standard equipment by the manufacturer. The following minimum equipment shall be furnished:

(a) Key-operated ignition switch.
(b) Ammeter, charging indicator or voltmeter.
(c) Fuel gage.
(d) Oil pressure gage or indicator.
(e) Engine temperature gage or indicator.
(f) Speedometer with recording odometer.
(g) Ash receptacle
(h) Dual sunvisors.
(i) Tachometer (diesel engine vehicles only).

3.4.18 Horn. The manufacturer's standard electric horn shall be furnished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:16Z
Check the source to verify that this is the current version before use.

3.4.19 Rearview mirrors. Outside rearview mirrors shall be mounted on each side of the vehicle. The mirrors shall be of the combination type having flat and convex areas enclosed in a common housing. The flat portion shall have not less than 50 square inches of reflective area. The convex portion shall have not less than 20 square inches of reflective area. The mirrors shall have not less than three supporting arms. An interior mirror, to monitor the rear compartment, shall be furnished.

3.5 Body. The armored vehicle shall be equipped with an all-steel, aluminum, or steel and aluminum body consisting of an integral driver's compartment and rear compartment. The body shall have the minimum dimensions specified in table II. The subframe and the floor of the body shall not be welded to the truck chassis frame. Exterior and interior sheet steel or aluminum lining and glass shall be bullet-resistant and provide protection against small arms fire up to and including .357 magnum, at a distance of 50 feet, when tested in accordance with ANSI/UL752. The .357 magnum projectile specified, refers to a 158 grain, soft point or lead projectile fired from an 8 1/2 inch barrel having a muzzle velocity of 1450 feet per second (fps) with a muzzle energy of 740 foot-pounds (ft-lb).

TABLE II. Body dimensions (inches, minimum).

Location	Length	Width	Height
Overall body (outside including skirting)	136	80	98
Driver's compartment (inside)	43	76	54
Rear compartment (inside)	90	76	54

3.5.1 Body construction. The body design and construction shall be manufacturer's standard for the armored payroll distribution truck as specified herein and shall be constructed in accordance with ANSI/UL752. The body, including body framing, subframing, roof bows, interior and exterior walls, roof and flooring shall be constructed of steel or aluminum. The inner and outer walls, doors, partition, roof, fire wall, kick plates, wheelwheels and flooring shall be of sufficient thickness and strength to defeat small arms fire as specified in 3.5. Effective means shall be taken to preclude electrolytic action between dissimilar metals. Bolting or riveting of body shall be avoided whenever possible. Welding techniques shall be of a quality to preclude weakening of material being welded.

3.5.1.1 Glass. Glass shall be tinted bullet-resistant safety glass (see 3.5.1.1.1). Glass shall be of sufficient thickness, ply, and density so as to defeat small arms fire as specified in 3.5. Glass

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:16Z
Check the source to verify that this is the current version before use.

shall be heat treated safety plate glass. Inner layer of glass shall have a spall shield to prevent splintering of inner glass and a scratch resistant coating. The interlayers shall be transparent and stable without edge sealing. Front ply shall be considered the ply that receives bullet impact. Glass shall be of uniform quality without noticeable distortion and shall be optically flat within a minimum radius curvature of 500 feet. Bullet resistant glass shall be capable of withstanding changes in temperature from minus 65°F to 160°F, without cracking, clouding, delaminating or other evidence of deterioration.

3.5.1.1.1 Tinting. Tinted heat-absorbing, bullet-resistant glass shall be furnished. All door, window, windshield, and partition glass shall be in accordance with the manufacturer's standard for tinted bullet-resistant glass. Tinting of lamination is not acceptable except for the rear door. Rear door glass shall be tinted to quadruple density allowing approximately 25 percent light transmission. Rear door glass with tinted lamination is acceptable.

3.5.1.2 Insulation. Insulation shall be provided in the exterior doors, walls, floor and ceiling of the body and shall provide resistance to transfer of heat equivalent to the protection afforded by a 1-inch thick batt having a thermal conductivity of 0.24, in normal ambient air temperatures. Insulation shall be either foamed in place, flexible or batt type, fibrous or cellular material, having a moisture absorption capacity of less than 2 percent by weight. Materials shall be odorless and fire retardent. Insulation shall not breed nor promote the growth of fungus and shall not cause nor accelerate corrosion of steel, copper or aluminum. Insulation shall be secured to inner side of external walls and provided with means to retain insulation under all operating conditions. Cement, where used, shall be waterproof. The installation of the insulation shall provide shear strength sufficient to prevent sag of the insulation when assembled vehicle is operated at speeds up to 55 mph over improved roads. All insulation, to maximum practicable extent, shall be installed prior to the closing of spaces in body sides, front and rear panels, ends, doors, upright body members, roof, roof bows, and other parts.

3.5.1.3 Floor covering. The floor area in both compartments shall have a raised pattern diamond plate surface or shall be covered with insulated rubber matting, with perimeter aluminum molding. When specified (see 6.2), indoor-outdoor carpeting shall be furnished.

3.5.1.4 Treatment and painting of interior surfaces. Treatment and painting of interior surfaces shall be in accordance with MIL-STD-1223. All surfaces within the body walls, floor, ceiling, doors and partitions shall be treated or primed and painted with a corrosion resistant finish or paint before the insulation is installed. Interior

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:16Z
Check the source to verify that this is the current version before use.

lining surfaces that face the body walls shall be treated or primed and painted with a corrosion resistant finish or paint before installation of the interior lining.

3.5.1.5 Running boards. Running boards shall be furnished on each side of the body from the rear of the front fenders to forward of the rear wheel housing and across the back of the body. The running boards shall be not less than six inches in width and covered with safety tread steel or aluminum plate. The rear running board shall form a step into the rear compartment and in addition shall be a rear bumper combination. Rear bumper combination shall be in accordance with Federal Motor Carrier Safety Regulation 393.86.

3.5.1.6 Gun ports. Not less than eleven gun ports shall be furnished and installed in the body. Gun ports shall be in accordance with the design and characteristics specified in ANSI/UL-752. Gun ports shall be spring loaded, aluminum, weatherproof, heavy duty, with rubber gaskets and equipped with self-closing doors suitable for one hand operation. Gun ports shall incorporate a locking device and shall be operable after being struck by a projectile. Gun ports shall be located at least as follows:

(a) One on each side under windshield.
(b) One on each door, to the side of or under the window opening.
(c) One at side of or under each curb and street side window.
(d) One in the partition between the forward and rear compartments.

3.5.1.7 Wheelhousings. Wheelhousings shall be furnished with interior splash shields. Wheelhousings shall be waterproof. Wheel well cutouts shall be furnished with rubber rim type rear fenders around the cutout. Splash shields shall extend below wheelhousings to shed road splash. All parts and surfaces of the wheelhousings and shields shall be primed and painted before and after assembly as specified in 3.5.1.4.

3.5.1.8. Lighting. Lighting shall be provided in the driver's compartment and the rear compartment. Driver's compartment shall have an under-dash light with individual switch and a dome light with a translucent shield and a switch. Rear compartment shall have two equally spaced ceiling lights with translucent shields. Lights shall be on the longitudinal centerline of the ceiling. Lights shall have a three way switch operable from driver's compartment and rear compartment.

3.5.1.9 Air conditioning. A high capacity air conditioning system shall be provided for each compartment. The evaporator(s) shall be located within the body and shall be ducted to both compartments. Controls readily accessible to the driver shall be furnished to adjust temperature and blower speeds. Each compartment shall be furnished with adjustable louvers to direct flow of air. Condensor and compressor

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:16Z
Check the source to verify that this is the current version before use.

shall be mounted under the hood or under the vehicle chassis within the body armor. The system shall be capable of maintaining not more than 80°F dry bulb and 68°F wet bulb temperature in both compartments in a 100°F outside air ambient temperature under full solar radiation.

3.5.2 Rear compartment.

3.5.2.1 Partition. A partition shall be provided to the rear of the driver's compartment. The partition shall be constructed of the same materials as specified in 3.5.1.

3.5.2.1.1 Partition window. A window shall be installed in the partition and shall be located on the longitudinal centerline of the partition and 32 inches above the floor. Window glass shall be not less than a nominal 12 inches by 12 inches and shall be as specified in 3.5.1.1.

3.5.2.1.2 Partition door. A sliding door shall be provided in the partition. The door opening shall be located on the right side of the partition. The door shall be approximately 24 inches in width and of a height to provide for an opening above the door frame. The opening above the door frame shall be covered with bullet resistant screen wire, 6 inches high by the width of the door opening. Door construction shall be as specified in 3.5.1. The door shall be capable of being locked from the driver's compartment side with a cylinder type lock. The door lock shall be two-point, with top and bottom latches. A door catch shall be provided to retain the door in open position. The door shall serve as access to the rear compartment. A gun port as specified in 3.5.1.6 shall be provided.

3.5.2.2 Windows. Eight windows shall be provided in the rear compartment, three on the curb side, three on the street side and one in each rear door. The windows shall be approximately equally spaced, located 30 inches from the floor, and bullet-resistant as specified in 3.5.1.1. Glass area shall be approximately 18 inches in length and 10 inches in height. Molding for the windows shall be bullet resistant, as specified in 3.5.1.

3.5.2.3 Rear doors. Double rear doors shall be provided. Door opening shall be not less than 67 inches in width and not less than 49 inches in height. Windows shall be as specified in 3.5.1.1. Door locks shall be operable from inside only and shall be two point, with top and bottom latches. Door holders for retaining the doors in an open position of not less than 120 degrees shall be furnished. Hinges shall be tamper proof. Each rear door shall be furnished with three heavy duty hinges. If hinges are external, hinge pins shall be secured and non-removable. The curb side rear door shall open ahead of street side rear door.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:16Z
Check the source to verify that this is the current version before use.

3.5.2.4 Roof vent(s) in rear compartment. Fan powered roof vent(s) shall be provided at the rear of the compartment. Vent(s) shall be sized to exhaust air at not less than 600 cubic feet per minute (cfm) with fan(s) operating or by free flow of air. Vent(s) shall incorporate multi-position louvers, intrusion guard, and rain shield and shall be operable from inside only. Vent(s) shall be watertight when closed.

3.5.2.5 Package doors. Two package doors in the body wall, one on each side, level with the inside top surface of the floor, shall be provided at the front end of the rear compartment adjacent to the partition wall. The package doors shall be not less than 20 inches by 20 inches in size and equipped with cylinder locks on the inside of the rear compartment to prevent opening from the outside of the vehicle. The doors shall be windproof and watertight. Hinges shall be tamper proof.

3.5.2.6 Seating. A stationary upholstered seat and back shall be provided in the center of the rear compartment. Manufacturer's standard seat belt fastenings and one pair of lap type seat belts shall be installed.

3.5.2.7 Circulating fan. An eight-inch oscillating circulating fan mounted near the roof on the street side wall shall be furnished. A three-way switch shall be provided to operate the fan from the driver's compartment and from the rear compartment. The fan shall be capable of position adjustment.

3.5.2.8 Auxiliary heater. When specified (see 6.2), an auxiliary heater shall be provided for the rear compartment. The heater shall be of the engine-coolant, heavy duty type. The heater shall be located so as not to restrict movement of personnel. The heater shall be equipped with a shutoff valve for shutting off the flow of coolant. Three-way electrical switches shall be mounted in locations easily accessible to the seated driver, and to personnel in the rear compartment. Heater shall have a rated capacity of not less than 30,000 British thermal units (Btu) per hour, which shall be exceeded, if required to maintain specified temperature. The heater shall be capable of maintaining the temperature inside of the compartment at a minimum of 70°F midway between floor and ceiling in an outside ambient air temperature of 0°F with no passengers, at all operating speeds.

3.5.3 Driver's compartment. The driver's compartment shall be manufacturer's full width compartment. Doors shall be equipped with locks, operable from inside the driver's compartment through mechanical linkage, and with street and curb side doors equipped with external, key-operated locks. The driver's compartment shall have upholstered,

Source: https://assist.dla.mil -- Downloaded: 202640-23T01:16Z
Check the source to verify that this is the current version before use.

adjustable seat and back for the driver and a stationary fold-down type seat for the assistant driver. Interior lighting (see 3.5.1.8) shall be provided. Manufacturer's standard seat belt fastenings and two pairs of lap type seat belts shall be installed.

3.5.3.1 Driver's compartment doors. Doors shall have an opening of not less than 28 inches in width and not less than 49 inches in height and shall be provided with bullet-resistant glass (see 3.5.1.1) in the upper portion of the door. Glass size shall be approximately 25 inches long by 18 inches high but not less than 450 square inches. Doors shall be constructed as specified in 3.5.1. Doors shall be tamper proof, watertight and windproof. If hinges are external, hinge pins shall be secured and non-removable.

3.5.3.2 Windshield. The windshield shall consist of two pieces of glass, each not less than 36 inches wide by 16 inches high, and shall be bullet-resistant glass (see 3.5.1.1). Channel between windshields shall be bullet resistant as specified in 3.5.1.

3.5.3.3 Roof vents (driver's compartment). Two roof vents shall be provided. Roof vents shall be mounted on roof, over the windshields with open end to the front. Vents shall be of adequate size to provide not less than 600 cfm air flow into the truck when vehicle is not in motion and outside air is at zero wind velocity. Roof vents shall incorporate intrusion guard, rain shield operable from inside only and shall be watertight when closed. Vents shall deflect air on driver and guard.

3.5.3.4 Circulating fan. An eight-inch oscillating circulating fan mounted above the dash shall be provided. The fan shall have a guard over the blades. The fan shall be capable of adjustment.

3.5.3.5 Warning light. A dash mounted red warning light shall be installed to flash a signal to the driver when any door, including package door(s), is not completely closed.

3.5.4 Fire extinguishers. Two dry chemical type fire extinguishers shall be furnished, one for the driver's compartment and one for the rear compartment. Fire extinguisher brackets to suspend the extinguishers in the vehicle shall be installed. Fire extinguishers shall have a capacity not less than 2 1/2 pounds and shall be in accordance with type I, class 2 of O-E-915.

3.5.5 Mounting. The body shall be mounted with not less than six U-bolts or twin studs, per side, having 9/16 inch minimum body diameter with 5/8 inch minimum thread diameter, or other equivalent method(s). Tie-plates shall be at least 1/2 inch thick. Vehicle chassis frame

Source: https://assist.dla.mil -- Downloaded: 202610-23T01:16Z
Check the source to verify that this is the current version before use.

shall be braced, using hardwood blocks at each mounting point unless mounting point is located at a full depth, frame crossmember. Blocks shall incorporate a keeper strap or groove for mounting bolt, and shall be of a width to assure retention. Two shear bolts shall be provided, one on each side of rear portion of body sub-frame, to maintain body alinement on vehicle chassis. A hardwood breaker strip of not less than 1/2 inch finished thickness shall be installed between longitudinal main sills and vehicle chassis frame. When body is secured by brackets attached to chassis frame rails, attachments shall be made to the web of the frame rails. When additional holes are required to secure mounting brackets to chassis frame rails they shall be located within the area of the rail which is designated as being safe for drilling in accordance with the chassis manufacturer's body builders layouts. When body is mounted by bolting bracket(s) to side of frame, the hardwood block at mounting point and shear bolts are not required.

3.5.6 Locks. Locks shall be of the interchangeable cylinder type having a tumbler with a minimum of 5 pins. All locks for the doors shall be keyed alike.

3.6 Dissimilar metals. All dissimilar metals throughout the vehicle shall be insulated from one another to preclude galvanic action or electrolytic action.

3.7 Servicing and adjusting. Prior to acceptance of the vehicle by the Government inspector, the contractor shall service and adjust the vehicle and its mounted equipment for operational use including at least the following: alinement of lights; adjustment of engine; adjustment of brake system; filling and charging of battery; alinement of front wheels; inflation of all tires; complete lubrication of chassis, engine, running gear, and mounted equipment with grades of lubricants recommended for the ambient air temperature at the delivery point; servicing of cooling system with a solution of ethylene glycol and water in equal parts by volume; and servicing of windshield washer reservoir with water and appropriate additives. The air conditioner shall be fully charged and operational.

3.8 Workmanship. Defective components or parts and assemblies which have been repaired or modified to overcome deficiencies shall not be furnished. Welded, bolted, and riveted construction utilized shall be in accordance with the highest standards of the industry.

3.9 Welding. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Weld penetration shall provide transference of maximum design stress through basic metal juncture. Fillet welds shall be provided when necessary to reduce stress concentration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:16Z
Check the source to verify that this is the current version before use.

3.10 Ballistic specimens. Ballistic specimens shall be prepared by the contractor for body and glass and shall be in accordance with ANSI/UL752. Specimens shall be used to represent the minimum acceptable in production (see 3.5). The specimens shall be prepared to represent the body cross section area and glass used in production.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Government verification. Quality assurance operations performed by the contractor will be subject to Government verification at unscheduled intervals. Verification will consist of observation of the operations to determine that practices, methods, and procedures of the contractor's inspection are being properly applied. Failure of the contractor to promptly correct product deficiencies discovered shall be cause for suspension of acceptance until correction has been made or until conformance of product to specification criteria has been demonstrated.

4.3 Ballistic test. Prior to the start of production, ballistic specimens shall be furnished by the contractor (see 3.10). Upon submission of specimens by the contractor the quality level and identification shall be subject to approval by the Government. Ballistic tests shall be conducted by the contractor and observed by the Government to evaluate that the specimens meet the requirements of the contract. Specimens and testing shall be in accordance with ANSI/UL752.

4.4 First production vehicle inspection. The first vehicle produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of Government representatives. The purpose of the inspection shall be to determine vehicle conformance to the contract. Acceptance of the first production vehicle shall not constitute a waiver by the Government of its rights under the provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:16Z
Check the source to verify that this is the current version before use.

4.4.1 Vehicle weight. The first production vehicle shall be weighed to determine curb weight and distribution of curb weight on front and rear axles. The imposed loading on front and rear axles will be computed using the curb weight, the operator and assistant weight at 175 pounds each, and a 2,500 pound payload to provide not less than the specified GVW. The calculated imposed loads on front and rear axles will be utilized to ascertain that the suspension, axles and tires furnished are of adequate capacity to meet contractual requirements.

4.4.2 Road test. The first production vehicle shall be examined and road tested with payload. The road test shall cover not less than 30 miles on paved highways at speeds up to 55 mph and 20 miles of stop-and-go operation on city streets.

4.4.3 Radio frequency suppression verification. The vehicle manufacturer shall furnish with the questionnaire (commercial vehicle engineering data) a description of all interference suppression devices used to suppress vehicle electromagnetic radiation in accordance with SAE J551. Data shall be sufficient for visual determination that all required suppression devices are installed on the vehicle.

4.4.4 Production sample. Upon acceptance of the first production vehicle, it shall remain at the manufacturing facility as a production sample, and be the last vehicle shipped on the contract. The contractor shall maintain the vehicle in a serviceable condition for the duration of the contract.

4.4.5 Failure. Failure of the first production vehicle to meet requirements of the contract shall be cause for the Government to refuse acceptance of all vehicles under contract until corrective action has been taken. In addition, subsequent vehicles that do not conform to the accepted production sample vehicle shall be rejected until corrected.

4.5 Inspection of production vehicles. The contractor's inspection system shall, as a minimum, assure that the vehicle conforms to the physical and dimensional requirements and is capable of meeting performance requirements contained herein. For each vehicle under contract, the contractor shall make available to the Government, at the point of final acceptance, records acceptable to the Government indicating that the servicing and adjusting required by 3.7 have been accomplished.

5. PACKAGING

5.1 Vehicle processing. The vehicle shall be processed for shipment, from manufacturer's plant to initial receiving activity, in accordance with the manufacturer's standard commercial practice.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:16Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The vehicles covered by this specification are intended for general nontactical use by the Government for the transportation and protection of payrolls and to be utilized as a mobile check cashing facility.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Identification of appropriate service for painting and marking (see 3.1.1.1).
(c) Concealed marking, if required (see 3.1.1.1).
(d) Rustproofing, if required (see 3.1.1.2).
(e) Gasoline engine, if required (see 3.4.1.2).
(f) Power plant heaters and fuel warmer, if required (see 3.4.1.6).
(g) If a battery heater is not required (see 3.4.1.6).
(h) A measured shot type ether system, if required (see 3.4.2.1).
(i) If a spark arresting muffler is not required (see 3.4.4).
(j) Traction control, if required (see 3.4.9.1).
(k) Disc type wheels, if required (see 3.4.10).
(l) Bias ply or other type tires, if required (see 3.4.10.1).
(m) If spare wheel or rim and carrier is not required (see 3.4.10.3).
(n) If spare tire is not required (see 3.4.10.3.1).
(o) Air or air-hydraulic brakes, if required (see 3.4.11.2).
(p) If tools are not required (see 3.4.15).
(q) Right-hand drive, if required (see 3.4.17).
(r) Indoor-outdoor carpeting, if required (see 3.5.1.3).
(s) Auxiliary heater in rear compartment, if required (see 3.5.2.8).

6.3 Performance prediction. Completed copies of SAE Truck Ability Prediction Procedure form and computation for low speed requirement for each vehicle model furnished under contract should be submitted as specified in the contract. The SAE Work Sheet Item 1 should include vehicle model number, wheelbase, engine model number, and vehicle type. Unless other conditions are cited in the contract, computations should be made for normal atmospheric pressure, normal ambient air temperature, and still, dry, air. The factors to be used in predicting truck ability (see 3.3.1.1) are established as follows for the corresponding SAE Truck Ability Prediction Procedure Tables:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:16Z
Check the source to verify that this is the current version before use.

Table 1	- Tire Factor. This factor must relate to the size of tires furnished by the contractor in accordance with this specification.
Table 2	- Altitude Factor. 1.00.
Table 3	- Rolling Factor. 1.613.
Table 4	- Area Factor. 0.173.
Table 5	- Velocity Factor. 250.0.
Table 6	- Altitude Factor. 1.00.
Table 7	- Chassis Friction Horsepower. Use required GVW and the engine rpm (to nearest 100 revolutions) which is required for 50 mph geared speed.
Table 8	- Grade Factor. 0.75.
Table 8A	- Correction Factor. Not required.
Table 9	- Road Factor. 0.0.

6.4 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodian:
Army - AT
Air Force - 99
Navy - YD

Preparing activity:
Army - AT
Project No. 2320-1078

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:16Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Tank-Automotive Command
ATTN: DRSTA-GBS.1
Warren, MI 48090

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:16Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER (Number) AND TITLE MIL-T-62088A TRUCKS, ARMORED: PAYROLL DISTRIBUTION, 4x2

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY (Printed or typed name and address — Optional)

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:16Z
Check the source to verify that this is the current version before use.