MIL-C-43289E
4 September 1980
SUPERSEDING
MIL-C-43289D
14 December 1976

MILITARY SPECIFICATION

CHICKEN WITH RICE, DEHYDRATED, COOKED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for cooked, freeze-dried chicken with rice for use by the Armed Forces as a component of operational rations.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

L-P-378	-	Plastic Sheet and Strip, Thin Gauge, Polyolefin
EE-B-575	-	Bouillon (Soup and Gravy Bases)
EE-S-631	-	Spices, Ground and Whole, and Spice Blends
PP-C-248	-	Chickens, Chilled and Frozen (Ready-to-Cook)
QQ-A-1876	-	Aluminum Foil

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Command, Natick, MA 01760, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8940

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:05Z
Check the source to verify that this is the currentversion before use.

PPP-B-26 - Bag, Plastic (General Purpose)
PPP-B-636 - Boxes, Shipping, Fiberboard
PPP-C-843 - Cushioning Material, Cellulosic
PPP-C-1797 - Cushioning Material, Resilient, Low Density, Unicellular, Polypropylene Foam
PPP-T-60 - Tape: Packaging, Waterproof

MILITARY

MIL-R-35084 - Rice, Instant, Enriched

STANDARDS

FEDERAL

FED-STD-101 - Preservation, Packaging and Packing Materials: Test Procedures
FED-STD-595 - Colors

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-668 - Sanitary Standards for Food Plants

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

LAWS AND REGULATIONS

US DEPARTMENT OF HEALTH AND HUMAN SERVICES

Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder

(Application for copies should be addressed to the Superintendent of Documents, US Government Printing Office, Washington, DC 20402.)

US DEPARTMENT OF AGRICULTURE

United States Standards for Grade of Canned Pimientos

Regulations Governing the Grading and Inspection of Poultry and Edible Products Thereof and United States Classes, Standards, and Grades with Respect Thereto (7 CFR, Part 70)

(Application for copies should be addressed to the US Department of Agriculture, Information Division, Agricultural Marketing Service, Washington, DC 20250.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:05Z
Check the source to verify that this is the current version before use.

Meat and Poultry Inspection Regulations

(Application for copies should be addressed to the Superintendent of Documents, US Government Printing Office, Washington, DC 20402.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

THE UNITED STATES PHARMACOPOEIAL CONVENTION, INC.

Pharmacopoeia of the United States

(Application for copies should be addressed to the United States Pharmacopoeial Convention, Inc., Mack Publishing Co., 20th and Northhampton Sts., Easton, PA 18042.)

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS

Official Methods for Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

D 882-73 - Tensile Properties of Thin Plastic Sheeting

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 First article. When specified (see 6.1), the contractor shall furnish a sample for first article inspection and approval (see 4.3 and 6.2).

3.2 Material. All material shall be in excellent condition, clean, sound, wholesome, and free from evidence of insect infestation, foreign and undesirable odors, flavors, colors, and extraneous materials. The material shall be so handled and processed that the end product shall comply with the finished requirements of 3.6.

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:05Z
Check the source to verify that this is the current version before use.

* 3.2.1 Chicken. The chicken shall meet the commodity requirements for type I or IV, class 1 or 2, style 1 through 5 of PP-C-248. Identity of bird type, age, quality and wholesomeness will be certified by the US Department of Agriculture. When chicken parts are used, they shall be used in their natural proportions (light-dark meat), except that light meat may be used in excess of natural proportions. If type IV frozen chickens are used, they shall have been maintained during storage at a temperature of 0°F (-18°C) or lower and shall have been properly packaged and wrapped so as to avoid freezer burn or other damage. The product shall be in excellent condition and shall show no evidence of thawing or refreezing.

3.2.1.1 In addition, the raw chicken meat shall meet the following requirements:

a. The carcass or parts shall be skinned and rawboned.

b. There shall be no heads, feet, metacarpus-phalanges sections of wings, giblets, or viscera.

c. There shall be no bones, coarse connective tissue, blood clots, skin, bruised or discolored meat exceeding 1/4-inch (6 mm) in any dimension.

d. There shall be no ligaments, tendons, or cartilage exceeding 1/4-inch (6 mm) in any dimension.

e. There shall be no ground or comminuted chicken meat.

3.2.2 Pimientos, canned. Pimientos shall be pieces (diced style) and shall meet the requirements of grade C or better of U.S. Standards for Grades of Canned Pimientos.

* 3.2.2.1 Sweet, red peppers. Sweet red peppers, if used, shall be fresh, canned or frozen and shall be prepared in accordance with commercial practice. They shall be mechanically diced with dicer settings at approximately 1/4 x 1/4 x 1/4 inch (6 x 6 x 6 mm).

3.2.3 Rice, instant enriched. Instant rice shall comply with type I of MIL-R-35084.

3.2.4 Soup and gravy base, chicken. The chicken flavored soup and gravy base shall comply with type II of EE-B-575.

3.2.5 Vegetable oil. The vegetable oil shall be a bland flavored, winterized, bleached, deodorized corn oil. The oil shall be stabilized with butylated hydroxyanisole or butylated hydroxytoluene or both in equal amounts. Total quantity of stabilizer shall be 0.02 percent by weight of oil.

3.2.6 Salt. Salt shall be white refined, sodium chloride with or without anti-caking agent.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:05Z
Check the source to verify that this is the current version before use.

3.2.7 Nitrogen. Nitrogen shall be US Pharmacopoeia grade and shall be water or liquid nitrogen pumped (see 3.4).

3.2.8 Turmeric, ground. Turmeric shall be of the Alleppey type complying with type II (ground) of EE-S-631.

3.3 Preparation.

* 3.3.1 Chicken. The chicken meat shall be cooked in suitable casings or metal molds by any suitable means until it is tender. A minimum internal temperature of 170°F (77°C) shall be reached during the cooking process. The cooked meat shall be chilled (not less than 25°F) (-4°C) and mechanically diced with the dicer setting at approximately 1/2 by 1/2 by 1/4 inch (13 by 13 by 6 mm). If frozen chicken is used, the diced chicken meat shall not be refrozen before being used in preparation of the product. Chicken shall not be frozen more than three times including final freezing for dehydration. No ground or comminuted chicken meat or pieces of similar size may be used. Any intermediate stage of preparation necessitating holding of product within limits specified in 3.5 shall require prompt cooling to 40°F (4°C) or below. Preparation, cooking, dicing, formulation and dehydration shall be conducted so that the final dry product shall comply with the finished product requirements of 3.6. Salt may be used in the preparation of the cooked chicken but shall not exceed a total of 1.25 percent in the cooked product.

3.3.2 Formulation. The chicken and rice shall be prepared in accordance with the following formula:

Ingredients 1/	Percentage
Chicken, diced, cooked	35.0
Instant rice	8.7
Water	48.2
Vegetable oil	4.5
Pimientos, diced 3/	2.4
Soup and gravy base, chicken	1.2
Turmeric 2/	
	100.0

1/ Total amount of salt in the formula shall equal 1.0 percent. If sufficient salt is not contributed by the chicken and soup and gravy base, then salt shall be added to the formula as necessary to bring the total salt level to 1.0 percent.

2/ Turmeric may be added to the formula to improve the color. The amount added shall not exceed .005 percent.

3/ An equivalent amount of diced, sweet red peppers may be substituted for pimientos.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:05Z
Check the source to verify that this is the current version before use.

3.3.3 Cooking. All ingredients except rice and chicken shall be stirred while heating to a minimum temperature of 180°F (82°C). The rice shall be added and the mixture brought to a boil, then allowed to stand 5 minutes. The chicken shall be added with gentle stirring and the mixture brought to a minimum temperature of 180°F (82°C). Any process which produces an equivalent product shall be acceptable. If it is found that less water than specified in 3.3.2 can be used, the quantity of water may be decreased. However, increased amounts of water shall not be used unless the density and moisture absorption properties of the raw materials require additional water to accomplish the desired effect. The prepared product shall be spread on dehydrator trays and frozen.

3.4 Dehydration. The product shall be freeze-dehydrated at an absolute pressure not to exceed 1.5 millimeters of mercury (200 kPa) and a product temperature as indicated by suitable instruments, not to exceed 150°F (66°C). If the platen temperature is maintained at 155°F (68°C) or below with radiant heating, the product temperature may be disregarded. After dehydration is completed, the pressure shall be equalized to atmospheric level with nitrogen and the product shall be preserved immediately as specified in 5.1. If it is necessary to hold the product more than 2 hours between dehydration and preservation, it shall be adequately protected from oxygen and moisture by either holding under a nitrogen atmosphere with 2.0 percent or less oxygen, or under a vacuum of at least 27 inches of mercury (9.79 kPa). If vacuum is used, it shall be broken with nitrogen.

3.5 Time and temperature limitations. The chicken and product shall be so handled as to comply with the following:

Time and temperature limitations for handling and storage of component chicken and chicken meat 1/

Stage	Maximum Holding period	Maximum Temperature
1. Chilled chicken or chicken meat		
(a) From preparation (see 3.2.1.1) to completion of cooking. 2/	72 hours	40°F (4°C)
(b) After cooling, in rolls or logs, to start of dicing. 3/	72 hours	40°F (4°C)
(c) Between dicing and freeze dehydration.	48 hours	40°F (4°C)
(d) After formulation, before freezing for dehydration.	24 hours	40°F (4°C)
(e) Total time - all stages combined (preparation, cooking, dicing and formulation before freezing for dehydration).	9 days	

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:05Z
Check the source to verify that this is the current version before use.

Time and temperature limitations for handling and storage of component chicken and chicken meat 1/ (cont'd)

Stage	Maximum Holding period	Maximum Temperature
2. Frozen chicken or chicken meat (after preparation and cooking, see stage 1a, above)		
(a) Total freezer time - all stages combined (raw, cooked and diced).	60 days	0°F (-18°C)
Cooked rolls or logs	45 days	0°F (-18°C)
After dicing	15 days	0°F (-18°C)
(b) Between dicing and formulation.	30 days 4/	0°F (-18°C) 5/
(c) Between frozen formulated product and placement of same in the dehydrator.	5 days 6/	0°F (-18°C)
3. In-transit		
Maximum internal temperature of frozen or cooked meat at the completion of any transit between plants (product shall be placed in a 0°F (-18°C) or lower freezer immediately upon receipt).	-	10°F (-12°C)

1/ The various increments of time specified for each state of handling or processing are given to permit maximum flexibility to the contractor and to the processor. At no stage shall the quality of the product show any evidence of deterioration in its organoleptic properties.

2/ Following cooking, internal product temperature of 40°F (4°C) or less, when chilling is intended, shall be reached within 24 hours; if the product is to be frozen, internal temperature of 0°F (-18°C) or less shall be reached within 48 hours.

3/ Maximum temperature permissible for tempering in preparation for dicing as specified in 3.3.1.

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:05Z
Check the source to verify that this is the currentversion before use.

4/ The key word is "dicing". Example: Of the total 60 day maximum permitted under 2(a), if the rolls are diced within 10 days of manufacture, it is necessary to process the diced chicken within a 30 day period, even if the total of 60 days has not elapsed.

5/ A maximum of 30°F (-1°C) is permitted to temper frozen meat to facilitate dicing. This tempering shall not be considered as a thaw cycle provided that the diced product is placed in a freezer at 0°F (-18°C) or lower immediately after dicing.

6/ When product is set aside to be stored for not more than 5 days, adequate product protection against uncontrolled drying shall be provided, such as shrouding.

3.6 Finished product.

* 3.6.1 Physical characteristics. The finished product shall comply with the following physical characteristics. The product shall have distinct pieces of chicken meat approximately 1/2 by 1/2 by 1/4 inch (13 by 13 by 6 mm) in size and shall not be an indistinguishable mass of chicken meat fibers and rice.

Dehydrated product:

(1) There shall be no foreign material such as, but not limited to, dirt, glass or paint.

(2) There shall be no evidence of incomplete dehydration such as damp or soggy areas.

(3) There shall be no evidence of thawing in the dehydrator such as glazed surface areas measuring more than 1/2 inch (13 mm) in any dimension or dark colored cores of any dimension.

Rehydrated product:

(4) When rehydrated in hot water (180°F to 212°F) (82°C to 100°C) using the proportion of 4 ounces (113 g) of product to 13 fluid ounces (384 ml) of water for 10 minutes, the product shall show complete water penetration through all dice and rice. 1/ Callous-like areas ascribable to gristle, gelatinous material, and connective tissue hindering rehydration in the chicken, shall not be considered evidence of improper rehydration.

(5) The rehydrated product shall possess flavor, odor and texture considered normal for frozen and heated chicken and rice. There shall be no scorched, burnt, or foreign flavors or odors.

1/ Up to, but not exceeding, two ounces (59 ml) of additional hot water may be added to aid in rehydration and improve consistency of the product.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:05Z
Check the source to verify that this is the currentversion before use.

3.6.2 Analytical requirements. Moisture in the product shall not exceed 2.0 percent when tested in accordance with 4.5.3.

3.6.3 Microbiological requirements. The product shall comply with the following microbiological requirements:

Aerobic plate count	Not more than 75,000 per gram.
E. coli	1/ 2/

1/ The product shall be accepted if the E. coli content is less than 3 per gram (no positive tube in the standard 3-tube MPN technique) in at least four of five samples from one specific lot providing that the remaining sample does not have E. coli of more than 10 per gram.

2/ The product shall be rejected if (a) any one of the five samples has a confirmed E. coli count greater than ten (10) per gram or (b) if two or more of the five samples have confirmed E. coli.

* 3.7 Plant qualification. The product shall originate, be processed, marked and handled in plants which are operated under the Meat and Poultry Inspection Regulations of the U.S. Department of Agriculture. Finished product facilities (freezer, storage and shipping) not operating under these regulations shall meet the requirements of MIL-STD-668.

3.8 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Plant qualification. The product shall be unacceptable if not produced and stored in plants which currently meet the qualification requirements of 3.7.

* 4.3 First article inspection. When a first article is required, the chicken with rice shall be examined as specified in 4.4.4 and tested as specified in 4.4.5. The presence of any defect or failure of any test shall be cause for rejection of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:05Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with the requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.4.1.1 Examination of chicken. Examination of chicken shall be made in accordance with the examination criteria of the referenced specification in 3.2.1 to determine conformance to the pertinent commodity requirements contained therein and to determine conformance to the condition and identity requirements of 3.2 and 3.2.1. Records of temperatures and storage time shall be maintained. Nonconformance to one or more condition or identity requirements or to temperature and storage requirements reflected by actual examinations or by records, shall be cause for rejection of the involved quantity of product or the finished product made therefrom, as applicable. Conformance to the identity requirements shall be ascertained by examination of USDA certificate. Identification of defects found during examination shall be as shown in table I. Lot size shall be expressed as the number of chickens or pounds (kg) of chicken. The sample size for examination shall be the number of sample units indicated by inspection level S-3. The sample unit shall be one chicken or one pound (0.45 kg) as applicable. The AQL shall be 2.5 for the major B defects and 10.0 for minor defects expressed as defects per hundred units.

TABLE I. Examination of chicken

Category		Defect
Major B	Minor	
151		Not skinned and rawboned
152		Presence of head, feet, metacarpus phalanges section of wings, giblets or viscera
153		Presence of bone, coarse connective tissue, blood clots, skin, braised or discolored meat exceeding 1/4 inch (6 mm) in any dimension 1/
	201	Presence of ligaments, tendons or cartilage which exceed 1/4 inch (6 mm) in any dimension
154		Presence of ground or comminuted chicken meat

1/ Measure to the nearest 1/8-inch (nearest 1 mm).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:05Z
Check the source to verify that this is the current version before use.

4.4.1.2 Examination of pimientos, canned. Examination of canned pimientos shall be made to determine compliance with the condition requirements of 3.2 and grade and style requirements of 3.2.2. The sample for examination of the condition requirements of 3.2 shall be an 8 ounce (227 g) composite derived from five primary containers or all of the containers if less than five form a lot. Determination of the compliance to grade and style requirement of 3.2.2 shall be ascertained by USDA Certificate of Grade. Nonconformance to one or more of the above referenced requirements shall be cause for rejection of the involved quantity of product or the finished product made therefrom, as applicable.

* 4.4.1.2.1 Examination of peppers, red, sweet. If sweet, red peppers are used in lieu of pimientos, examination shall be made to determine compliance with the applicable requirements of 3.2 and 3.2.2.1. The sample for examination of the condition requirements of 3.2 shall be an 8 ounce (227 g) composite derived from five primary containers or all of the containers if less than five form a lot, for canned peppers or 8 ounces (227 g) fresh or frozen peppers. Failure to comply with reference requirements shall be basis for rejection of the involved quantity of product or the finished product made therefrom, as applicable.

4.4.1.3 Examination of instant rice, chicken soup and gravy base, and turmeric. Examination shall be made in accordance with the examination criteria for product characteristics contained in the applicable subsidiary specification except that the sampling plans and acceptance criteria shall be as specified herein. The sample for examination shall be a 1 pound (454 g) composite for instant rice and a 1/2-pound (227 g) for turmeric, derived from five primary containers or all the containers, if less than five containers form a lot. Finding of one or more defects shall be cause for rejection of the involved quantity of product or the finished product made therefrom, as applicable.

4.4.1.4 Examination of vegetable oil and salt. Examination shall be made to determine compliance with the identity requirements of the applicable component paragraph. This determination shall be made by examination of pertinent labels, invoices, or other valid documents. In addition, examination of ingredients except nitrogen shall be made to determine compliance with the condition requirements of 3.2. The sample for examination shall be a 1/2 pound (227 g) composite derived from five primary containers or all containers if less than five form a lot. Noncompliance with one or more identity or condition requirements shall indicate an unacceptable component and use of such shall be cause for rejection of the involved end item.

* 4.4.2 Testing of components. Testing of components described in this specification shall be as shown in table II. Results shall be applicable to the lot average, except for the polyethylene and laminated plastic foil bags which shall be both the individual specimen and the sample unit average requirements. Nonconformance to test requirements shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:05Z
Check the source to verify that this is the current version before use.

TABLE II. Testing of components

Component	Sample unit	Lot size expressed in	Inspection level	Characteristic	Results reported to nearest	Test ref. and rqmt para.
Polyethylene 1/	Bag or sheet	Bags or sheets	S-1	Thickness	0.0001 inch (0.001 mm)	5.1.1 4.5.2
				Seal strength	1/4 pound (1 N)	5.1.1 4.5.6
Laminated plastic foil bag material 2/	Bag or sheet	Bags or sheets	S-1			
Ionomer or polyethylene film				Thickness	0.0001 inch (0.001 mm)	5.1.2 4.5.2
Aluminum foil				Thickness	0.00001 inch (0.0001 mm)	5.1.2 4.5.2
Polyester or nylon 6				Thickness	0.0001 inch (0.001 mm)	5.1.2 4.5.2
Polyethylene				Pounds per ream	1/4 pound (100 g)	5.1.2 4.5.2
Laminated bag 3/ 4/	Bag	Bags	S-1	Seal strength	1/4 pound (1 N)	5.1.2 4.5.6
Cooked chicken	8 oz. (227 g) composite	Pounds	5/	Salt	Nearest 0.01 percent	3.3.1 4.5.5
Baseboard	Board	Boards	S-1	Thickness	0.001 inch (0.01 mm)	5.1.1.2 4.5.7

1/ The lot shall be rejected if testing indicates the seal strength specimen of any polyethylene bag is less than 4 pounds (18 N) or the average seal strength is less than 5 pounds (22 N).

2/ In lieu of testing the thickness of each lamina, determination of conformance may be ascertained by examination of labels or invoices. Nonconformance to the above requirements shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:05Z
Check the source to verify that this is the current version before use.

3/ The lot shall be rejected if testing indicates the seal strength specimen of any laminated bag is less than 5 pounds (22 N) or the average seal strength is less than 6 pounds (27 N).

4/ Samples of finished product shall be tested for closure seal.

5/ The composite shall be derived from five primary containers or all containers if less than five form a lot.

4.4.3 In-process inspection. Examination shall be made during processing to determine compliance with the requirements of 3.3.1, 3.3.2, 3.3.3, 3.4 and 3.5 as concerns preparation, formulation, cooking, dehydration, and time and temperature limitations and to determine compliance with 5.1.1.1 and 5.1.1.2. Records of times, temperatures, absolute pressures, vacuums, and formulation shall be maintained. Nonconformance to one or more of the above referenced requirements reflected by actual examination or by records shall be cause for rejection of the lot or the finished product made therefrom, as applicable.

* 4.4.4 End item inspection. Classification of defects found during examination shall be in accordance with tables IV through VIII. Acceptable quality levels (AQLs) shall be expressed as percent defective for table IV and as defects per hundred units for tables V, VI, VII and VIII. End item examination criteria shall be as shown in table III.

TABLE III. Criteria for end item sampling

Table	Inspection level	Sample unit	Lot size expressed in	AQL Major A	AQL Major B	AQL Minor
IV	S-3	One filled and sealed bag	Bags	-	-	2.5
V	S-2	Contents of one filled and sealed bag	Bags	1/	1.5	-
VI	S-2	One filled and closed bag	Bags	-	1.5	6.5

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:05Z
Check the source to verify that this is the current version before use.

TABLE III. Criteria for end item sampling (cont'd)

Table	Inspection level	Sample unit	Lot size expressed in	AQL Major A	AQL Major B	AQL Minor
VII	S-3	One filled and sealed bag	Bags	-	1.5	6.5
VIII	S-3	One shipping container	Shipping containers	-	1.5	6.5

1/ Finding of one or more major A defects shall be cause for rejection of the lot.

TABLE IV. Examination of net weight 1/

Category	Defect
Minor	
201	Net weight less than 3-3/4 ounces (106 g). 2/

1/ Lot shall be rejected if sample data indicate that lot average net weight is less than specified net weight.

2/ Report to the nearest 1/8 ounce (nearest 1 gram).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:05Z
Check the source to verify that this is the current version before use.

TABLE V. Examination of product characteristics

Category		Defect
Major A	Major B	Applicable to dehydrated product
101		Presence of foreign material e.g., dirt, glass or paint, etc.
	151	Evidence of incomplete dehydration e.g., damp or soggy areas.
	152	Glazed surface areas that measure more than 1/2 inch (13 mm) in any dimension. 1/
	153	Dark colored cores of any dimension.
		Applicable to rehydrated product
	154	Incomplete water penetration through all dice and rice (see 3.6.1, item 4). 2/
	155	Flavor, odor or texture not considered normal for frozen and heated chicken and rice (not comparable to preproduction sample when applicable).
102		Presence of foreign odors, e.g., scorched, burnt, etc.
	156	Product appears as an indistinguishable mass of chicken meat fibers and rice.

1/ Report results to the nearest 1/8 inch (nearest 1 mm).

2/ Dry or callous-like areas attributable to gristle and similar material shall not be considered as defects.

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:05Z
Check the source to verify that this is the currentversion before use.

TABLE VI. Examination of polyethylene and laminated foil bag prior to filling and sealing

Category		Defect	Polyethylene bag	Laminated plastic-foil bag
Major B	Minor			
151		Dimensions not as specified (see 5.1.1 and 5.1.2). 1/	X	X
152		Not style or material specified.	X	X
	201	Insufficient slip characteristic.		X
153		Three edges not heat sealed.		X
	202	"V" or "U" shaped notch exceeds 1/8 inch (3 mm) or less than 1/16 inch (2 mm). 2/		X
	203	"V" or "U" shaped notch not 1-1/2 inches (38 mm) ± 1/8 inch (3 mm) from open end of bag. 2/		X
	204	Lip does not extend 1/4 inch (6 mm) beyond outer edge when applicable. 2/		X
	205	Tape missing, incorrect type or class or not placed over bag ears when applicable (see 5.1.1).	X	

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:05Z
Check the source to verify that this is the currenversion before use.

TABLE VI. Examination of polyethylene and laminated foil bag prior to filling and sealing (cont'd)

Category		Defect		
Major B	Minor		Polyethylene bag	Laminated plastic-foil bag
		Applicable to baseboard		
	206	Baseboard material not as specified.	X	
	207	Not a natural color ranging from brown to gray where applicable.	X	
	208	Not dimension specified.	X	
	209	Corners not rounded.	X	

1/ Bag dimensions are inside dimensions exclusive of seams or seals. Deviations from bag dimensions due to seal creep, or seams not being paralled with each other shall be scored as a defect.

2/ Measured to the nearest 1/16 inch (nearest 1 mm).

TABLE VII. Examination of the polyethylene and laminated foil bag after filling and sealing

Category		Defect		
Major B	Minor		Polyethylene bag	Laminated foil bag
151		Not formed as specified.	X	X
152		Broken, sifter, tear or hole.	X	X
153		Seal closure width less than 5/16 inch (8 mm) or more than 1/2 inch (13 mm). 1/		X

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:05Z
Check the source to verify that this is the current version before use.

TABLE VII. Examination of the polyethylene and laminated foil bag after filling and sealing (cont'd)

Category		Defect	Polyethylene bag	Laminated foil bag
Major B	Minor			
	201	Maximum thickness exceeds 2-1/4 inches (57 mm) at any point. 2/		X
	202	Not folded as specified.		X
154		Label nomenclature missing, incorrect or illegible.		X
	203	Information other than nomenclature, missing, incorrect or illegible.		X
155		Color of label white or other than dull non-reflecting color.		X
156		Printing not bold black face or indelible ink. 3/		X
	204	Label not affixed as specified.		X

1/ Measure to nearest 1/32 inch (nearest 1 mm).

2/ Measure to nearest 1/8 inch (nearest 1 mm).

3/ When applicable, determination of compliance to the indelible ink requirements shall be ascertained by examination of labels, invoices or other valid documents.

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:05Z
Check the source to verify that this is the current version before use.

TABLE VIII. Examination of packing (level C)

Category		Defect
Major B	Minor	
	201	Less than 44 filled and sealed food component packages. 1/
	202	Not material specified (see 5.2.1).
151		One or both pads missing.
	203	Not arranged as specified (see 5.2.1).
152		Dunnage material missing or not placed as specified (see 5.2.1).
	204	Dunnage material dimensions less than the length or width of the shipping container. 2/
	205	Dunnage material thickness less than 1/8 inch (3 mm) thick or 1/16 inch (1.6 mm) thick, as applicable. 3/
153		Name of product, missing, incorrect or illegible.
	206	Other markings missing, incorrect, or illegible.
	207	Box not closed as specified in 5.2.1.

1/ Lot shall be rejected if the average count is less than specified count.

2/ Measured to the nearest 1 inch (nearest 1 mm).

3/ Measured to the nearest 1/16 inch (nearest 1 mm) for 1/8 inch (3 mm) thick material and to the nearest 1/32 inch (nearest 1 mm) for 1/16 inch (1.6 mm) thick material.

* 4.4.4.1 Vacuum examination of evacuated packets. The evacuated packets shall be examined on a 100 percent basis to determine compliance with the vacuum requirements of 5.1.2.1. The examination shall be made not less than 24 hours after sealing. Nonconformance to the vacuum requirements reflected by actual examination or by records shall be cause for rejection of the individual packet (see 4.5.1). Records shall be maintained to reflect the 100 percent examination and results thereof. Nonconformance to this requirement shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:05Z
Check the source to verify that this is the current version before use.

4.4.5 End item testing.

* 4.4.5.1 Moisture and microbiological testing. The finished product (dehydrated form) shall be tested for moisture and microbiological content in accordance with the requirements of 3.6.2 and 3.6.3. Procedures for testing shall be in accordance with 4.5. Test requirements shall be applicable to the sample unit. The sample unit for testing shall be one filled and sealed primary container. For determination of the moisture and aerobic plate count lot size shall be expressed in terms of primary containers and the sample size shall be the number of samples indicated by inspection level S-2. A nonconformance to a test requirement shall be scored as a major defective for each characteristic and shall be cause for rejection of the lot. For determination of the E. coli count, five samples shall be used. The product shall be rejected if it fails to comply with 3.6.3, footnote 1/. Results for moisture shall be reported to the nearest 0.1 percent and microbiological counts as specified in 4.5.4.

4.5 Methods of inspection.

4.5.1 Vacuum examination. During the examination, the packet shall continue to exhibit a tight adherence of the packet to the surface contours of the contents along the seams when a force is applied away from the contents at the center of each side seam (holding each side seam between thumb and forefinger of each hand, simultaneously exert a slight pull with both hands). Repackaging of the product into a new laminated foil-plastic bag will be permitted provided that the repackaging and resealing is accomplished within seven days of the original sealing.

4.5.2 Laminae thickness tests. These procedures are to apply to tests that are to be conducted at the film laminator's plant to verify the following material structure:

Laminated polyethylene
Aluminum foil
Extruded polyethylene
Polyester

4.5.2.1 Polyethylene lamina. The thickness of the polyethylene lamina shall be tested in accordance with L-P-378, except that a machinist's micrometer may be used, provided graduations and accuracy conform to the requirements stated in L-P-378.

4.5.2.2 Aluminum foil. The thickness of the foil shall be determined in accordance with the procedure specified in QQ-A-1876.

4.5.2.3 Polyethylene extrusion. If the equipment performing the extrusion operation is equipped with a beta gauge reading device, direct readings shall be observed and these will be regarded as the thickness of the extrusion. Alternatively, the following method can be utilized: A sample of at least 4 by 4 inches (102 by 102 mm) shall be cut from the completed material immediately after the extrusion operation is completed on the specific roll being constructed. Separation

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:05Z
Check the source to verify that this is the currentversion before use.

of the laminae shall be attempted, under proper conditions, utilizing a solvent such as tetrahydrofuran or toluene (separation of the laminae can be accomplished easier immediately after the material has been fabricated before the adhesives have cured). If this method is successful, the extrusion coating shall be removed, dried, and tested for thickness as specified for the polyethylene lamina. NOTE: Of the two methods specified, the first is considered to be the more accurate.

4.5.2.4 Polyester. The thickness of the polyester lamina shall be determined by a gauge measurement as specified for the polyethylene lamina.

* 4.5.3 Moisture test. Moisture in the product shall be determined in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists; Chapter: Meat and Meat Products: Section: Meat; Method: Moisture - Drying in Vacuum. Use a temperature of 70°C for 16 hours under a pressure of 13 kPa (100 mm Hg).

4.5.4 Microbiological test. Microbiological testing of the product shall be made, as applicable, in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists, Chapter: Microbiological Methods: Section: Examination of Frozen, Chilled, Precooked, or Prepared Foods - Official First Action, except as specified in 4.5.4.1.

* 4.5.4.1 Preparation and dilution of the food homogenate. The finished product shall be prepared for chemical and microbiological testing by being adequately comminuted, care being taken to avoid contamination of product and moisture pickup. A representative sample shall then be removed and handled as specified in AOAC. For E. coli determinations prepare proper dilutions using 25 gram samples. Following addition of the diluent to the dry product, allow to stand for 15 minutes before blending. Continue as directed by AOAC.

4.5.5 Salt content test. Chemical analysis for salt shall be in accordance with the Official Analytical Chemists; Chapter: Meat and Meat Products, Section: Meat; Test: Salt (sodium chloride); Method: Salt.

4.5.6 Seal strength test (polyethylene and plastic-foil bags). Seal strength shall be tested in accordance with the procedure specified in Method A or B of ASTM D 882. Seal specimens shall be 1/2 inch (13 mm) or 1 inch (25 mm) in width and shall be pulled at a uniform rate of 10 inches (25 cm) per minute. Readings shall record tensile strength at time of seal break. Two nonadjacent specimens shall be taken from each of the three manufacturer's seals (bottom seal only of the polyethylene bag) of the bag to be tested, and the average of the specimens shall represent the seal strength of the bag tested. The seal strength of the processor's closure seal shall be determined in the same manner.

4.5.7 Baseboard thickness test. Thickness of baseboard shall be determined in accordance with Method 1003 of FED-STD-101.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:05Z
Check the source to verify that this is the currentversion before use.

5. PACKAGING

5.1 Preservation. The product shall be filled in polyethylene bags as specified in 5.1.1. These shall then be unit packed in laminated foil bags as specified in 5.1.2.

* 5.1.1 Polyethylene bags. A net weight of four ounces (113 g) of the product shall be filled into a 0.005 inch (0.13 mm) thick ± 10 percent polyethylene bag made in accordance with type I bags of PPP-B-26, except that the bag shall be made from food grade and low slip polyethylene. A minus 1/4-ounce (7 g) tolerance will be allowed in any one bag provided the average net weight of the bags inspected in accordance with table IV is not less than 4-ounces (113 g). If medium density polyethylene is used, a minimum thickness of 0.003 inch (0.08 mm) is acceptable. The bag shall not impart any undesirable odor or flavor to the product and shall be approved by the Food and Drug Administration for food items. The seal strength of the manufacturer's seal shall be not less than 5 pounds (22 N) per linear inch (lot average) when tested in accordance with 4.5.6 with no individual test specimen evidencing a seal strength of less than 4 pounds (18 N) per linear inch. The inside dimensions of the bag shall be 5-1/2 by 3-1/2 by 8 inches (140 by 89 by 203 mm) (± 1/8 inch (3 mm) in each dimension) with the open end of the bag having the 5-1/2 by 3-1/2 inch (140 by 89 mm) dimensions. After filling, the end panels of the bag (corresponding to the 3-1/2 inch (89 mm) dimension) shall be folded in to form gussets, and the bag shall be closed by folding over its open end. Where required by the bulkiness of the product, the bulk of the contents within the bag shall be compressed to a depth of not more than 2-1/4 inches (57 mm) by applying a constant uniform pressure over the entire top surface of the product. The filled bag with its open top folded over to prevent spillage of the product shall be inserted to the bottom of the laminated plastic-foil bag specified in 5.1.2. Alternatively, in lieu of polyethylene bags, conforming to type I of PPP-B-26, bags made in accordance with type II of PPP-B-26, with inside dimensions of 9 by 8 inches (229 by 203 mm) (± 1/8 inch (3 mm) in each dimension) with the open end of the bag having the 9 inch (229 mm) dimension, may be used. The material and seal strength shall be as specified for type I bags. When type II bags are used, they shall be formed over a mandrel as specified in 5.1.1.1 before filling. While the bag is positioned on the mandrel, the two bag ears shall be taped down over a 5-1/2 by 3-1/2 inch (140 by 89 mm) baseboard constructed in accordance with 5.1.1.2. An 8 inch (203 mm) long strip of 1 inch (25 mm) wide tape complying with type III, class 2 of PPP-T-60 shall be applied across both ears to fasten them securely to the baseboard.

5.1.1.1 Mandrel. The mandrel face shall be 5-3/8 by 3-3/8 inches (137 by 86 mm) and the height shall be not less than 12 inches (305 mm). All corners and edges of the mandrel shall be rounded and all surfaces finished to prevent damage to the bag material.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:05Z
Check the source to verify that this is the current version before use.

5.1.1.2 Baseboard. The baseboard shall be constructed from unbleached and uncoated solid sulfate or sulfite paperboard not less than 0.022 inch (0.56 mm) thick. Alternatively, the baseboard may be constructed from 0.022 inch (0.56 mm) thick food grade paperboard made from recycled fibers. If paperboard made from recycled fibers is used, it shall be natural color ranging from brown to gray. The baseboard shall be 5-1/2 by 3-1/2 inches (140 by 89 mm) (± 1/8 inch) (3 mm) and shall have all corners rounded to form a smooth contour.

* 5.1.2 Laminated plastic-foil bag. The bag shall be fabricated from a material consisting of 0.0025 inch (0.064 mm) thick ionomer or polyethylene film, (± 10 percent) laminated or extrusion coated to 0.00035 inch (0.0089 mm) thick ± 10 percent aluminum foil, laminated on the plain side to 0.001 inch (0.025 mm) thick ± 20 percent polyester or nylon 6. The polyester or nylon 6 shall be bonded to the aluminum foil by hot extruding 10 pounds (4.5 kg) ± 10 percent per ream of polyethylene between the laminae. The exterior (polyester or nylon 6) surface of the material shall be colored overall with a color in the number ranges from 34052 to 34108 inclusive, or 20045, 20062 or 30045 of FED-STD-595. Reverse printing of the exterior layer will be acceptable and any luster contributed by the polyester or nylon 6 lamina (external) shall not be considered as affecting the color gloss. The combined sheet material shall show no evidence of delamination before or after heat sealing. The laminated material shall be suitably formulated for food products in compliance with the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder. The interior surface of the laminated material shall not impart any undesirable odor or flavor to the product. The bag shall be a flat style bag having the inside dimensions of 6 by 10 inches (152 by 254 mm) or 6 by 10-5/8 inches (152 by 270 mm) (± 1/8 inch) (3 mm) in each dimension), and shall be heat sealed on three edges with 3/8 inch (10 mm) wide seals (± 1/8 inch) (3 mm). One side of the open end of the bag may be provided with a 1/4 inch (6 mm) (± 1/16 inch) (2 mm) extended or fold-over lip to facilitate opening and filling. The laminated bag material shall have an average seal strength of not less than 6 pounds per linear inch (1.05 kN/m) when tested in accordance with 4.5.6. A V-shaped or C-shaped (half-round) tear notch at least 1/32 inch (1 mm) deep located 1-1/4 to 1-1/2 inch (32 to 38 mm) from the top edge of the bag, shall be made in both seals. The distance between the inside edge of the tear notch and the inside edge of the seal shall be at least 3/16 inch (5 mm). The unit pack shall be closed as specified in 5.1.2.1.

* 5.1.2.1 Closure of filled laminated plastic-foil bag. The filled laminated bag shall be evacuated and closed by heat sealing the open end in a vacuum of not less than 28 inches (6.42 kPa) as registered on a vacuum gauge on the closing machine. After a storage period of 24 hours or more following the unit pack closing operation, an examination shall be made of each unit pack to determine compliance with the vacuum requirements (see 4.5.1 for procedure). The closure seal shall be not less than 1/4 inch (6 mm) wide nor more than 1/2 inch (13 mm) and shall have an average seal strength of not less than 6 pounds per linear inch (1.05 kN/m) with no individual seal strength specimen less than 5 pounds per linear inch (0.88 kN/m) when tested in accordance with 4.5.6.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:05Z
Check the source to verify that this is the current version before use.

Alternatively, an optional double seal may be applied to close the bags. The double closure seal shall be at least 5/16 inch (8 mm) wide and shall be above the tear notch and shall have an average seal strength of 6 pounds per linear inch (1.05 kN/m) and no individual specimen shall have a strength of less than 5 pounds per linear inch (0.88 kN/m) when tested in accordance with 4.5.6. If thermal impulse sealing is used for the closure seal, a seal width of not less than 1/8 inch (3 mm) is required. The unit pack shall be labeled in accordance with 5.3, subsequent to the closing operation. Unit packs which are improperly sealed or fail to maintain vacuum after sealing may be resealed or contents may be placed in a new laminated plastic-foil bag and resealed.

5.2 Packing.

* 5.2.1 Level C packing (for shipment of flexibly packed food to the ration assembler). Forty-five filled and sealed food unit packs, preserved as specified in 5.1 shall be packed in a fiberboard box complying with style RSC-L, type CF, class domestic, variety SW, grade 175 of PPP-B-636. In addition, top and bottom pads constructed of the same material as the shipping container shall be used in packing. The unit packs shall be packed flat or nested in three layers of fifteen unit packs each. Each unit pack shall be packed with its excess package material maintained in the flat (unfolded) state. Dunnage material not less than 1/8 inch (3 mm) thick conforming to type II, class B of PPP-C-843 or dunnage material not less than 1/16 inch (1.6 mm) thick conforming to PPP-C-1797 shall be placed between each of the three layers of unit packs and in the bottom and top of the cases to minimize movement of each individual packet. The length and width of the pieces of dunnage material shall be not less than the length and width of the shipping container. Each box shall be securely closed in accordance with method II as specified in the appendix of PPP-B-636.

5.3 Labeling and marking.

* 5.3.1 Unit packs (food packets). Each unit pack shall have labeling that complies with the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder. The label shall be pressure-sensitive and be a dull non-reflective color. The label shall be applied to one face of the bag with sufficient pressure to assure its adherence to the packet. The labels shall contain the following information:

CAUTION - INNER BAG IS OPEN ON ONE SIDE. REMOVE IT CAREFULLY HOLDING OUTER BAG UPRIGHT TO AVOID SPILLING CONTENTS.

NAME OF PRODUCT.

TEAR BAG OPEN AT NOTCHES.

ADD 1/2 CANTEEN CUP HOT OR COLD WATER TO FOOD IN BAG. LET SOAK ABOUT 5 MINUTES. ADD MORE WATER IF DESIRED. MAY BE EATEN DRY.

NET WT. 4 AVD. OZ. (113 g)

NAME AND ADDRESS OF PRODUCER.

USDA INSPECTION MARKING.

Source: https://assist.dla.mil - Downloaded: 2026-10-21T21:05Z
Check the source to verify that this is the current version before use.

5.3.1.1 Alternative printing on unit packs (food packets). Alternatively, the above information may be printed directly on the bag with indelible black ink. When printing is applied directly to the bag it shall be located in an area that will permit the printing to be legible after vacuum sealing.

5.3.2 Shipping containers. Shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) When a first article is required (see 3.1, 4.3 and 6.2).

6.2 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of ASPR 7-104.55. The first article shall be a preproduction sample and shall consist of ten 4-ounce (112 g) packages of the product. The contracting officer should include specific instructions in all procurement instruments regarding arrangements for inspection and approval of the first article.

* 6.3 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

6.4 Award of contract. Award of contract for the product specified in this document shall be limited to plants known to maintain the required sanitation conditions of 3.7 (also see 4.2).

* 6.5 Metric equivalents. Metric equivalents, indicated in parentheses throughout this document, are based on practices, conversion factors, and symbols specified in ASTM E 380 Standard for Metric Practice, and are for information only. In each instance, the value stated in US customary units shall be controlling.

Custodians:

Army - GL
Navy - SA
Air Force - 50

Review activities:

Army - MD
Navy - MC, MS
DP - SS

Preparing activity:

Army - GL

Project No. 8940-0363

Source: https://assist.dla.mil - Downloaded: 2026102T21:08Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-43289E: CHICKEN WITH RICE, DEHYDRATED, COOKED

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1426 1 OCT 76

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

27

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:05Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK RESEARCH and DEVELOPMENT COMMAND
NATICK, MASSACHUSETTS 01760
OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
DRDNA-ES

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD-314



Commander
US Army Natick Research and Development Command
ATTN: DRDNA-ES
Natick, MA 01760

NATICK OP 1 AUG 78
FOLD

☆ U.S. GOVERNMENT PRINTING OFFICE: 1980—603-121/4067 2-1

2 8

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:05Z
Check the source to verify that this is the current version before use.