MIL-D-43268A(ME)
16 March 1977
SUPERSEDING
MIL-D-43268(GL)
21 September 1964

MILITARY SPECIFICATION

DRAIN UNIT, WASTE OIL, PORTABLE

This specification is approved for use by the Mobility Equipment Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of portable drain unit for receiving waste oil or grease from automotive transmissions, rear ends, and engine pans.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

| | |
|---|---|
| QQ-S-781 | - Strapping, Steel, and Seals. |
| PPP-B-601 | - Boxes, Wood, Cleated-Plywood. |
| PPP-B-636 | - Boxes, Shipping, Fiberboard. |

STANDARDS

MILITARY

| | |
|---|---|
| MIL-STD-105 | - Sampling Procedures and Tables for Inspection by Attributes. |
| MIL-STD-129 | - Marking for Shipment and Storage. |
| MIL-STD-130 | - Identification Marking of US Military Property. |

FSC 4930

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:02Z
Check the source to verify that this is the current version before use.

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Traffic Department, 1616 P Street, NW, Washington, DC 20036.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification Rules.

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Description.. The drain unit shall consist of a receptacle mounted on a base with casters and a cover with a telescoping drain bowl assembly.

3.2 First article (first-produced drain unit). The contractor shall furnish one or more drain units as specified (see 6.2) for examination and testing within the time frame specified (see 6.2) to prove that his production methods and choice of design detail will produce drain units that comply with the requirements of this specification. Examination and tests shall be as specified in Section 4 and shall be subject to surveillance and approval by the Government (see 6.3).



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:02Z
Check the source to verify that this is the current version before use.

3.3 Material. Material shall be of a type and quality that will fulfill the requirements of this specification and conform to current commercial practice. Material shall be free from any defect or imperfection that will contribute to the failure of, or reduce the performance of, the drain unit.

3.4 Construction.

3.4.1 Receptacle. The waste receptacle shall have a minimum capacity of 16 gallons (120 pounds) and shall be provided with a fitting not more than 2 inches from the bottom (inside) to drain the waste oil from the receptacle. The receptacle shall not leak.

3.4.2 Base. The base shall be round or square and shall have four casters for portability.

3.4.3 Cover and drain bowl. The cover shall have a telescoping drain bowl not less than 11 inches in diameter, and a strainer with not more than 0.50 inch openings, design optional, and a detachable splash shield on the top edge. A device shall be provided to hold the bowl at any desired height between the high and low extremes.

3.5 Height. The overall height of the drain unit, with the bowl fully extended, shall be not less than 64 inches.

3.6 Performance.

3.6.1 Telescoping. The drain bowl, in the fully extended position and supporting a weight equal to that of the drain bowl filled to one inch from the top with water or oil, shall not move down from the extended position unassisted.

3.6.2 Portability. The drain unit, filled to capacity, shall be capable of being pushed over a 1/2-inch, half-round strip without overturning.

3.7 Identification marking. The drain unit shall be identified in accordance with MIL-STD-130.

3.8 Finish. Unless otherwise specified (see 6.2), the drain unit finish shall be at the option of the contractor.

3.9 Workmanship. The drain unit shall be free of sharp edges and burrs, the finish shall be continuous without skips, and the casters shall work freely.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:02Z
Check the source to verify that this is the current version before use.

## 4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards, as applicable.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) First-produced drain unit inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).
(c) Inspection of packaging (see 4.6).

4.3 First-produced drain unit inspection.

4.3.1 Examination. The first-produced drain unit shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The first-produced drain unit shall be tested as specified in 4.5.2.1 through 4.5.2.3. Failure of any test shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination and tests shall be in accordance with MIL-STD-105.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined as specified in 4.5.1. AQL shall be 4.0 percent defective for major defects and 6.5 percent defective for minor defects.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:02Z
Check the source to verify that this is the current version before use.

4.4.3 Tests. Samples selected in accordance with 4.4.1 shall be tested as specified in 4.5.2.1 through 4.5.2.3. AQL shall be 2.5 percent defective.

4.5 Inspection procedure.

4.5.1 Examination. The drain unit shall be examined as specified herein for the following defects:

Major

101. Components missing.
102. Capacity not as specified.
103. Drain fitting not located as specified.
104. Base not as specified.
105. Cover and drain bowl not as specified.
106. Height not as specified.
107. Finish not as specified.

Minor

201. Identification marking missing, incomplete, or not legible.
202. Workmanship not as specified.

4.5.2 Tests.

4.5.2.1 Leakage. The drain unit shall receive, through the drain bowl assembly, 16 gallons of oil and be allowed to stand for 1 hour. After 1 hour, the drain unit shall be examined. Evidence of leakage shall constitute failure of this test.

4.5.2.2 Telescoping. The drain bowl of the unit shall be set at the high position and filled to 1 inch from the top with water or oil or an equivalent weight. Nonconformance to 3.6.1 shall constitute failure of this test.

4.5.2.3 Portability. The drain unit shall be filled to capacity with oil and the drain bowl shall be located at the low position. The unit shall be pushed by the edge of the drain bowl over a 1/2-inch, half-round strip of wood or metal, in such a manner that two casters ride over the obstacle simultaneously. Nonconformance to 3.6.2 shall constitute failure of this test.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:02Z
Check the source to verify that this is the current version before use.

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

| | |
|---|---|
| 108. | Materials or containers not as specified. Each incorrect material or container shall constitute one defect. |
| 109. | Box closure not Method V as specified. |
| 110. | Strapping not as specified. |
| 111. | Marking illegible, incomplete, incorrect, or missing. |

5. PACKAGING

5.1 Preservation. Preservation shall be Level A, Level B, or Commercial, as specified (see 6.2).

5.1.1 Level A. Each drain unit shall be preserved in a close-fitting box conforming to PPP-B-636, W5c, style optional. The unit shall be immobilized within the box. Box closure shall be in accordance with the appendix to the box specification, Method V.

5.1.2 Level B. Each drain unit shall be preserved as specified for Level A and box closure shall not be required to be Method V.

5.1.3 Commercial. Drain units shall be preserved to afford protection against deterioration and damage during shipment and handling from the contractor to the initial shipping destination.

5.2 Packing. Packing shall be Level A, Level B, or Commercial, as specified (see 6.2).

5.2.1 Level A. Drain units, preserved as specified in 5.1, shall be packed in close-fitting boxes conforming to PPP-B-601, Overseas Type,



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:02Z
Check the source to verify that this is the current version before use.

style optional. Strapping shall conform to QQ-S-781, Class 1, Type I or IV, size as applicable. Unless otherwise specified (see 6.2), strapping shall be Finish B. When specified (see 6.2), strapping shall be Finish A.

5.2.2 Level B. Packing shall be as specified for Level A, except that boxes shall be Domestic Type and strapping shall be Finish A.

5.2.3 Commercial. Drain units, preserved as specified in 5.1, shall be packed to assure carrier acceptance and safe delivery to destination at the lowest ratings of the carrier in compliance with Uniform Freight Classification rules or National Motor Freight Classification rules.

5.3 Marking.

5.3.1 Military packaging. Marking shall be in accordance with MIL-STD-129.

5.3.2 Commercial packaging. Commercial packaging marking shall reflect as a minimum, the item name, national stock number, quantity, contract or purchase order number, and appropriate address markings. The marking shall be applied with a waterproof material, shall be legible, and shall provide a definite contrast.

6. NOTES

6.1 Intended use. The drain unit is intended for use in draining oil or grease from automotive equipment, either over a pit or elevated on a lift.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Time frame required for submission of first-produced drain units and number of drain units required (see 3.2).
(c) When the drain unit finish will not be at the option of the contractor (see 3.8).
(d) Degree of preservation and degree of packing required (see 5.1 and 5.2).
(e) When other than Finish B strapping is required (see 5.2.1).



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:02Z
Check the source to verify that this is the current version before use.

6.3 First-produced drain unit. Any changes or deviations of production drain units from the approved first-produced drain unit during production will be subject to the approval of the contracting officer. Approval of the first-produced drain unit will not relieve the contractor of his obligation to furnish drain units conforming to this specification.

Custodian:
Army - ME

Review activities:
Army - SM
DLA - CS

Preparing activity:
Army - ME

Project 4930-A190



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:02Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-D-43268A(ME) Drain Unit, Waste Oil, Portable

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:02Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Mobility Equipment Research
and Development Command
ATTN: DRDME-DS
Ft. Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:02Z
Check the source to verify that this is the current version before use.