MIL-S-43279D
30 August 1984
SUPERSEDING
MIL-S-43279C
2 May 1978

MILITARY SPECIFICATION

SLINGS, BAG AND CASE CARRYING: COMMUNICATIONS EQUIPMENT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers three types of bag and case carrying slings made from olive drab webbing with miscellaneous metallic hardware.

1.2 Classification. The individual slings shall be of the following types as specified (see 6.2):

Type I	ST-34
Type II	ST-38
Type III	19-1/2 inches long

2. APPLICABLE DOCUMENTS

* 2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Natick Research and Development Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8465

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:04Z
Check the source to verify that this is the currentversion before use.

SPECIFICATIONS

FEDERAL

T-T-871	-	Twine, Cotton, Wrapping.
V-T-285	-	Thread, Polyester.
UU-P-268	-	Paper, Kraft, Wrapping.
DDD-L-20	-	Label: for Clothing, Equipage, and Tentage (General Use).
PPP-B-636	-	Boxes, Shipping,Fiberboard.

MILITARY

MIL-C-496	-	Clips, End, Strap.
MIL-W-530	-	Webbing, Textile, Cotton, General Purpose, Natural or in Colors.
MIL-B-543	-	Buckles, Tongueless and Web Strap.
MIL-S-43770/9	-	Snap Hooks, Cast Body, Fixed Loop Eye, Trigger Closure.
MIL-W-44049	-	Webbing, Textile and Tape, Textile, Polypropylene General Purpose, Natural or in Colors.

STANDARDS

FEDERAL

MIL-STD-751	-	Stitches, Seams, and Stitchings.

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-147	-	Palletized Unit Loads.

DRAWINGS

U.S. ARMY NATICK RESEARCH AND DEVELOPMENT CENTER

2-3-156	-	Sling, Bag and Case, Carrying, Type I, ST-34; Assembly and Section.
2-3-252	-	Sling, Bag and Case, Carrying, Type II, ST-38; Assembly Complete.
2-3-253	-	Sling, Bag and Case, Carrying, Type III, 19-1/2" L; Assembly Complete.

(Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:04Z
Check the source to verify that this is the currentversion before use.

* 2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 Guide samples. Samples of the end item, when furnished, are solely for guidance and information to the manufacturer (see 6.3). Variation from this document may appear in the sample, in which case this document shall govern.

3.2 First article. When specified a sample shall be subject to first article inspection (see 4.3, 6.2, and 6.4).

3.3 Materials. (See 6.5.)

3.3.1 Type I.

3.3.1.1 Webbing. The cotton webbing for the type I sling shall be dyed Olive Drab 7 to match the standard shade sample (see 6.3). The webbing shall conform to type IIb, class 4, 3/4 inch width of MIL-W-530.

3.3.1.2 Buckle. The buckle shall conform to type I, style 2, class 1 or 3, construction A, 3/4 inch width of MIL-B-543.

3.3.1.3. Snap hook. The 3/4 inch loop eye, trigger type snap hook shall conform to M43770/9-MIZ1 of MIL-S-43770/9.

3.3.2 Type II.

* 3.3.2.1 Webbing. The webbing for the type II sling shall be dyed O. D. 7 to match the standard shade sample (see 6.3). The 1 1/4 inch webbing shall be cotton conforming to type IIa, class 4 of MIL-W-530, or as an alternate, the webbing shall be polypropylene conforming to type IIa, class 4 of MIL-W-44049.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:04Z
Check the source to verify that this is the current version before use.

3.3.2.2 Buckle. The buckle shall conform to type I, style 2, class 1 or 3, construction A, 1-1/4 inch width of MIL-B-543.

3.3.3 Type III.

3.3.3.1 Webbing. The cotton webbing for the type III sling shall be dyed O.D. 7 to match the standard shade sample (see 6.3). The webbing shall conform to type III, class 4, 1 inch width of MIL-W-530.

3.3.3.2 Buckle. The buckle shall conform to type I, style 2, class 1 or 3, construction A, 1 inch width of MIL-B-543.

3.3.3.3 Clip, end. The ball type end clip shall conform to type I, class 1 or 2, size 1 inch of MIL-C-496.

3.3.4 Thread, polyester. The polyester thread for the three types of slings shall conform to type I, class 1, subclass A, size F of V-T-285.

3.3.4.1 Color. The thread shall be dyed O.D. S-1 C.A. 66022 and shall show fastness to weathering equal to or better than the standard sample. When no standard sample is available, the thread shall show "good" fastness to weathering.

3.4 Construction. The construction shall conform in all respects to the drawings listed in section 2 and as specified herein.

3.4.1 Stitches, seams, and stitchings. All stitches, seams, and stitchings shall be performed using stitch type 301 of FED-STD-751, with 6 to 8 stitches per inch and 1/8 inch stitching margin.

3.4.1.1 Automatic stitching. Any of the stitching operations cited in this document may be performed with an automatic machine provided the requirements for stitch pattern, stitches per inch, and size and type of thread are met; and at least three tying stitches, overlapping stitches, or backstitches are used to secure the ends of stitching.

3.4.1.2 Type 301 stitching. Ends of all stitching shall be backstitched or backtacked not less than 3/4 inch except where ends are caught in other seams or stitching. Thread tensions shall be maintained so that there will be no loose or tight stitching and the lock will be imbedded in the materials sewed.

3.4.1.2.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks, skipped stitches, run-offs, or bobbin runouts occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of 3/8 inch back of the end of the stitching. 1/

b. Thread breaks or two or more consecutive skipped or run off stitches noted during inspection of the item (in-process or end item) shall be

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:04Z
Check the source to verify that this is the currentversion before use.

repaired by overstitching. The stitching shall start a minimum of 3/8 inch in back of the defective area, continue over the defective area and continue a minimum of 3/8 inch beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching without damaging the materials and restitching in the required manner. 1/

1/ When making the above repairs, the ends of the stitching are not required to be backstitched.

3.4.1.3 Thread ends. All thread ends shall be trimmed to 1/4 inch maximum length.

3.5 Marking. The identification marking shall be applied in the location shown on the applicable drawing and shall conform to type IV, class 5 of DDD-L-20. The markings "ST-34" for type I and "ST-38" for type II shall be applied in the size characters and in the location indicated on the applicable drawing, and shall conform to type IV, class 9 of DDD-L-20. Fastness of class 9 marking shall be as specified for class 5 marking.

3.6 Workmanship. The finished slings shall conform to the quality of product established by this document. The occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 6.2) it shall be examined for the defects specified in 4.4.3 and 4.4.4. The presence of any defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:04Z
Check the source to verify that this is the currentversion before use.

4.4.1 Component and material inspection. In accordance with 4.1 components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase documents.

4.4.2 In-process inspection (types I and II). Inspection shall be made at any point or during any phase of the manufacturing process to determine whether cut length for component listed below is in accordance with specified requirements. The lot size shall be expressed in units of cut lengths. The sample unit shall be one cut length of webbing prior to assembly. The inspection level shall be S-3 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Cut length of webbing (types I and II)	Not within specified tolerance.

* 4.4.3 End item visual examination. The end item shall be examined for the defects listed below. The lot size shall be expressed in units of slings. The sample unit shall be one sling. The inspection level shall be I and the AQL expressed in terms of defects per hundred units, shall be 4.0.

Examine	Defect
Webbing	Any hole, cut, tear, smash, or slub. Frayed or scalloped edge; not firmly or tightly woven. Broken or missing end or pick. Spliced; not one continuous piece.
Hardware	Broken or malformed, failing to serve intended purpose; corroded area, burr, or sharp edge. Finish omitted or not as specified, area of no finish, objectionable orange peel, wrinkle, drop, streak, thin film, or no film. Not type specified. Not assembled as specified.
Clip end (type III)	Improperly clinched; webbing not flat at point of insertion into clip. Clinched excessively tight, cutting surrounding webbing. Not sufficiently clinched, will not pass through buckle; clip can be disengaged from webbing.
Snap hook (type I)	Spring does not function properly, failing to return to closed position when pressure is released.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:04Z
Check the source to verify that this is the currentversion before use.

Examine	Defect
Open seam	Any. NOTE: A seam shall be classified as open when one or more stitches forming a seam are broken, or when two or more skipped or run-off stitches occur.
Raw edge (on edge required to be turned under)	Raw edge not securely caught in stitching.
Run-off	(See open seam).
Seam and stitch type	Wrong seam or stitch type.
Stitching	Incomplete or any row missing.
Stitch tension	Loose, resulting in a loosely exposed bobbin or top thread; tight, resulting in excessive puckering of fabric on seam.
Stitches per inch	Less than minimum specified. More than maximum specified.
Thread break	Backstitched less than 3/8 inch. NOTE: Thread break not backstitched shall be classified as an open seam.
Stitching ends	Backstitched less than 3/4 inch or not secured as specified when stitching is performed on automatic machine.
Thread ends	Not trimmed to 1/4 inch maximum length.
Components and assembly	Any component part or required operation omitted (unless otherwise classified herein). Needle chew. Mend or darn.
Marking	Omitted, illegible, incorrect, or misplaced.
Cleanliness	Spot or stain.

4.4.4 End item dimensional examination. The end item shall be examined for the defects listed below. Any dimension not as specified shall be classified as a defect. The lot size shall be expressed in units of slings. The sample unit shall be one sling. The inspection level shall be S-3 and the AQL,

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:04Z
Check the source to verify that this is the currentversion before use.

expressed in terms of defects per hundred units, shall be 4.0.

Examine	Defect
Type III length	Less than 19 inches. More than 20 inches.
Component, stitching margin and gage, and location dimensions	Not within specified tolerances.

* 4.4.5 Packaging inspection. An examination shall be made to determine that the preservation, packing, and marking comply with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully packaged. The lot size shall be the number of shipping containers in the inspection lot. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged, or otherwise defective.
Workmanship	Inadequate application of components, such as; incomplete closure of container flap, loose strapping, improper taping, or inadequate stapling. Bulged or distorted container.
Content	Number of slings per shipping container is more or less than required.

* 4.4.6 Palletization inspection. An examination shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the inspection lot. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:04Z
Check the source to verify that this is the currentversion before use.

Examine	Defect
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

5. PACKAGING

* 5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A. Each sling shall be compactly coiled or folded and then securely tied with twine conforming to type I or II, 8 ply of T-T-871.

* 5.1.2 Commercial. The sling shall be preserved in accordance with ASTM D 3951.

* 5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

* 5.2.1 Level A packing. Two hundred and fifty slings of one type only, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to type I, grade B of UU-P-268. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5.

5.2.2 Level B packing. Two hundred and fifty slings of one type only, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, type CF (variety SW) of SF, class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to type I, grade B of UU-P-268. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636, except that the inspection shall be in

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:04Z
Check the source to verify that this is the currentversion before use.

accordance with 4.4.5.

* 5.2.2.1 Weather-resistant container. When specified (see 6.2), the fiberboard shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5.

* 5.2.3 Commercial packing. Slings, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), slings of one type only, packed as specified in 5.2, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

* 5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951. Each tenth unit pack shall have attached a manila colored paper shipping tag for the identification information.

6. NOTES

6.1 Intended use. The three types of slings are used by Military personnel within the Department of Defense. These slings are components used with or without various bag or case assemblies to carry miscellaneous equipment as follows:

Type I, ST-34 sling is used with the following items:
Reeling Machine, Hand-RL-39 to 31W1-3RL394.
Radio Set-AN/GLQ-2.
Type II, ST-38 sling is used with the following:
Radio Set, -AN/PRC-6.
Type III sling is used with the following items:
Attenuator, CN-7/URA-T1
Trnr. Generator, - AN/URA-T1.

* 6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this document.
b. Type required (see 1.2).
c. When first article is required (see 3.2, 4.3, and 6.4).
d. Selection of the applicable levels of preservation and packing (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:04Z
Check the source to verify that this is the currentversion before use.

e. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
f. When palletization is required (see 5.3).

6.3 Samples. For access to samples, address the procuring activity issuing the invitation for bids.

* 6.4 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.204-4. The first article should be a preproduction sample consisting of at least one sling. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for inspection and approval of the first article.

6.5 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the document (see 3.3).

6.6 Changes from previous issue. The margins of this document are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - NU
Air Force - 99

Review activities:

Army - MD
Air Force - 82
DLA - CT

User activities:

Army - ER
Navy - MC
Air Force - 45

Preparing activity:

Army - GL

Project NO. 8465-0884

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:04Z
Check the source to verify that this is the currentversion before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
US Army Natick Research and Development Center
Natick, Massachusetts 01760-5014

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STRNC-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:04Z
Check the source to verify that this is the currentversion before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL–S–43279D	Slings, Bag and Case Carrying: Communications Equipment

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 1 Apr 84

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:04Z
Check the source to verify that this is the current version before use.