FED SUP CLASS
2405

REVIEW ACTIVITY : DCSC, 69
USER ACTIVITY : YD





Ⓓ CANCELED AFTER 23 JUNE 1982
NO SUPERSEDING STANDARD


NC

..EAD LINING, S.A.E. NO. 49
..EEL, S.A.E. NO. 1008 OR 1010
..D-TIN PLATE I.D. (6% MIN. TIN) TO A THICKNESS .001 NOMINAL. FLASH-TIN PLATE ALL OVER AFTER
. PLATE.

3. ..4375 DIA. INSPECTION BLOCK WITH ONE PARTING LINE FACE AGAINST A STOP AT HORIZONTAL CENTER LINE OF ..LOCK AND A PRESSURE OF 2140 LBS. ON OTHER P.L. FACE. HEIGHT WILL BE 1.21925-1.22025 ON SIDE OPPOSITE STOP.
4. REMOVE ALL BURRS.
5. MS PART NUMBER AND PART MANUFACTURER'S IDENTIFICATION TO BE CLEARLY MARKED WITHOUT INTERFERING WITH THE FUNCTION OF THE PART.
6. TOLERANCES: UNLESS OTHERWISE SPECIFIED, LINEAR MACHINED DIMENSIONS ± .010: ANGULAR MACHINED DIMENSIONS ± 30'. DO NOT SCALE DRAWING.
7. FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.
8. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.
9. ALL DIMENSIONS IN INCHES.

Ⓒ ENTIRE STANDARD REVISED

PART NO. MS 13987-1

| | |
|---|---|
| P.A. Army - MO(ERDL)<br>Other Cust<br>A.F. - 69<br>NAVY - YD | TITLE<br>BEARING, SLEEVE: ENGINE, PLAIN 2-1/4" X 1-5/8" |
| PROCUREMENT SPECIFICATION<br>MIL-E-'1275 | SUPERSEDES: |

MILITARY STANDARD
MS 13987
SHEET 1 OF 1


APPROVED 19 JUNE 1952 REVISED (A) 27 NOVEMBER 1953 (B) 24 OCTOBER 1955 (C) 8 JULY 1966 (D) 23 JUNE 1982



This Military Standard has been approved by the Department of Defense and is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use will be made from this document.



Source: https://assist.dla.mil -- Downloaded: 202640-23T13:31Z
Check the source to verify that this is the current version before use.