FED SUP CLASS
2805



Ⓓ CANCELED AFTER 23 JUNE 1982
NO SUPERSEDING STANDARD

NOTES:

..A.E. NO. 49
.. 1008 OR 1010
.. (6% MIN. TIN) TO A THICKNESS .001 NOMINAL. FLASH-TIN PLATE ALL OVER AFTER

3 ..ION BLOCK WITH ONE PARTING LINE FACE AGAINST A STOP AT HORIZONTAL CENTER LINE OF ..RE OF 1865 LBS. ON OTHER P.L. FACE. HEIGHT WILL BE 1.21925-1.22025 ON SIDE OPPOSITE STOP ..

..ER AND PART MANUFACTURER'S IDENTIFICATION TO BE CLEARLY MARKED WITHOUT INTERFERING WITH HE ..ON OF THE PART.

6. ..ES: UNLESS OTHERWISE SPECIFIED, LINEAR MACHINED DIMENSIONS ± .010: ANGULAR MACHINED DIMEN- .. ± 30'. DO NOT SCALE DRAWING.

7. .. DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.

8. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

9. ALL DIMENSIONS IN INCHES.

Ⓒ ENTIRE STANDARD REVISED

REVIEW ACTIVITY : DESC, 69
USER ACTIVITY : YD

This Military Standard has been approved by the Department of Defense and is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

APPROVED 19 JUNE 1952 REVISED Ⓐ 27 NOVEMBER 1953 Ⓑ 24 OCTOBER 1955 Ⓒ 8 JULY 1966 Ⓓ 23 JUNE 1982

P.A. Army - MO(ERDL) Other Cust A.F. - 69 NAVY - YD	TITLE BEARING, SLEEVE: ENGINE, PLAIN, 2-1/4" X 1-5/16"	PART NO. MS 13988-1 MILITARY STANDARD MS 13988
PROCUREMENT SPECIFICATION MIL-B-11275	SUPERSEDES:	SHEET 1 OF 1

Source: https://assist.dla.mil -- Downloaded: 202640-23T13:31Z
Check the source to verify that this is the current version before use.